



C interfaces to GALAHAD SHA

Jari Fowkes and Nick Gould
STFC Rutherford Appleton Laboratory
Fri Mar 18 2022

1 GALAHAD C package sha	1
1.1 Introduction	1
1.1.1 Purpose	1
1.1.2 Authors	1
1.1.3 Originally released	1
2 File Index	3
2.1 File List	3
3 File Documentation	5
3.1 sha.h File Reference	5
3.1.1 Data Structure Documentation	5
3.1.1.1 struct sha_control_type	5
3.1.1.2 struct sha_inform_type	6
Index	7

Chapter 1

GALAHAD C package sha

1.1 Introduction

1.1.1 Purpose

Find an approximation to a sparse Hessian using componentwise secant approximation.

Currently, only the control and inform parameters are exposed; these are provided and used by other GALAHAD packages with C interfaces.

1.1.2 Authors

N. I. M. Gould, STFC-Rutherford Appleton Laboratory, England.

C interface, additionally J. Fowkes, STFC-Rutherford Appleton Laboratory.

1.1.3 Originally released

April 2013, C interface January 2022.

Chapter 2

File Index

2.1 File List

Here is a list of all files with brief descriptions:

sha.h	5
---------------------------------	---

Chapter 3

File Documentation

3.1 sha.h File Reference

```
#include <stdbool.h>
#include "galahad_precision.h"
```

Data Structures

- struct [sha_control_type](#)
- struct [sha_inform_type](#)

3.1.1 Data Structure Documentation

3.1.1.1 struct sha_control_type

control derived type as a C struct

Data Fields

bool	f_indexing	use C or Fortran sparse matrix indexing
int	error	error and warning diagnostics occur on stream error
int	out	general output occurs on stream out
int	print_level	the level of output required. ≤ 0 gives no output, $= 1$ gives a one-line summary for every iteration, $= 2$ gives a summary of the inner iteration for each iteration, ≥ 3 gives increasingly verbose (debugging) output
int	approximation_algorithm	which approximation algorithm should be used? <ul style="list-style-type: none">• 0 : unsymmetric (alg 2.1 in paper)• 1 : symmetric (alg 2.2 in paper)• 2 : composite (alg 2.3 in paper)• 3 : composite 2 (alg 2.2/3 in paper)

Data Fields

int	dense_linear_solver	which dense linear equation solver should be used? <ul style="list-style-type: none">• 1 : Gaussian elimination• 2 : QR factorization• 3 : singular-value decomposition• 4 : singular-value decomposition with divide-and-conquer
int	max_sparse_degree	the maximum sparse degree if the combined version is used
bool	space_critical	if space is critical, ensure allocated arrays are no bigger than needed
bool	deallocate_error_fatal	exit if any deallocation fails
char	prefix[31]	all output lines will be prefixed by .prefix(2:LEN(TRIM(.prefix))-1) where .prefix contains the required string enclosed in quotes, e.g. "string" or 'string'

3.1.1.2 struct sha_inform_type

inform derived type as a C struct

Data Fields

int	status	return status. See SHA_solve for details
int	alloc_status	the status of the last attempted allocation/deallocation
int	max_degree	the maximum degree in the adgacency graph
int	differences_needed	the number of differences that will be needed
int	max_reduced_degree	the maximum reduced degree in the adgacency graph
char	bad_alloc[81]	the name of the array for which an allocation/deallocation error occurred

Index

sha.h, [5](#)
sha_control_type, [5](#)
sha_inform_type, [6](#)