





GALAHAD UGO

USER DOCUMENTATION

GALAHAD Optimization Library version 4.0

1 SUMMARY

This package aims to find the global minimizer of a univariate twice-continuously differentiable function f(x) of a single variable over the finite interval $x^l \le x \le x^u$. Function and derivative values may be provided either via a subroutine call, or by a return to the calling program. Second derivatives may be used to advantage if they are available.

ATTRIBUTES — Versions: GALAHAD_UGO_single, GALAHAD_UGO_double. Uses: GALAHAD_CLOCK, GALAHAD_SYMBOLS, GALAHAD_SPECFILE, GALAHAD_SPACE, GALAHAD_STRINGS, and GALAHAD_USERDATA. Date: May 2016. Origin: N. I. M. Gould, Rutherford Appleton Laboratory. Language: Fortran 95 + TR 15581 or Fortran 2003.

2 HOW TO USE THE PACKAGE

Access to the package requires a USE statement such as

Single precision version

USE GALAHAD_UGO_single

Double precision version

USE GALAHAD_UGO_double

If it is required to use both modules at the same time, the derived types UGO_time_type, UGO_control_type, UGO_inform_type, UGO_data_type and (Section 2.1) and the subroutines UGO_initialize, UGO_solve, UGO_terminate, (Section 2.2) and UGO_read_specfile (Section 2.6) must be renamed on one of the USE statements.

2.1 The derived data types

Four derived data types are accessible from the package.

2.1.1 The derived data type for holding control parameters

The derived data type UGO_control_type is used to hold controlling data. Default values may be obtained by calling UGO_initialize (see Section 2.2.1), while components may also be changed by calling GALAHAD_UGO_read_spec (see Section 2.6.1). The components of UGO_control_type are:

- error is a scalar variable of type default INTEGER, that holds the stream number for error messages. Printing of error messages in UGO_solve and UGO_terminate is suppressed if error ≤ 0 . The default is error = 6.
- out is a scalar variable of type default INTEGER, that holds the stream number for informational messages. Printing of informational messages in UGO_solve is suppressed if out < 0. The default is out = 6.
- print_level is a scalar variable of type default INTEGER, that is used to control the amount of informational output which is required. No informational output will occur if print_level ≤ 0 . If print_level = 1, a single line of output will be produced for each iteration of the process. If print_level ≥ 2 , this output will be increased to provide significant detail of each iteration. The default is print_level = 0.

All use is subject to the conditions of the GNU Lesser General Public License version 3. See http://galahad.rl.ac.uk/galahad-www/cou.html for full details.

UGO GALAHAD ■

start_print is a scalar variable of type default INTEGER, that specifies the first iteration for which printing will occur in UGO_solve. If start_print is negative, printing will occur from the outset. The default is start_print = -1.

- stop_print is a scalar variable of type default INTEGER, that specifies the last iteration for which printing will occur in UGO_solve. If stop_print is negative, printing will occur once it has been started by start_print. The default is stop_print = -1.
- print_gap is a scalar variable of type default INTEGER. Once printing has been started, output will occur once every print_gap iterations. If print_gap is no larger than 1, printing will be permitted on every iteration. The default is print_gap = 1.
- maxit is a scalar variable of type default INTEGER, that holds the maximum number of iterations which will be allowed in UGO_solve. The default is maxit = 1000.
- initial_points is a scalar variable of type default INTEGER, that gives the number of initial (uniformly-spaced) evaluation points; if initial_points; 2, it will be reset to 2. The default is initial_points = 2.
- storage_increment is a scalar variable of type default INTEGER, that specifies the incremement size of additional workspace storage that will be allocated as needed; if storage_increment; 1000, it will be reset to 1000. The default is storage_increment = 1000.
- buffer is a scalar variable of type default INTEGER, that specifies the unit number for any out-of-core i/o when expanding workspace arrays. The default is buffer = 70.
- lipschitz_estimate_used is a scalar variable of type default INTEGER, that specifies what sort of Lipschitz constant estimate will be used. Possible values are
 - 1. the global contant is provided in global_lipschitz_constant.
 - 2. the global contant is estimated.
 - 3. local constants are estimated.

The default is lipschitz_estimate_used = 3.

- next_interval_selection is a scalar variable of type default INTEGER, that specifies how the next interval for examination is chosen. Possible values are
 - 1. traditional, based on the best overall predicted value
 - 2. a local improvement algorithm is used (not currently implemented, and defaults to 1)

The default is next_interval_selection = 1.

- refine_with_newton is a scalar variable of type default INTEGER, that specifies the maximum number of Newton steps that may be used in the vacinity of a global minimizer to try to improve the estimate. The default is refine_with_newton = 5.
- alive_unit is a scalar variable of type default INTEGER. If alive_unit > 0, a temporary file named alive_file (see below) will be created on stream number alive_unit on initial entry to GALAHAD_UGO_solve, and execution of GALAHAD_UGO_solve will continue so long as this file continues to exist. Thus, a user may terminate execution simply by removing the temporary file from this unit. If alive_unit ≤ 0 , no temporary file will be created, and execution cannot be terminated in this way. The default is alive_unit = 40.
- stop_length is a scalar variable of type default REAL (double precision in GALAHAD_UGO_double), that is used to assess convergence. The method will stop if all sub-intervals that could cntain the global minimizer are smaller than stop_length in length. The default is $stop_length = 10^{-5}$.

- small_g_for_newton is a scalar variable of type default REAL (double precision in GALAHAD_UGO_double), that is used to assess when to use a Newton correction. If the absolute value of the gradient (first derivative) of f is smaller than small_g_for_newton, the next evaluation point may be at a Newton estimate of a local minimizer. The default is small_g_for_newton = 10^{-3} .
- small_g is a scalar variable of type default REAL (double precision in GALAHAD_UGO_double), that is used to assess when no Newton search is necessary. This will be the case if the absolute value of the gradient at the end of the interval search is small_g. The default is = $small_g 10^{-6}$.
- obj_sufficient is a scalar variable of type default REAL (double precision in GALAHAD_UGO_double), that may be used to stop the iteration if a value of x is found for which the objective function is sufficiently small. Specifically, the search will stop if the objective function is smaller than obj_sufficient. The default is obj_sufficient = $-u^{-2}$, where u is EPSILON(1.00) (EPSILON(1.000) in GALAHAD_UGO_double).
- global_lipschitz_constant is a scalar variable of type default REAL (double precision in GALAHAD_UGO_double), that is used to specify the global Lipschitz constant for the gradient; a negative value indicates that the value is unknown. The default is global_lipschitz_constant = -1.0.
- reliability_parameter is a scalar variable of type default REAL (double precision in GALAHAD_UGO_double), that is used to boost insufficiently large estimates of the Lipschitz constant if necessary. If reliability_parameter is not positive, it will be reset to 1.2 when second derivatives are provided (see second_derivatives_available below, and 2.0 if they are not. The default is reliability_parameter = -1.0.
- lipschitz_lower_bound is a scalar variable of type default REAL (double precision in GALAHAD_UGO_double), that provides a lower bound on the Lipschitz constant for the gradient. This must be non-negative (and not zero unless the function is constant). The default is lipschitz_lower_bound = 10^{-8} .
- cpu_time_limit is a scalar variable of type default REAL (double precision in GALAHAD_UGO_double), that is used to specify the maximum permitted CPU time. Any negative value indicates no limit will be imposed. The default is cpu_time_limit = -1.0.
- clock_time_limit is a scalar variable of type default REAL (double precision in GALAHAD_UGO_double), that is used to specify the maximum permitted elapsed system clock time. Any negative value indicates no limit will be imposed. The default is clock_time_limit = 1.0.
- second_derivatives_available is a scalar variable of type default LOGICAL, that must be set .TRUE. when second derivatives of f(x) are available, and .FALSE. otherwise. The package is generally more effective if second derivatives are available. The default is second_derivatives_available = .TRUE..
- space_critical is a scalar variable of type default LOGICAL, that must be set .TRUE. if space is critical when allocating arrays and .FALSE. otherwise. The package may run faster if space_critical is .FALSE. but at the possible expense of a larger storage requirement. The default is space_critical = .FALSE..
- deallocate_error_fatal is a scalar variable of type default LOGICAL, that must be set .TRUE. if the user wishes to terminate execution if a deallocation fails, and .FALSE. if an attempt to continue will be made. The default is deallocate_error_fatal = .FALSE..
- alive_file is a scalar variable of type default CHARACTER and length 30, that gives the name of the temporary file whose removal from stream number alive_unit terminates execution of GALAHAD_UGO_solve. The default is alive_unit = ALIVE.d.
- prefix is a scalar variable of type default CHARACTER and length 30, that may be used to provide a user-selected character string to preface every line of printed output. Specifically, each line of output will be prefaced by the string prefix(2:LEN(TRIM(prefix))-1), thus ignoreing the first and last non-null components of the supplied string. If the user does not want to preface lines by such a string, they may use the default prefix = ""

All use is subject to the conditions of the GNU Lesser General Public License version 3. See http://galahad.rl.ac.uk/galahad-www/cou.html for full details.

UGO GALAHAD 🌌

2.1.2 The derived data type for holding timing information

The derived data type UGO_time_type is used to hold elapsed CPU and system clock times for the calculation. The components of UGO_time_type are:

total is a scalar variable of type default REAL, that gives the CPU total time spent in the package.

clock_total is a scalar variable of type default REAL, that gives the total elapsed system clock time spent in the package.

2.1.3 The derived data type for holding informational parameters

The derived data type UGO_inform_type is used to hold parameters that give information about the progress and needs of the algorithm. The components of UGO_inform_type are:

- status is a scalar variable of type default INTEGER, that gives the exit status of the algorithm. See Sections 2.4 and 2.5 for details.
- alloc_status is a scalar variable of type default INTEGER, that gives the status of the last attempted array allocation or deallocation. This will be 0 if status = 0.
- bad_alloc is a scalar variable of type default CHARACTER and length 80, that gives the name of the last internal array for which there were allocation or deallocation errors. This will be the null string if status = 0.
- iter is a scalar variable of type default INTEGER, that holds the number of iterations performed.
- f_eval is a scalar variable of type default INTEGER, that gives the total number of evaluations of the objective function.
- g_eval is a scalar variable of type default INTEGER, that gives the total number of evaluations of the first derivative of the objective function.
- h_eval is a scalar variable of type default INTEGER, that gives the total number of evaluations of the second derivative of the objective function.
- dx_best is a scalar variable of type default INTEGER, that gives the length of the largest remaining search interval.
- time is a scalar variable of type UGO_time_type whose components are used to hold elapsed elapsed CPU and system clock times for the various parts of the calculation (see Section 2.1.2).

2.1.4 The derived data type for holding problem data

The derived data type UGO_data_type is used to hold all the data for a particular problem, or sequences of problems with the same structure, between calls of UGO procedures. This data should be preserved, untouched (except as directed on return from GALAHAD_UGO_solve with positive values of inform%status, see Section 2.4), from the initial call to UGO_initialize to the final call to UGO_terminate.

2.1.5 The derived data type for holding user data

The derived data type GALAHAD_userdata_type is available to allow the user to pass data to and from user-supplied subroutines for function and derivative calculations (see Section 2.3). Components of variables of type GALAHAD_userdata_type may be allocated as necessary. The following components are available:

integer is a rank-one allocatable array of type default INTEGER.

real is a rank-one allocatable array of type default REAL (double precision in GALAHAD_UGO_double)

complex is a rank-one allocatable array of type default COMPLEX (double precision complex in GALAHAD_UGO_double).

character is a rank-one allocatable array of type default CHARACTER.

logical is a rank-one allocatable array of type default LOGICAL.

integer_pointer is a rank-one pointer array of type default INTEGER.

real_pointer is a rank-one pointer array of type default REAL (double precision in GALAHAD_UGO_double)

complex_pointer is a rank-one pointer array of type default COMPLEX (double precision complex in GALAHAD_UGO_double).

character_pointer is a rank-one pointer array of type default CHARACTER.

logical_pointer is a rank-one pointer array of type default LOGICAL.

2.2 Argument lists and calling sequences

There are three procedures for user calls (see Section 2.6 for further features):

- 1. The subroutine UGO_initialize is used to set default values, and initialize private data, before solving one or more problems with the same sparsity and bound structure.
- 2. The subroutine UGO_solve is called to solve the problem.
- 3. The subroutine UGO_terminate is provided to allow the user to automatically deallocate array components of the private data, allocated by UGO_solve, at the end of the solution process.

We use square brackets $[\]$ to indicate ${\tt OPTIONAL}$ arguments.

2.2.1 The initialization subroutine

Default values are provided as follows:

```
CALL UGO_initialize( data, control, inform )
```

- data is a scalar INTENT (INOUT) argument of type UGO_data_type (see Section 2.1.4). It is used to hold data about the problem being solved.
- control is a scalar INTENT (OUT) argument of type UGO_control_type (see Section 2.1.1). On exit, control contains default values for the components as described in Section 2.1.1. These values should only be changed after calling UGO_initialize.
- inform is a scalar INTENT (OUT) argument of type UGO_inform_type (see Section 2.1.3). A successful call to UGO_initialize is indicated when the component status has the value 0. For other return values of status, see Section 2.5.

2.2.2 The minimization subroutine

The minimization algorithm is called as follows:

x_l and x_u are scalar INTENT(IN) variables of type default REAL (double precision in GALAHAD_UGO_double)that must be set to the lower and upper interval bounds x^l and x^u , respectively.

UGO GALAHAD 💆

is a scalar INTENT (INOUT) variable of type default REAL (double precision in GALAHAD_UGO_double)that holds the next value of x at which the user is required to evaluate the objective (and its derivatives) when inform%status > 0, or the value of the approximate global minimizer when inform%status = 0. x need not be set on initial (inform%status = 1) entry.

- is a scalar INTENT (INOUT) variable of type default REAL (double precision in GALAHAD_UGO_double)that must be set by the user to hold the value of the objective f(x) at x given in x whenever UGO_solve returns with inform%status x 0. If inform%status x 0, f will contain the value of the approximate global minimum x 1 at the approximate minimizer x given in x 1 need not be set on initial (inform%status x 1 entry.
- is a scalar INTENT (INOUT) variable of type default REAL (double precision in GALAHAD_UGO_double)that must be set by the user to hold the value of the first derivative f'(x) of f(x) at x given in x whenever UGO_solve returns with inform%status x 0. If inform%status x 0, y will contain the value of the gradient of y at the approximate minimizer y given in y. y need not be set on initial (inform%status y 1) entry.
- is a scalar INTENT (INOUT) variable of type default REAL (double precision in GALAHAD_UGO_double)that must be set by the user to hold the value of the second derivative f''(x) of f(x) at x given in x whenever UGO_solve returns with inform%status = 4 and the user has set control%second_derivatives_available = .TRUE. If inform%status = 0, h will contain the value of the second derivative of f(x) at the approximate minimizer x given in x when second derivatives are available. h need not be set on initial (inform%status = 1) entry.
- control is a scalar INTENT (IN) argument of type UGO_control_type (see Section 2.1.1). Default values may be assigned by calling UGO_initialize prior to the first call to UGO_solve.
- inform is a scalar INTENT (INOUT) argument of type UGO_inform_type (see Section 2.1.3). On initial entry, the component status must be set to the value 1. Other entries need note be set. A successful call to UGO_solve is indicated when the component status has the value 0. For other return values of status, see Sections 2.4 and 2.5.
- data is a scalar INTENT (INOUT) argument of type UGO_data_type (see Section 2.1.4). It is used to hold data about the problem being solved. With the possible exceptions of the components eval_status and U (see Section 2.4), it must not have been altered by the user since the last call to UGO_initialize.
- userdata is a scalar INTENT (INOUT) argument of type GALAHAD_userdata_type whose components may be used to communicate user-supplied data to and from the OPTIONAL subroutine eval_FGH (see Section 2.1.5).
- eval_FGH is an OPTIONAL user-supplied subroutine whose purpose is to evaluate the value of the objective function f(x) and its derivatives at a given vector x. See Section 2.3.1 for details. If eval_FGH is present, it must be declared EXTERNAL in the calling program. If eval_FGH is absent, GALAHAD_UGO_solve will use reverse communication to obtain objective function and derivative values (see Section 2.4).

2.2.3 The termination subroutine

All previously allocated arrays are deallocated as follows:

```
CALL UGO_terminate( data, control, inform )
```

- data is a scalar INTENT (INOUT) argument of type UGO_data_type exactly as for UGO_solve, which must not have been altered by the user since the last call to UGO_initialize. On exit, array components will have been deallocated.
- control is a scalar INTENT (IN) argument of type UGO_control_type exactly as for UGO_solve.
- inform is a scalar INTENT (OUT) argument of type UGO_inform_type exactly as for UGO_solve. Only the component status will be set on exit, and a successful call to UGO_terminate is indicated when this component status has the value 0. For other return values of status, see Section 2.5.



2.3 Function and derivative values

2.3.1 The objective function value via internal evaluation

If the argument eval_FGH is present when calling GALAHAD_UGO_solve, the user is expected to provide a subroutine of that name to evaluate the value of the objective function f(x) and its first and (possibly) second derivatives, f'(x) and f''(x).

The routine must be specified as

```
SUBROUTINE eval_FGH( status, x, userdata, f, g, h)
```

whose arguments are as follows:

- status is a scalar INTENT (OUT) argument of type default INTEGER, that should be set to 0 if the routine has been able to evaluate the objective function and its derivatives, and to a non-zero value if the evaluation has not been possible.
- is a scalar INTENT (IN) array argument of type default REAL (double precision in GALAHAD_UGO_double) whose components contain the value x.
- userdata is a scalar INTENT (INOUT) argument of type NLPT_userdata_type whose components may be used to communicate user-supplied data to and from the subroutine (see Section 2.1.5).
- is a scalar INTENT (OUT) argument of type default REAL (double precision in GALAHAD_UGO_double), that should be set to the value of the objective function f(x) evaluated at the vector x input in x.
- is a scalar INTENT (OUT) argument of type default REAL (double precision in GALAHAD_UGO_double), that should be set to the value of the first derivative f'(x) of the objective function f(x) evaluated at the vector x input in x.
- is a scalar INTENT (OUT) argument of type default REAL (double precision in GALAHAD_UGO_double), that should be set to the value of the second derivative f''(x) of the objective function f(x) evaluated at the vector x input in x if control%second_derivatives_available has been set to .TRUE.İt need not be set otherwise.

2.4 Reverse Communication Information

A positive value of inform%status on exit from UGO_solve indicates that GALAHAD_UGO_solve is seeking further information—this will happen if the user has chosen not to evaluate function or derivative values internally (see Section 2.3). The user should compute the required information and re-enter GALAHAD_UGO_solve with inform%status and all other arguments (except those specifically mentioned below) unchanged.

Possible values of inform%status and the information required are

- 3. The user should compute the objective function value f(x) and its first derivative f'(x) at the point x indicated in x. The required values should be set in f and g. respectively, and data%eval_status should be set to 0. If the user is unable to evaluate f(x) or its first derivative—for instance, if the function is undefined at x—the user need not set f or g, but should then set data%eval_status to a non-zero value. This value can only occur when control%second_derivatives_available = .FALSE.
- 4. The user should compute the objective function value f(x) and its first two derivatives f'(x) and f''(x) at the point x indicated in x. The required values should be set in f, g and h, respectively, and data%eval_status should be set to 0. If the user is unable to evaluate f(x) or either of its derivatives—for instance, if the function is undefined at x—the user need not set f, g or h, but should then set data%eval_status to a non-zero value. This value can only occur when control%second_derivatives_available = .TRUE.

Other values are reserved for future developments.

UGO GALAHAD ■

2.5 Warning and error messages

A negative value of inform%status on exit from UGO_solve or UGO_terminate indicates that an error has occurred. No further calls should be made until the error has been corrected. Possible values are:

- -1. A workspace allocation error occurred. A message indicating the offending array is written on unit control%error, and the returned allocation status and a string containing the name of the offending array are held in inform%alloc_status and inform%bad_alloc, respectively.
- -2. A workspace deallocation error occurred. A message indicating the offending array is written on unit control%error and the returned allocation status and a string containing the name of the offending array are held in inform%alloc_status and inform%bad_alloc, respectively.
- -4. The bound constraints are inconsistent.
- -7. The objective function appears to be unbounded from below on the feasible set.
- -18. Too many iterations have been performed. This may happen if control%maxit is too small, but may also be symptomatic of a badly scaled problem.
- -19. The elapsed CPU or system clock time limit has been reached. This may happen if either control%cpu_time_limit or control%clock_time_limit is too small, but may also be symptomatic of a badly scaled problem.
- -82. The user has forced termination of GALAHAD_UGO_solve by removing the file named control%alive_file from unit control%alive_unit.

2.6 Further features

In this section, we describe an alternative means of setting control parameters, that is components of the variable control of type UGO_control_type (see Section 2.1.1), by reading an appropriate data specification file using the subroutine UGO_read_specifile. This facility is useful as it allows a user to change UGO control parameters without editing and recompiling programs that call UGO.

A specification file, or specifie, is a data file containing a number of "specification commands". Each command occurs on a separate line, and comprises a "keyword", which is a string (in a close-to-natural language) used to identify a control parameter, and an (optional) "value", which defines the value to be assigned to the given control parameter. All keywords and values are case insensitive, keywords may be preceded by one or more blanks but values must not contain blanks, and each value must be separated from its keyword by at least one blank. Values must not contain more than 30 characters, and each line of the specifie is limited to 80 characters, including the blanks separating keyword and value.

The portion of the specification file used by UGO_read_specfile must start with a "BEGIN UGO" command and end with an "END" command. The syntax of the specifile is thus defined as follows:

```
( .. lines ignored by UGO_read_specfile .. )
BEGIN UGO
    keyword value
    ..... keyword value
END
( .. lines ignored by UGO_read_specfile .. )
```

where keyword and value are two strings separated by (at least) one blank. The "BEGIN UGO" and "END" delimiter command lines may contain additional (trailing) strings so long as such strings are separated by one or more blanks, so that lines such as

BEGIN UGO SPECIFICATION

and

END UGO SPECIFICATION

are acceptable. Furthermore, between the "BEGIN UGO" and "END" delimiters, specification commands may occur in any order. Blank lines and lines whose first non-blank character is ! or * are ignored. The content of a line after a ! or * character is also ignored (as is the ! or * character itself). This provides an easy manner to "comment out" some specification commands, or to comment specific values of certain control parameters.

The value of a control parameters may be of three different types, namely integer, logical or real. Integer and real values may be expressed in any relevant Fortran integer and floating-point formats (respectively). Permitted values for logical parameters are "ON", "TRUE", ".TRUE.", "T", "YES", "Y", or "OFF", "NO", "N", "FALSE", ".FALSE." and "F". Empty values are also allowed for logical control parameters, and are interpreted as "TRUE".

The specification file must be open for input when UGO_read_specfile is called, and the associated device number passed to the routine in device (see below). Note that the corresponding file is REWINDed, which makes it possible to combine the specifications for more than one program/routine. For the same reason, the file is not closed by UGO_read_specfile.

2.6.1 To read control parameters from a specification file

Control parameters may be read from a file as follows:

```
CALL UGO read specfile (control, device)
```

control is a scalar INTENT (INOUT) argument of type UGO_control_type (see Section 2.1.1). Default values should have already been set, perhaps by calling UGO_initialize. On exit, individual components of control may have been changed according to the commands found in the specifile. Specifile commands and the component (see Section 2.1.1) of control that each affects are given in Table 2.1 on the following page.

device is a scalar INTENT (IN) argument of type default INTEGER, that must be set to the unit number on which the specifile has been opened. If device is not open, control will not be altered and execution will continue, but an error message will be printed on unit control%error.

2.7 Information printed

If control*print_level is positive, information about the progress of the algorithm will be printed on unit control*out. If control*print_level = 1, a single line of output will be produced for each iteration of the process. This will include the value of the current iterate x and its corresponding objective function and gradient values, as well as the current best x and objective values. If control*print_level = 2, a final summary of the intervals considered is given, while if control*print_level > 2, additional debugging information will be given.

3 GENERAL INFORMATION

Use of common: None.

Workspace: Provided automatically by the module.

Other routines called directly: None.

Other modules used directly: UGO_solve calls the GALAHAD packages GALAHAD_CLOCK, GALAHAD_SYMBOLS, GALAHAD_SPECFILE, GALAHAD_SPACE, GALAHAD_STRINGS, and GALAHAD_USERDATA.

All use is subject to the conditions of the GNU Lesser General Public License version 3. See http://galahad.rl.ac.uk/galahad-www/cou.html for full details.

command	component of control	value type
error-printout-device	%error	integer
printout-device	%out	integer
print-level	%print_level	integer
start-print	%start_print	integer
stop-print	%stop_print	integer
iterations-between-printing	%print_gap	integer
maximum-number-of-iterations	%maxit	integer
number-of-initial-points	initial_points	integer
block-of-storage-allocated	storage_increment	integer
out-of-core-buffer	buffer	integer
lipschitz-estimate-used	lipschitz_estimate_used	integer
next-interval-selection-method	next_interval_selection	integer
refine-with-newton-iterations	refine_with_newton	integer
alive-device	%alive_unit	integer
stop_length	maximum-interval-length-required	real
small_g_for_newton	try-newton-tolerance	real
small_g	sufficient-gradient-tolerance	real
obj_sufficient	sufficient-objective-value	real
global-lipschitz-constant	global_lipschitz_constant	real
reliability_parameter	lipschitz-reliability-parameter	real
lipschitz_lower_bound	lipschitz-lower-bound	real
maximum-cpu-time-limit	%cpu_time_limit	real
maximum-clock-time-limit	%clock_time_limit	real
space-critical	%space_critical	logical
deallocate-error-fatal	%deallocate_error_fatal	logical
alive-filename	%alive_file	character

Table 2.1: Specifle commands and associated components of control.

Input/output: Output is under control of the arguments control%error, control%out and control%print_level.

Restrictions: None.

Portability: ISO Fortran 95 + TR 15581 or Fortran 2003. The package is thread-safe.

4 METHOD

The algorithm starts by splitting the interval $[x^l, x^u]$ into a specified number of subintervals $[x_i, x_{i+1}]$ of equal length, and evaluating f and its derivatives at each x_i . A surrogate (approximating) lower bound function is constructed on each subinterval using the function and derivative values at each end, and an estimate of the first- and second-derivative Lipschitz constant. This surrogate is minimized, the true objective evaluated at the best predicted point, and the corresponding interval split again at this point. Any interval whose surrogate lower bound value exceeds an evaluated actual value is discarded. The method continues until only one interval of a maximum permitted width remains.

References:

Many ingredients in the algorithm are based on the paper

Daniela Lera and Yaroslav D. Sergeyev, "Acceleration of univariate global optimization algorithms working with

Lipschitz functions and Lipschitz first derivatives" SIAM J. Optimization Vol. 23, No. 1, pp. 508–529 (2013) but adapted to use second derivatives.

5 EXAMPLES OF USE

Suppose we wish to minimize the parametric objective function $f(\mathbf{x}) = x^2 \sin(ax)$ when the parameter a takes the value 10, and x is required to satisfy the bounds $-1 \le x \le 2$. We may use the following code:

```
PROGRAM GALAHAD_UGO_EXAMPLE ! GALAHAD 4.0 - 2022-03-07 AT 10:05 GMT
USE GALAHAD_UGO_double
                                           ! double precision version
USE GALAHAD_USERDATA_double
IMPLICIT NONE
INTEGER, PARAMETER :: wp = KIND( 1.0D+0 ) ! set precision
TYPE ( UGO_control_type ) :: control
TYPE ( UGO_inform_type ) :: inform
TYPE ( UGO_data_type ) :: data
TYPE ( GALAHAD_userdata_type ) :: userdata
EXTERNAL :: FGH
REAL ( KIND = wp ) :: x_1, x_u, x, f, g, h
REAL ( KIND = wp ), PARAMETER :: a = 10.0_wp
x_1 = -1.0_{wp}; x_u = 2.0_{wp}
                                             ! bounds on x
ALLOCATE ( userdata%real ( 1 ) )
                                            ! Allocate space for parameter
userdata%real(1) = a
                                            ! Record parameter, a
CALL UGO_initialize( data, control, inform )
inform%status = 1
                                             ! set for initial entry
CALL UGO_solve(x_l, x_u, x, f, g, h, control, inform, data, userdata,
               eval_FGH = FGH ) ! Solve problem
IF ( inform%status == 0 ) THEN
                                            ! Successful return
 WRITE( 6, "( ' UGO: ', IO, ' evaluations', /,
      ' Optimal solution =', ES14.6, /,
       ' Optimal objective value and gradient =', 2ES14.6 )" )
          inform%iter, x, f, g
ELSE
                                            ! Error returns
  WRITE( 6, "( ' UGO_solve exit status = ', I6 ) " ) inform%status
END IF
CALL UGO_terminate( data, control, inform ) ! delete internal workspace
END PROGRAM GALAHAD UGO EXAMPLE
SUBROUTINE FGH ( status, x, userdata, f, q, h )
USE GALAHAD_USERDATA_double
INTEGER, PARAMETER :: wp = KIND( 1.0D+0 )
INTEGER, INTENT( OUT ) :: status
REAL ( KIND = wp ), INTENT( IN ) :: x
REAL ( KIND = wp ), INTENT( OUT ) :: f, g, h
TYPE ( GALAHAD_userdata_type ), INTENT( INOUT ) :: userdata
REAL ( KIND = wp ) :: a, ax, sax, cax
a = userdata%real( 1 )
ax = a * x
sax = SIN(ax)
cax = COS(ax)
f = x * x * cax
q = -ax * x * sax + 2.0_wp * x * cax
h = -a * a* x * x * cax - 4.0_wp * ax * sax + 2.0_wp * cax
status = 0
```

All use is subject to the conditions of the GNU Lesser General Public License version 3. See http://galahad.rl.ac.uk/galahad-www/cou.html for full details.

UGO GALAHAD 🌌

```
RETURN
END SUBROUTINE FGH
```

Notice how the parameter a is passed to the function evaluation routines via the real component of the derived type userdata. The code produces the following output:

```
UGO: 20 evaluations 
 Optimal solution = 1.583361E+00 
 Optimal objective value and gradient = -2.487269E+00 1.558900E-10
```

The same problem may be solved by returning to the user to provide the desired function and derivative values as follows:

```
USE GALAHAD_UGO_double
                                      ! double precision version
USE GALAHAD_USERDATA_double
IMPLICIT NONE
INTEGER, PARAMETER :: wp = KIND( 1.0D+0 ) ! set precision
TYPE ( UGO_control_type ) :: control
TYPE ( UGO_inform_type ) :: inform
TYPE ( UGO_data_type ) :: data
TYPE ( GALAHAD_userdata_type ) :: userdata
EXTERNAL :: FGH
REAL ( KIND = wp ) :: x_1, x_u, x, f, g, h
REAL ( KIND = wp ), PARAMETER :: a = 10.0_wp
REAL ( KIND = wp ) :: ax, sax, cax
x_1 = -1.0_{wp}; x_u = 2.0_{wp}
                                      ! bounds on x
ALLOCATE( userdata%real( 1 ) )
                                     ! Allocate space for parameter
                                      ! Record parameter, a
userdata%real(1) = a
CALL UGO_initialize( data, control, inform )
                                      ! set for initial entry
inform%status = 1
DO ! Solve problem using reverse communication
 CALL UGO_solve(x_l, x_u, x, f, q, h, control, inform, data, userdata)
 SELECT CASE ( inform%status )
                                      ! Successful return
   WRITE( 6, "( ' UGO: ', IO, ' evaluations', /,
                                                                       δ
        ' Optimal solution =', ES14.6, /,
                                                                       λ
        ' Optimal objective value and gradient =', 2ES14.6 )" )
            inform%iter, x, f, g
   EXIT
  CASE ( 4 )
                                      ! obtain function/derivative values
   ax = a * x
   sax = SIN(ax)
   cax = COS(ax)
   f = x * x * cax
   q = -ax * x * sax + 2.0_wp * x * cax
   h = -a * a* x * x * cax - 4.0_wp * ax * sax + 2.0_wp * cax
   data%eval status = 0
  CASE DEFAULT
                                     ! Error returns
   WRITE(6, "('UGO_solve exit status = ', I6) ") inform%status
   EXIT
 END SELECT
CALL UGO_terminate( data, control, inform ) ! delete internal workspace
END PROGRAM GALAHAD_UGO_EXAMPLE2
```

This produces the same output.