



C interfaces to GALAHAD IR

Jari Fowkes and Nick Gould
STFC Rutherford Appleton Laboratory
Mon Feb 21 2022

1 GALAHAD C package ir	1
1.1 Introduction	1
1.1.1 Purpose	1
1.1.2 Authors	1
1.1.3 Originally released	1
2 File Index	3
2.1 File List	3
3 File Documentation	5
3.1 ir.h File Reference	5
3.1.1 Data Structure Documentation	5
3.1.1.1 struct ir_control_type	5
3.1.1.2 struct ir_inform_type	6
Index	7

Chapter 1

GALAHAD C package

1.1 Introduction

1.1.1 Purpose

Given a sparse symmetric $n \times n$ matrix $A = a_{ij}$ and the factorization of A found by the GALAHAD package SLS, this package **solves the system of linear equations $Ax = b$ using iterative refinement.**

Currently, only the control and inform parameters are exposed; these are provided and used by other GALAHAD packages with C interfaces.

1.1.2 Authors

N. I. M. Gould, STFC-Rutherford Appleton Laboratory, England.

C interface, additionally J. Fowkes, STFC-Rutherford Appleton Laboratory.

1.1.3 Originally released

October 2008, C interface January 2022

Chapter 2

File Index

2.1 File List

Here is a list of all files with brief descriptions:

ir.h	5
--------------------------------	---

Chapter 3

File Documentation

3.1 ir.h File Reference

```
#include <stdbool.h>
#include "galahad_precision.h"
```

Data Structures

- struct [ir_control_type](#)
- struct [ir_inform_type](#)

3.1.1 Data Structure Documentation

3.1.1.1 struct ir_control_type

control derived type as a C struct

Data Fields

bool	f_indexing	use C or Fortran sparse matrix indexing
int	error	unit for error messages
int	out	unit for monitor output
int	print_level	controls level of diagnostic output
int	itref_max	maximum number of iterative refinements allowed
real_wp_	acceptable_residual_relative	refinement will cease as soon as the residual $\ Ax - b\ $ falls below $\max(\text{acceptable_residual_relative} * \ b\ , \text{acceptable_residual_absolute})$
real_wp_	acceptable_residual_absolute	see acceptable_residual_relative
real_wp_	required_residual_relative	refinement will be judged to have failed if the residual $\ Ax - b\ \geq \text{required_residual_relative} * \ b\ $. No checking if required_residual_relative < 0
bool	record_residuals	record the initial and final residual
bool	space_critical	if space is critical, ensure allocated arrays are no bigger than needed
bool	deallocate_error_fatal	exit if any deallocation fails
char	prefix[31]	all output lines will be prefixed by <code>prefix(2:LEN(TRIM(.prefix))-1)</code> where prefix contains the required string enclosed in quotes, e.g. "string" or 'string'

3.1.1.2 struct ir_inform_type

inform derived type as a C struct

Data Fields

int	status	reported return status: <ul style="list-style-type: none">• 0 the solution has been found• -1 an array allocation has failed• -2 an array deallocation has failed
int	alloc_status	STAT value after allocate failure.
char	bad_alloc[81]	name of array which provoked an allocate failure
real_wp_	norm_initial_residual	infinity norm of the initial residual
real_wp_	norm_final_residual	infinity norm of the final residual

Index

ir.h, [5](#)
ir_control_type, [5](#)
ir_inform_type, [6](#)