

PEL MEL TECH

Matériels d'impression & routiere

性能特点 (Performance characteristics)

- 采用进口直线导轨传动，速度快，精度高，声音小，质量稳定。
- 自主研发的ARM控制系统，刻绘切割效果优良。
- 最快切割速度达1000mm/s
- 全面拓展多种传输接口，USB,U盘,(选配WIFI) 打造不同场景的高效切割体验。
- The imported linear guide rail is used for transmission, with fast speed, high precision, low sound and stable quality.
- The self-developed ARM control system has excellent engraving and cutting effects.
- The fastest cutting speed is up to 1000mm/s.
- Various transmission interfaces, USB, U disk(optional WIFI), which create an efficient cutting experience in different scenarios



不干胶半切
Sticker half cut



纸艺镂空切割
Paper art hollow cut



品牌切割
Brand Cutting



纸盒切割
Cartonmaking

性能参数/Technical Specifications

型号 Model	FC5070E	FC7090E
工作特性 Work Characteristics	电脑操作与切割同时进行，快速完成数据传输，可连续使用Computer operation and cutting carried out at same time with faster data transfer speed and support continuously cutting	
切割速度 Cutting speed	直线1000mm/s 曲线800mm/s	
切割厚度 Cut thickness	≤1mm	≤1mm
切割材料 Cutting material	PP纸、铜纸、车贴、光膜、镜膜、反光膜、地贴膜、七折、不干胶、磁性贴等(板材类需选配 加厚磨边刀)For perspective paper/bar stickers/light film/metal film/reflexive film/flooring film/clothboard	
切割方式 Cutting method	物理半刀全刀裁切Cutting way	
笔型/刀型 Pen/Blade Type	签字笔、油性笔、圆珠笔/特种乌钢刀Ordinary signature pens, oil-based pens, ballpoint pens/special black steel knives	
固定方式 Fixing method	双面胶黏贴/真空吸附 Double-frame adhesive/vacuum adsorption	
机械分辨率 Mechanical Resolution	0.05mm	0.05mm
软件分辨率 Software Resolution	0.025mm, 0.01mm, 0.1mm可选	
传输接口 Transmission interface	USB/U盘/选配WIFI USB/U DISK/WIFI(optional)	
机身内存 Body memory	256M	256M
指令系统 Command System	HP-GL兼容格式 HP-GL compatible	
数控面板 Numerical control panel	触摸屏显示 Touch screen	
工作电压/功率 Operating voltage / power	交流220V ± 10%/50Hz	
电机 Motor	步进电机/伺服电机 step /servo	
外形尺寸 Dimension	1180X985X920mm	1180X985X920mm
切割面积 Cutting area	700X500mm	700X500mm
运输重量 Shipping weight	130kg	130kg

Rue Camelia Quartier Berger Maarif
Bd Yaacoub El Mansour , Casablanca - Maroc

pelmeltechpurchasing@gmail.com

+212 6 60 40 08 94



Pel Meltech

