AtlasDesk | Company Overview

AtlasDesk is a fictional software company used solely for retrieval-augmented generation (RAG) experiments. All people, prices, dates, policies, and service details in this document are invented for testing.

Company profile

• Founded: 2018. Headquarters: Chennai, India.

• Main product: AtlasDesk Cloud, a subscription-based customer support and ticket-management platform.

• Primary customers: small and medium-sized businesses with 10 to 500 employees.

• Support languages: English and Tamil.

• Business hours: Monday to Friday, 9:00 AM to 6:00 PM India Standard Time (IST).

Product capabilities

AtlasDesk Cloud includes ticket assignment, shared inboxes, priority labels, customer profiles, automated email notifications, audit logs, and analytics dashboards. Administrators can configure role-based access control (RBAC) for agents, supervisors, and account owners.

Key contacts

Customer Support: support@atlasdesk.example. Billing: billing@atlasdesk.example. Security: security@atlasdesk.example. These .example addresses are fictional and should not be used to send real email.

Retrieval note

When answering questions, use the facts in this document rather than guessing. If a requested fact is not included, say the document does not specify it.

Plans, Pricing & Billing

Subscription plans

Plan	Monthly price	Included agents	Ticket limit / month
Starter	INR 1,499	5	2,000
Growth	INR 4,999	20	10,000
Enterprise	Custom quote	Unlimited	Custom

Trial and payment rules

• New organizations receive a 14-day free trial of the Growth plan. No credit card is required.

• Subscriptions are billed at the start of each billing period.

• Annual billing offers a 15% discount on the listed monthly equivalent, paid upfront.

• Accepted payment methods: credit card, debit card, and bank transfer.

• Taxes, where applicable, are added at checkout and are not included in the listed plan prices.

Cancellation and refunds

Account owners can cancel from Settings > Billing > Cancel Subscription. Cancellation takes effect at the end of the current paid billing period. Refund requests must be submitted within 7 calendar days of the first paid invoice. Renewal payments are not eligible for refunds under this fictional policy.

Upgrades and downgrades

Upgrades take effect immediately with prorated charges. Downgrades take effect at the next billing renewal. Enterprise customers must contact the billing team to change their contracts.

Technical Architecture & API

Technology stack

The AtlasDesk Cloud frontend uses React and TypeScript. The backend uses Node.js with Express. MongoDB stores organizations, users, tickets, and audit events. Redis caches short-lived session metadata. Files are stored in object storage. The platform is deployed in an India-based cloud region.

Authentication and access

API clients authenticate using a bearer access token in the Authorization header. Access tokens expire after 60 minutes. Refresh tokens expire after 14 days. RBAC roles are Owner, Supervisor, and Agent. Only Owners can change billing settings.

Example API endpoints

• GET /api/v1/tickets - list tickets for the authenticated organization.

• POST /api/v1/tickets - create a ticket; requires subject, description, and priority.

• PATCH /api/v1/tickets/:id - update an existing ticket.

• GET /api/v1/analytics/summary - retrieve ticket totals and response metrics.

Limits and reliability

The public API allows 120 requests per minute per organization. When the limit is exceeded, the server returns HTTP 429. The default API timeout is 30 seconds. A successful ticket creation returns HTTP 201. API availability target is 99.9% per calendar month, excluding announced maintenance.

Webhooks

Supported webhook events are ticket.created, ticket.updated, and ticket.closed. Webhook delivery is retried up to 3 times after transient failures. Event payloads include event_id, organization_id, event_type, and created_at.

Support, SLAs & Security

Support channels and response targets

Support is provided by email and an in-app help center. Live phone support is available only to Enterprise customers. All response targets below apply during business hours, Monday through Friday, 9:00 AM to 6:00 PM IST.

Severity	Definition	First response target
Critical	Production system unavailable	1 business hour
High	Major feature unusable	4 business hours
Normal	General issue or question	1 business day
Low	Feature suggestion	3 business days

Data protection

Data is encrypted in transit using TLS and encrypted at rest. Daily backups are retained for 30 days. Production access is limited to authorized operations staff and is logged. Customer data is not used to train public AI models.

Data retention and deletion

Closed tickets remain available while the subscription is active. Following account deletion, customer data is scheduled for deletion within 30 days, except records that must be retained for legal obligations. Backups may persist until their normal 30-day retention window ends.

Incident reporting

Suspected security incidents should be reported to security@atlasdesk.example. The security team aims to acknowledge valid reports within 2 business days.

Onboarding & Troubleshooting

How do I start a new organization?

Create an account, verify your email address, enter the organization name, and invite agents from Settings > Team. The initial account creator receives the Owner role. Trial organizations start on the Growth plan for 14 days.

How do I import existing tickets?

Owners and Supervisors can import a CSV file from Settings > Data Import. Required columns are subject, description, priority, and customer_email. Each CSV file can contain up to 5,000 ticket rows. Duplicate rows are not automatically removed.

Why am I receiving HTTP 429?

HTTP 429 means the organization exceeded 120 API requests per minute. Wait before retrying, apply exponential backoff, and avoid unnecessary polling. Repeated retries without delay can prolong rate limiting.

Can I recover a deleted ticket?

Tickets moved to Trash can be restored within 15 days. After 15 days, they are permanently deleted from the active application and cannot be restored through the user interface.

How are priority levels defined?

Supported ticket priority values are low, normal, high, and critical. The default for newly created tickets is normal unless a different priority is supplied.

Which details are intentionally unspecified?

This document does not state the company CEO, employee headcount, specific cloud vendor, exact database version, or whether a mobile app exists. A grounded RAG assistant should answer "Not specified in the document" rather than invent these details.

END OF KNOWLEDGE BASE