

main.jsx

```
import React from "react";
import ReactDOM from "react-dom/client";
import App from "./App";
import { Provider } from "react-redux";
import store from "./store";

ReactDOM.createRoot(document.getElementById("root")).render(
  <Provider store={store}>
    <App />
  </Provider>
);
```

App.jsx

```
import Counter from "./Counter";
import Todos from "./Todos";

function App() {
  return (
    <>
      <Counter />
      <Todos />
    </>
  );
}

export default App;
```

store.js

```
import { configureStore } from "@reduxjs/toolkit";

import counterReducer from "../counterSlice";

import todosReducer from "../todosSlice";

const store = configureStore({
  reducer: {
    counter: counterReducer,
    todos: todosReducer,
  },
});

export default store;
```

counterSlice.js

```
import { createSlice } from "@reduxjs/toolkit";

const counterSlice = createSlice({
  name: "counter",
  initialState: {
    count: 0,
  },

  reducers: {
    increment: (state) => {
      state.count += 1;
    },
  },
});
```

```
    decrement: (state) => {  
      state.count -= 1;  
    },  
  },  
});
```

```
export const {  
  increment,  
  decrement,  
} = counterSlice.actions;
```

```
export default counterSlice.reducer;
```

todosSlice.js

```
import { createSlice } from "@reduxjs/toolkit";
```

```
const todosSlice = createSlice({  
  name: "todos",  
  initialState: {  
    todos: [],  
  },
```

```
  reducers: {  
    addTodo: (state, action) => {  
      state.todos.push({  
        text: action.payload,  
        completed: false,  
      });
```

```
},  
},  
});
```

```
export const {addTodo,} = todosSlice.actions;  
export default todosSlice.reducer;
```

Counter.jsx

```
import {  
  useSelector,  
  useDispatch,  
} from "react-redux";  
  
import {increment, decrement} from "./counterSlice";  
  
function Counter() {  
  
  const count = useSelector( (state) => state.counter.count );  
  const dispatch = useDispatch();  
  
  return (  
    <>  
      <h1>  
        Count : {count}  
      </h1>  
  
      <button  
        onClick={() => dispatch(increment())}> + </button>
```

```
    <button onClick={() => dispatch(decrement())} > - </button>

  </>

);

}

export default Counter;
```

Todos.jsx

```
import { useState } from "react";

import { useSelector, useDispatch } from "react-redux";
import { addTodo } from "../todosSlice";

function Todos() {

  const [text, setText] = useState("");
  const todos = useSelector( (state) => state.todos.todos );
  const dispatch = useDispatch();

  return (

    <>

      <input type="text" value={text} onChange={(e) => setText(e.target.value)} />

      <button onClick={() => dispatch(addTodo(text))}> Add </button>

      {todos.map((todo, index) => ( <p key={index}> {todo.text}</p> ))}

    </>

  );

}
```

export default Todos;

Output:

