Curriculum

# SE Foundations Average: 137.49%

You have a captain's log due before 2024-04-21 (in 1 day)! Log it now! (/captain\_logs/5596018/edit)

# 0x03. C - Debugging

C Debugging

- Weight: 1
- An auto review will be launched at the deadline

## In a nutshell...

• Auto QA review: 40.0/40 mandatory

• Altogether: 100.0%

Mandatory: 100.0%

o Optional: no optional tasks

# Resources

#### Read or watch:

- Debugging (/rltoken/faGcpiJiejHH6GhqpmbhUw)
- Rubber Duck Debugging (/rltoken/RaecqJBNkmZ92vLMpNDuGg)

Debugging is the process of finding and fixing errors in software that prevents it from running correctly you become a more advanced programmer and an industry engineer, you will learn how to use debugging tools such as gdb or built-in tools that IDEs have. However, it's important to understand the concepts processes of debugging manually.

# He attac



# He protec



but most importantly

he prevent overflow on stac



# **Learning Objectives**

At the end of this project, you are expected to be able to explain to anyone (/rltoken/b8uX1nly0A55tWVIIRTaHQ), without the help of Google:

**General** 

· What is debugging

Q

- What are some methods of debugging manually
- (/). How to read the error messages

# Copyright - Plagiarism

- You are tasked to come up with solutions for the tasks below yourself to meet with the above learning objectives.
- You will not be able to meet the objectives of this or any following project by copying and pasting someone else's work.
- You are not allowed to publish any content of this project.
- Any form of plagiarism is strictly forbidden and will result in removal from the program.

# Requirements

# General

- Allowed editors: vi , vim , emacs
- All your files will be compiled on Ubuntu 20.04 LTS using gcc, using the options -Wall -Werror -Wextra -pedantic -std=gnu89
- All your files should end with a new line
- Your code should use the Betty style. It will be checked using betty-style.pl and betty-doc.pl
- A README.md file at the root of the repo, containing a description of the repository
- A README.md file, at the root of the folder of this project (i.e. 0x03-debugging), describing what this project is about

## **Quiz questions**

Great! You've completed the quiz successfully! Keep going! (Show quiz)

# **Tasks**

## 0. Multiple mains

mandatory

Score: 100.0% (Checks completed: 100.0%)

In most projects, we often give you only one main file to test with. For example, this main file is a test for a postitive\_or\_negative() function similar to the one you worked with in an earlier C project (/rltoken/IKcOFkG-GCivSDXgWgld2g):

```
farrie@ubuntu:/debugging$ cat main.c
#include "main.h"

/**

* main - tests function that prints if integer is positive or negative

* Return: 0

*/

int main(void)
{
    int i;
    i = 98;
    positive_or_negative(i);
    return (0);
}
carrie@ubuntu:/debugging$
```

```
carrie@ubuntu:/debugging$ cat main.h
#ifndef MAIN_H
#define MAIN_H

#include <stdio.h>

void positive_or_negative(int i);

#endif /* MAIN_H */
carrie@ubuntu:/debugging$
```

```
carrie@ubuntu:/debugging$ gcc -Wall -pedantic -Werror -Wextra -std=gnu89 positive_or_negativ
e.c main.c
carrie@ubuntu:/debugging$ ./a.out
98 is positive
carrie@ubuntu:/debugging$
```

Based on the main.c file above, create a file named <code>0-main.c</code>. This file must test that the function <code>positive\_or\_negative()</code> gives the correct output when given a case of <code>0</code>.

You are not coding the solution / function, you're just testing it! However, you can adapt your function from 0x01. C - Variables, if, else, while - Task #0 (/rltoken/IKcOFkG-GCivSDXgWgld2g) to compile with this main file to test locally.

- You only need to upload 0-main.c and main.h for this task. We will provide our own positive\_or\_negative() function.
- You are not allowed to add or remove lines of code, you may change only **one** line in this task.



(Arrie@ubuntu:/debugging\$ gcc -Wall -pedantic -Werror -Wextra -std=gnu89 positive\_or\_negative.c 0-main.c -o 0-main

carrie@ubuntu:/debugging\$ ./0-main

0 is zero

carrie@ubuntu:/debugging\$ wc -l 0-main.c

16 1-main.c

carrie@ubuntu:/debugging\$

## Repo:

• GitHub repository: alx-low\_level\_programming

• Directory: 0x03-debugging

• File: 0-main.c, main.h

☑ Done!

Check your code

**QA** Review

## 1. Like, comment, subscribe

mandatory

Score: 100.0% (Checks completed: 100.0%)

Copy this main file. Comment out (don't delete it!) the part of the code that is causing the output to go into an infinite loop.

- Don't add or remove any lines of code, as we will be checking your line count. You are only allowed to comment out existing code.
- You do not have to compile with -Wall -Werror -Wextra -pedantic for this task.

```
farrie@ubuntu:/debugging$ cat 1-main.c
#include <stdio.h>
 /**
 * main - causes an infinite loop
 * Return: 0
 */
 int main(void)
 {
          int i;
          printf("Infinite loop incoming :(\n");
          i = 0;
          while (i < 10)
                  putchar(i);
          printf("Infinite loop avoided! \\o/\n");
          return (0);
 carrie@ubuntu:/debugging$
Your output should look like this:
 carrie@ubuntu:/debugging$ gcc -std=gnu89 1-main.c -o 1-main
 carrie@ubuntu:/debugging$ ./1-main
 Infinite loop incoming :(
 Infinite loop avoided! \o/
 carrie@ubuntu:/debugging$ wc -l 1-main.c
 24 1-main.c
 carrie@ubuntu:/debugging$
Repo:
   • GitHub repository: alx-low_level_programming
   • Directory: 0x03-debugging
   • File: 1-main.c
 ☑ Done!
            Check your code
                             >_ Get a sandbox
                                                QA Review
```

2. 0 > 972? mandatory

Score: 100.0% (Checks completed: 100.0%)

This program prints the largest of three integers. (/)

```
carrie@ubuntu:/debugging$ cat 2-main.c
#include <stdio.h>
#include "main.h"
/**
* main - prints the largest of 3 integers
* Return: 0
*/
int main(void)
        int a, b, c;
        int largest;
        a = 972;
        b = -98;
        c = 0;
        largest = largest_number(a, b, c);
        printf("%d is the largest number\n", largest);
        return (0);
}
carrie@ubuntu:/debugging$
```

```
farrie@ubuntu:/debugging$ cat 2-largest_number.c
#include "main.h"
/**
 * largest_number - returns the largest of 3 numbers
 * @a: first integer
 * @b: second integer
 * @c: third integer
 * Return: largest number
 */
int largest_number(int a, int b, int c)
    int largest;
    if (a > b \&\& b > c)
        largest = a;
    }
    else if (b > a \&\& a > c)
        largest = b;
    }
    else
    {
        largest = c;
```

```
carrie@ubuntu:/debugging$ gcc -Wall -Werror -Wextra -pedantic -std=gnu89 2-largest_number.c
2-main.c -o 2-main
carrie@ubuntu:/debugging$ ./2-main
0 is the largest number
carrie@ubuntu:/debugging$
```

? That's definitely not right.

return (largest);

carrie@ubuntu:/debugging\$

}

}

Fix the code in 2-largest\_number.c so that it correctly prints out the largest of three numbers, no matter the case.

• Line count will not be checked for this task.

#### Repo:

- GitHub repository: alx-low\_level\_programming
- Directory: 0x03-debugging

```
• File: 2-largest_number.c, main.h
(/)
```

☑ Done!

Check your code

**>\_** Get a sandbox

**QA** Review

## 3. Leap year

mandatory

Score: 100.0% (Checks completed: 100.0%)

This program converts a date to the day of year and determines how many days are left in the year, taking leap year into consideration.

```
carrie@ubuntu:/debugging$ cat 3-main_a.c
#include <stdio.h>
#include "main.h"
/**
* main - takes a date and prints how many days are left in the year, taking
* leap years into account
* Return: 0
*/
int main(void)
{
    int month;
    int day;
    int year;
    month = 4;
    day = 01;
    year = 1997;
    printf("Date: %02d/%02d/%04d\n", month, day, year);
    day = convert_day(month, day);
    print_remaining_days(month, day, year);
    return (0);
}
carrie@ubuntu:/debugging$
```

```
prrie@ubuntu:/debugging$ cat 3-convert_day.c
#include "main.h"
/**
* convert_day - converts day of month to day of year, without accounting
* for leap year
* @month: month in number format
* @day: day of month
* Return: day of year
*/
int convert_day(int month, int day)
    switch (month)
    {
        case 2:
            day = 31 + day;
            break;
        case 3:
            day = 59 + day;
            break;
        case 4:
            day = 90 + day;
            break;
        case 5:
            day = 120 + day;
            break;
        case 6:
            day = 151 + day;
            break;
        case 7:
            day = 181 + day;
            break;
        case 8:
            day = 212 + day;
            break;
        case 9:
            day = 243 + day;
            break;
        case 10:
            day = 273 + day;
            break;
        case 11:
            day = 304 + day;
            break;
        case 12:
            day = 334 + day;
            break;
        default:
            break;
    }
    return (day);
```

```
carrie@ubuntu:/debugging$ cat 3-print_remaining_days.c
#include <stdio.h>
#include "main.h"
/**
* print_remaining_days - takes a date and prints how many days are
* left in the year, taking leap years into account
* @month: month in number format
* @day: day of month
* @year: year
* Return: void
*/
void print_remaining_days(int month, int day, int year)
    if ((year % 4 == 0 || year % 400 == 0) && !(year % 100 == 0))
    {
        if (month >= 2 \&\& day >= 60)
        {
            day++;
        }
        printf("Day of the year: %d\n", day);
        printf("Remaining days: %d\n", 366 - day);
    }
    else
    {
        if (month == 2 && day == 60)
        {
            printf("Invalid date: %02d/%02d/%04d\n", month, day - 31, year);
        }
        else
        {
            printf("Day of the year: %d\n", day);
            printf("Remaining days: %d\n", 365 - day);
        }
    }
}
carrie@ubuntu:/debugging$
```

parrie@ubuntu:/debugging\$ gcc -Wall -Werror -Wextra -pedantic -std=gnu89 3-convert\_day.c 3-print\_remaining\_days.c 3-main\_a.c -o 3-main\_a

carrie@ubuntu:/debugging\$ ./3-main\_a

Date: 04/01/1997
Day of the year: 91
Remaining days: 274

carrie@ubuntu:/debugging\$

Output looks good for 04/01/1997! Let's make a new main file 3-main\_b.c to try a case that is a leap year: 02/29/2000.

carrie@ubuntu:/debugging\$ gcc -Wall -Werror -Wextra -pedantic -std=gnu89 3-convert\_day.c 3-p

rint\_remaining\_days.c 3-main\_b.c -o 3-main\_b

carrie@ubuntu:/debugging\$ ./3-main\_b

Date: 02/29/2000

Invalid date: 02/29/2000
carrie@ubuntu:/debugging\$

? That doesn't seem right.

Fix the print\_remaining\_days() function so that the output works correctly for all dates and all leap years.

- Line count will not be checked for this task.
- You can assume that all test cases have valid months (i.e. the value of month will never be less than 1 or greater than 12) and valid days (i.e. the value of day will never be less than 1 or greater than 31).
- You can assume that all test cases have valid month/day combinations (i.e. there will never be a June 31st or November 31st, etc.), but not all month/day/year combinations are valid (i.e. February 29, 1991 or February 29, 2427).

## Repo:

- GitHub repository: alx-low\_level\_programming
- Directory: 0x03-debugging
- File: 3-print remaining days.c, main.h

☑ Done!

Check your code

**QA** Review