

IMA204_TP_DEFMODEL_LS_IMA201_2025- 26_STUDENTS_shared

January 4, 2026

```
[ ]: import numpy as np
import matplotlib
import skimage
import IPython
import imagecodecs #(New 2025)

import matplotlib.pyplot as plt
from IPython.display import HTML
from matplotlib import animation, rc

from skimage.color import rgb2gray
from skimage import data
from skimage.filters import gaussian
from skimage.segmentation import active_contour # For active_contour function
from skimage.util import random_noise

# For active_contour function
from skimage.segmentation import chan_vese, morphological_chan_vese,
    ↪ checkerboard_level_set, morphological_geodesic_active_contour

# For some image filtering
from skimage.morphology import white_tophat, black_tophat, disk

import skimage.io

from IPython.core.interactiveshell import InteractiveShell
InteractiveShell.ast_node_interactivity = "all"

# PRINT VERSIONS
print("np.__version__",np.__version__)
print("matplotlib.__version__",matplotlib.__version__)
print("skimage.__version__",skimage.__version__)
print("IPython.__version__",IPython.__version__)
print("imagecodecs.__version__",imagecodecs.__version__)
```

```

[ ]: def edge_map(img,sigma):
    blur = skimage.filters.gaussian(img,sigma)
    return skimage.filters.sobel(blur)

def edge_map2(img,sigma):
    blur = skimage.filters.gaussian(img,sigma)
    return skimage.filters.scharr(blur)

def subtract_background(image, radius=5, light_bg=False):
    str_el = disk(radius)
    if light_bg:
        return black_tophat(image, str_el)
    else:
        return white_tophat(image, str_el)

def define_initial_circle(R0,r0,c0,Nber_pts=400):
    # Define initial contour shape
    s = np.linspace(0, 2*np.pi, Nber_pts)
    Radius = R0
    r = r0 + Radius*np.sin(s)
    c = c0 + Radius*np.cos(s) #col
    init = np.array([r, c]).T
    return init

## Create slides for animation
def animate_cv(image, segs, interval=1000):
    fig, ax = plt.subplots(figsize=(8, 8))
    ax.imshow(image, cmap='gray');
    im = ax.imshow(segs[0], alpha=0.5, cmap='inferno');
    ax.axis('off')

    def init():
        im.set_data(segs[0])
        return [im]

    def animate(i):
        im.set_array(segs[i])
        return [im]

    anim = animation.FuncAnimation(fig, animate, init_func=init,
                                   frames=len(segs), interval=1000, blit=True);
    return anim

def animate_snake(image, segs, interval=500):

```

```

fig, ax = plt.subplots(figsize=(6, 6))
ax.imshow(image, cmap='gray');
# im = ax.imshow(segs[0], alpha=0.5, cmap='inferno');
#ax.plot(segs[0][:, 1], segs[0][:, 0], '--r', lw=3)
ax.axis('off')
line, = ax.plot([], [], '-r', lw=2)

def init():
    line.set_data(segs[0,:,1],segs[0,:,0])
    return [line,]

def animate(i):
    line.set_data(segs[i,:,1],segs[i,:,0])
    return [line,]

anim = animation.FuncAnimation(fig, animate, init_func=init,
                               frames=len(segs), interval=1000, blit=True);
return anim

#####
def store_evolution_in(lst):
    """Returns a callback function to store the evolution of the level sets in
    the given list.
    """

    def _store(x):
        lst.append(np.copy(x))

    return _store

```

1 Read images

This part reads a series of images that you can then use in various tests. Note that some images are provided with ground-truth masks of structures of interest: 1. OCT_tissue 2. CTabd (CT of the abdomen) 3. US nodule (Ultrasound image with a nodule) 4. images_blood_cells/XX.png [several images available]

```

[ ]: # import warnings
# warnings.filterwarnings( "ignore", module = "matplotlib\.*" )
# skimage.io.imshow(img_mask)

# Binary images - w/o ground truth
img_star = skimage.io.imread('./images_misc/smooth_star.png', as_gray_
    ↪ True)

```

```

edge_star          = edge_map(img_star, sigma=0)
img_star_noisy     = skimage.io.imread('./images_misc/smooth_star_noisy.png',
    ↪as_gray = True)
edge_star_noisy    = edge_map(img_star_noisy, sigma=0)
img_binshape       = skimage.io.imread('./images_misc/binary_shape_2024.png',
    ↪as_gray = True)
edge_binshape      = edge_map(img_binshape, sigma=0)
img_cardiacshape   = skimage.io.imread('./images_misc/cardiac_mri_mask.png',
    ↪as_gray = True)
edge_cardiacshape  = edge_map(img_cardiacshape, sigma=0)

# Microscopy images - w/o ground truth # line changed 2025
img_hela           = skimage.io.imread('./images_misc/hela_big.png')

# OCT eye images - w/o ground truth
img_oct_eye        = skimage.io.imread('./images_misc/OCT_normal.jpeg', as_gray =
    ↪True)
img_oct_eye        = np.squeeze(img_oct_eye)
img_oct_eye        = img_oct_eye.astype('float64')
img_oct_eye        = img_oct_eye/np.max(img_oct_eye)
edge_oct_eye       = edge_map(img_oct_eye, sigma=2)

# CHANGED
img_oct_eye2       = skimage.io.imread('./images_misc/OCT200.bmp', as_gray = True)
img_oct_eye2       = img_oct_eye2/np.max(img_oct_eye2)
edge_oct_eye2      = edge_map(img_oct_eye2, sigma=2)

# CT abdo images - with ground truth
img_CTabd         = skimage.io.imread('./images_misc/CT_kidney_im.png', as_gray =
    ↪True)
edge_CTabd        = edge_map(img_CTabd, sigma=2)
gt_CTabd          = skimage.io.imread('./images_misc/CT_kidney_mask.png', as_gray =
    ↪True)
edge_gt_CTabd     = edge_map(gt_CTabd, sigma=2)

#CHANGED # Cell images - with ground truth
img_cell          = skimage.io.imread('./images_blood_cells/0000186.png', as_gray =
    ↪True)
edge_cell         = edge_map(img_cell, sigma=2)
#skimage.io.imshow(img_cell)
gt_cell           = skimage.io.imread('./masks_blood_cells/0000186.png', as_gray = True)
edge_gt_cell      = edge_map(gt_cell, sigma=2)

```

```

# Cell image - challenge multi
img_cell2      = skimage.io.imread('./images_misc/cell_00236.tif', as_gray =
    ↪True)
edge_cell2     = edge_map(img_cell2, sigma=2)
gt_cell2       = skimage.io.imread('./images_misc/cell_00236_label.tif',
    ↪as_gray = True)
edge_gt_cell2  = edge_map(gt_cell2, sigma=2)

# Hela Cell image - Cell tracking challenge
img_helat1     = skimage.io.imread('./images_misc/hela_t001.tif', as_gray =
    ↪True)
edge_helat1    = edge_map(img_helat1, sigma=2)
gt_helat1      = skimage.io.imread('./images_misc/hela_mask001.tif', as_gray =
    ↪True)
edge_gt_helat1 = edge_map(gt_helat1, sigma=2)

# Fluo Cell image - Cell tracking challenge
img_fluo       = skimage.io.imread('./images_misc/fluo000.tif', as_gray = True)
edge_fluo      = edge_map(img_fluo, sigma=2)
gt_fluo        = skimage.io.imread('./images_misc/fluo000_seg.tif', as_gray =
    ↪True)
edge_gt_fluo   = edge_map(gt_fluo, sigma=2)

# OCT image of tissue - with ground truth
img_oct_tissue = skimage.io.imread('./OCT_myocardium/case272.tif', as_gray =
    ↪True)
edge_oct_tissue = edge_map(img_oct_tissue, sigma=2)
gt_oct_tissue   = skimage.io.imread('./OCT_myocardium/case272_label.tif',
    ↪as_gray = True)
edge_gt_oct_tissue = edge_map(gt_oct_tissue, sigma=2)

# US image of a nodule - with ground truth
img_USnodule   = skimage.io.imread('./thyroid_nodule/1074.png', as_gray = True)
edge_USnodule  = edge_map(img_USnodule, sigma=2)
gt_USnodule    = skimage.io.imread('./thyroid_nodule/1074_mask.png', as_gray =
    ↪True)
edge_gt_USnodule = edge_map(gt_USnodule, sigma=2)

#CHANGED # Challenge image 2026
img_challenge  = skimage.io.imread('./challenge_image_snake/
    ↪lung_slicesaxial_230_image.png', as_gray = True)
edge_challenge = edge_map(img_challenge, sigma=2)
gt_challenge   = skimage.io.imread('./challenge_image_snake/
    ↪lung_slicesaxial_230_mask.png', as_gray = True)

```

```

edge_gt_challenge = edge_map(gt_challenge, sigma=2)

# PLOTS

fig, axes = plt.subplots(6,4, figsize=(8, 8))
ax = axes.ravel()

ax[0].imshow(img_cell, cmap=plt.cm.gray);
ax[1].imshow(edge_cell, cmap=plt.cm.gray);
ax[2].imshow(gt_cell, cmap=plt.cm.gray);
ax[3].imshow(edge_gt_cell, cmap=plt.cm.gray);

ax[4].imshow(img_CTabd, cmap=plt.cm.gray);
ax[5].imshow(edge_CTabd, cmap=plt.cm.gray);
ax[6].imshow(gt_CTabd, cmap=plt.cm.gray);
ax[7].imshow(edge_gt_CTabd, cmap=plt.cm.gray);

ax[8].imshow(img_fluo, cmap=plt.cm.gray);
ax[9].imshow(edge_fluo, cmap=plt.cm.gray);
ax[10].imshow(gt_fluo, cmap=plt.cm.gray);
ax[11].imshow(edge_gt_fluo, cmap=plt.cm.gray);

ax[12].imshow(img_oct_tissue, cmap=plt.cm.gray);
ax[13].imshow(edge_oct_tissue, cmap=plt.cm.gray);
ax[14].imshow(gt_oct_tissue, cmap=plt.cm.gray);
ax[15].imshow(edge_gt_oct_tissue, cmap=plt.cm.gray);

ax[16].imshow(img_cardiacshape, cmap=plt.cm.gray);
ax[17].imshow(edge_cardiacshape, cmap=plt.cm.gray);

ax[18].imshow(img_oct_eye, cmap=plt.cm.gray);
ax[19].imshow(edge_oct_eye, cmap=plt.cm.gray);

ax[20].imshow(img_star, cmap=plt.cm.gray);
ax[21].imshow(edge_star, cmap=plt.cm.gray);
ax[22].imshow(img_star_noisy, cmap=plt.cm.gray);
ax[23].imshow(edge_star_noisy, cmap=plt.cm.gray);

for i in range(0,24):
    ax[i].set_xticks([]), ax[i].set_yticks([]);
fig.tight_layout()
plt.show();

```

2 Image properties:

2.1 Range of values and data type matter ...

Some routines won't work if your image type is int8 or uint8... Here is how to check your image data type

And regularly check your image content in terms of: * intensities range of values * distributions of intensities via its histogram

```
[ ]: img_test = img_challenge #img_star_noisy#img_oct_eye #img_CTabd #img_cell
Sigma_val = 2
edge_test = edge_map(img_test, sigma=Sigma_val)

## Print some basic image properties
print("Image size of img_test is: ", img_test.shape)
print("Data type of img_test is: ", img_test.dtype)
print("min - max value in image:" , np.min(img_test), np.max(img_test))

## Code to plot a Histogram
hist_test, bins_test = np.histogram(img_test.flatten(), bins=256)
hist_edge_test, bins_edges_test = np.histogram(edge_test.flatten(), bins=256)

fig, axes = plt.subplots(2,2, figsize=(4, 4))
ax = axes.ravel()
ax[0].imshow(img_test, cmap=plt.cm.gray);
ax[0].set_title("Original Im", fontsize=6);
ax[1].plot(bins_test[0:-1],hist_test);
ax[1].set_title("Hist Im", fontsize=6);
ax[2].imshow(edge_test, cmap=plt.cm.gray);
ax[2].set_title("Edge Map Im", fontsize=6);
ax[3].plot(bins_edges_test[0:-1],hist_edge_test);
ax[3].set_title("Hist Edge map", fontsize=6);
fig.tight_layout()
plt.show();
```

3 Edge maps

Deformable models rely on edge maps. Most routines have their own strategy coded to compute the edge map.

- Edge maps usually involve smoothing of the image, to be robust to noise. Make sure you understand how this is controlled in the routine you use.
- Edge maps usually show pixels with high gradient magnitudes in white (high values)
- Most deformable model routines can be fed directly with an Edge Map rather than the original image as its input

- Some routine expect to be fed with an inverse edge map where high gradient locations have small values, to stop the contour via a velocity set to ~zero.

```
[ ]: img_to_test = img_cell
print("Data type of img_test is: ", img_test.dtype)
print("min - max value in image:" , np.min(img_test), np.max(img_test))

Font_size = 9

# Classic Edge map with Gaussian smoothing controled by sigma
edge_test1      = edge_map(img_to_test, sigma=1)
edge_test2      = edge_map(img_to_test, sigma=2)
edge_test2_1    = np.log2((edge_test2*100)+1)
edge_test1_2    = edge_map(np.log2((img_to_test+1)*100), sigma=2)

# Inversed Edge map
# Returns Edge map = 1.0 / np.sqrt(1.0 + alpha * gradnorm)
edge_inv_test   = skimage.segmentation.inverse_gaussian_gradient(img_to_test,
    ↪alpha=1.0, sigma=2.0)

fig, axes = plt.subplots(2,3, figsize=(6, 6))
ax = axes.ravel()

ax[0].imshow(img_to_test, cmap=plt.cm.gray);
ax[0].set_title("Original image", fontsize=Font_size);
ax[1].imshow(edge_test1, cmap=plt.cm.gray);
ax[1].set_title("Edge map sigma = 1", fontsize=Font_size);
ax[2].imshow(edge_test2, cmap=plt.cm.gray);
ax[2].set_title("Edge map sigma = 2", fontsize=Font_size);
ax[3].imshow(edge_inv_test, cmap=plt.cm.gray);
ax[3].set_title("Edge map inversed + sigma = 2", fontsize=Font_size);
ax[4].imshow(edge_test2_1, cmap=plt.cm.gray);
ax[4].set_title("Log(Edge map) + sigma = 2", fontsize=Font_size);
ax[5].imshow(edge_test1_2, cmap=plt.cm.gray);
ax[5].set_title("Edge map on Log+ sigma = 2", fontsize=Font_size);

for i in range(0,6):
    ax[i].set_xticks([]), ax[i].set_yticks([]);

fig.tight_layout()
plt.show();
```

4 Image transforms

Let you test some image transformations based on morphological operators and histogram manipulation. When transforming image contrast, it is always interesting to look at the differences

between the original image and the transformed version.

```
[ ]: img_ori_to_test = img_helat1; #img_cell #img_CTabd #img_oct_eye #img_CTabd
img_to_test      = img_ori_to_test
epsilon         = 0.000001 #to prevent log on 0
img_eps         = np.full_like(img_to_test, epsilon)
PRE_ENHANCE     = 1
OPTION_ENHANCE  = 4 # can be 0 (nothing) OR 1,2,3,4 for different enhancement
    ↪ options
Font_size      = 9

# Run all OPTION_ENHANCE for display here
gamma_corrected = skimage.exposure.adjust_gamma(img_to_test, 0.8)
logarithmic_corrected = skimage.exposure.adjust_log(img_to_test, gain=
    ↪ 1, inv=True)
img_open        = skimage.morphology.diameter_opening(img_to_test, 40,
    ↪ connectivity=2)
img_adapteq     = skimage.exposure.equalize_adapthist(img_to_test,
    ↪ clip_limit=0.03)

# PRE ENHANCEMENT OPTIONS:
if PRE_ENHANCE==1:
    if OPTION_ENHANCE==1:
        # Gamma
        img_to_test = gamma_corrected
    elif OPTION_ENHANCE==2:
        # Logarithmic (O = gain*log(1 + I)) or if Inv (O = gain*(2**I - 1))
        img_to_test = logarithmic_corrected
    elif OPTION_ENHANCE==3:
        # Morpho Opening
        img_to_test = img_open
    elif OPTION_ENHANCE==4:
        # Contrast Limited Adaptive Histogram Equalization (CLAHE).
        img_to_test = img_adapteq

# Enhance details either dark around light background of vice versa with the
    ↪ Top-Hat transform
Radius_val = 15
img_test1 = subtract_background(img_to_test, radius=Radius_val, light_bg=False)
img_test2 = subtract_background(img_to_test, radius=Radius_val, light_bg=True)

# SHOW OUTPUTS
fig, axes = plt.subplots(2,5, figsize=(10, 4), constrained_layout=True)
ax = axes.ravel()
Shrink_factor_colormap = 0.5
ax[0].imshow(img_ori_to_test, cmap=plt.cm.gray);
ax[0].set_title("Ori", fontsize=6);
```

```

ax[1].imshow(img_open, cmap=plt.cm.gray);
ax[1].set_title("Opening", fontsize=Font_size);
ax[2].imshow(gamma_corrected, cmap=plt.cm.gray);
ax[2].set_title("Gamma correction", fontsize=Font_size);
ax[3].imshow(logarithmic_corrected, cmap=plt.cm.gray);
ax[3].set_title("Log correction", fontsize=Font_size);
ax[4].imshow(img_adapteq, cmap=plt.cm.gray);
ax[4].set_title("Adapt Hist Eq", fontsize=Font_size);

ax[5].imshow(img_test1, cmap=plt.cm.gray);
ax[5].set_title("Tophat Dark bkg", fontsize=Font_size);
ax[6].imshow(img_test2, cmap=plt.cm.gray);
ax[6].set_title("Tophat Light bkg", fontsize=Font_size);

tmp_show = ax[7].imshow(img_to_test-img_test2, cmap=plt.cm.gray);
ax[7].set_title("Diff: (Ori-Light bkg)", fontsize=Font_size);
plt.colorbar(tmp_show,ax=ax[7], shrink=Shrink_factor_colormap, location='right')

tmp_show = ax[8].imshow(abs(img_to_test-img_test2), cmap=plt.cm.gray);
ax[8].set_title("Diff: abs(Ori-Light bkg)", fontsize=Font_size);
plt.colorbar(tmp_show,ax=ax[8], shrink=Shrink_factor_colormap, location='right')

tmp_show = ax[9].imshow(np.log2(abs(img_to_test-img_test2+img_eps)), cmap=plt.
    ↪cm.gray);
ax[9].set_title("Diff: log(abs(Ori-Light bkg))", fontsize=Font_size);
plt.colorbar(tmp_show,ax=ax[9], shrink=Shrink_factor_colormap, location='right')

for i in range(0,10):
    ax[i].set_xticks([]), ax[i].set_yticks([]);

#fig.tight_layout() # not compatible with option constrained_layout=True in plt.
    ↪subplots needed to display the colorbar
plt.show();

```

5 Seg #1:

5.0.1 Snake on a binary shape + noise effects

This part of the practical work uses the routine **active_contour** from **skimage**. Default **parameter values** are: * $\alpha=0.01$ (Snake length shape parameter. Higher values makes snake contract faster.) * $\beta=0.1$ (Snake smoothness shape parameter. Higher values makes snake smoother.) * $\gamma=0.01$ (Explicit time stepping parameter - Equivalent to the viscosity of the environment) * $\max_px_move=1.0$

There are two **other parameters** that define the final image information used to define external forces used to define regions. $\text{img} = w_line \times \text{img} + w_edge \times \text{edge}$: * $w_line_val=0$ (default) | $=1$

if want to input `_edge` map directly. Use negative values to attract toward dark * `w_edge_val= 1` (default) | `= 0` if do not want to use internal edge map. Use negative values to repel snake from edges

5.1 TODO:

Provide answers in text boxes **Q1.1.** Run the code for `img_to_seg=img_cardiacshape` using `img_ori` and all parameter values as provided, except for changing the `R0` value. Comment on behavior for: - `R0=20`:

- `R0=30`:

- `R0=50`:

*** **Q1.2.** For `R0=30` test the segmentation without smoothing. Comment on the segmentation quality for: - no smoothing:

Q1.3. Now run the segmentation on the **noisy version** of the image. 2 types of noise are simulated: (1) Additive Gaussian noise, (2) Speckle (multiplicative) noise. **Q1.3a** Check **appearance** of the 2 noisy images. What is the main difference and why? **Answer:**

Q1.3b Using `R0=50`, run the segmentation on the noisy images with **smoothing** (`Niter_smooth= 1`). Comment on segmentation quality or issues for: **Answer:** - Speckle noise + smoothing:

- Gaussian noise + smoothing:

```
[ ]: # 1ST image
img_ori      = img_cardiacshape; r0 = 150; c0=150; R0 = 20
img_noisy    = random_noise(img_ori, mode='gaussian', mean = 0.1,clip =_
↳True)
img_noisy2   = random_noise(img_ori, mode='speckle', mean = 0.1,clip = True)

# Choose image to segment
img_to_seg   = img_ori
#img_to_seg  = img_noisy
img_to_seg_raw = img_to_seg # to plot later on

alpha_val   = 0.01 ; beta_val = 0.1 ;gamma_val = 0.01;
convergence_val = 1e-4;Niter_snake = 1800;

# Initialise contour
init = define_initial_circle(R0,r0,c0)

# Pre-smooth the image
Niter_smooth = 1 # set to 0 for no smoothing
img_to_seg    = gaussian(img_to_seg, Niter_smooth, preserve_range=False)
```

```

# Run active contour
snake1 = active_contour(img_to_seg,
                        init, max_num_iter=1, convergence=convergence_val,
                        alpha=alpha_val, beta=beta_val, gamma=gamma_val)
snake10 = active_contour(img_to_seg,
                        init, max_num_iter=10, convergence=convergence_val,
                        alpha=alpha_val, beta=beta_val, gamma=gamma_val)
snake_max = active_contour(img_to_seg,
                        init, max_num_iter=Niter_snake,
                        ↪convergence=convergence_val,
                        alpha=alpha_val, beta=beta_val, gamma=gamma_val)

# Display results
fig, axes = plt.subplots(1,2, figsize=(8, 4),constrained_layout=True)
ax = axes.ravel()
Font_size = 9
ax[0].imshow(img_to_seg_raw, cmap=plt.cm.gray);
ax[0].set_xticks([]), ax[0].set_yticks([]);
ax[0].set_title("Image to segment", fontsize=Font_size);

ax[1].imshow(img_to_seg, cmap=plt.cm.gray);
ax[1].plot(init[:, 1], init[:, 0], '--y', lw=1);
ax[1].plot(snake10[:, 1], snake1[:, 0], '-b', lw=1);
ax[1].plot(snake10[:, 1], snake10[:, 0], '-g', lw=1);
ax[1].plot(snake_max[:, 1], snake_max[:, 0], '-r', lw=2);
ax[1].set_xticks([]), ax[1].set_yticks([]);
ax[1].axis([0, img_to_seg.shape[1], img_to_seg.shape[0], 0]);
ax[1].set_title("Smoothed image + Seg", fontsize=Font_size);

plt.show();

```

6 Seg #2:

6.0.1 Snake on Cell image

We are using here `img_to_seg = img_cell` for which you have a ground truth mask `gt_cell` of the target segmentation for the bright central cell.

6.1 TODO

Q2.1a Segment large cell: Run with code as provided and comment quality of the segmentation versus the ground-truth. **Answer:** ***

Q2.1b Segment large cell: Run with code as provided but on version of the `img_cell` transformed (above) as `img_adapteq`. Explain the appearance of `img_adapteq` and if you think this image is

better suited for the segmentation task and the original `img_cell`. **Answer:** ***

Q2.2 Now aiming to segment the **internal dark part** of the cell: choose the version of the image you want to use (`img_cell` OR `img_adapteq`) and change only values for `Niter_smooth` and `R0` and propose a solution that works. **Answer:** managed to obtain a correct segmentation with `img = XX`, `Niter_smooth = XX` and `R0 = XX` ***

Q2.3 Segment small cell: Run with the proposed initialisation and check correct segmentation of the small cell. Now change ONLY `img` versions (original or `img_adapteq`) with the proposed initial contour parameters [`r0 = 203`; `c0=76`; `R0 = 25`] and confirm which version(s) generate(s) a perfect segmentation of the small cell and why. **Answer:** managed to obtain a correct segmentation with : ***

```
[ ]: # Input image and parameter values
img_to_seg = img_cell;
#img_to_seg = img_adapteq;
img_gt = gt_cell;

# Large cell - ground truth provided
r0 = 128; c0=128; R0 = 73
# Small cell - no ground truth
#r0 = 203; c0=76; R0 = 25

alpha_val = 0.01 ; beta_val = 0.1 ; gamma_val = 0.01;
convergence_val = 1e-4; Niter_snake = 1200;

# Pre smooth the image
Niter_smooth = 1
img_to_seg = gaussian(img_to_seg, Niter_smooth, preserve_range=False)

# Initialise contour
init = define_initial_circle(R0,r0,c0)

# Run active contour
snake30 = active_contour(img_to_seg,
                        init, max_num_iter=30, convergence=convergence_val,
                        alpha=alpha_val, beta=beta_val, gamma=gamma_val)
snake = active_contour(img_to_seg,
                      init, max_num_iter=Niter_snake,
                      ↪convergence=convergence_val,
                      alpha=alpha_val, beta=beta_val, gamma=gamma_val)
```

```

# Display results
fig, axes = plt.subplots(1,2, figsize=(8, 4),constrained_layout=True)
ax      = axes.ravel()
Font_size = 9

ax[0].imshow(img_to_seg, cmap=plt.cm.gray)
ax[0].plot(init[:, 1], init[:, 0], '--c', lw=1.5)
ax[0].plot(snake30[:, 1], snake30[:, 0], '-b', lw=1.5)
ax[0].plot(snake[:, 1], snake[:, 0], '-r', lw=2)
ax[0].set_xticks([]), ax[0].set_yticks([])
ax[0].axis([0, img_to_seg.shape[1], img_to_seg.shape[0], 0])

ax[1].imshow(img_gt, cmap=plt.cm.gray)
ax[1].plot(init[:, 1], init[:, 0], '--c', lw=1)
ax[1].plot(snake30[:, 1], snake30[:, 0], '-b', lw=1.5)
ax[1].plot(snake[:, 1], snake[:, 0], '-r', lw=2)
ax[1].set_xticks([]), ax[1].set_yticks([])
ax[1].axis([0, img_to_seg.shape[1], img_to_seg.shape[0], 0])

plt.show();

```

7 Seg # 3

7.0.1 A tool to visualise the deformations of the snake over iterations

7.1 TO DO:

Run the code with provided parameter values. * **Q3.1 Checking the video (you can control manually the slider on the video image to move forward or backward in time), would you confirm that the snake has converged and is stable and why? Answer**:**

Q3.2a Change ONLY `alpha_val = 0.1`. Same question **Answer:**

Q3.2b Running 800 iterations is faster for `alpha_val = 0.1` than for `alpha_val = 0.01`. Propose an explanation for this: **Answer:**

```

[ ]: img_to_seg      = img_cell
     img_to_seg_ori  = img_to_seg

# Init to segment cell
r0 = 128; c0=128; R0 = 33
alpha_val = 0.01 ; beta_val = 0.1 ; gamma_val = 0.01;
convergence_val = 1e-4; Niter_snake = 800;

# Pre filter the image

```

```

img_adapteq = skimage.exposure.equalize_adapthist(img_to_seg, clip_limit=0.03)
#img_to_seg = img_adapteq

# Pre smooth the image
Niter_smooth = 1
img_to_seg = gaussian(img_to_seg, Niter_smooth, preserve_range=False)

# Initialise contour
init = define_initial_circle(R0,r0,c0)

# Run active contour while saving intermediate contours to see deformations
segs = []
print('start')
for i in range(1,Niter_snake,20):
    print(i, " ", end='')
    segs.append(active_contour(img_to_seg, init, max_num_iter=i,
    ↪convergence=convergence_val,
        alpha=alpha_val, beta=beta_val, gamma=gamma_val))

print('stop')
np.save('ANIM_contours.npy', np.array(segs))

# display animation
segs = np.load('ANIM_contours.npy')
anim = animate_snake(img_to_seg, segs);
HTML(anim.to_html5_video())

```

8 Seg # 4

8.0.1 Snake with Gradient Vector Flow (GVF)

This implementation of the GVF is performed by computing the edge map, diffusing the gradient over the whole image and directly input the GVF_edge_map to be used as external forces by setting $w_{line}=1$ and $w_{edge}=0$ in the active_contour function.

8.1 TODO:

Q4.1.1 Report the visual differences in the GVF_map between $\mu=5$ and $\mu=15$. **Answer:**

Q4.1.2 What is the μ parameter controlling? **Answer:** The μ parameter controls for XX.

Q4.2 Why does $\mu=15$ enable to obtain a correct segmentation? **Answer:** **Q4.3** Report what happens when segmenting with the classic Edge_map rather than the GVF_map. **Answer:** ***

```

[ ]: import gvf_elsa2
from gvf_elsa2 import gradient_field, gradient_vector_flow

```

```

# Image to seg
img_to_seg = img_star
r0 = 64; c0=64; R0 = 50

alpha_val = 0.01 ; beta_val = 0.1; gamma_val = 0.01;
convergence_val = 1e-4; Niter_snake = 200;

# Initialise contour
init = define_initial_circle(R0,r0,c0,Nber_pts=400)

# Compute edge map and gvf
img_to_seg = img_to_seg.astype(np.float32) / np.max(img_to_seg)
Edge_map = edge_map(img_to_seg,sigma=1)

fx, fy = gradient_field(img_to_seg)
gx, gy = gradient_vector_flow(fx, fy, mu=5)
GVF_map = np.sqrt(gx**2 + gy**2)

# Run active contour while saving intermediate contours to see deformations
Map_to_seg = Edge_map

# Run active contour while saving intermediate contours to see deformations
segs = []
print('start')
for i in range(1,Niter_snake,10):
    print(i, " ", end='')
    segs.append(active_contour(Map_to_seg, init, max_num_iter=i,
    ↪convergence=convergence_val,
        alpha=alpha_val, beta=beta_val, gamma=gamma_val,
        w_line=1,w_edge=0))

print('stop')
np.save('ANIM_contours.npy', np.array(segs))

# display animation
segs = np.load('ANIM_contours.npy')
anim = animate_snake(Map_to_seg, segs);
HTML(anim.to_html5_video())

```

9 Seg # 5:

9.0.1 The active contour with fixed end points

You will now run the `active_contour` with the option to maintain some points from the initial contour fixed. You are working with the `img_oct_eye` which shows different layers of the retina. The `active_contour` routine is called to use directly the `Edge_map` as input.

9.1 TO DO:

Q5.1 Rank the 4 options for the `Edge_map` options from top to worst to segment the two layers wrt to segmentation quality and robustness to layer selection. **Answer:** Ranked `Edge_map` options from best to worst: 1. `edge_test1` 2. `edge_test2` 3. `edge_test2_l` 4. `edge_testl_2` **Q5.2** Change the code to handle `img_to_seg = img_oct_eye2` (pre read above) for segmenting the top similar layer of the retina as with `img_to_seg = img_oct_eye` **Answer:** Show code + results on notebook

```
[ ]: img_to_seg = img_oct_eye

# init for 1st layer
r_left = 103; r_right=138; c_left=0; c_right = 510
# init for 2nd layer
#r_left = 158; r_right=204; c_left=0; c_right = 510

alpha_val = 0.01 ; beta_val = 0.1; gamma_val = 0.01;
convergence_val = 1e-4; Niter_snake = 500;
w_line_val=1; w_edge_val=0;

# Computation of edge maps
edge_test1      = edge_map(img_to_seg, sigma=1)
edge_test2      = edge_map(img_to_seg, sigma=2)
edge_test2_l    = np.log2((edge_test2*100)+1)
edge_testl_2    = edge_map(np.log2((img_to_seg+1)*100), sigma=2)

# Selection of edge_map to use
Edge_map        = edge_test1

# Initialise contour
Nber_pts_contour = 200
r                = np.linspace(r_left, r_right, Nber_pts_contour)
c                = np.linspace(c_left, c_right, Nber_pts_contour)
init            = np.array([r, c]).T

snake = active_contour(Edge_map,
```

```

        init,
        ↪boundary_condition='fixed-fixed',max_num_iter=Niter_snake,
        alpha=alpha_val, beta=beta_val, gamma=gamma_val,
        w_line=w_line_val, w_edge=w_edge_val)

# FIGURE

fig, ax = plt.subplots(figsize=(9, 5));
ax.imshow(Edge_map[0:300,:], cmap=plt.cm.gray);
ax.plot(init[:, 1], init[:, 0], '--y', lw=2);
ax.plot(snake[:, 1], snake[:, 0], '-r', lw=3);
ax.set_xticks([]), ax.set_yticks([]);
ax.set(xlim=(0, 500));
plt.show();

```

10 Seg # 6

BONUS - Optional ### Your turn on proposing a motivated pipeline using the snake capabilities from the `active_contour` function

10.1 TODO:

Use the **2026 snake Challenge image** (`img_challenge` and `gt_challenge` pre-read above) and propose a segmentation pipeline using the `active_contour` approach. Options on points to work on include: * Pre-filter the image as you wish * Manually or automatically position the initial contour * Provide one segmentation result or merge several solutions in a probability map * Detect issues in contour shape during deformations and propose an early stop criteria. * Provide a semi-automated pipeline for the left lung and infer an automated extension for the right lung.

Q6 Provide code + visual illustrations of results **Answer *****

11 STOP HERE FOR 1st PART -

12 Seg #7

12.0.1 Test on the Geometric Level-Set formulation using the Chan-Vese model.

Skimage provides two implementations of the Chan-Vese approach: [1] **chan_vese**: implementation or original paper and [2] **morphological_chan_vese**: faster implementation but less precise. “Active contours without edges implemented with morphological operators. It is required that the inside of the object looks different on average than the outside (i.e., the inner area of the object should be darker or lighter than the outer area on average).”

The contours of objects are now encoded in a level set function **Phi**.

The **initialisation** tested here is with a “checkerboard” pattern for 2 classes (object and background).

For the **chan_vese** original implementation, the **hyper-parameters** include: * mu = edge regularisation terms. Similar to ‘edge length’ weight parameter. Higher mu values will produce ‘smoother’ contours. * dt = delta time step for each optimisation step.

* lambda1, lambda2 = weights in the cost metric to balance inside and outside homogeneity terms.

* tol= Tolerance to test if the contours are “stable” and stop early.

The output contains: cv[0]=Seg and cv[1]=Phi

For the **morphological_chan_vese** implementation, the only **hyper-parameter** is the number of smoothing iterations (1 to 4 recommended).

12.1 TO DO:

Using **Chan-Vese** original implementation:

Q7.1 Run the code on **img_hela** with 200 iterations using **raw_image** (**PRE_FILTER=0**) and the same image after **histogram equalisation** (**PRE_FILTER=1**) . What are the differences observed in the segmentation results and in the numerical values of the Phi level set function?

Answers:

Q7.1a : Differences in the segmentation results:

Q7.1b : Differences in the Phi values:

Q7.2 Run the code on **img_hela** with **2** iterations only using **raw_image**. Why does the segmentation result show the structures to segment but with “gray” values while this is a binary image?

Answer:

Q7.3 Run the code on **img_hela** with 200 iterations using **raw_image** but changing the **tol_val = 10-5**. Comment on major differences observed compared to **tol_val = 10-3** and propose an explanation: **Answer:**

Q7.4 Run the code on **img_cell** with 200 iterations using **raw_image**. Comment on the issue observed with this method if you compare to the segmentation targeted given in **gt_cell**: **Answer:**

Q7.5 Using **morphological_chan_vese** implementation (change options in code accordingly). Run the code using Morpho CV on **img_cell** with 100 iterations + using raw image. **Answers:**

Q7.5a Comment on benefits observed on result from this implementation of Chan-Vese:

Q7.5b Comment on issues observed on result when changing **Init_method_cv_morpho=“disk”** instead of **Init_method_cv_morpho= “checkerboard”** as initialisation method:

Q7.5c Do you think the background average value `c_i` has become darker or brighter?

Q7.5d Can you propose an explanation based on the position and size of the initial disk versus the image content?:

12.2 Bonus points

Q7.6: Segment the image: `img_helat1` using: `chan_vese_ori` implementation + `PRE_FILTER = 3` + baseline values for these parameters: `mu_val=0.5` ; `lambda1_val=1`; `lambda2_val=1`; `tol_val=1e-3`; `dt_val=0.5`. Compare and comment segmentation results as follows: **Answers:** **Q7.6a** Explain why `PRE_FILTER = 3` helps compared to `PRE_FILTER = 0`:

Q7.6b Explain effect seen when changing only `mu_val=0.5` to `mu_val=1`:

Q7.6c Explain effect seen when changing only `lambda1_val=1` to `lambda1_val=1.5`:

```
[ ]: img_raw      = img_hela # img_helat1; NB: img_hela[0] changed 2025 for some ↵
      ↪environments - img_cell, img_fluo
img_to_seg = img_raw

# PARAMETERS
mu_val=0.5 ; lambda1_val=1; lambda2_val=1;
tol_val=1e-3; dt_val=0.5

smoothing_val = 1; # used by cv_morpho
PRE_FILTER     = 0; # 0=none ,1=histeq, 2=gamma gaon; 3=sigmoid trnsform

Num_iter_cv_ori      = 200
Num_iter_cv_morpho   = 200

CHAN_VESE_ORI  = 1
Init_method_cv_ori      = "checkerboard" # "checkerboard" or "disk"
Init_method_cv_morpho   = "checkerboard" # "disk" : (center=center of image, ↵
      ↪radius = 75% of img size)

# Pre-filter (TO TURN ON IF ASKED)
if PRE_FILTER==1:
    img_to_seg = skimage.exposure.equalize_adapthist(img_raw, clip_limit=0.03)
elif PRE_FILTER==2:
    img_to_seg = skimage.exposure.adjust_gamma(img_raw, 0.2)
elif PRE_FILTER==3:
    img_to_seg = skimage.exposure.adjust_sigmoid(img_raw, cutoff=0.5, ↵
      ↪gain=100, inv=False)
```

```

# Select image to segment and print information
print("min - max value in image:" , np.min(img_to_seg), np.max(img_to_seg))
print("size of image:" , img_to_seg.shape)

# run segmentation
if CHAN_VESE_ORI == 1:
    # STANDARD implementation from original paper
    init_ls = checkerboard_level_set(img_to_seg.shape, 45)

    cv = chan_vese(img_to_seg, mu=mu_val, lambda1=lambda1_val,
↳ lambda2=lambda2_val,
                    tol=tol_val, dt=dt_val,
                    max_num_iter=Num_iter_cv_ori,
↳ init_level_set=Init_method_cv_ori,
                    extended_output=True)

    # Show results
    Nber_plots = 6
    fig, axes = plt.subplots(2,3,figsize=(7, 7))
    ax = axes.ravel()
    ax[0].imshow(img_raw, cmap=plt.cm.gray)
    ax[0].set_title("Image raw", fontsize=12);
    ax[1].imshow(img_to_seg, cmap=plt.cm.gray)
    ax[1].set_title("Image to segment", fontsize=12);
    ax[2].imshow(1-cv[0], cmap=plt.cm.gray)
    title = f'C-V with - {len(cv[2])} iterations'
    ax[2].set_title(title, fontsize=12)

    ax[3].imshow(img_to_seg[200:300,200:300], cmap=plt.cm.gray)
    ax[3].set_title("Zoom on img to seg", fontsize=12);
    ax[4].imshow(1-cv[0][200:300,200:300], cmap=plt.cm.gray)
    ax[4].set_title("Zoom result", fontsize=12);
    tmp_show = ax[5].imshow(cv[1][200:300,200:300], cmap=plt.cm.jet)
    ax[5].set_title("Zoom final Phi", fontsize=12);
    plt.colorbar(tmp_show,ax=ax[5], shrink=0.75, location='right')

    print("min - max value in Seg (cv[0]):" , np.min(cv[0]), np.max(cv[0]))

else:
    # FASTER implementation with morphological operators BUT LESS PRECISE
    cv = morphological_chan_vese(img_to_seg, num_iter=Num_iter_cv_morpho,
                                smoothing=smoothing_val,
↳ init_level_set=Init_method_cv_morpho)

```

```

# Show results
Nber_plots = 2
fig, ax = plt.subplots(1,2,figsize=(7, 7))
ax[0].imshow(img_to_seg, cmap=plt.cm.gray)
ax[0].set_title("Image to segment", fontsize=12);
ax[1].imshow(1-cv, cmap=plt.cm.gray)
title = f'C-V_morph with - {Num_iter_cv_morpho} iterations'
ax[1].set_title(title, fontsize=12)

for i in range(0,Nber_plots):
    ax[i].set_xticks([]), ax[i].set_yticks([]);

plt.show();

```

13 Seg # 8

13.1 Geodesic active contours with balloon force

Controlling level-set deformable model with speed values acting on the contour. You are provided with a tool to track the deformation patterns of the active contour over iterations.

The geometric active contour routine is **morphological_geodesic_active_contour** which deforms a level set function with local speed values. It has the following **hyper-parameters** : * **Thresh_cont_val** = 'auto'=> np.percentile(image, 40) (default if 'auto') | pixels < Thresh_cont_val are considered borders. The evolution of the contour will stop on these pixels. (It is used in the code to cancel the balloon speed using: Threshold_mask_balloon = image > threshold / np.abs(Balloon_weight)) * **Balloon_weight** = 1 (default) | weight of the balloon force. Can be ponegative to inflate/deflate * **Smooth_cont_iter** = 1 (default) | Number of times a smoothing operator is applied per iteration

14 TO DO:

Q8.1: Segment the **img_cell** with the provided configuration to **inflate** the initial contour using Conf #1. What is the issue when compared to the targeted ground-truth (GT) segmentation ?

Answer:

Q8.2: Segment the **img_cell** with the provided configuration to **inflate** the initial contour using Conf #2. What has happened that could not have happened with a parametric snake implementation ? **Answer:**

Q8.3: Now Segment the **img_CTabd** with the provided configuration Conf #3 to **deflate** the initial contour. Adjust balloon parameter accordingly. Also change: (1) Threshold_contour_level = 20 to Threshold_contour_level = 10 and (2) Smooth_cont_iter = 2 to Smooth_cont_iter = 1 . Why do you think the geodeic active contour was able to segment only one kidney?: **Answer:**

14.1 Bonus points

Q8.4: Comment why changing the two parameter values for **img_CTabd** was necessary to obtain de segmentation of the kidney. What effect do they have on the behavior of the deformable contour?

Answer:

```
[ ]: # img_cell:
img_raw      = img_cell ;
gt_seg       = gt_cell;

# img_CTabd:
# img_raw     = img_CTabd ;
# gt_seg      = gt_CTabd

# Select img to segment
img_to_seg = img_raw;

# Conf #1: Disk parameters to initialise shape for INFLATION on img_cell
r0 = 130;  c0 = 125 ; R0 = 30  # inflate
# Conf #2: Disk parameters to initialise shape for INFLATION on img on img_cell
r0 = 130;  c0 = 125 ; R0 = 45  # inflate
# Conf #3: Disk parameters to initialise shape for DEFLATION on img
#r0 = 130;  c0 = 155 ; R0 = 85  # deflate TO KEEP ON CTabd

# Hyper-parameter for Balloon velocity:
Balloon_weight = 0.87 ; # +/- to Inflate or deflate

# Additional Hyper-parameters for geodesic deformable model:
Threshold_contour_level = 20; # lower:= moves more over small gradients
Smooth_cont_iter        = 2 ; # Number of times a smoothing operator is applied
    ↳per iteration
Niter_snake              = 600

# Hyper-parameter for preparing the input data:
INV_EDGE_MAP = 1;

# Inverse edge image: Compute the magnitude of the gradients in the image and
# then inverts the result in the range [0, 1]
if INV_EDGE_MAP:
    img_to_seg = skimage.segmentation.inverse_gaussian_gradient(
        img_to_seg,alpha=50,sigma=2)

# Print information
print("min - max value in image to seg:" , np.min(img_to_seg), np.
    ↳max(img_to_seg))
```

```

print("size of image to seg:" , img_to_seg.shape)

# Set and print threshold used in morphological_geodesic_active_contour
# Areas of the inverse edge map with value < Threshold will be considered
↳ borders
Threshold_contour = np.percentile(img_to_seg, Threshold_contour_level);
Thresh_cont_val    = Threshold_contour ; # 'auto' ; # pixels < Thresh_cont_val
↳ are considered borders. The evolution of the contour will stop on these
↳ pixels.
print("threshold used in morphological_geodesic", Thresh_cont_val)

# initialise call back
evolution = []
callback = store_evolution_in(evolution)

# Initialise contour as a disk
init_ls = skimage.segmentation.disk_level_set(img_to_seg.shape,
↳ center=[r0,c0], radius=R0)

# Run geodesic active contour
ls      = morphological_geodesic_active_contour(
            img_to_seg, Niter_snake, init_ls,
            smoothing=Smooth_cont_iter, balloon=Balloon_weight,
            threshold=Thresh_cont_val,
            iter_callback=callback);

# Figure with plots of level-set evolution
fig, axes = plt.subplots(2, 2, figsize=(8, 8));
ax = axes.flatten();

ax[0].imshow(img_raw, cmap="gray");
ax[0].set_axis_off();
contour = ax[0].contour(evolution[0], [0.5], colors='y');
#contour.collections[0].set_label("Contours"); #removed 2025
ax[0].contour(ls, [0.5], colors='r');
ax[0].set_title("Img ori + contours", fontsize=12);

ax[1].imshow(img_to_seg, cmap="gray");
ax[1].set_axis_off();
contour = ax[1].contour(evolution[0], [0.5], colors='y');
#contour.collections[0].set_label("Contours"); #removed 2025
#contour.set_label("Contours"); # option to update 2025
#ax[0].contour(ls, [0.5], colors='r');#removed 2025
ax[1].contour(ls, [0.5], colors='r');
ax[1].set_title("Img to seg + contours", fontsize=12);
#ax[1].contour(ls, [0.5], colors='r');#removed 2025

```

```

ax[2].imshow(img_to_seg, cmap="gray");
ax[2].set_axis_off();
contour = ax[2].contour(evolution[0], [0.5], colors='y');
#contour.collections[0].set_label("Contours"); # removed 2025
title = f'Morphological GAC Curve evolution';
ax[2].set_title(title, fontsize=12);
for i in range(1, Niter_snake-1, 5):
    contour = ax[2].contour(evolution[i], [0.5], linewidths=0.5, colors='r'); #
    ↪changed 2025 0.01 to 0.5

ax[3].imshow(gt_seg, cmap="gray");
ax[3].set_axis_off();
ax[3].contour(ls, [0.5], colors='r');
ax[3].set_title("GT segmentation mask", fontsize=12);

plt.show();

```