

- Review
- Standard Library
 - <stdio.h>
 - <ctype.h>
 - <stdlib.h>
 - <assert.h>
 - <stdarg.h>
 - <time.h>

6.087 Lecture 10 – January 25, 2010

- Review
- Standard Library
 - `<stdio.h>`
 - `<ctype.h>`
 - `<stdlib.h>`
 - `<assert.h>`
 - `<stdarg.h>`
 - `<time.h>`

Review: Libraries

- linking: binds symbols to addresses.
- static linkage: occurs at compile time (static libraries).
- dynamic linkage: occurs at run time (shared libraries).
- shared libraries:
 - ld.so - locates shared libraries
 - ldconfig - updates links seen by ld.so
 - dlopen(), dlsym(), dlclose() - load shared libraries on demand.
- compiling static libraries: gcc, ar
- compiling shared libraries: gcc, ldconfig

Review: BTree

- generalized search tree—multiple children.
- except for root, each node can have between t and $2t$ children.
- tree is **always** balanced.
- Used in file systems, databases etc.

Review: Priority Queue

- abstract data structure: many implementations
- common implementations: heaps,bst,linked list
- elements are queued and dequeued in order of priority.
- operations:
`peek() , insert() , extract-max() / extract-min()`

- Review
- Standard Library
 - `<stdio.h>`
 - `<ctype.h>`
 - `<stdlib.h>`
 - `<assert.h>`
 - `<stdarg.h>`
 - `<time.h>`

<stdio.h>: Opening, closing files

FILE* fopen(**const char*** filename,**const char*** mode)

- mode can be "r"(read),"w"(write),"a"(append).
- "b" can be appended for binary input/output (unnecessary in *nx)
- returns NULL on error.

FILE* freopen(**const char*** filename,**const char*** mode,FILE* stream)

- redirects the stream to the file.
- returns NULL on error.
- Where can this be used? (redirecting stdin,stdout,stderr)

int fflush (FILE* stream)

- flushes any unwritten data.
- if stream is NULL flushes all outputs streams.
- returns EOF on error.

<stdio.h>: File operations

int remove(**const char*** filename)

- removes the file from the file system.
- retrn non-zero on error.

int rename(**const char*** oldname,**const char*** newname)

- renames file
- returns non-zero on error (reasons?: permission, existence)

<stdio.h>:Temporary files

FILE* tmpfile(void)

- creates a temporary file with mode "wb+".
- the file is removed **automatically** when program terminates.

char* tmpnam(char s[L_tmpnam])

- creates a string that is not the name of an existing file.
- return reference to internal static array if s is NULL.
Populate s otherwise.
- generates a new name every call.

<stdio.h>: Raw I/O

size_t fread(**void*** ptr, size_t size, size_t nobj, FILE* stream)

- reads at most `nobj` items of size `size` from stream into `ptr`.
- returns the number of items read.
- `feof` and `ferror` must be used to test end of file.

size_t fwrite(**const void*** ptr, size_t size, size_t nobj, FILE* stream)

- write at most `nobj` items of size `size` from `ptr` onto `stream`.
- returns number of objects written.

<stdio.h>: File position

int fseek(FILE* stream, **long** offset, **int** origin)

- sets file position in the stream. Subsequent read/write begins at this location
- origin can be SEEK_SET, SEEK_CUR, SEEK_END.
- returns non-zero on error.

long ftell (FILE* stream)

- returns the current position within the file. (limitation? long data type).
- returns -1L on error.

int rewind(FILE* stream)

- sets the file pointer at the beginning.
- equivalent to fseek(stream,0L,SEEK_SET);

<stdio.h>: File errors

void clearerr (FILE* stream)

- clears EOF and other error indicators on stream.

int feof (FILE* stream)

- return non-zero (TRUE) if end of file indicator is set for stream.
- only way to test end of file for functions such as `fwrite()`, `fread()`

int ferror (FILE* stream)

- returns non-zero (TRUE) if **any** error indicator is set for stream.

<ctype.h>: Testing characters

isalnum(c)	isalpha(c) isdigit (c)
iscntrl (c)	control characters
isdigit (c)	0-9
islower(c)	'a'-'z'
isprint (c)	printable character (includes space)
ispunct(c)	punctuation
isspace(c)	space, tab or new line
isupper(c)	'A'-'Z'

<string.h>: Memory functions

void* memcpy(**void*** dst,**const void*** src,size_t n)

- copies n bytes from src to location dst
- returns a pointer to dst.
- src and dst **cannot overlap**.

void* memmove(**void*** dst,**const void*** src,size_t n)

- behaves same as memcpy () function.
- src and dst **can overlap**.

int memcmp(**const void*** cs,**const void*** ct,int n)

- compares first n bytes between cs and ct.

void* memset(**void*** dst,int c,int n)

- fills the first n bytes of dst with the value c.
- returns a pointer to dst

<stdlib.h>:Utility

double atof(**const char*** s)

int atoi(**const char*** s)

long atol(**const char*** s)

- converts character to float, integer and long respectively.

int rand()

- returns a pseudo-random numbers between 0 and RAND_MAX

void srand(**unsigned int** seed)

- sets the seed for the pseudo-random generator!

<stdlib.h>: Exiting

void abort(**void**)

- causes the program to terminate abnormally.

void exit (**int** status)

- causes normal program termination. The value `status` is returned to the operating system.
- 0 `EXIT_SUCCESS` indicates successful termination. Any other value indicates failure (`EXIT_FAILURE`)

<stdlib.h>:Exiting

void atexit (**void** (*fcn) (**void**))

- registers a function `fcn` to be called when the program terminates normally;
- returns non zero when registration cannot be made.
- After `exit()` is called, the functions are called in reverse order of registration.

int system(**const char*** cmd)

- executes the command in string `cmd`.
- if `cmd` is not null, the program executes the command and returns exit status returned by the command.

<stdlib.h>: Search and sorting

```
void* bsearch(const void* key, const void* base,
             size_t n, size_t size,
             int (*cmp)(const void* keyval, const void* datum));
```

- searches base[0] through base[n-1] for *key.
- function cmp() is used to perform comparison.
- returns a pointer to the matching item if it exists and NULL otherwise.

```
void qsort(void* base, size_t n,
           size_t sz,
           int (*cmp)(const void*, const void*))!
```

- sorts base[0] through base[n-1] in ascending/descending order.
- function cmp() is used to perform comparison.

<assert.h>:Diagnostics

void assert(**int** expression)

- used to check for invariants/code consistency during debugging.
- does nothing when expression is true.
- prints an error message indicating, expression, filename and line number.

Alternative ways to print filename and line number during execution is to use: `__FILE__`, `__LINE__` macros.

<stdarg.h>: Variable argument lists

Variable argument lists:

- functions can variable number of arguments.
- the data type of the argument can be different for each argument.
- atleast one mandatory argument is required.
- Declaration:

`int printf (char* fmt ,...); /*fmt is last named argument*/`

`va_list ap`

- `ap` defines an iterator that will point to the variable argument.
- before using, it has to be initialized using `va_start`.

<stdarg.h>: Variable argument list

`va_start(va_list ap, lastarg)`

- `ap` `lastarg` refers to the **name** of the last named argument.
- `va_start` is a macro.

`va_arg(va_list ap, type)`

- each call of `va_arg` points `ap` to the next argument.
- `type` has to be inferred from the fixed argument (e.g. `printf`) or determined based on previous argument(s).

`va_end(va_list ap)`

- must be called before the function is exited.

<stdarg.h>:Variable argument list(cont.)

```
int sum(int num,...)
{
    va_list ap; int total=0;
    va_start(ap,num);
    while(num>0)
    {
        total+=va_arg(ap,int);
        num--;
    }
    va_end(ap);
    return total;
}
```

```
int suma=sum(4,1,2,3,4); /* called with five args */
int sumb=sum(2,1,2); /* called with three args */
```

time_t, clock_t, **struct** tm data types associated with time.

struct tm:	int tm_sec	seconds
	int tm_min	minutes
	int tm_hour	hour since midnight (0,23)
	int tm_mday	day of the month (1,31)
	int tm_mon	month
	int tm_year	years since 1900
	int tm_wday	day since sunday (0,6)
	int tm_yday	day since Jan 1 (0,365)
	int tm_isdst	DST flag

<time.h>

clock_t clock()

- returns processor time used since beginning of program.
- divide by CLOCKS_PER_SEC to get time in seconds.

time_t time(time_t * tp)

- returns current time (seconds since Jan 1 1970).
- if tp is not NULL, also populates tp.

double difftime(time_t t1, time_t t2)

- returns difference in seconds.

time_t mktime(struct tm* tp)

- converts the structure to a time_t object.
- returns -1 if conversion is not possible.

`char* asctime(const struct tm* tp)`

- returns string representation of the form "Sun Jan 3 15:14:13 1988".
- returns static reference (can be overwritten by other calls).

`struct tm* localtime(const time_t * tp)`

- converts **calendar time** to local time".

`char* ctime(const time_t * tp)`

- converts **calendar time** to string representation of local time".
- equivalent to `sctime(localtime(tp))`!

<time.h>

```
size_t strftime (char* s, size_t smax, const char* fmt, const struct tm* tp)
```

- returns time in the desired format.
- does not write more than `smax` characters into the string `s`.

%a	abbreviated weekday name
%A	full weekday name
%b	abbreviated month name
%B	full month name
%d	day of the month
%H	hour (0-23)
%I	hour (0-12)
%m	month
%M	minute
%p	AM/PM
%S	second

MIT OpenCourseWare

<http://ocw.mit.edu>

6.087 Practical Programming in C

January (IAP) 2010

For information about citing these materials or our Terms of Use, visit: <http://ocw.mit.edu/terms>.