Anatomy of a Function
Scope
Parameters
Return vs Print
Multiple Returns
Function Decomposition
Update Functions
Containers
Lists
For-Each Loops
Dictionaries
Strings
Tuples
File Reading
Memory
Intro to References
Objects
Mutation
Guides
Python Documentation
Debugging Tips

Style Guide

## Multiple Returns

## Quest

Welcome to part 2 of our saga on return statements. We know what return statements are (statements that give back information from the function) and we know how to distinguish them from print statements. So what is left to learn? Well, as the title of this section suggests, it is possible to have multiple return statements in a function. WHAT? HOW is this possible? Let's see below.

```
def get_max(num1, num2):
    '''
    gets the maximum of the two input numbers
    params:
        num1 (int or float): the first input number
        num2 (int or float): the second input number
    returns: the maximum of num1 and num2
    '''
    if num1 > num2:
        | return num1
        return num2

    def main():
        print(get_max(4, 7))

        | main()
        | main()
        | main()
```

This code is completely valid. Let's discuss why. Based on what we know about if statements, any code not in an attached else statement should also run after the body of the if has finished executing (given that the condition was true). So why doesn't the second return statement run? As we've said before, return statements end the function. This means that if the conditional is true and return num1 runs, everything after that will not be executed. We never get to return num2 even though it is not in an else.

Let's look at another example. This example doesn't have multiple return statements in code, but it has a single return statement within a for loop that runs multiple times. What will this do?

## [A Buggy Code]

Huh. That's not what we wanted. We wanted our function to count all the way from one to the inputted number, but it only returned the first number. Even in for loops, the return statements end the function. The rest of the for loop is not executed, so the only number that is returned is 1. In this particular case, the issue can be fixed by changing the return statement to a print statement.

This solution does not actually lead to returning multiple things, but avoids having to do that all

together. We will see a few ways to return multiple things in later sections. Below is another example of how **not** to return multiple things:

## [A Buggy Code

As you can see, no error occurs, but the second return statement is completely ignored. If statements and conditionals allow for multiple return statements, but they cannot just exist side by side.