

① Git Clone

→ `git clone <repository-url>`. It is used to copy an remote Git repository to our local pc computer so that we can work on project locally. For example `git clone https://github.com/user/project.git`.

② Git Config

→ `git config <setting> <value>`. It is used to configure Git settings such as our user name and user email address. For example `git config --global user.name "jerry"`.

③ Git status:

→ `git status`. It is used to check the current status of files in the working directory including modified, staged and untracked files. For example `git status`.

④ Git add

→ `git add <filename>`. It is used to add modified or new files to the staging area before committing them. For example `git add index.html`.

⑤ Git commit

→ `git commit -m <"message">` It is used to save staged changes to the local git repository with a descriptive message. For example, `git commit -m "Added new"`

⑥ Git push

→ `git push <remote> <branch>`. It is used to upload local commits to a remote Git repository such as GitHub. For example: `git push origin main`.

⑦ Git branch

→ `git branch <branch name>`. It is used to create, check branches for developing features or making changes separately from main branch. For example `git branch login`.

⑧ Git merge

→ `git merge <branch name>`. It is used to combine the changes from another branch into the current branch. For example `git merge login`.

⑩ Git Pull

→ `git pull <remote> <branch>`. It is used to download the latest changes from a remote repository and merge them into the current branch. For example, `git pull origin main`.

⑪ Git fetch

→ `git fetch <remote>`. It is used to download the latest information and changes from a remote repo without automatically merging them into the current branch. For example, `git fetch origin`.

⑫ Git restore

→ `git restore <file-name>`. It is used to restore a file to its previous committed version and discard its unstaged changes.

`git restore --index <file-name>`