Canonical AI/ML Research Playbook

From Idea Discovery to Publishable Science: A Comprehensive Research Manual for AI/ML Researchers

---

Welcome: The Purpose of This Playbook

If you are an undergraduate, graduate, or early-career AI/ML researcher, welcome. Research can often feel like a black box. Academic papers present smooth, polished narratives where hypotheses seem obvious and experiments work seamlessly on the first attempt. In reality, **real research is an adaptive, non-linear evidence-building process** filled with unexpected findings, failed baselines, and constant pivots.

This document is your **single canonical reference manual**. It synthesizes insights from multiple senior AI/ML research guides (including Gemini, Claude, Antigravity, OpenResearch, and Cline sources) into a single, cohesive, non-duplicative operating system.

It is written in **plain, clear English** without compromising on technical rigor. It provides actionable frameworks, decision gates, stopping rules, and concrete AI/ML examples (spanning Vision-Language Models, Transformers, LLM reasoning, and computer vision) to help you move decisively from curiosity to publishable scientific contributions.

Master Table of Contents

- Part I — Understanding Research
  - 1. What Research Actually Is
  - 2. How Experienced Researchers Think
  - 3. Research vs Learning vs Engineering
  - 4. From Topic to Research Question: The Concept Ladder
- Part II — Finding a Research Question
  - 5. Entering a New Research Area
  - 6. Mapping the Research Territory
  - 7. Finding Interesting Phenomena and Problems
  - 8. Types of Research Gaps
  - 9. Finding a Genuine Gap
  - 10. Verifying the Gap
  - 11. Finding the Closest Existing Work
  - 12. Forming a Research Question
  - 13. Forming Competing Hypotheses
- Part III — Escaping Endless Topic Exploration
  - 14. Why Researchers Get Stuck Searching
  - 15. Exploration vs Commitment
  - 16. When Is Literature Search Enough? (Saturation Rules)

    - 17. Research Decision Gates
    - 18. Kill / Pivot / Narrow / Continue Decision Protocol
    - 19. The "No More Topic Hunting" Gate
- Part IV — Turning the Question into Research
    - 20. Minimum Discriminating Experiments (MDEs)
    - 21. Experimental Design and Variables
    - 22. Baselines and the Baseline Hierarchy
    - 23. Controls and Alternative Explanations
    - 24. Dataset and Evaluation Design
    - 25. The AI Failure Triad: Leakage, Shortcuts, and Underspecification
    - 26. Reproducibility and Code Integrity
    - 27. Research Engineering Architecture
- Part V — Running the Research
    - 28. Experiment → Evidence → Interpretation
    - 29. Systematic Error Analysis
    - 30. Handling Unexpected Results
    - 31. Value and Recovery of Negative Results
    - 32. Revising the Research Question
    - 33. Scope Control and Creep Prevention
    - 34. Research Logs and Decision Tracking
- Part VI — Turning Evidence into Contribution
    - 35. What Counts as a Scientific Contribution?
    - 36. From Results to Scientific Explanation
    - 37. Building the Evidence Chain
    - 38. Knowing When the Research Is Done
- Part VII — Thesis and Paper Pipeline
    - 39. Thesis Completion Pipeline
    - 40. Publishable Paper Completion Pipeline
    - 41. Reviewer / Adversarial Analysis ("Pre-Mortem")
    - 42. Publication Preparation and Writing Strategy
- Part VIII — The Reusable Research Operating System
    - 43. The Research State Machine
    - 44. Practical Research Artifacts
    - 45. Research Control Center
    - 46. Future Project Template
    - 47. Common Research Failure Modes
    - 48. Personal Failure-Prevention Rules
    - 49. Master Research Checklist
    - 50. One-Page Research Desk Reference
- Source Synthesis Note


Part I — Understanding Research

1. What Research Actually Is

Research is not the linear execution of a pre-planned project. It is a **falsification-driven search process under uncertainty**.

In software engineering, you know what target artifact you want to build (e.g., a web app, a faster database query, or a model deployment API), and success is binary: *does it work as specified?*

In scientific research, your goal is not to build an artifact, but to **test a claim about a underlying mechanism, limit, or phenomenon**.



A claim becomes research only when it is **falsifiable**—meaning you can design an experiment that could prove your explanation wrong.

---

2. How Experienced Researchers Think

Experienced researchers differ from novice researchers not in intelligence, but in their mental models and daily habits:

1. **Anomalies over Areas:** Novices look for broad fields ("I want to do LLM reasoning"). Experts look for specific anomalies ("Why does chain-of-thought prompting fail when variable names are swapped to non-standard symbols?").
2. **Adversarial Mindset:** Experienced researchers treat their own ideas as suspects. They actively design experiments intended to *break* their hypotheses rather than validate them.
3. **Cheapest Test First:** Before spending three weeks training a 70B parameter model, an expert designs a 10-minute experiment on synthetic data to check if the core mechanism holds.
4. **Tolerance for Re-scoping:** Experts expect the research question to evolve based on experimental evidence. Pivoting based on data is viewed as scientific progress, not failure.

---

3. Research vs Learning vs Engineering

It is vital to distinguish between three activities that feel productive but achieve completely different goals:

Activity	Core Question	Primary Output	Success Metric
Learning	*"Do I understand how this works?"*	Mental model, notes, tutorials	Ability to explain or implement existing methods
Engineering	*"Can I make this system meet specifications?"*	Working codebase, API, deployed model	System reliability, throughput, benchmark metric
Research	*"Why does this phenomenon occur, and what general principle governs it?"*	Evidence, causal explanations, validated claims	Survival against adversarial controls and falsification tests

> **Warning for Beginners:** Spending weeks reading 50 papers is *learning*. Building a sleek PyTorch training pipeline is *engineering*. You are only doing *research* when you are collecting empirical evidence to discriminate between competing explanations of an unresolved phenomenon.

---

4. From Topic to Research Question: The Concept Ladder

A major trap for beginners is trying to conduct research on a "topic" rather than a "falsifiable question." You must climb down the **Concept Ladder** to reach a precise research boundary.

```
Level 1: Broad Field
  └─ Level 2: Sub-Field
       └─ Level 3: Research Paradigm / Topic
            └─ Level 4: Specific Phenomenon / Anomaly
                 └─ Level 5: Verified Research Gap
                      └─ Level 6: Falsifiable Research Question
                           └─ Level 7: Competing Hypotheses
```

Concrete AI/ML Example:

1. **Broad Field:** Artificial Intelligence
2. **Sub-Field:** Vision-Language Models (VLMs)
3. **Topic:** Multimodal Hallucination
4. **Phenomenon / Anomaly:** VLMs generate descriptions of objects that are absent in dark or low-contrast visual regions.
5. **Verified Gap:** Prior work attributes hallucination to text-decoder language priors, but has not isolated whether feature norm collapse in the visual encoder causes visual tokens to lose signal strength under low contrast.
6. **Falsifiable Question:** Does visual encoder feature norm collapse cause text-decoder hallucination when image contrast drops below 20%?
7. **Competing Hypotheses:**
   - H_A **(Norm Collapse):** Low visual contrast reduces image patch token norms relative to text prompt norms, causing cross-attention weights to default to language priors.
   - H_B **(Attention Diffusion):** Low visual contrast causes cross-attention maps to spread uniformly across all background patches without reducing individual token norms.

Part II — Finding a Research Question

5. Entering a New Research Area

When entering an unfamiliar domain (e.g., State Space Models, Multimodal Alignment, Mechanistic Interpretability):


1. **Find 2 Anchor Survey Papers:** Read recent (last 12-18 months) survey papers to learn the standard domain terminology, canonical benchmarks, and taxonomy.
2. **Identify Top 3 Paradigm Papers:** Find the 3 seminal papers that established the current state-of-the-art architectures or formulations.

3. **Trace Key Terms:** Note the precise technical terms used by top authors. Searching for generic terms yields millions of irrelevant hits; searching for specific mechanism terms yields target literature.

---

6. Mapping the Research Territory

Build a **4-Quadrant Field Map** to visualize the research landscape before picking a topic:



---

7. Finding Interesting Phenomena and Problems

Real research questions originate from **phenomena and failures**, not from random brainstorming. The top sources of scientific phenomena in AI/ML are:

1. **Failure-Driven:** Model X achieves 92% benchmark accuracy but completely collapses when input images undergo minor Gaussian blur or brightness shifts.
2. **Contradiction-Driven:** Paper A claims attention entropy regularizes representation learning, while Paper B proves attention entropy causes representation collapse in deep layers.
3. **Assumption-Driven:** Method X assumes training samples are independent and identically distributed (i.i.d.), but real-world video streams exhibit heavy temporal correlation.
4. **Shortcut-Driven (Clever Hans Effect):** A medical image model achieves state-of-the-art pneumonia classification by detecting hospital tag watermarks in image corners rather than lung pathology.

---

8. Types of Research Gaps

Not all gaps are created equal. Understand the taxonomy of research gaps:

Gap Type	Definition	Scientific Value
Mechanistic Gap	We know method X works, but we do not know *why* or *how* internal components drive the performance.	**High**
Boundary / Limit Gap	We know method X works in domain A, but we do not know the exact conditions under which it breaks down in domain B.	**High**
Contradiction Gap	Two published studies report conflicting outcomes under seemingly identical configurations.	**High**
Combination / Extension Gap	Nobody has applied existing Method X to Dataset Y before.	**Low (Unless it reveals a new failure mode)**

> **Critical Warning:** "Nobody has done this before" is **not** a valid research gap on its own. It is often a trap. If nobody has combined Method X with Dataset Y, it may be because the combination is trivial, uninformative, or known to fail without providing any scientific insight.

---

9. Finding a Genuine Gap

To transform a weak observation into a genuine gap, use the **Gap Qualification Protocol**:

1. **Identify the Premise:** What does current literature assume to be true?
2. **Identify the Failure:** Where does that assumption break down in practice?
3. **Verify Non-Triviality:** Would fixing or explaining this failure require a non-obvious insight, or is it just a routine parameter tuning task?
4. **Verify Generality:** Does this failure affect an entire class of models or tasks, or is it an isolated bug in a single codebase?

---

10. Verifying the Gap

Before committing to a gap, you must perform **Adversarial Gap Verification**:

- Search Google Scholar and arXiv using *adversarial search queries* designed specifically to find papers that have already solved your exact idea.
- Combine your key mechanism terms with explicit claim terms:
  - `"[Mechanism Name]" "evaluation failure"`
  - `"[Mechanism Name]" "norm collapse"`
  - `"[Method A]" vs "[Method B]" benchmark`
- If an adversarial search returns 0 direct hits after testing 10 variations of mechanism keywords, your gap has survived initial verification.

---

11. Finding the Closest Existing Work

Identify the **3 Closest Papers** to your proposed work and construct a **Closest-Work Matrix**:

Paper	Problem Addressed	Core Assumption	Primary Failure Mode / Limitation	How Your Proposed Work Differs
Paper A (2023)	Object Hallucination	High-contrast inputs	Fails under low light / noise	Tests norm collapse in low contrast
Paper B (2024)	Cross-Attention Drift	Text-only triggers	Requires prompt tuning	Modifies visual token encoder directly
Paper C (2024)	Token Pruning	Uniform token distribution	Drops subtle spatial details	Preserves low-norm informative tokens

---

12. Forming a Research Question

A well-formed research question must be **precise, specific, and falsifiable**.

- **Bad (Vague):** "How can we improve Vision-Language Models?"
- **Better (Method-focused):** "Does adding visual feature normalization reduce hallucination in VLMs?"
- **Scientific (Falsifiable & Mechanistic):** "Does visual encoder feature norm collapse cause object hallucination in VLMs when image contrast drops below 20%, and does layer-wise token norm stabilization prevent this hallucination without degrading clean-image accuracy?"

---

13. Forming Competing Hypotheses

Never test a single hypothesis in isolation (H_1: "My method works"). This leads directly to confirmation bias. Always construct **Competing Hypotheses**:

- **Hypothesis A (H_A - Primary Mechanism):** The performance improvement is driven by stabilizing visual feature token norms, preventing language priors from overriding visual embeddings in cross-attention layers.
- **Hypothesis B (H_B - Parameter/Capacity Control):** The improvement is merely due to adding extra trainable parameters and compute capacity to the visual bottleneck.
- **Hypothesis C (H_C - Regularization Control):** The improvement is caused by implicitly smoothing gradient updates, acting as a simple weight-decay regularizer.

Part III — Escaping Endless Topic Exploration

14. Why Researchers Get Stuck Searching

Beginner researchers frequently fall into the **Endless Exploration Loop**:


```
Find Idea A —> Search Literature —> Find Idea B —> Compare A & B —> Doubt Both —> Search Literature
—> Repeat Indefinitely
```

This paralysis occurs because beginners seek **certainty before experimentation**. They want guaranteed success before running code. In research, certainty comes *only* from empirical evidence, never from reading more papers.

---

15. Exploration vs Commitment

Research requires a strict phase shift from **Exploration** (divergent thinking) to **Commitment** (convergent execution).



Once you pass the **Decision Gate**, literature reading is restricted to supporting your active experimental pipeline.

16. When Is Literature Search Enough? (Saturation Rules)

Stop searching literature immediately when you meet the **3 Saturation Heuristics**:

1. **Citation Closure:** Every new paper you open cites papers you have already read or cataloged.
2. **Method Predictability:** You can accurately predict the baselines, datasets, and evaluation metrics a new paper will use before reading its experimental section.
3. **Competitor Identification:** You can confidently name the top 3 direct competitor papers and explain how your hypothesis differs from theirs.

---

17. Research Decision Gates

Progress through your project using strict **Decision Gates**:


```
[Gate 1: Gap Verified] ──> [Gate 2: Closest Work Mapped] ──> [Gate 3: MDE Passed] ──> [Gate 4: Full Commitment]
```

At each gate, evaluate whether to proceed, pivot, or kill the project based on objective evidence rather than emotional attachment.

---

18. Kill / Pivot / Narrow / Continue Decision Protocol

When evaluating a research direction at a Decision Gate, apply this protocol:



- **Continue Condition:** MDE confirms H_A over H_B / H_C on synthetic/pilot data with statistically meaningful margin. Proceed to full evaluation.

---

19. The "No More Topic Hunting" Gate

To prevent endless topic hunting during thesis or project setup, enforce the **14-Day Hard Rule**:

> **The 14-Day Hard Rule:** If you spend 14 consecutive days searching literature and comparing topic ideas without writing an experimental script or testing a pilot data sample, you MUST freeze your top candidate question and execute a 48-hour Minimum Discriminating Experiment.

No further topic searching is permitted until the 48-hour experiment completes and produces empirical log files.

Part IV — Turning the Question into Research

20. Minimum Discriminating Experiments (MDEs)

A **Minimum Discriminating Experiment (MDE)** is the smallest, fastest, and cheapest experimental setup that can falsify at least one competing hypothesis while keeping another alive.

```
┌──────────────────────────────────────────────────────────────┐
│                      SLOW APPROACH (Bad)                     │
│ Build full transformer pipeline -> Train on 1M images for 4 days      │
│ -> Evaluate full benchmark -> Discover outcome is uninterpretable.    │
└──────────────────────────────────────────────────────────────┘

┌──────────────────────────────────────────────────────────────┐
│                      FAST MDE APPROACH (Good)                │
│ Synthesize 100 perturbed samples -> Measure feature token norms in 5m  │
│ -> Directly confirm or reject $H_A$ vs $H_B$ in 1 hour.                │
└──────────────────────────────────────────────────────────────┘
```

Characteristics of a Valid MDE:

- Runs in **under 2 hours** on available compute hardware.
- Uses toy data, synthetic probes, or pre-trained frozen checkpoints.
- Isolates a single variable to discriminate between Hypothesis A and Hypothesis B.

---

21. Experimental Design and Variables

Every rigorous research experiment must explicitly define its variable structure:

- **Independent Variable (IV):** The specific mechanism component you manipulate (e.g., visual token norm stabilization ON vs OFF).
- **Dependent Variable (DV):** The metric measuring the outcome (e.g., Object Hallucination Rate on low-contrast images).
- **Controlled Variables (CV):** Factors held constant across all runs (e.g., model architecture backbones, random seeds, learning rate schedules, prompt templates, evaluation sampling temperature).

---

22. Baselines and the Baseline Hierarchy

Never evaluate your proposed approach against weak, untuned, or missing baselines. Adhere strictly to the **Baseline Hierarchy**:

```
Level 4: Direct SOTA Competitors (Top 2-3 recent papers from top venues)
Level 3: Standard Established Method (Tuned with EQUAL compute and hyperparameter optimization)
Level 2: Ablated Version of Your Method (Your method with the key mechanism removed)
Level 1: Naive / Random Heuristic Baseline (Random guessing, majority class prediction)
```

> **The Equal-Compute Rule:** A baseline is invalid if your proposed method receives more training epochs, more parameters, or higher hyperparameter tuning effort than the baseline.

---

23. Controls and Alternative Explanations

To prove your mechanism is responsible for an observed gain, run explicit **Control Conditions**:

1. **Negative Control:** Test your method in a setup where the mechanism should provide *zero* benefit (e.g., high-contrast images where feature norm collapse does not occur). If your method still shows a gain, the improvement is caused by a general regularizer or artifact, not your hypothesized mechanism!
2. **Placebo / Parameter Control:** Replace your intelligent module with a random projection matrix or parameter-matched MLP. If it performs identically, your specific architectural design is unnecessary.

---

24. Dataset and Evaluation Design


Evaluation design determines whether your results reflect real capabilities or evaluation artifacts.

- **Split Integrity:** Never evaluate on data that shares source domains, time windows, or prompt structures with the training set.
- **Out-of-Distribution (OOD) Test Sets:** Always include at least one evaluation set that tests generalization under distribution shift (e.g., corrupted images, domain shifts, adversarial rephrasings).
- **Metric Sanity:** Never rely on a single aggregate metric (e.g., mean accuracy). Report precision, recall, variance, error distributions, and qualitative failure samples.

---

25. The AI Failure Triad: Leakage, Shortcuts, and Underspecification

When evaluating AI/ML models, be vigilant against the **AI Failure Triad**:



Mitigation Strategies:

- **For Leakage:** Perform string matching / feature embedding overlap checks between train and test splits.
- **For Shortcuts:** Evaluate models on counterfactual / background-swapped evaluation sets.
- **For Underspecification:** Evaluate performance across 5+ random seeds and report standard deviations.

---

26. Reproducibility and Code Integrity

Unreproducible research is not science. Enforce the following software rules:

1. **Deterministic Seeds:** Explicitly set random seeds across PyTorch, NumPy, Python `random`, and CUDA backend deterministic flags (`torch.backends.cudnn.deterministic = True`).
2. **Environment Locking:** Store complete `environment.yml` or `requirements.txt` with exact pinned version numbers.
3. **Commit Hash Logging:** Every experiment output file must automatically save the current Git commit hash (`git rev-parse HEAD`) into its metadata header.

---

27. Research Engineering Architecture

Do not write research code as monolithic scripts. Maintain a modular **Repository Hierarchy**:

```
my-research-project/
├── configs/             # YAML configuration files for every run
├── src/
│   ├── models/          # Isolated model architectures & baseline implementations
│   ├── data/            # Data loaders, preprocessing, and leak checks
│   ├── mechanisms/      # Your specific novel mechanism modules
│   └── utils/           # Deterministic seeds, logging, metrics
├── experiments/         # Standalone, runnable experiment execution scripts
├── tests/               # Unit tests for data shapes, loss functions, & gradient flow
├── logs/                # Raw metric outputs, JSON logs, and artifacts
└── Canonical_AI_ML_Research_Playbook.md
```

Part V — Running the Research

28. Experiment → Evidence → Interpretation

Do not confuse **experimental output** with **scientific evidence**:

- **Raw Output:** Model A achieved 84.2% accuracy; Model B achieved 81.0% accuracy.
- **Evidence:** Model A out-performed Model B by 3.2% on low-contrast samples across 5 random seeds ($p < 0.01$).
- **Interpretation:** Stabilizing feature token norms mitigates performance degradation under visual signal attenuation.

Always bridge raw output to interpretation using rigorous statistical comparisons and controls.

29. Systematic Error Analysis


When an experiment completes, do not look only at aggregate scores. Conduct **Manual Error Analysis**:

1. Randomly sample **50 failed outputs** (misclassified images, hallucinated text outputs, wrong predictions).
2. Manually inspect and categorize every failure into a taxonomy matrix (e.g., 40% ambiguous input labels, 35% low-contrast norm collapse, 25% out-of-vocabulary terms).
3. Plot error category distributions to discover the true underlying bottlenecks.

---

30. Handling Unexpected Results

When an experiment produces surprising or counter-intuitive results:



First, rule out implementation bugs (90% of unexpected results are bugs). If the code is verified correct, the unexpected result is often a **scientific breakthrough**.

---

31. Value and Recovery of Negative Results

A negative result (H_A failed to improve baseline performance) is **not a failed project**. A negative result is valuable science if:

1. You prove *why* the intuitive idea failed using rigorous diagnostics.
2. You show that a widely cited paper's claims do not generalize under realistic conditions.
3. You establish a clear boundary condition where existing methods break down.

To convert a negative result into a publication: shift the paper's focus from "We built a better method" to "We reveal a fundamental limitation in existing paradigms."

---

32. Revising the Research Question

When experimental evidence falsifies your initial hypothesis, update your research question using the **Dynamic Question Revision Protocol**:

```
Initial Question: "Does mechanism X improve accuracy on task Y?"
      |
      ▼ [Evidence shows mechanism X fails, but uncovers severe token collapse in Layer 8]
Revised Question: "Why does mechanism X induce feature norm collapse in layer 8 during cross-attention
alignment?"
```

This pivoting process is how major scientific insights are discovered.

---

33. Scope Control and Creep Prevention

Prevent **Feature Creep** during experimentation:

- If an exciting idea occurs to you during coding that is not directly required to test your current active hypothesis, **do not implement it immediately**.
- Write it down in your **Idea Backlog**.
- Finish testing your active hypothesis first before evaluating backlog items.

---

34. Research Logs and Decision Tracking

Maintain two living text artifacts throughout execution:

1. The Experiment Ledger (`experiment_ledger.csv`)

Run ID	Date	Git Commit	Hypothesis Tested	Changes Made	Primary Metric	Result Status	Artifact Path
EXP-001	Oct 12	a1b2c3d	H_0 Baseline	Baseline ResNet-50	Acc: 74.2%	Baseline set	/logs/exp001
EXP-002	Oct 12	e4f5g6h	H_A Norm fix	Added norm clamp layer	Acc: 78.5%	H_A supported	/logs/exp002

2. The Decision Log (`decision_log.md`)

```
## Decision 2024-10-14: Switching Evaluation Benchmark
- **Context:** Benchmark X contains 15% mislabeled background patches.
- **Decision:** Switch primary evaluation to Benchmark Y.
- **Evidence:** Manual audit of 100 samples in Benchmark X revealed label ambiguity.
```

Part VI — Turning Evidence into Contribution

35. What Counts as a Scientific Contribution?

In AI/ML, a scientific contribution is **not** merely getting a higher benchmark score ("SOTA chasing"). A valid contribution falls into one of four categories:

1. **Mechanistic Explanation:** Explaining *why* an existing class of models succeeds or fails.
2. **Boundary Discovery:** Proving the precise breakdown conditions of an established paradigm.
3. **Novel Methodology:** Introducing a new technique that yields significant, validated improvements with clear mechanistic justification.
4. **New Diagnostic Benchmark:** Designing a benchmark that isolates a previously unmeasured failure mode or capability gap.

---

36. From Results to Scientific Explanation

Transform raw experimental results into a scientific narrative using the **Evidence Translation Chain**:

$$\text{Raw Metric Shift} \longrightarrow \text{Ablation Isolation} \longrightarrow \text{Diagnostic Probe Confirmation} \longrightarrow \text{General Scientific C}$$

- **Example:**
  - *Raw Shift:* Model accuracy increases from 72% to 81%.
  - *Ablation:* 8% of the 9% gain disappears when norm stabilization is removed.
  - *Probe:* Feature space visualization confirms token norm variance drops by 65%.
  - *Scientific Claim:* Token norm stabilization prevents language prior dominance during low-contrast multimodal cross-attention.

---

37. Building the Evidence Chain

Your paper or thesis must build an unbroken **Evidence Chain** where every claim is backed by a specific experiment:

```
Claim 1: Low visual contrast causes token norm collapse in VLM encoders.
  └→ Verified by Experiment 1 (Layer-wise norm probing across contrast levels).

Claim 2: Token norm collapse allows language priors to dominate predictions (Hallucination).
  └→ Verified by Experiment 2 (Cross-attention weight analysis & text-only ablation).

Claim 3: Norm stabilization eliminates low-contrast hallucination without degrading clean performance.
  └→ Verified by Experiment 3 (Benchmark evaluation vs SOTA baselines + controls).
```

---

38. Knowing When the Research Is Done

You have completed your research project when you satisfy the **3 Completion Criteria**:

1. **Claim Coverage:** Every core claim listed in your introduction is directly supported by an experiment with controls and error bars.
2. **Alternative Explanations Ruled Out:** You have executed negative controls or ablations that rule out parameter count, hyperparameter tuning, or data leakage as explanations.
3. **Failure Boundary Identified:** You can explicitly describe the conditions under which your proposed method stops working.

Part VII — Thesis and Paper Pipeline

39. Thesis Completion Pipeline

To complete a thesis efficiently without last-minute panic, execute the **Thesis Assembly Pipeline**:

```
[Phase 1: Skeleton & Claims] ──> [Phase 2: Methods & Setup] ──> [Phase 3: Results & Evidence Chain] ──>
[Phase 4: Discussion & Limitations]
```

- Write Chapter 3 (Methodology) and Chapter 4 (Experimental Setup) *while running experiments*, not after!
- Draft figures and tables first, then write narrative prose to explain them.

---

40. Publishable Paper Completion Pipeline

When targeting peer-reviewed conferences (e.g., NeurIPS, ICML, ICLR, CVPR, ACL):

1. **Title & Abstract:** Draft early to force crisp framing of the problem, mechanism, and quantitative findings.
2. **Introduction (1.5 pages):** Clearly state problem, gap, key insight, core claims, and a summary of results.
3. **Related Work (1 page):** Position your work against Quadrant 2 direct competitors; do not write a history textbook.
4. **Methodology (2 pages):** Formalize your approach with clear notation, architecture diagrams, and mechanistic rationale.
5. **Experiments (3 pages):** Present Main Results, Ablations, Diagnostic Probes, and Qualitative Failure Analyses.
6. **Limitations & Ethics (0.5 page):** Frankly detail failure modes and computational requirements.

---

41. Reviewer / Adversarial Analysis ("Pre-Mortem")

Before submitting your manuscript, conduct a **Reviewer Pre-Mortem**. Act as an aggressive reviewer and attack your paper with these standard review objections:

- *"The baseline is untuned or weak."* $\longrightarrow$ **Fix:** Add tuned SOTA baselines with equal compute.
- *"The improvement is just due to more parameters."* $\longrightarrow$ **Fix:** Add parameter-matched MLP control.
- *"The method was only tested on one benchmark."* $\longrightarrow$ **Fix:** Evaluate on a second distinct dataset split.
- *"The paper lacks mechanistic understanding."* $\longrightarrow$ **Fix:** Include internal representation probes/visualizations.

---

42. Publication Preparation and Writing Strategy


- **Use Direct, Active Voice:** "We demonstrate that visual norm collapse drives hallucination" instead of "It was demonstrated that hallucination might be driven by norm collapse."

- **Self-Contained Figures:** Every figure caption must be completely self-contained—a reviewer reading *only* your figures and captions should understand your key findings.
- **Open Source Release:** Prepare a clean GitHub repository containing a one-click reproduction script (`run_all_experiments.sh`) and pre-trained weights. Open code dramatically increases paper acceptance rates.

Part VIII — The Reusable Research Operating System

43. The Research State Machine

To enforce research discipline and eliminate endless topic hunting, treat your project as a formal **State Machine**:



State Operating Rules:

- `EXPLORE`**:** Literature mapping only. *Exit rule:* Saturation reached.
- `CANDIDATE`**:** Formulating competing hypotheses and closest-work matrix. *Exit rule:* Gap verified.
- `PILOT MDE`**:** Writing code for cheap 2-hour MDE script. *Exit rule:* Mechanism validated or killed.
- `COMMITTED`**:** Running full benchmarks and baselines. **NO topic searching allowed in this state!**
- `ANALYZING`**:** Conducting manual error analysis, probes, and ablations.
- `WRITING`**:** Draft manuscript, pre-mortem review, and code cleanup.

---

44. Practical Research Artifacts

Maintain these essential research artifacts in your repository:

1. **Field Map:** 4-quadrant layout of bedrock, competitors, infrastructure, and anomalies.
2. **Closest-Work Matrix:** Comparison table against top 3 competing papers.
3. **Hypothesis Sheet:** Explicit formulation of H_A, H_B, H_C.
4. **Experiment Ledger:** CSV file tracking every run hash, metric, and config.
5. **Decision Log:** Markdown log of major strategic choices and rationale.
6. **Evidence Matrix:** Map connecting intro claims to experiment section figures.

---

45. Research Control Center

Implement a central tracking dashboard file (`RESEARCH_CONTROL_CENTER.md`) in your project root:

```
# Research Control Center

- **Active State:** COMMITTED
- **Current Question:** Does visual encoder token norm collapse cause object hallucination in low contrast?
- **Active Hypothesis:** $H_A$ (Norm stabilization prevents text prior dominance)
- **Direct Competitor Papers:** Smith et al. (2023), Zhang et al. (2024), Lee et al. (2024)
- **Next Milestone:** Complete EXP-008 (Parameter-matched control evaluation)
- **Blocking Issues:** None
```

---

46. Future Project Template

When starting any new AI/ML research initiative, clone this standard directory and document layout:

```
mkdir -p my_new_research/{configs,src/{models,data,mechanisms,utils},experiments,tests,logs,docs}
touch my_new_research/{RESEARCH_CONTROL_CENTER.md,experiment_ledger.csv,decision_log.md,README.md}
```

---

47. Common Research Failure Modes

Be aware of these classic failure patterns that ruin research projects:

1. **SOTA Chasing Without Understanding:** Tweaking hyperparameters endlessly to beat a benchmark by 0.2% without knowing why.
2. **The "Too Big to Fail" Architecture:** Spending 3 months coding a massive complex pipeline before testing the core mechanism on toy data.
3. **Endless Topic Hopping:** Abandoning a direction the moment literature reading reveals a minor challenge, returning to state `EXPLORE` forever.
4. **Confirmation Bias:** Ignoring control conditions and celebrating accuracy gains that are actually caused by random seed noise or data leakage.

---

48. Personal Failure-Prevention Rules

To protect yourself against these failure modes, commit to these **5 Rules**:

1. **Rule 1 (14-Day Limit):** Never stay in state `EXPLORE` longer than 14 days without running an MDE.
2. **Rule 2 (Cheapest First):** Always test mechanisms on small models/synthetic data before large cluster runs.
3. **Rule 3 (Rule Out H_B):** Never claim a new module works until you test a parameter-matched random baseline.
4. **Rule 4 (Manual Audit):** Personally inspect at least 50 raw error samples before writing the results section.
5. **Rule 5 (Adversarial Self-Review):** Run a formal pre-mortem review before submitting any manuscript.

---

49. Master Research Checklist

Before declaring any AI/ML research project finished, verify every item:

- ☐ **Question Precision:** Is the research question specific, mechanistic, and falsifiable?
- ☐ **Gap Verification:** Have adversarial search queries confirmed the gap is unaddressed in recent literature?
- ☐ **Closest-Work Matrix:** Are the top 3 competitor papers cataloged with explicit differences noted?
- ☐ **Competing Hypotheses:** Are H_A, H_B, H_C explicitly formulated?
- ☐ **MDE Executed:** Did a cheap pilot experiment confirm mechanism viability before full training?
- ☐ **Baseline Rigor:** Are baselines evaluated with equal compute, hyperparameter tuning, and parameter matching?
- ☐ **Failure Triad Checks:** Have data leakage, shortcut learning, and seed variance been audited?
- ☐ **Reproducibility:** Are deterministic seeds set, dependencies locked, and commit hashes logged?
- ☐ **Error Analysis:** Have 50+ raw error samples been manually categorized?
- ☐ **Evidence Chain Complete:** Does an unbroken link connect every intro claim to a figure/table?
- ☐ **Pre-Mortem Conducted:** Have major reviewer objections been addressed with control experiments?

---

50. One-Page Research Desk Reference

```
┌──────────────────────────────────────────────────────────────────────────┐
│                      ONE-PAGE AI/ML RESEARCH DESK REFERENCE              │
├──────────────────────────────────────────────────────────────────────────┤
│ 1. CONCEPT LADDER: Field -> Sub-field -> Topic -> Phenomenon -> Gap -> Question -> $H_A$│
│ 2. GAP CHECK: "Nobody tried X on Y" is NOT a gap. Search adversarial mechanism terms.  │
│ 3. SATURATION RULE: Stop reading when citations loop and competitors are clear.       │
│ 4. 14-DAY RULE: Max 14 days in exploration before executing a 2-hour MDE script.     │
│ 5. MDE: Smallest experiment that falsifies $H_A$ vs $H_B/H_C$ in < 2 hours compute.   │
│ 6. BASELINE RULE: Tune baselines with EQUAL compute and match total parameter counts. │
│ 7. FAILURE TRIAD: Audit data contamination, shortcut correlations, & seed variance.   │
│ 8. ERROR AUDIT: Manually inspect 50 raw misclassified samples; categorize failure types.│
│ 9. REVISION: Pivoting your research question based on empirical data IS progress!     │
│ 10. PRE-MORTEM: Attack your paper like a hostile reviewer before submitting.          │
└──────────────────────────────────────────────────────────────────────────┘
```

Source Synthesis Note

This canonical playbook was created by conducting a complete synthesis and reconciliation of multiple research playbook sources in the `Research_Playbook/` repository, including:

- `AI Research Methodology Playbook (Gemini).md`
- `AI_ML Research Playbook (Claude).md`
- `AI_ML Research Playbook (Antigravity).md`
- `AI_ML Research Playbook- From Research Discovery to Publishable Paper (Antigravity).md`
- `ai-ml-research-playbook (OpenResearch).md`
- `AI_ML_Research_Playbook (Cline).md`

Synthesis Method:

1. **Deduplication:** Repeated conceptual explanations across sources (e.g., gap definitions, search queries, baseline setups) were unified into single, high-clarity canonical definitions.
2. **Reconciliation:** Methodological differences between sources (e.g., linear vs dual-loop models, reading depth ratios) were reconciled by establishing context-dependent guidelines (e.g., Phase Shift from Exploration to Commitment).
3. **Technical Preservation:** Core technical mechanisms—including the Concept Ladder, Failure Triad, Baseline Hierarchy, Minimum Discriminating Experiments, and Research State Machine—were fully preserved and enhanced with concrete AI/ML examples.
4. **Actionable Restructuring:** The unified document was reorganized into 8 Parts and 50 standalone sections designed to guide a researcher sequentially from initial curiosity to thesis and paper completion.