

Safety Data Sheet

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

SECTION 1: Identification

Product identifier

Trade name/designation:	Acetone CMOS
Product No.:	9015
Synonyms:	none

Relevant identified uses of the substance or mixture and uses advised against

Recommended use	For Laboratory, Research or Manufacturing Use.
Uses advised against	Not determined.

Details of the supplier of the safety data sheet

Supplier

Avantor Performance Materials, LLC.

Street	100 Matsonford Rd, Suite 200
Postal code/City	Radnor, PA 19087, United States
Telephone	+1-855-282-6867
Telefax	+1-610-573-2610

Emergency phone number

Telephone	+1-800-424-9300 (Chemtrec, 24 hrs/day, 7 days/week, USA and Canada)
-----------	---

Preparation Information

Product Information Compliance

E-mail	SDS@avantorsciences.com
--------	-------------------------

SECTION 2: Hazards identification

Classification of the substance or mixture

Label elements

Physical hazards

Flammable liquid, category 2

Health hazards

Aspiration hazard, category 2

Eye irritation, category 2

Specific target organ toxicity (single exposure), category 3, narcotic effect

Hazard pictograms



Signal word: Danger

Hazard statements

H225 - Highly flammable liquid and vapor.

H305 - May be harmful if swallowed and enters airways.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

Precautionary statements**Prevention:**

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting/equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.

Response:

- P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340+P312 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331 - Do NOT induce vomiting.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P370+P378 - In case of fire: Use water spray, foam, dry powder or carbon dioxide to extinguish.

Storage:

- P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.

Disposal:

- P501 - Dispose of contents/container to an appropriate treatment or disposal facility in accordance with applicable laws and regulations.

Hazard(s) not otherwise classified (HNOC)

none

SECTION 3: Composition/information on ingredients**Substances**

Substance name:	Acetone
Molecular formula:	CH ₃ COCH ₃
Molecular weight:	58.08 g/mol
CAS No.:	67-64-1

SECTION 4: First aid measures**General information**

Do not leave affected person unattended. If unconscious but breathing normally, place in recovery position and seek medical advice. Take off immediately all contaminated clothing. Highly flammable liquid and vapor. Wash contaminated clothing before reuse. When in doubt or if symptoms are observed, get medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Remove contaminated, saturated clothing immediately. Wash off any skin contamination immediately. When in doubt or if symptoms are observed, get medical advice.

After eye contact:

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Consult an ophthalmologist.

In case of ingestion

Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person or a person with cramps. Call a POISON CENTER.

Most important symptoms/effects, acute and delayed

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation). In severe cases, pneumonia or a pulmonary oedema may develop. May cause headaches, nausea, vomiting and gastrointestinal disturbances. Conjunctivitis. Unconsciousness.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours. Monitor respiration. Apply cortisone spray at early stage. After swallowing: activated charcoal (20-60 g) and sodium sulfate (1 tablespoon/250 ml) should reduce absorption.

SECTION 5: Fire fighting measures
--

Extinguishing media**Suitable extinguishing media**

ABC-powder
Carbon dioxide (CO₂).
Dry sand
Nitrogen

Extinguishing media which must not be used for safety reasons

Full water jet.

Specific hazards arising from the chemical

Flammable liquids.
Risk of ignition.
Causes eye irritation.
The product causes narcotic-like effects.
Vapor may form explosive mixtures with air.
Fire may produce irritating, corrosive and/or toxic gases.
In case of fire may be liberated:
Carbon monoxide
Carbon dioxide (CO₂).

Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Protective equipment and precautions for firefighters:
Wear a self-contained breathing apparatus and chemical protective clothing.
Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Wear personal protection equipment (refer to section 8). Avoid contact with eyes and skin. Do not breathe gas/fume/vapor/spray. Keep away from sources of ignition - No smoking. Provide adequate ventilation. Remove victim out of the danger area. First Aid, decontamination, treatment of symptoms. For emergency responders: Wear a self-contained breathing apparatus and chemical protective clothing. Wear fire/flammable resistant/retardant clothing.

Environmental precautions

Do not allow to enter into surface water or drains. Fire hazard.

Methods and material for containment and cleaning up

Take up mechanically, placing in appropriate containers for disposal. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Dispose according to legislation. Ventilate affected area.

Reference to other sections

Personal protection equipment (PPE): see section 8 Disposal information: see section 13

SECTION 7: Handling and storage

Precautions for safe handling

Advices on safe handling

Vapors may form explosive mixtures with air.

Use personal protective equipment as required.

Use extractor hood (laboratory).

Use only in well-ventilated areas.

Avoid breathing vapours.

Avoid contact with eyes and skin.

Measures to prevent fire, aerosol and dust generation

Usual measures for fire prevention.

Have fire-extinguishers in readiness before opening containers.

Take precautionary measures against static discharges.

Use only in well-ventilated areas.

Measures required to protect the environment

Do not empty into drains.

Collect spillage.

Wash hands before breaks and after work. Avoid contact with eyes and skin. When using do not eat, drink or smoke. Provide eye shower and label its location conspicuously.

Conditions for safe storage, including any incompatibilities

Recommended storage temperature: 15°C – 25°C or 30°C depending on climatic conditions.

Storage: Keep container tightly closed and in a well-ventilated place. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Take precautionary measures against static discharge. Protect from sunlight. Suitable container/equipment material: Glass High density polyethylene (HDPE) Stainless steel

Unsuitable container/equipment material: No information available.

SECTION 8: Exposure controls/personal protection

Control parameters

Ingredient (Designation)	Source	Country	parameter	Limit value
Acetone	NIOSH	US	LTV	590 mg/m ³ - 250 ppm
Acetone	OSHA	US	LTV	2400 mg/m ³ - 1000 ppm

Engineering controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment. If handled uncovered, arrangements with local exhaust ventilation have to be used.

Personal protection equipment (PPE)

Wear suitable protective clothing. When handling with chemical substances, protective clothing must be worn.

Eye/face protection

Eye glasses with side protection

Skin protection

Wear suitable gloves. When handling with chemical substances, protective gloves must be worn. In the case of wanting to use the gloves again, clean them before taking off and air them well. Check leak tightness/impermeability prior to use.

By short-term hand contact

Suitable material:	CR (polychloroprene, chloroprene rubber)
Thickness of the glove material:	0,75 mm
Breakthrough time	< 30 min

By long-term hand contact

Suitable material:	Butyl caoutchouc (butyl rubber)
Thickness of the glove material:	0,50 mm
Breakthrough time	> 480 min

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

Additional information

Wash hands before breaks and after work. Avoid contact with eyes and skin. When using do not eat, drink or smoke. Provide eye shower and label its location conspicuously.

Environmental exposure controls

no data available

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	
Physical state:	liquid
Color:	colorless
Odor:	characteristic
Odor threshold:	no data available

Safety relevant basic data

pH:	5-6 (400 g/l; H ₂ O; 20 °C)
Melting point/freezing point:	-95.4 °C
Initial boiling point and boiling range:	56.2 °C (1013 hPa)
Flash point:	-20 °C (closed cup)
Evaporation rate:	no data available
Flammability:	Highly flammable liquid and vapor.
Lower and upper explosion limit	
Lower explosion limit:	2.6 % (v/v)
Upper explosion limit:	12.8 % (v/v)
Vapor pressure:	233 hPa (20 °C)
Relative vapour density:	2.01 (20 °C)
Density:	0.792 g/cm ³ (20 °C)
Solubility(ies)	
Water solubility:	soluble (20 °C)
Soluble (g/L) in Ethanol:	no data available
Partition coefficient: n-octanol/water:	-0.24 (20 °C)
Auto-ignition temperature:	465 °C (DIN 51794)
Decomposition temperature:	Not applicable
Viscosity	
Kinematic viscosity:	no data available
Dynamic viscosity:	0.32 mPa*s (20 °C)
Explosive properties:	Not applicable
Oxidising properties:	Not applicable

Other information

Bulk density:	no data available
Refraction index:	1.3591 (589 nm; 20 °C)
Dissociation constant:	no data available
Surface tension:	no data available
Henry's Law Constant:	no data available

SECTION 10: Stability and reactivity

Reactivity

- Vapor may form explosive mixtures with air.
- Risk of ignition.
- Risk of ignition if heated.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

Possibility of hazardous reactions

Formation of explosive mixtures with:

Oxidizing agent, strong.

Chlorine

Iodine

Peroxides

Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials:

Rubber articles

Plastic articles

Hazardous decomposition products:

Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information
--

Information on hazard classes as defined in Regulation**Acute effects**

Acute oral toxicity:

Based on available data, the classification criteria are not met.

LD50: > 5800 mg/kg - Rat - (RTECS)

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

LD50: > 20000 mg/kg - Rabbit - (IUCLID)

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

LC50: > 76 mg/l (4 h) - Rat

Irritant and corrosive effects:

Primary irritation to the skin:

Not applicable

Irritation to eyes:

Causes serious eye irritation.

Irritation to respiratory tract:

Not applicable

Respiratory or skin sensitisation

In case of skin contact: not sensitizing

In case of inhalation: not sensitizing

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not applicable

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**Carcinogenicity**

No indication of human carcinogenicity.

IARC Monographs on the Identification of Carcinogenic Hazards to Humans:

Not listed

Occupational Safety and Health Administration (OSHA, 29 CFR Part 1910.1003):

Not listed

National Toxicology Program (NTP) Report:

Not listed

Germ cell mutagenicity

No indications of human germ cell mutagenicity exist.

Reproductive toxicity

No indications of human reproductive toxicity exist.

Aspiration hazard

Not applicable

Other adverse effects

no data available

SECTION 12: Ecological information

Toxicity**Fish toxicity:**

LC50: 4350 - 11000 mg/l (96 h) - Cairns, J.Jr., and A. Scheier 1968. A Comparison of the Toxicity of Some Common Industrial Waste Components Tested Individually and Combined. Prog.Fish-Cult. 30(1):3-8

Daphnia toxicity:

EC50: 13500 - 23500 mg/l (48 h) - Randall, T.L., and P.V. Knopp 1980. Detoxification of Specific Organic Substances by Wet Oxidation. J.Water Pollut.Control Fed. 52(8):2117-2130

LC50: 10 - 30600 mg/l (48 h) - Cowgill, U.M., and D.P. Milazzo 1991. The Sensitivity of Ceriodaphnia dubia and Daphnia magna to Seven Chemicals Utilizing the Three-Brood Test. Arch.Environ.Contam.Toxicol. 20(2):211-217

Algae toxicity:

EC50: 7200 mg/l (96 h) - Slooff, W. 1982. A Comparative Study on the Short-Term Effects of 15 Chemicals on Fresh Water Organisms of Different Tropic Levels. Natl.Tech.Inf.Serv., Springfield, VA :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386)

Bacteria toxicity:

EC10: 1 000 mg/l (30 min) - OECD 209

Persistence and degradability

Biodegradable.

Bioaccumulative potential

Partition coefficient: n-octanol/water: -0.24 (20 °C)

Mobility in soil:

no data available

Other adverse effects

no data available

SECTION 13: Disposal considerations**Waste treatment methods****Appropriate disposal / Product**

Dispose according to legislation. Consult the appropriate local waste disposal expert about waste disposal. Waste requires monitoring.

Appropriate disposal / Package

Dispose according to legislation. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (DOT)**

UN number or ID number:	UN1090
UN proper shipping name:	ACETONE
Transport hazard class(es):	3
Hazard label(s):	3
Packing group:	II
Environmental hazards:	No
Marine pollutant:	No
Special precautions for user:	

Sea transport (IMDG)

UN number or ID number:	1090
UN proper shipping name:	ACETONE
Transport hazard class(es):	3
Hazard label(s):	3
Packing group:	II
Environmental hazards:	No
Marine pollutant:	No
Special precautions for user:	
Segregation group:	-
EmS-No.	F-E S-D

Maritime transport in bulk according to IMO instruments
not relevant

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number:	1090
UN proper shipping name:	ACETONE
Transport hazard class(es):	3
Classification code:	
Hazard label(s):	3
Packing group:	II
Special precautions for user:	

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Toxic Substances Control Act (TSCA)

Listed

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 313 Components

Not listed.

US State Regulations

Massachusetts Right To Know Components

Listed

Pennsylvania Right To Know Components

Listed

New Jersey Right To Know Components

Listed

California Prop. 65 Components



WARNING:

This product can expose you to chemicals including Acetone which is known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Abbreviations and acronyms

ACGIH - American Conference of Governmental Industrial Hygienists
DOT - Department of Transportation
IARC - International Agency for Research on Cancer
IATA-DGR - International Air Transport Association-Dangerous Goods Regulations
ICAO-TI - International Civil Aviation Organization-Technical Instructions
IMDG - International Maritime Code for Dangerous Goods
LTV - Long Term Value
NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety & Health Administration
PBT - Persistent, Bioaccumulative and Toxic
PEL - Permissible Exposure Limit
STV - Short Term Value
SVHC - Substances of Very High Concern
TDG - Transport of Dangerous Goods
TLV - Threshold Limit Value
vPvB - very Persistent, very Bioaccumulative

Key literature references and sources for data

This Safety Data Sheet has been prepared based on information available for public as TOXNET information, European Chemicals Agency (ECHA) substance dossier, papers from international cancer research institutes (IARC Monographs), U.S. National Toxicology Program data, U.S. Agency for Toxic Substances and Disease Control (ATSDR), PubChem websites and SDS from our raw material manufacturers.

Revision date	Version	Print date
01.12.2025	3.2	2025-12-01

Additional information

Indication of changes:

general update

If you need an explanation of the change, contact the supplier (SDS@avantorsciences.com).

Disclaimer

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, AVANTOR PERFORMANCE MATERIALS ("AVANTOR") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of Avantor's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, AVANTOR DISCLAIMS LIABILITY FOR, AND BY USING AVANTOR'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL AVANTOR BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

