

Brain alignment as a usable training signal: the internal extended manuscript

MohammadErfan Jabbari

June 30, 2026

Abstract

For a person and a language model reading the same text, a simple linear map predicts the person’s brain activity from the model’s middle-layer activations. For a decade this correspondence has been used in one direction only: to measure a model’s alignment with the brain after it is trained. We ask whether it can instead be used during training. We test this in the setting of model compression: we distill a language model into a smaller student with brain alignment in the objective, at a matched budget, and ask whether the student preserves or improves that alignment, a question that remains untested. An information-budget argument implies that such a signal is far too small to act as a second teacher; at most it is a weak prior. Such a prior should help only where the text signal is weakest (small models, scarce data, aggressive compression) and wash out wherever data is abundant. **[GAP: Results summary deferred (checkpoint 2): the two established findings (the powered reality result and the no-preservation distillation screen) and the downstream arc (per-individual null, averaging confound, quality law, predictability ceiling, no practical payoff) are summarised here only once R08–R14 are consolidated; close on the payoff line then.]**

Contents

Notation and terms	2
1 Introduction	3
2 Related work	5
2.1 The classical brain-score literature	6
2.2 Brain-tuning	6
2.3 Alignment under compression	6
2.4 The empty cell	6
2.5 The measurement bar	7
3 Methods	7
3.1 The alignment score	7
3.2 What the score measures	7
3.3 Why a brain signal is only a weak prior	8
3.4 The trained–untrained gap	8
3.5 The controls	9
3.6 Data and models	9
3.7 Distillation and the brain term	10

4 Results	10
4.1 The alignment signal is real, beyond confounds	10
4.2 Plain distillation does not preserve alignment by default	12
4.3 An alignment-guided objective moves alignment, weakly and confounded by quality	14
4.4 No per-individual gain at matched perplexity, and the averaging confound	14
4.5 No practical payoff	14
5 Discussion	14
6 Limitations	15
7 Conclusion	15
Checkpoint log	15

Notation and terms

Encoding model

A ridge regression from a model’s per-stimulus features to measured brain activity, scored out-of-sample. The standard brain-alignment instrument.

Voxel / ROI

A voxel is one 3D measurement location in an fMRI scan; an ROI is a predefined region (here, the five left-hemisphere language regions of the ROI screen).

ΔR^2 (unique R^2)

The variance the language-model features add *on top of* the nuisance set: $R^2([Z_{\text{nuis}}, \text{LM}]) - R^2([Z_{\text{nuis}}])$. The semipartial R^2 , not the partial. The only predictive score this work reports.

Trained–untrained gap

The verdict statistic: the unique R^2 of a language-trained model minus that of a same-architecture untrained network, under identical nuisance and splits. Isolates what *language training* adds over random initialisation.

Z_{nuis} (nuisance set)

The low-level confounds subtracted in both arms of the gap: utterance length, position, word and phoneme rate, word duration, log word-frequency, and a static word-embedding block (eng1000). Surprisal is deliberately excluded (it is itself LM-derived).

Noise ceiling

The maximum variance any model could explain, set by the reliability of the neural measurement itself; reported here as split-half reliability of a held-out repeated story.

Permuted twin

The per-kind shuffled-target null that tests brain-*specificity*. It belongs to the lever question (whether the signal can be *moved*), not to the reality question, and so does not appear in the Results section written here.

$\mathbb{E}[Y \mid S]$

The stimulus-predictable mean response: the strong conditioning variable behind the ceiling question, as opposed to the weak low-level proxy Z_{nuis} .

$\mathcal{L}_{\text{brain}}$

The brain-alignment training loss: the term added to a language objective that rewards representations predictive of recorded brain activity.

Knowledge distillation (KD)

Training a small student model to match a larger teacher’s output distribution rather than the raw text labels. Pure logit KD is the perplexity-only form (temperature-scaled KL on the teacher’s next-token logits, no hidden-state or brain term).

Cold-init / warm-init KD

A *cold-init* student is randomly initialised before KD, so any alignment it ends with was transmitted through the distillation channel; a *warm-init* student starts from a pretrained checkpoint and is therefore a fine-tuning-drift control, not a test of what KD carries.

Headroom (Δ)

The teacher-minus-student gap in unique R^2 , $\Delta = A_T - A_S$, with A_T the teacher’s alignment and A_S the student’s. The alignment a perplexity-only objective leaves below the teacher.

Floor-anchored retention (ρ')

The fraction of the teacher’s alignment a student keeps above the untrained floor, $\rho' = (A_S - A_0)/(A_T - A_0)$, where A_0 is the untrained score: $\rho' = 0$ is the floor (destroyed), $\rho' = 1$ is the teacher (preserved). Distinct from the partial correlation $\rho_{XY \cdot Z}$ of the methods (the primed symbol is retention, never a correlation).

Data-processing inequality (DPI)

For a Markov chain $A \rightarrow B \rightarrow C$, no processing of B can increase information about A : $I(A; C) \leq I(A; B)$. Here it bounds a fixed-function compression to lose, never create, alignment relative to its teacher.

1 Introduction

For a decade, one instrument has anchored the study of language and the brain. A person and a language model read the same text. A linear map predicts the person’s recorded brain activity from the model’s middle-layer activations. Its accuracy on held-out text is the model’s brain-alignment score [1].

This map almost always runs in one direction. It *measures* alignment, as a property read off a model after training. We ask whether it can run the other way. Can alignment instead be *used* during training, as a term in the objective that rewards representations from which brain activity is linearly predictable? And if it can, does a model trained that way gain anything a text-only model does not?

Problem. The concrete setting is model compression. Knowledge distillation trains a small *student* model to imitate a larger *teacher*, refitting the student’s representations from scratch. That refit tends to discard the structured middle-layer representations where brain alignment lives. The problem this thesis studies is whether brain alignment, used as a training signal during distillation, can preserve or even improve it in the student at a matched compute budget, and whether the result buys anything beyond the alignment score itself. The case matters because compression is how small, deployable models are built, and the recent literature leaves it untested.

Hypothesis. If a brain signal helps at all, it helps as a weak prior, not as a second teacher. The reason is a mismatch in scale. A language model learns from on the order of a trillion tokens of text. A language-fMRI dataset offers a few thousand noisy recordings, and a low noise ceiling caps the variance any model can explain in them. A prior that small cannot install knowledge the text does not already carry. What it can do is select among the many

[DIAGRAM PLACEHOLDER: pipeline / method schematic]

Left-to-right setup, then the inversion. (a) A stimulus (a story or sentence) is read by a person and by a frozen language model; the model’s middle-layer activations X are extracted. (b) A ridge encoding map $\hat{W}$ predicts recorded brain activity Y (fMRI) from X ; alignment is the held-out unique variance $\Delta R^2(X; Y \mid Z_{\text{nuis}})$, the increment over a low-level nuisance floor, reported as the trained–untrained gap. (c) The inversion: the same alignment becomes a training term $\lambda \mathcal{L}_{\text{brain}}$ added to knowledge distillation, where a smaller student is trained from a teacher at a matched budget. Render in TikZ; keep three labelled stages (extract / measure / use).

Figure 1: The instrument and its inversion: how brain alignment is measured, and how it is turned into a training signal during distillation. **[GAP: Round-3: finalise caption once §3.6 (training term) is written.]**

text-consistent solutions a large model admits, the way a weak regularizer does. This gives a falsifiable prediction. A brain prior should help most where the text signal is weakest, in small, heavily compressed, or data-starved models, and should wash out wherever text data is abundant. Section 3 makes the argument precise.

Using fMRI to shape a language model is not new. It has been done for speech models [2] and for text models [3], and its effect is causal: text models pushed to be brain-*misaligned* at matched perplexity perform worse across a broad downstream suite [4]. Every one of these methods *grows* the model, by fine-tuning it, adding adapters, or attaching a brain-prediction head, and none compresses it. The single study that compresses language models only measures how quantization and pruning move an alignment score. It never puts alignment in the objective, and never tests distillation [5]. The work splits along two questions: does an intervention grow or shrink the model, and does it measure or optimize alignment? Three of the four combinations are occupied, and one is empty (Figure 2). This thesis occupies the empty cell. It studies alignment-guided distillation at a matched student budget, the regime where our hypothesis says a brain prior could matter, rather than one where it is assumed to pay off.

Brain-alignment scores are easy to inflate. Shuffled splits leak through the temporal autocorrelation of fMRI, and low-level features such as sentence length carry much of an apparent score, so an untrained network can appear to explain brain data on its own [8]. We therefore hold every number in this thesis to a fixed standard, set before measuring anything. The contributions below summarize that standard, and Section 3 defines it [1, 9].

Contributions. This thesis makes the following contributions, scoped to the results it establishes here.

- It formulates alignment-guided distillation and locates it as the one combination the recent literature leaves open (Figure 2).
- It gives an information-budget argument that predicts where a brain prior can and cannot help, turning a vague argument for using brain data into a falsifiable prediction.
- It fixes a measurement protocol that controls for the artifacts that can fake an alignment score: unique variance over a capacity-matched nuisance floor, contiguous splits, a same-

[DIAGRAM PLACEHOLDER: 2×2 positioning of the field]

*A two-by-two grid. Rows = what an intervention does to the parameter budget (grow / shrink); columns = how it treats brain alignment (measured / optimised). Cells: (grow, measured) classical brain-score [1, 6, 7]; (grow, optimised) brain-tuning [2–4]; (shrink, measured) compression robustness [5]; (shrink, optimised) **this thesis**, starred, labelled “empty in the 2026 literature”. Render in TikZ from Table 1; visually emphasise the starred empty cell.*

Figure 2: The field on two axes; three cells are occupied and the fourth, where this work sits, is empty.

architecture untrained control, a held-out noise ceiling, and a permuted-target control for specificity, the controls the alignment-training literature has largely lacked.

- It establishes, at voxel scale and with statistical power, that the alignment signal is real beyond those artifacts [E006].
- It shows that plain perplexity-only distillation does not preserve alignment by default, while making explicit that the drop cannot yet be separated from the language-model quality the student loses [E003].
- It shows that optimizing an alignment objective moves alignment only weakly, that the effect is confounded by quality, and that it does not survive the honest unit of inference [E004].

The program asks five questions in sequence, each only if the previous one holds. Is the signal real, or an artifact? Does plain distillation preserve it? Does an alignment objective move it beyond what perplexity already implies? Does any gain survive per individual at matched perplexity? And does it improve a downstream task?

The first three are settled here: the signal is real [E006], plain distillation does not preserve it [E003], and an alignment objective moves it only weakly and in step with model quality [E004].

2 Related work

This thesis sits in the one empty cell of a two-by-two grid: grow or shrink the model, and measure or optimize alignment (Table 1). We review the three occupied cells in turn, then the measurement standard this work adopts.

Table 1: The field on two axes: what an intervention does to the parameter budget, and how it treats brain alignment. Three cells are occupied; the fourth, shrinking a model while alignment is in the objective, is empty in the 2026 literature and is where this work sits.

	Alignment measured	Alignment optimized
Model grown	classical brain-score [1, 6, 7]	brain-tuning [2–4]
Model shrunk	compression robustness [5]	this thesis (empty in the literature)

2.1 The classical brain-score literature

The largest body of work fits encoding models to frozen, pretrained networks, then reads off how alignment varies with architecture, scale, and training. Three findings recur. Alignment lives in the structured middle layers, where syntax drives the layerwise trend and semantics is more region-specific [1]. It grows with model scale and saturates around a few billion parameters, and at a matched parameter count scale moves it more than instruction-tuning does, which is why a base model is the right teacher to align against [6]. Beyond that scale the trend can flatten or reverse, as the largest models outgrow the human language network and track formal competence more than behavior [7]. This line of work shows the signal exists and is structured, but it never intervenes through alignment, so it cannot say whether alignment is usable.

2.2 Brain-tuning

A second line puts alignment in the objective of a fine-tuned or grown model, across modalities. For speech, a voxelwise brain loss fine-tunes compact encoders and improves both alignment and several downstream tasks, with a multi-participant variant reporting further gains at higher data efficiency [2, 10]. For text, training GPT-2 and LLaMA-2 with a cosine brain loss beats text-only baselines, though the gains are mixed and the splits are shuffled with no brain-shuffled control, so they would not clear the measurement bar this work adopts [3]. The strongest evidence is causal. Training a text model to be *less* brain-aligned, at fixed perplexity, makes it worse across a suite of more than two hundred tasks, while training it to be *more* aligned improves performance on the same suite [4]. Alignment is therefore doing causal work, not just riding along with a good model. The bare inverted idea is not novel, but no study here compresses a model: every method grows or holds the parameter budget, leaving the compression question open.

2.3 Alignment under compression

The closest prior work to this thesis is the compression study of Oota et al. [5], which tracks how alignment changes as a model is compressed. They find that alignment survives only certain post-training quantizers on models of at least a few billion parameters; other quantizers, smaller models, and pruning all degrade it, and distillation is never tested. That study measures alignment under compression but never optimizes it. It reports how quantization and pruning move the score, and never makes alignment a training target. Distillation is a different and lossier operation. It refits a smaller model from scratch against the teacher, the step most likely to destroy the middle-layer structure where alignment lives. So alignment surviving quantization, a gentle reshaping of fixed weights, does not imply it survives distillation. Whether distillation preserves alignment is therefore an open empirical question: how much does it lose by default, and can a brain objective recover the rest? We develop the information-theoretic bound behind this in Section 3.

2.4 The empty cell

No prior work occupies the empty cell. Two nearby precedents, one in vision and one in audio, are sometimes cited as indirect support for a brain regularizer when data is scarce, but neither isolates a brain-specific effect. Pirlot et al. [11] regularize a vision network with neural data and improve both accuracy and adversarial robustness, yet a shuffled-label control reproduces the accuracy gain, so only the robustness benefit depends on real neural structure. Freteault et al. [12] fine-tune a small audio network on fMRI and improve most downstream tasks, but without an interaction test or a matched non-brain control, the low-data advantage is not isolated. Neither study is in the distillation regime this work targets, so both inform our design without testing the claim.

2.5 The measurement bar

A separate line of work warns that alignment scores are easy to inflate and over-read, and it sets the standard this work adopts. Shuffled splits leak through the temporal autocorrelation of fMRI, low-level features like sentence length carry much of the apparent signal, and some published scores fail basic predictive and reliability checks [8, 13]. The same headline score can reflect real semantics in one model and shallow phonology in another, so the number alone does not pin down the mechanism [14]. A differentiable, fMRI-free surrogate would go further, but the literature does not agree on its direction: local intrinsic dimension correlates with alignment in opposite ways across language and vision, and similarity-based surrogates track width and depth as much as alignment [15–17]. We therefore leave a surrogate to future work, since real fMRI must first establish which way to push it.

3 Methods

3.1 The alignment score

We measure alignment with a ridge encoding model that maps a frozen model’s per-stimulus middle-layer activations X to recorded brain activity Y , fit on training stimuli and scored on held-out ones. For activations $X \in \mathbb{R}^{n \times d}$ over n stimuli and a v -voxel response Y , the fitted map is

$$\hat{W} = \arg \min_W \|Y - XW\|_F^2 + \lambda \|W\|_F^2, \quad (1)$$

and the score for each voxel is the held-out correlation between its predicted and measured response. A raw score of this kind means little on its own, because a model can predict the brain for reasons that have nothing to do with language: utterance length, word position, generic word identity. We therefore report not the raw score but the variance the model adds *on top of* a low-level nuisance set Z_{nuis} , the difference of two cross-validated fits,

$$\Delta R^2 = R^2([Z_{\text{nuis}}, \text{LM}]) - R^2([Z_{\text{nuis}}]). \quad (2)$$

A positive ΔR^2 says the contextual representation explains brain activity that length, rate, and static word identity cannot [E002].

3.2 What the score measures

The score has an exact meaning in information terms: it is a lower bound on the information the model’s representation carries about brain activity, beyond the low-level baseline. The object behind it is conditional mutual information. For three variables (X, Y, Z) ,

$$I(X; Y \mid Z) = H(Y \mid Z) - H(Y \mid X, Z) \quad (3)$$

is the dependence between X and Y that remains once Z is known [18]. Conditioning is what makes it the right object: plain mutual information cannot separate a genuine dependence from a shared cause, in which X and Y are both driven by some common Z , and there $X \perp Y \mid Z$ holds and the conditional term is zero, even when the unconditional one is positive. The chain rule splits the dependence into a baseline and the increment over it,

$$I(B; [Z_{\text{nuis}}, \text{LM}]) = I(B; Z_{\text{nuis}}) + I(B; \text{LM} \mid Z_{\text{nuis}}), \quad (4)$$

with B the brain response, so the information the model’s representation adds over the nuisance is exactly the conditional term $I(B; \text{LM} \mid Z_{\text{nuis}})$. The reality claim is that this term is positive.

The unique-variance score estimates that term under a linear-Gaussian model. For jointly Gaussian variables the conditional mutual information is a monotone function of the squared partial correlation,

$$I(X; Y \mid Z) = -\frac{1}{2} \ln(1 - \rho_{XY \cdot Z}^2), \quad (5)$$

so it is positive exactly when the partial correlation is [18, Ch. 8]. The reported score is the *semipartial* R^2 , the raw increment, which differs from the partial ρ^2 only by the factor $1/(1 - R^2([Z_{\text{nuis}}]))$. Both vanish together, so a positive semipartial score is equivalent to a positive conditional mutual information. Ridge is linear, so the score captures the linearly decodable part of that information, a population-level lower bound.

The choice of Z fixes what the claim means. Conditioning on the low-level nuisance Z_{nuis} shows the signal is real beyond low-level features, not beyond the stimulus as a whole. Conditioning instead on the full stimulus-predictable response $\mathbb{E}[Y \mid S]$ is a stronger and separate question, the one the downstream ceiling analysis takes up with the same chain rule and a larger Z .

3.3 Why a brain signal is only a weak prior

Whether a brain term can matter at all follows from an information budget, and that budget predicts where to look for an effect. Adding a brain term to a language objective is, up to constants, a maximum-a-posteriori estimate: the text is the likelihood, the brain term is the log-prior. The two enter on very different scales. A training corpus carries on the order of 10^{12} to 10^{13} bits of supervision. The brain side offers a few thousand noisy stimuli, and the information each voxel can carry is capped by its noise ceiling, a channel capacity

$$I \leq \frac{1}{2} \log_2(1 + \text{SNR}), \quad \text{SNR} = \frac{r_{\text{max}}^2}{1 - r_{\text{max}}^2}, \quad (6)$$

which puts the usable brain budget, as an order of magnitude, around 10^4 to 10^6 bits [18]. The data-processing inequality shrinks it further. The brain response is a noisy function of the same stimulus the model already trains on, so along the chain $S \rightarrow R(S) \rightarrow B$ it carries no more about the optimal parameters than the stimulus does,

$$I(\theta^*; B) \leq I(\theta^*; S). \quad (7)$$

A prior this small cannot teach new task structure against a likelihood this large. What it can do is *select* among the many near-equivalent solutions a large model admits, which is the precise sense in which a brain term is a regularizer, not a second teacher.

A generalization bound makes the consequence quantitative. Modelling training as a channel from the data Z^n to the learned parameters W , the expected generalization gap is bounded by the information the parameters keep about the data,

$$\overline{\text{gen}} \leq \sqrt{\frac{2\sigma^2 I(W; Z^n)}{n}}, \quad (8)$$

for σ -sub-Gaussian loss [19]. If the brain prior adds ΔI bits to that quantity, its benefit to generalization is at most $O(\sqrt{\Delta I/n})$: real, but small, and shrinking as the task data n grows. A weak but well-targeted brain prior should therefore help most where the text signal is weakest, in small, under-trained, or aggressively compressed models, and fade where text data already dominates. Distillation is the regime where that prediction is most testable.

3.4 The trained–untrained gap

The reported statistic is the *gap* between a trained model and a same-architecture untrained network, fit under identical nuisance and splits, rather than the trained model’s absolute score.

**[DIAGRAM PLACEHOLDER: the unique-variance score and the
trained–untrained gap]**

A small construction diagram. Top: for one network, two nested cross-validated ridge fits, $R^2([Z_{\text{nuis}}])$ and $R^2([Z_{\text{nuis}}, \text{LM}])$; their difference is the unique-variance score ΔR^2 (the increment the representation adds over the nuisance floor). Bottom: the same construction run twice, once for the trained network and once for the same-architecture untrained one; the reported statistic is the gap, trained ΔR^2 minus untrained ΔR^2 , so the shared nuisance term cancels. Render in TikZ as two stacked bar-pairs with the increment and the gap annotated.

Figure 3: The reported number: the unique variance a network adds over the nuisance floor, and the gap between the trained network and its untrained twin.

On naturalistic data even an untrained network can score slightly positive. The stimulus drives both the brain response and the untrained features, so when the nuisance captures the stimulus only in part, a residual shared-cause dependence is left behind, and the absolute score is not a clean measure of what training adds. Both arms pass through the byte-identical nuisance subtraction, so the baseline term cancels in the difference. The gap therefore isolates what *language training* adds over random initialisation, holding architecture, tokenisation, and residual temporal structure fixed [E006].

3.5 The controls

Three controls make that gap trustworthy, and we apply them uniformly. *Contiguous splits*: train and test are divided in blocks (block cross-validation on the ROI screen, whole-story-held-out cross-validation on the voxelwise run), because shuffling time-adjacent fMRI samples leaks near-duplicate timepoints across the split and inflates the score [E002][E006]. *A capacity-fair nuisance floor*: the wide contextual block and the wide static-embedding block are each reduced by PCA to the same rank, fit on the training fold only, so that when the model wins it wins on content rather than on carrying more dimensions; the few low-level scalars stay raw [E006]. *A held-out noise ceiling*: on the voxelwise run only reliable voxels are kept, and they are selected on a separate story repeated ten times and held entirely out of the cross-validation pool, scored by split-half reliability, so the estimate is not inflated by voxels that happen to correlate with the model by chance [E006]. Surprisal is deliberately left out of the nuisance set, since it is itself an LM-derived quantity and subtracting it would over-subtract the construct under test; log word-frequency, a static lexical scalar, is distinct and is subtracted [E006]. The permuted-target null (brain responses shuffled across stimuli, which breaks the stimulus-response pairing while preserving temporal structure) tests brain-*specificity*, not reality, and enters only where the question is whether the signal can be moved.

3.6 Data and models

We use two real datasets. The ROI screen uses 1000 isolated sentences and the five left-hemisphere language regions of Tuckute et al. [20], a coarse but high-ceiling, train-participant-averaged benchmark whose isolated-sentence design sidesteps the temporal-autocorrelation leakage of naturalistic time series; its reported noise ceiling is $r \approx 0.35$ [E002]. The powered measure-

ment uses subject UTS03 of the deep-sampled naturalistic story-listening dataset of LeBel et al. [21], with 20 stories, story-level folds, and 11,442 voxels retained at split-half reliability above 0.5 on a held-out repeated story [E006]. The models are GPT-2, GPT-2-medium, and Qwen2.5-0.5B, each read at its alignment-peak middle layer, with a same-architecture untrained network as the control in every comparison [E002][E006].

3.7 Distillation and the brain term

The compression setting is knowledge distillation: a smaller *student* learns to reproduce a larger *teacher*’s next-token distribution, rather than learning from text directly. This connects to perplexity through one identity: per-token cross-entropy is code length, maximum-likelihood training minimizes the KL divergence from the data distribution to the model’s, and perplexity is the exponential of that cross-entropy [18]. Plain language-model training and distillation are the same KL objective against different references: plain training projects the student onto the empirical data, distillation onto the teacher’s softened distribution. Matching *held-out perplexity* across arms therefore holds output quality fixed while only the objective varies, which is the control the alignment-training literature usually lacks; matching compute is not that control.

This objective does not force alignment to be preserved, for two reasons. The objective constrains the *output* distribution, whereas alignment is a property of the *internal* representation, and the readout from representation to logits is many-to-one,

$$D(p_T \parallel q_S) \rightarrow 0 \not\Rightarrow Z_S \approx Y_{\text{teacher}} \not\Rightarrow I(Z_S; B \mid Z_{\text{nuis}}) = I(Y_{\text{teacher}}; B \mid Z_{\text{nuis}}), \quad (9)$$

so matching the teacher’s output need not match its representation. A from-scratch student also fits the stimulus through a side-channel the teacher’s features do not mediate, which breaks the Markov chain behind the data-processing bound, so the teacher’s alignment no longer even upper-bounds the student’s. Whether distillation preserves alignment is therefore an empirical question, not a corollary.

The brain term enters the objective as a co-trained regression loss,

$$\mathcal{L} = \mathcal{L}_{\text{KD}} + \lambda \mathcal{L}_{\text{brain}}, \quad (10)$$

with mixing weight λ . The verdict-bearing arm is a randomly initialised student, the one arm whose surviving alignment was carried through the distillation channel; a warm-initialised student and a no-teacher fine-tune are kept as labelled drift controls, and every arm is scored at one fixed layer within a single architecture so no layer choice biases the comparison [E003]. Brain *specificity* is tested by the permuted twin of the controls above, the same loss against brain targets shuffled across stimuli. The match across arms is the compute budget, and the from-scratch arm runs about twice the optimizer steps of the warm arms, a caveat carried into the results [E003].

4 Results

4.1 The alignment signal is real, beyond confounds

A trained model’s middle layer carries unique, out-of-sample variance about real language-network activity that a same-architecture untrained network does not, and the effect survives the full low-level nuisance regression under contiguous splits. The ROI screen passes on every model tested, and the powered voxelwise run confirms it where the screen could only hint.

The ROI screen, on the five left-hemisphere language regions of Tuckute et al. [20] with 1000 isolated sentences over five contiguous folds, shows a positive trained-minus-untrained gap for all three models, with the untrained control negative at every layer and seed (Table 2). The

signal is positive across a broad plateau of middle layers rather than at a single peak, and is absent from random features [E002].

Table 2: ROI screen on Tuckute 2024 (five LH language ROIs, five contiguous folds). Unique R^2 is the semipartial increment over the nuisance set; the gap is trained minus untrained. NC-norm is the gap as a fraction of the $r \approx 0.353$ noise ceiling.

Model	Best layer	Trained ΔR^2 (mean $\pm$ SD)	Untrained ΔR^2	Gap	NC-norm	Source
GPT-2 (12L)	L7	$+0.020 \pm 0.008$	-0.011	$+0.030$	0.056	[E002]
GPT-2-medium (24L)	L14	$+0.019 \pm 0.005$	-0.014	$+0.033$	0.053	[E002]
Qwen2.5-0.5B (24L)	L12	$+0.036 \pm 0.010$	-0.014	$+0.050$	0.102	[E002]

The powered voxelwise run, on subject UTS03 of LeBel et al. [21] over 20 naturalistic stories and 11,442 voxels selected at split-half reliability above 0.5 on a held-out repeated story, gives a trained-minus-untrained gap of $+0.0207$ [95% CI $+0.0205$, $+0.0209$] for GPT-2 and $+0.0277$ [95% CI $+0.0274$, $+0.0280$] for Qwen2.5-0.5B, with 95% and 99% of reliable voxels positive respectively and the untrained unique R^2 at -0.017 in both (Table 3) [E006]. The confidence intervals exclude zero, and the gap is carried by language training rather than by architecture or the temporal structure the nuisance floor absorbs [E006].

Table 3: Powered voxelwise run on LeBel UTS03 (20 stories, story-level folds). The gap is the trained-minus-untrained unique R^2 ; CIs are bootstrap.

Model	Layer	Trained – untrained gap [95% CI]	% reliable voxels gap > 0	Source
GPT-2	L7	$+0.0207$ [95% CI $+0.0205$, $+0.0209$]	95%	[E006]
Qwen2.5-0.5B	L12	$+0.0277$ [95% CI $+0.0274$, $+0.0280$]	99%	[E006]

Three controls rule out the obvious artifacts, and the screen and the powered run are complementary on them. The ROI screen uses isolated sentences, which removes the temporal-autocorrelation inflation that contaminates naturalistic time series, so its positive is harder to obtain rather than easier [E002]. The voxelwise run reintroduces naturalistic stimuli but adds whole-story-held-out cross-validation, so test timepoints are never adjacent to training timepoints, and voxel selection on a separate held-out repeated story, so the score cannot be inflated by voxels that correlate with the model by chance [E006]. The nuisance set subtracted in both arms is the low-level set most likely to manufacture a false positive: word and phoneme rate, word duration and length, log word-frequency, and a static word-embedding block [E006]. Surprisal and imageability are deliberately left unsubtracted, so a residual contextual nuisance is not ruled out by the floor alone; what rules it out is the same-architecture untrained network, which sees the identical set and scores negative at -0.017 , so architecture, rate, and residual temporal structure cannot manufacture the gap [E006].



Figure 4: The powered reality result: the trained-minus-untrained unique- R^2 gap is positive across the overwhelming majority of reliable voxels on LeBel UTS03 [E006].

The signal is real beyond confounds on real neural data. The three-model ROI screen carries the breadth, and the deeply-sampled single subject UTS03 carries the statistical power at voxel scale. Cross-subject generality of the powered effect is a question this single-subject design leaves open, not one it settles. Qwen aligns more strongly than either GPT-2 variant, while the two GPT-2 variants are nearly tied despite a threefold parameter difference, so this single cross-family contrast does not by itself establish a quality ordering; that question is taken up later [E002]. This is the foundational positive in the program: necessary but not sufficient for everything after it. *Real* does not imply *movable*, and *movable* does not imply *useful*: this result establishes only that the signal is real.

4.2 Plain distillation does not preserve alignment by default

Knowledge distillation (KD) trains a smaller student to match a larger teacher’s output distribution rather than to learn directly from text. A student trained that way does not keep the teacher’s brain alignment for free: ordered by how much of each representation was rebuilt through the distillation channel rather than inherited from ordinary pretraining, unique R^2 falls monotonically, and a from-scratch logit-KD student lands far below its teacher, a gap of +0.0181 ($p < 0.001$) at which it retains only 0.37 [0.14, 0.58] of the teacher’s alignment above an untrained floor [E003]. This rules out the outcome that would have made the compression question a non-problem, preservation by default, and sizes the alignment a perplexity-only objective leaves below the teacher. What it does not establish is the stronger claim that the distillation objective sheds alignment beyond the language-model quality it costs: across the trained and distilled models alignment tracks log-perplexity at Pearson -0.88 , so quality alone could account for the whole gradient [E003][L011].

The quantity is the headroom $\Delta = A_T - A_S$ between the teacher’s alignment A_T and the student’s A_S , both measured on the apparatus of the reality result: unique R^2 on the Tuckute ROI screen, contiguous folds, the capacity-fair nuisance floor. The gap is an empirical question rather than a corollary, and the reason fixes the design. For a deterministic post-processing of a fixed teacher, the quantization and pruning of Oota et al. [5], the student’s features depend on the stimulus only through the teacher’s, so the data-processing inequality bounds $I(Z_{\text{student}}; B) \leq I(Y_{\text{teacher}}; B)$ and a fixed-function compression can only lose alignment, never create it; there the scientific content is how much is lost, not whether. Distillation is not that regime: a from-scratch student fit by gradient descent on the teacher’s logits has a side-channel to the stimulus through the raw next-token targets that bypasses the teacher’s

Missing figure: ../figures/fig_kd_retention.png

Figure 5: [PLACEHOLDER: generate from [E003]] Two panels. (A) Floor-anchored retention ρ' along the rebuild ordering (teacher, conventional GPT-2, warm-init KD, distilgpt2, cold-init KD, untrained floor) with bootstrap CIs, showing the monotone fall. (B) Unique R^2 versus log-perplexity across the same arms, with the Pearson -0.88 fit, showing that alignment co-varies with model quality. **[GAP: Round-3: render the two-panel figure (scripts/figures) and finalise the caption.]**

features, the data-processing premise fails, and nothing forces the student back to the teacher’s alignment [E003].

The verdict therefore rests on a cold-init student. A warm-started student inherits full teacher-grade alignment from its own pretraining, which the reality result already measures, so a high retention for it would show only that a few KD epochs did not erase the alignment the student already had, not that the KD channel carried it [E003]. The verdict-bearing arm is a randomly initialised GPT-2 trained on the teacher’s logits alone, the one arm whose surviving alignment was transmitted through distillation; we keep a warm-init KD arm and a no-teacher plain-LM-finetune arm as labelled fine-tuning-drift and corpus-drift controls, and we score every arm at a fixed layer within the 12-layer GPT-2 architecture so no cross-architecture layer choice confounds the comparison [E003].

Table 4: Knowledge-distillation arms on the Tuckute ROI screen at the fixed verdict layer (NC-normalised unique R^2 , noise ceiling 0.353) [E003]. Floor-anchored retention $\rho' = (A_S - A_0)/(A_T - A_0)$ is 0 at the untrained floor and 1 at the teacher; Δ is the gap versus the teacher; $p(\text{no-drop})$ is the bootstrap probability of no drop from the teacher.

Arm	Init / objective	ΔR^2	ρ' [boot. CI]	Δ vs teacher	$p(\text{no-drop})$	ppl	Source
teacher gpt2-medium	pretrained	+0.0188	n/a	n/a	n/a	74	[E003]
gpt2	pretrained (conventional)	+0.0195	1.02 [0.77, 1.27]	≈ 0	0.57	105	[E003]
lmft_warm	warm + plain-LM finetune	+0.0174	0.95 [0.81, 1.13]	+0.0016	0.265	44	[E003]
kd_warm	warm + pure logit KD	+0.0144	0.84 [0.67, 1.04]	+0.0046	0.061	95	[E003]
distilgpt2	real distillation (+hidden-cosine)	+0.0076	0.60 [0.42, 0.84]	+0.0119	0.001	169	[E003]
kd_cold	random + pure logit KD	+0.0005	0.37 [0.14, 0.58]	+0.0181	0.000	477	[E003]
untrained	random (floor)	-0.0102	0	n/a	n/a	~ 50000	[E003]

The durable finding is the monotone gradient (Table 4). Retention falls cleanly along the rebuild ordering: conventional GPT-2 at the teacher’s level ($\rho' \approx 1.0$), warm-init KD at 0.84, the published distilgpt2 at 0.60, the from-scratch cold-init student at 0.37, and the untrained floor at 0 [E003]. The reference arms validate the measurement: off-the-shelf GPT-2 sits at the teacher’s level and the untrained control at the floor, and two runs scoring the same references on different GPUs reproduced them to about 0.0003 [E003]. The ordering holds at every PCA

rank tested ($n_{\text{pca}} \in \{25, 50, 100\}$), but the absolute shed fractions are rank-sensitive and the two confounded arms flip sign across ranks, so the ordering is the finding and the magnitudes are rank-dependent [E003].

The gradient does not isolate the distillation objective from the language-model quality the student loses, because alignment co-varies with quality across the same arms. Alignment is tightly predicted by log-perplexity across these arms (Pearson -0.88). On that fit, warm-init KD lies essentially on the regression line, and conventional GPT-2 is the lone point above it, the only arm more aligned than its perplexity predicts. The two contrasts that would separate an objective-specific loss from "alignment tracks quality" are both only marginal: warm-init KD is less aligned than GPT-2 despite lower perplexity, but the bootstrap $P(\text{gpt2} \leq \text{kd_warm}) = 0.092$, and at matched budget the no-teacher finetune beats warm-init KD on both perplexity and alignment, but $P(\text{lmft} \leq \text{kd_warm}) = 0.085$; each leans on a single unreplicated point and, under a paired-fold test, on one fold carrying about 44% of the signal [E003][L011]. The cold-init arm compounds the difficulty with under-training, its held-out perplexity (477) sitting far above the converged arms' (44 to 95), so part of its near-floor alignment is simply a worse language model rather than distillation shedding alignment, the convergence caveat the design predeclared [E003]. The match across arms was the compute budget, not the optimizer-step count: the from-scratch arm ran about twice the steps of the warm arms, which deepens this caveat rather than flattering it [E003].

Plain perplexity-only distillation does not preserve brain alignment by default, and the headroom below the teacher is genuine but quality-confounded. Whether an alignment-guided objective can recover that headroom beyond what perplexity already implies is the matched-perplexity question the rest of the program takes up, not one this screen settles. The benchmark here is a cheap ROI screen ($\text{NC} \approx 0.35$) at matched compute budget, under-powered to resolve a ~ 0.005 objective-specific gap and not run at matched perplexity, which is why that question moves to the powered voxelwise substrate [E003][L011].

4.3 An alignment-guided objective moves alignment, weakly and confounded by quality

[GAP: Results Q2 (source E004), to write in Round 3: optimising $\mathcal{L}_{\text{brain}}$ on the strong aligner moves held-out alignment only weakly; the effect is confounded by perplexity; at the honest fold-level inference unit the interval includes zero, so no lever is demonstrated (undemonstrated, not proven zero).]

4.4 No per-individual gain at matched perplexity, and the averaging confound

[GAP: Results Q3 awaits finding-reports R09–R13 (sources E005, E008, E011, E013, E017, E019, E020): the per-individual null, the cross-subject-averaging confound, the method-general failure, the quality law, the stimulus-predictability ceiling, and the external reproduction. The parked draft reports/_pending-Q3 reclaims R09.]

4.5 No practical payoff

[GAP: Results Q4/A3 awaits finding-report R14 (source E009): the bounded OOD-perplexity null and its null-by-construction reading.]

5 Discussion

[GAP: Discussion awaits the consolidated Results arc (R07–R14). The intended

Missing figure: ../figures/fig_lever.png

Figure 6: [PLACEHOLDER: generate from [E004]] The brain-specific lever on the strong aligner: held-out unique- R^2 change from optimising $\mathcal{L}_{\text{brain}}$ against its permuted twin control, shown at the honest fold-level inference unit (folds, not pooled cells), with the interval spanning zero and the single dominant fold marked. [GAP: Round-3: render from the E004 record and finalise the caption.]

spine: the positive contribution is a measurement-validity finding plus a confound-clean protocol, not a bare null; the cross-subject-averaging confound manufactures apparent brain-specificity, and the matched-perplexity, per-kind permuted-twin, per-subject protocol is the control the alignment-training literature lacks. Write only once the Results sections it interprets exist.]

6 Limitations

[GAP: Limitations awaits the consolidated Results arc. The intended content, each tied to its result: the absolute unique variance is a few percent of the noise ceiling (a scale fact, not a weakness); the reality claim is "beyond the nuisance actually subtracted," with surprisal held out by design; the per-individual null is measured at one power level on one cohort; the stimulus-predictability ceiling is instrument-limited rather than closed. Write once the results exist.]

7 Conclusion

[GAP: Conclusion awaits the consolidated Results arc. It should restate the established positive (the alignment signal is real and powered beyond confounds) and the program's net finding once R07–R14 are consolidated, without reaching past the report layer.]

Checkpoint log

2026-06-16: Checkpoint 1, the manuscript is opened

This is the first checkpoint: the extended manuscript is created and the layers that already trace to a written finding-report are drafted. The science behind it was produced over the preceding working sessions and recorded in the experiment files; this checkpoint consolidates the part of that record that the report layer has so far narrated.

What is folded in at this checkpoint. The measurement apparatus and the one established positive result: a trained language model’s middle layer carries unique variance about real language-network activity beyond a low-level nuisance regression, and a same-architecture untrained network does not [E006]. This is consolidated from the finding-report on the reality of the signal (R06), which itself rests on the ROI screen [E002] and the powered voxelwise run [E006]. The front matter (Introduction, Related work) is consolidated from the background reports: the first-principles case for the brain as a weak prior (R03), the gap analysis that locates the contribution in the empty *shrink* $\times$ *optimize* cell (R04), and the synthesis of the measurement literature (R01).

What is deliberately left open. The Results sections beyond the reality of the signal (whether plain distillation preserves alignment, whether the loss is a usable lever, the per-individual null, the quality law, the predictability ceiling, and the practical-payoff question) are marked with \gap because their finding-reports (R07–R14) are not yet written. Knowledge flows down only: a number is narrated in a report before it is consolidated here, so these sections wait on the report layer rather than reaching past it into the raw experiment records. The abstract is provisional for the same reason: it can state the question and the reality result, but not yet summarise an arc whose later findings have no narration layer.

How this checkpoint was built. The draft was written through the scientific-writing skill on the full loop, with the review pass run continuously: adversarial critique agents argued against the reasoning and the prose quality section by section, and the objections that held were addressed before the section was kept.

2026-06-22: Checkpoint 2, the distillation-preservation result and a register repair

This checkpoint does two things, neither of which changes a recorded number: it folds in the next finding-report, and it repairs the prose register the first checkpoint shipped.

What is folded in. The Q1 result, that plain perplexity-only knowledge distillation does not preserve a teacher’s brain alignment by default, is consolidated from its finding-report (R07, source [E003]) into the second Results subsection. A from-scratch logit-KD student lands a gap of +0.0181 below its teacher ($p < 0.001$, retaining 0.37 [0.14, 0.58] of the teacher’s alignment above the untrained floor), and unique R^2 falls along a monotone gradient ordered by how far each representation was rebuilt away from conventional pretraining [E003]. The stronger claim, that the distillation objective sheds alignment beyond the language-model quality it costs, is left unsupported in the prose, because alignment co-varies with log-perplexity at Pearson -0.88 and the two objective-specific dissociations are only marginal [E003][L011]. The abstract and Introduction are updated to state this second result with that hedge, and their downstream-summary \gap markers are narrowed from R07–R14 to R08–R14. The glossary gains the terms the new section needs (knowledge distillation, cold-init/warm-init, headroom Δ , floor-anchored retention ρ' , the data-processing inequality); the retention symbol ρ' is disambiguated from the partial correlation $\rho_{XY.Z}$ of the methods, a notation collision the consolidation guard flagged.

The register repair. A supervisor reading the v0.1 body flagged a storytelling register that the writing-style rules forbid (L054, D046): abstractions handed verbs of agency, the rhetorical move narrated instead of made, the repo’s internal scaffolding metaphors leaking into reader-facing prose, and a reflex passive density above the threshold in the Introduction and Related work. This checkpoint rewrites those passages in the Introduction, abstract, Related work, and Results to assert the content directly, with a subject that acts and a verb that states, and varies the passive where the agent is the real topic. No claim, number, or hedge changed under the rewrite; only the voice did.

What is still open. The Discussion, Limitations, and Conclusion remain \gap because the results they interpret (the per-individual null, the averaging confound, the quality law, the ceiling, the practical-payoff question) await their finding-reports R08–R14. R07’s own caveats

are carried inside the Results prose, as the report convention requires, rather than opened as a partial Limitations section ahead of the consolidated arc.

How this checkpoint was built. Written as its own logged `/write` session on the full loop (the ship gate D046 forbids folding a manuscript revision into another session), with the deterministic checks run on each edit and the non-skippable review pass, the `prose-register-auditor` included, run before handoff.

References

- [1] Subba Reddy Oota et al. “Joint processing of linguistic properties in brains and language models”. In: *NeurIPS* (2023). syntax drives the layer trend; alignment peaks mid-depth; see canonical/oota-2023.
- [2] Moussa, Klakow, and Mariya Toneva. “Brain-tuning improves brain alignment and downstream performance of speech language models”. In: *ICLR*. L2 voxelwise loss, 90M speech LMs; see canonical/moussa-2025. 2025.
- [3] Bilgin, Leila Wehbe, et al. “Brain-informed training of text language models”. In: *ICLR*. GPT-2 124M + LLaMA-2 7B, cosine brain loss, random-shuffle splits; see canonical/bilgin-2026. 2026.
- [4] Gabriele Merlin and Mariya Toneva. “When language models lose their mind: brain (mis)alignment at matched perplexity”. In: *ICLR*. gradient-reversal de-alignment hurts 200+ tasks; see canonical/merlin-2026. 2026.
- [5] Subba Reddy Oota et al. “Brain alignment under quantization and pruning of language models”. In: *Preprint (arXiv:2602.07547)* (2026). AWQ/SmoothQuant preserve on $\geq 3B$; GPTQ/pruning degrade; KD untested; see canonical/oota-2026.
- [6] Gao et al. “Scaling, not instruction-tuning, drives brain alignment”. In: *Preprint* (2024). use a base teacher, not instruct; see canonical/gao-2024.
- [7] Badr AlKhamissi et al. “Large language models can outgrow the human language network”. In: *Preprint* (2025). alignment tracks formal competence, can reverse at scale; see canonical/alkhamissi-2025.
- [8] Nima Hadidi, Fegghi, et al. “Illusions of alignment: brain-score inflation from low-level and static features”. In: *Nature Communications* (2026). the published anti-confound protocol; see canonical/hadidi-2024. DOI: 10.1038/s41467-026-72253-7.
- [9] Gabriele Merlin and Mariya Toneva. “Language models and brain alignment: beyond word-level and next-word prediction”. In: *Preprint* (2024). a residual survives next-word controls in IFG/AG; see canonical/merlin-2024.
- [10] Moussa et al. “Multi-participant brain-tuning of speech language models”. In: *NeurIPS*. per-participant LoRA, 3 training participants; see canonical/moussa-2025b. 2025.
- [11] Pirlot et al. “Neural-data regularization of CNNs via deep CCA to monkey V1”. In: *Preprint (arXiv:2209.02582)* (2022). accuracy gain survives a shuffled-label control; only robustness needs neural data; see canonical/pirlot-2022.
- [12] Freteault et al. “fMRI fine-tuning of a compact audio CNN improves downstream auditory tasks”. In: *Imaging Neuroscience* (2025). 12/19 HEAR tasks; low-data advantage uncontrolled; see canonical/freteault-2025.
- [13] Jia et al. “L-PACT: prediction scores are not enough for brain alignment”. In: *Preprint* (2026). four-gate audit of frozen-encoding alignment; see canonical/jia-2026.
- [14] Subba Reddy Oota et al. “Speech language models lack important brain-relevant semantics”. In: *ACL* (2024). raw scores can be hollow phonology; decompose; see canonical/oota-2024.

- [15] Cheng et al. “Abstraction induces brain alignment: local intrinsic dimension and predictivity”. In: *Preprint (arXiv:2602.04081)* (2026). higher local LID -> more aligned (language); causal claim thin; see canonical/cheng-2026.
- [16] Yu et al. “Intrinsic dimension, alignment, and generalization”. In: *Preprint (arXiv:2601.22722)* (2026). lower local LID -> more aligned (vision); opposite sign to cheng-2026; see canonical/yu-2026.
- [17] Groger et al. “Aristotelian versus Platonic representational alignment”. In: *Preprint* (2026). CKA confounded by width/depth; only mutual-kNN survives null-calibration; see canonical/groger-2026.
- [18] Thomas M. Cover and Joy A. Thomas. *Elements of Information Theory*. 2nd ed. DPI, conditional MI, Gaussian closed form, rate-distortion; mapped in 06-theory-grounding. Wiley-Interscience, 2006.
- [19] Aolin Xu and Maxim Raginsky. “Information-theoretic analysis of generalization capability of learning algorithms”. In: *NeurIPS*. arXiv:1705.07809, Thm 1: gen bound scales as $\sqrt{2 \sigma^2 I(W; S_n)/n}$; the lecture-26 MI bound. 2017.
- [20] Greta Tuckute et al. “Driving and suppressing the human language network using large language models”. In: *Nature Human Behaviour* (2024). 1000 isolated sentences, 5 LH language ROIs; see 05-dataset-registry.
- [21] Amanda LeBel et al. “A natural language fMRI dataset for voxelwise encoding models”. In: *Scientific Data* (2023). ds003020; UTS01-03 deep-sampled; CC_norm ceiling; see canonical + 05-dataset-registry.