

UserAddress		
PK	<u>AddressID</u>	<u>BIGSERIAL</u>
FK	owner	BIGINT -> user.id ON DELETE CASCADE
	label	VARCHAR(255) NOT NULL
	address_line_1	TEXT NOT NULL
	address_line_2	TEXT
	city	VARCHAR(255) NOT NULL
	state	VARCHAR(255) NOT NULL
	postal_code	VARCHAR(11) NOT NULL
	country	VARCHAR(255) NOT NULL
	created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
	updated_at	TIMESTAMPTZ NOT NULL
	is_deleted	BOOLEAN DEFAULT FALSE
	deleted_at	TIMESTAMPTZ

Review		
PK	<u>ReviewID</u>	<u>BIGSERIAL</u>
FK	user	BIGINT -> user.id ON DELETE CASCADE
FK	product	BIGINT -> product.id ON DELETE CASCADE
	rating	SMALLINT NOT NULL CHECK (rating IN (1,2,3,4,5))
	comment	TEXT NOT NULL UNIQUE (product.id)
	created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
	updated_at	TIMESTAMPTZ NOT NULL
	is_deleted	BOOLEAN DEFAULT FALSE
	deleted_at	TIMESTAMPTZ

CartItem		
PK	<u>CartItemID</u>	<u>BIGSERIAL</u>
FK	cart	BIGINT -> cart.id ON DELETE CASCADE
FK	store_item	BIGINT -> store_item.id ON DELETE CASCADE
	quantity	INT NOT NULL
	created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
	updated_at	TIMESTAMPTZ NOT NULL
	is_deleted	BOOLEAN DEFAULT FALSE
	deleted_at	TIMESTAMPTZ

Cart		
PK	<u>CartID</u>	<u>BIGSERIAL</u>
FK	customer	BIGINT -> user.id ON DELETE CASCADE
	created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
	updated_at	TIMESTAMPTZ NOT NULL
	is_deleted	BOOLEAN DEFAULT FALSE
	deleted_at	TIMESTAMPTZ

Payment		
PK	<u>PaymentID</u>	<u>BIGSERIAL</u>
FK	order	BIGINT -> order.id ON DELETE NO ACTION
	status	TEXT NOT NULL CHECK (status IN ('success', 'pending', 'failed'))
	transaction_id	VARCHAR(255)

OrderItem		
PK	<u>OrderItemID</u>	<u>BIGSERIAL</u>
FK	order	BIGINT -> order.id ON DELETE CASCADE
FK	store_item	BIGINT -> store_item.id ON DELETE CASCADE
	quantity	INT NOT NULL
	created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
	updated_at	TIMESTAMPTZ NOT NULL
	is_deleted	BOOLEAN DEFAULT FALSE
	deleted_at	TIMESTAMPTZ

User		
PK	<u>UserID</u>	<u>BIGSERIAL</u>
	username	VARCHAR(150) UNIQUE NOT NULL
	email	VARCHAR(255) UNIQUE
	password	VARCHAR(128)
	first_name	VARCHAR(150)
	last_name	VARCHAR(150)
	phone	VARCHAR(16) UNIQUE NOT NULL
	is_seller	BOOLEAN DEFAULT FALSE
	picture	TEXT
	created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
	updated-at	TIMESTAMPTZ NOT NULL --trigger on UPDATE
	is_deleted	BOOLEAN DEFAULT FALSE
	deleted-at	TIMESTAMPTZ

Order		
PK	<u>OrderID</u>	<u>BIGSERIAL</u>
FK	customer	BIGINT -> user.id ON DELETE CASCADE
FK	address	BIGINT -> user_address.id ON DELETE NO ACTION
	status	TEXT NOT NULL CHECK (status IN ('pending', 'processing', 'delivered', 'cancelled', 'failed')) DEFAULT 'pending'
	total_price	NUMERIC(10,2) DEFAULT 0 NOT NULL
	explanation	TEXT
	created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
	updated_at	TIMESTAMPTZ NOT NULL
	is_deleted	BOOLEAN DEFAULT FALSE
	deleted_at	TIMESTAMPTZ

StoreAddress		
PK	<u>AddressID</u>	<u>BIGSERIAL</u>
	label	VARCHAR(255) NOT NULL

transaction_id	VARCHAR(255)
amount	NUMERIC(10,2) DEFAULT 0 NOT NULL
reference_id	VARCHAR(255)
card_pan	VARCHAR(255)
fee	NUMERIC(10,2) DEFAULT 0 NOT NULL
created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
updated_at	TIMESTAMPTZ NOT NULL
is_deleted	BOOLEAN DEFAULT FALSE
deleted_at	TIMESTAMPTZ

FK	store_item	BIGINT -> sto
	quantity	INT NOT NUL
	price	NUMERIC(10
	discount_price	NUMERIC(10
	total_price	NUMERIC(10
	total_discount	NUMERIC(10
	final_price	NUMERIC(10
	status	TEXT NOT NU 'rejected', con
	created_at	TIMESTAMPT
	updated_at	TIMESTAMPT
	is_deleted	BOOLEAN DE
	deleted_at	TIMESTAMPT

StoreItem		
PK	<u>StoreItemID</u>	<u>BIGSERIAL</u>
FK	store	BIGINT -> store.id ON DELETE CASCADE
FK	product	BIGINT -> product.id ON DELETE CASCADE
	price	NUMERIC(10,2) DEFAULT 0 NOT NULL
	discount_price	NUMERIC(10,2) DEFAULT 0
	stock	INT NOT NULL
	is_active	BOOLEAN DEFAULT FALSE
	created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
	updated_at	TIMESTAMPTZ NOT NULL
	is_deleted	BOOLEAN DEFAULT FALSE
	deleted_at	TIMESTAMPTZ

Product		
PK	<u>ProductID</u>	<u>BIGSERIAL</u>
	name	VARCHAR
	description	TEXT
FK	category	BIGINT SET NL
	is_active	BOOLEAN
	created_at	TIMESTAMPTZ NOT NULL
	updated_at	TIMESTAMPTZ
	is_deleted	BOOLEAN
	deleted_at	TIMESTAMPTZ

Image		
PK	<u>ImageID</u>	<u>BIGSERIAL</u>
	image	TEXT NOT NULL
FK	product	BIGINT -> product.id ON DELETE CASCADE
	created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
	updated_at	TIMESTAMPTZ NOT NULL
	is_deleted	BOOLEAN DEFAULT FALSE
	deleted_at	TIMESTAMPTZ

re_item.id ON DELETE CASCADE

.L

,2) DEFAULT 0 NOT NULL

,2) DEFAULT 0

,2) DEFAULT 0

,2) DEFAULT 0 NOT NULL

,2) DEFAULT 0 NOT NULL

ULL CHECK (status IN ('pending',
firmed')) DEFAULT 'pending'

IZ DEFAULT NOW() NOT NULL

IZ NOT NULL

EFAULT FALSE

IZ

address_line_1	TEXT NOT NULL
address_line_2	TEXT
city	VARCHAR(255) NOT NULL
state	VARCHAR(255) NOT NULL
postal_code	VARCHAR(11) NOT NULL
country	VRCHAR(255) NOT NULL
created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
updated_at	TIMESTAMPTZ NOT NULL
is_deleted	BOOLEAN DEFAULT FALSE
deleted_at	TIMESTAMPTZ

Store		
PK	<u>StoreID</u>	<u>BIGSERIAL</u>
	name	VARCHAR(255) NOT NULL
	description	TEXT
FK	seller	BIGINT -> user.id ON DELETE RESTRICT
FK	address	BIGINT -> store_address.id ON DELETE SET NULL
	created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
	updated_at	TIMESTAMPTZ NOT NULL
	is_deleted	BOOLEAN DEFAULT FALSE
	deleted_at	TIMESTAMPTZ

uct	
<u>RIAL</u>	
	CHAR(255) NOT NULL
	-> category.id ON DELETE JLL
	EAN DEFAULT FALSE
	TAMPTZ DEFAULT NOW() ULL
	TAMPTZ NOT NULL
	EAN DEFAULT FALSE
	TAMPTZ

Category		
PK	<u>CategoryID</u>	<u>BIGSERIAL</u>
	name	VARCHAR(255) NOT NULL
	description	TEXT
	image	TEXT
	is_active	BOOLEAN DEFAULT FALSE
FK	parent	BIGINT -> category.id ON_DELETE SET NULL
	created_at	TIMESTAMPTZ DEFAULT NOW() NOT NULL
	updated_at	TIMESTAMPTZ NOT NULL
	is_deleted	BOOLEAN DEFAULT FALSE
	deleted_at	TIMESTAMPTZ