```
      --totals[=SIGNAL]      print total bytes after processing the archive;
                             with an argument - print total bytes when this
                             SIGNAL is delivered; Allowed signals are: SIGHUP,
                             SIGQUIT, SIGINT, SIGUSR1 and SIGUSR2; the names
                             without SIG prefix are also accepted
      --utc                  print file modification times in UTC
  -v, --verbose              verbosely list files processed
      --warning=KEYWORD      warning control
  -w, --interactive, --confirmation
                             ask for confirmation for every action

 Compatibility options:

  -o                         when creating, same as --old-archive; when
                             extracting, same as --no-same-owner

 Other options:

  -?, --help                 give this help list
      --restrict             disable use of some potentially harmful options
      --usage                give a short usage message
      --version              print program version

Mandatory or optional arguments to long options are also mandatory or optional
for any corresponding short options.

The backup suffix is '~', unless set with --suffix or SIMPLE_BACKUP_SUFFIX.
The version control may be set with --backup or VERSION_CONTROL, values are:

  none, off       never make backups
  t, numbered     make numbered backups
  nil, existing   numbered if numbered backups exist, simple otherwise
  never, simple   always make simple backups

Valid arguments for the --quoting-style option are:

  literal
  shell
  shell-always
  shell-escape
  shell-escape-always
  c
  c-maybe
  escape
  locale
  clocale

*This* tar defaults to:
--format=gnu -f- -b20 --quoting-style=escape --rmt-command=/usr/lib/tar/rmt.exe
--rsh-command=/usr/bin/rsh

user@DESKTOP-3CHU19V MINGW64 ~
```