

قطعه‌بندی فضای دامنه

محمد تنهایی

Input Domains

The input domain to a program contains all the possible inputs to that program

For even small programs, the input domain is so large that it might as well be infinite

Testing is fundamentally about choosing finite sets of values from the input domain

Input parameters define the scope of the input domain

- Parameters to a method

- Data read from a file

- Global variables

- User level inputs

Domain for each input parameter is partitioned into regions

At least one value is chosen from each region

Benefits of ISP

Can be **equally applied** at several levels of testing

Unit

Integration

System

Relatively easy to apply with **no automation**

Easy to **adjust** the procedure to get more or fewer tests

No **implementation knowledge** is needed

just the input space

Partitioning Domains

Domain D

Partition scheme q of D

The partition q defines a set of blocks, $Bq = b_1, b_2, \dots, b_Q$

The partition must satisfy two **properties** :

1. blocks must be pairwise disjoint (no overlap)
2. together the blocks cover the domain D (complete)

Partitioning Domains


Domain D

Partition scheme q of D

The partition q defines a set of blocks, $Bq = b_1, b_2, \dots, b_Q$

The partition must satisfy two **properties** :

1. blocks must be pairwise disjoint (no overlap)
2. together the blocks cover the domain D (complete)



Partitioning Domains


Domain D

Partition scheme q of D

The partition q defines a set of blocks, $Bq = b_1, b_2, \dots, b_Q$

The partition must satisfy two **properties** :

1. blocks must be pairwise disjoint (no overlap)
2. together the blocks cover the domain D (complete)



$$b_i \cap b_j = \Phi, \forall i \neq j, b_i, b_j \in B_q$$

Partitioning Domains


Domain D

Partition scheme q of D

The partition q defines a set of blocks, $B_q = b_1, b_2, \dots, b_Q$

The partition must satisfy two **properties** :

1. blocks must be pairwise disjoint (no overlap)
2. together the blocks cover the domain D (complete)



$$b_i \cap b_j = \Phi, \forall i \neq j, b_i, b_j \in B_q$$

$$\bigcup_{b \in B_q} b = D$$

Using Partitions – Assumptions

Choose a **value** from each partition

Each value is assumed to be **equally useful** for testing

Application to testing

Find characteristics in the inputs : parameters, semantic descriptions, ...

Partition each characteristics

Choose tests by combining values from characteristics

Example Characteristics

Input X is null

Order of the input file F (sorted, inverse sorted, arbitrary, ...)

Min separation of two aircraft

Input device (DVD, CD, VCR, computer, ...)

Choosing Partitions

Choosing (or defining) partitions seems easy, but is easy to get wrong

Consider the “order of file F”

Choosing Partitions

Choosing (or defining) partitions seems easy, but is easy to get wrong

Consider the “order of file F”

b_1 = sorted in ascending order
 b_2 = sorted in descending order
 b_3 = arbitrary order

Choosing Partitions

Choosing (or defining) partitions seems easy, but is easy to get wrong

Consider the “order of file F”

b_1 = sorted in ascending order
 b_2 = sorted in descending order
 b_3 = arbitrary order

but ... something's fishy ...

Choosing Partitions

Choosing (or defining) partitions seems easy, but is easy to get wrong

Consider the “order of file F”

b_1 = sorted in ascending order
 b_2 = sorted in descending order
 b_3 = arbitrary order

but ... something's fishy ...

What if the file is of length 1?

Choosing Partitions

Choosing (or defining) partitions seems easy, but is easy to get wrong

Consider the “order of file F”

b_1 = sorted in ascending order
 b_2 = sorted in descending order
 b_3 = arbitrary order

but ... something's fishy ...

What if the file is of length 1?

The file will be in all three blocks ...
That is, disjointness is not satisfied

Choosing Partitions

Choosing (or defining) partitions seems easy, but is easy to get wrong

Consider the “order of file F”

b_1 = sorted in ascending order
 b_2 = sorted in descending order
 b_3 = arbitrary order

Solution:

Each characteristic should
address just one property

but ... something's fishy ...

What if the file is of length 1?

The file will be in all three blocks ...
That is, disjointness is not satisfied

Choosing Partitions

Choosing (or defining) partitions seems easy, but is easy to get wrong

Consider the “order of file F”

b_1 = sorted in ascending order
 b_2 = sorted in descending order
 b_3 = arbitrary order

but ... something's fishy ...

What if the file is of length 1?

The file will be in all three blocks ...
That is, disjointness is not satisfied

Solution:

Each characteristic should
address just one property

File F sorted ascending

- b_1 = true
- b_2 = false

File F sorted descending

- b_1 = true
- b_2 = false

Properties of Partitions

If the partitions are not **complete** or **disjoint**, that means the partitions have not been considered carefully enough

They should be reviewed carefully, like any design attempt

Different **alternatives** should be considered

We model the input domain in **five steps** ...

Two Approaches to Input Domain Modeling

1. **Interface-based** approach

Develops characteristics directly from **individual input** parameters

Simplest application

Can be **partially automated** in some situations

2. **Functionality-based** approach

Develops characteristics from a **behavioral view** of the program under test

Harder to develop—requires more design effort

May result in **better tests**, or fewer tests that are as effective

Two Approaches to Input Domain Modeling

1. **Interface-based** approach

Develops characteristics directly from **individual input** parameters

Simplest application

Can be **partially automated** in some situations

2. **Functionality-based** approach

Develops characteristics from a **behavioral view** of the program under test

Harder to develop—requires more design effort

May result in **better tests**, or fewer tests that are as effective

Input Domain Model (IDM)

1. Interface-Based Approach

Mechanically consider each parameter in isolation

This is an easy modeling technique and relies mostly on **syntax**

Some domain and semantic information won't be used

Could lead to an incomplete IDM

Ignores relationships among parameters

1. Interface-Based Approach

Mechanically consider each parameter in isolation

This is an easy modeling technique and relies mostly on **syntax**

Some domain and semantic information won't be used

Could lead to an incomplete IDM

Ignores relationships among parameters

Consider TriTyp from Chapter 3

Three *int* parameters

1. Interface-Based Approach

Mechanically consider each parameter in isolation

This is an easy modeling technique and relies mostly on **syntax**

Some domain and semantic information won't be used

Could lead to an incomplete IDM

Ignores relationships among parameters

Consider TriTyp from Chapter 3

Three *int* parameters

IDM for each parameter is identical

Reasonable characteristic : *Relation of side with zero*

2. Functionality-Based Approach

Identify characteristics that correspond to the intended functionality

Requires more **design effort** from tester

Can incorporate **domain** and **semantic** knowledge

Can use **relationships** among parameters

Modeling can be based on **requirements**, not implementation

The same parameter may appear in multiple characteristics, so it's **harder** to translate values to test cases

2. Functionality-Based Approach

Identify characteristics that correspond to the intended functionality

Requires more **design effort** from tester

Can incorporate **domain** and **semantic** knowledge

Can use **relationships** among parameters

Modeling can be based on **requirements**, not implementation

The same parameter may appear in multiple characteristics, so it's **harder** to translate values to test cases

Consider TriTyp again

The three parameters represent a *triangle*

2. Functionality-Based Approach

Identify characteristics that correspond to the intended functionality

Requires more **design effort** from tester

Can incorporate **domain** and **semantic** knowledge

Can use **relationships** among parameters

Modeling can be based on **requirements**, not implementation

The same parameter may appear in multiple characteristics, so it's **harder** to translate values to test cases

Consider TriTyp again

The three parameters represent a *triangle*

IDM can combine all parameters

Reasonable characteristic : *Type of triangle*

Interface-Based IDM – TriTyp

Interface-Based IDM – TriTyp

First Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3
$q_1 = \text{"Relation of Side 1 to 0"}$	greater than 0	equal to 0	less than 0
$q_2 = \text{"Relation of Side 2 to 0"}$	greater than 0	equal to 0	less than 0
$q_3 = \text{"Relation of Side 3 to 0"}$	greater than 0	equal to 0	less than 0

Interface-Based IDM – TriTyp

TriTyp, from Chapter 3, had one testable function and three integer inputs

First Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3
$q_1 = \text{"Relation of Side 1 to 0"}$	greater than 0	equal to 0	less than 0
$q_2 = \text{"Relation of Side 2 to 0"}$	greater than 0	equal to 0	less than 0
$q_3 = \text{"Relation of Side 3 to 0"}$	greater than 0	equal to 0	less than 0

Interface-Based IDM – TriTyp

TriTyp, from Chapter 3, had one testable function and three integer inputs

A maximum of $3 \times 3 \times 3 = 27$ tests

First Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3
$q_1 = \text{"Relation of Side 1 to 0"}$	greater than 0	equal to 0	less than 0
$q_2 = \text{"Relation of Side 2 to 0"}$	greater than 0	equal to 0	less than 0
$q_3 = \text{"Relation of Side 3 to 0"}$	greater than 0	equal to 0	less than 0

Interface-Based IDM – TriTyp

TriTyp, from Chapter 3, had one testable function and three integer inputs

A maximum of $3 \times 3 \times 3 = 27$ tests

Some triangles are valid, some are invalid

First Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3
$q_1 = \text{"Relation of Side 1 to 0"}$	greater than 0	equal to 0	less than 0
$q_2 = \text{"Relation of Side 2 to 0"}$	greater than 0	equal to 0	less than 0
$q_3 = \text{"Relation of Side 3 to 0"}$	greater than 0	equal to 0	less than 0

Interface-Based IDM – TriTyp

TriTyp, from Chapter 3, had one testable function and three integer inputs

A maximum of $3 \times 3 \times 3 = 27$ tests

Some triangles are valid, some are invalid

Refining the characterization can lead to more tests ...

First Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3
$q_1 = \text{"Relation of Side 1 to 0"}$	greater than 0	equal to 0	less than 0
$q_2 = \text{"Relation of Side 2 to 0"}$	greater than 0	equal to 0	less than 0
$q_3 = \text{"Relation of Side 3 to 0"}$	greater than 0	equal to 0	less than 0

Interface-Based IDM – TriTyp (*cont*)

Interface-Based IDM – TriTyp (*cont*)

Second Characterization of TriTyp's Inputs

Characteristic

b_1

b_2

b_3

b_4

$q_1 = \text{"Refinement of } q_1\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_2 = \text{"Refinement of } q_2\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_3 = \text{"Refinement of } q_3\text{"}$	greater than 1	equal to 1	equal to 0	less than 0

Interface-Based IDM – TriTyp (*cont*)

Second Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3	b_4
$q_1 = \text{"Refinement of } q_1\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_2 = \text{"Refinement of } q_2\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_3 = \text{"Refinement of } q_3\text{"}$	greater than 1	equal to 1	equal to 0	less than 0

Interface-Based IDM – TriTyp (*cont*)

Second Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3	b_4
$q_1 = \text{"Refinement of } q_1\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_2 = \text{"Refinement of } q_2\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_3 = \text{"Refinement of } q_3\text{"}$	greater than 1	equal to 1	equal to 0	less than 0

A maximum of $4 \times 4 \times 4 = 64$ tests

Interface-Based IDM – TriTyp (*cont*)

Second Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3	b_4
$q_1 = \text{"Refinement of } q_1\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_2 = \text{"Refinement of } q_2\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_3 = \text{"Refinement of } q_3\text{"}$	greater than 1	equal to 1	equal to 0	less than 0

A maximum of $4 \times 4 \times 4 = 64$ tests

This is only **complete** because the inputs are integers (0 . . 1)

Interface-Based IDM – TriTyp (*cont*)

Second Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3	b_4
$q_1 = \text{"Refinement of } q_1\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_2 = \text{"Refinement of } q_2\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_3 = \text{"Refinement of } q_3\text{"}$	greater than 1	equal to 1	equal to 0	less than 0

A maximum of $4 \times 4 \times 4 = 64$ tests

This is only **complete** because the inputs are integers (0 . . 1)

Possible values for partition q_1

Characteristic	b_1	b_2	b_3	b_4
Side1	5	1	0	-5

Interface-Based IDM – TriTyp (*cont*)

Second Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3	b_4
$q_1 = \text{"Refinement of } q_1\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_2 = \text{"Refinement of } q_2\text{"}$	greater than 1	equal to 1	equal to 0	less than 0
$q_3 = \text{"Refinement of } q_3\text{"}$	greater than 1	equal to 1	equal to 0	less than 0

A maximum of $4 \times 4 \times 4 = 64$ tests

This is only **complete** because the inputs are integers (0 . . 1)

Possible values for partition q_1

Characteristic	b_1	b_2	b_3	b_4
Side1	5	1	0	-5

Test boundary conditions

Functionality-Based IDM – TriTyp

First two characterizations are based on syntax-parameters and their type

A semantic level characterization could use the fact that the three integers represent a triangle

Functionality-Based IDM – TriTyp

First two characterizations are based on syntax-parameters and their type

A semantic level characterization could use the fact that the three integers represent a triangle

Geometric Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3	b_4
q_1 = “Geometric Classification”	scalene	isosceles	equilateral	invalid

Functionality-Based IDM – TriTyp

First two characterizations are based on syntax-parameters and their type

A semantic level characterization could use the fact that the three integers represent a triangle

Geometric Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3	b_4
q_1 = “Geometric Classification”	scalene	isosceles	equilateral	invalid

- Oops ... something's **fishy** ... equilateral is also isosceles !

Functionality-Based IDM – TriTyp

First two characterizations are based on syntax-parameters and their type

A semantic level characterization could use the fact that the three integers represent a triangle

Geometric Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3	b_4
q_1 = “Geometric Classification”	scalene	isosceles	equilateral	invalid

- Oops ... something's **fishy** ... equilateral is also isosceles !
- We need to **refine** the example to make characteristics valid

Functionality-Based IDM – TriTyp

First two characterizations are based on syntax–parameters and their type

A semantic level characterization could use the fact that the three integers represent a triangle

Geometric Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3	b_4
q_1 = “Geometric Classification”	scalene	isosceles	equilateral	invalid

- Oops ... something's **fishy** ... equilateral is also isosceles !
- We need to **refine** the example to make characteristics valid

Correct Geometric Characterization of TriTyp's Inputs

Characteristic	b_1	b_2	b_3	b_4
q_1 = “Geometric Classification”	scalene	isosceles, not equilateral	equilateral	invalid

Functionality-Based IDM – TriTyp (*cont*)

Values for this partitioning can be chosen as

Functionality-Based IDM – TriTyp (*cont*)

Values for this partitioning can be chosen as

Possible values for geometric partition q_1

Characteristic

b_1

b_2

b_3

b_4

Triangle	(4, 5, 6)	(3, 3, 4)	(3, 3, 3)	(3, 4, 8)
----------	-----------	-----------	-----------	-----------

Functionality-Based IDM – TriTyp (*cont*)

A **different approach** would be to break the geometric characterization into four separate characteristics

Functionality-Based IDM – TriTyp (*cont*)

A **different approach** would be to break the geometric characterization into four separate characteristics

Four Characteristics for TriTyp

Characteristic	b_1	b_2
$q_1 = \text{“Scalene”}$	True	False
$q_2 = \text{“Isosceles”}$	True	False
$q_3 = \text{“Equilateral”}$	True	False
$q_4 = \text{“Valid”}$	True	False

Functionality-Based IDM – TriTyp (*cont*)

A **different approach** would be to break the geometric characterization into four separate characteristics

Four Characteristics for TriTyp

Characteristic	b_1	b_2
$q_1 = \text{“Scalene”}$	True	False
$q_2 = \text{“Isosceles”}$	True	False
$q_3 = \text{“Equilateral”}$	True	False
$q_4 = \text{“Valid”}$	True	False

- Use **constraints** to ensure that
 - Equilateral = True implies Isosceles = True
 - Valid = False implies Scalene = Isosceles = Equilateral = False

Modeling the Input Domain

Modeling the Input Domain

Step 1 : Identify testable **functions**

Individual **methods** have one testable function

In a **class**, each method has the same characteristics

Programs have more complicated characteristics—modeling documents such as UML use cases can be used to design characteristics

Systems of integrated hardware and software components can use devices, operating systems, hardware platforms, browsers, etc

Step 2 : Find all the **parameters**

Often fairly **straightforward**, even mechanical

Important to be **complete**

Methods : Parameters and state (non-local) variables used

Components : Parameters to methods and state variables

System : All inputs, including files and databases

Modeling the Input Domain (*cont*)

Modeling the Input Domain (*cont*)

Step 3 : Model the **input domain**

The domain is scoped by the **parameters**

The structure is defined in terms of **characteristics**

Each characteristic is **partitioned** into sets of **blocks**

Each block represents a set of **values**

This is the most **creative design step** in applying ISP

Step 4 : Apply a test **criterion** to choose **combinations** of values

A test input has a **value** for each parameter

One **block** for each characteristic

Choosing **all combinations** is usually infeasible

Coverage criteria allow **subsets** to be chosen

Step 5 : Refine combinations of blocks into **test inputs**

Choose **appropriate values** from each block

Steps 1 & 2 – Identifying Functionalities, Parameters and Characteristics

A creative engineering step

More characteristics means more tests

Interface-based : Translate parameters to characteristics

Candidates for characteristics :

- Preconditions and postconditions

- Relationships among variables

- Relationship of variables with special values (zero, null, blank, ...)

Should not use program source – characteristics should be based on the input domain

- Program source should be used with graph or *logic* criteria

Better to have **more characteristics** with **few blocks**

- Fewer mistakes and fewer tests

Steps 1 & 2 : Interface vs Functionality-Based

Steps 1 & 2 : Interface vs Functionality-Based

```
public boolean findElement (List list, Object element)
// Effects: if list or element is null throw NullPointerException
//         else return true if element is in the list, false otherwise
```

Steps 1 & 2 : Interface vs Functionality-Based

```
public boolean findElement (List list, Object element)
// Effects: if list or element is null throw NullPointerException
//         else return true if element is in the list, false otherwise
```

Interface-Based Approach

Two parameters : list, element

Characteristics :

list is null (block1 = true, block2 = false)

list is empty (block1 = true, block2 = false)

Steps 1 & 2 : Interface vs Functionality-Based

```
public boolean findElement (List list, Object element)
// Effects: if list or element is null throw NullPointerException
//          else return true if element is in the list, false otherwise
```

Interface-Based Approach

Two parameters : list, element

Characteristics :

list is null (block1 = true, block2 = false)

list is empty (block1 = true, block2 = false)

Functionality-Based Approach

Two parameters : list, element

Characteristics :

number of occurrences of element in list

(0, 1, >1)

element occurs first in list

(true, false)

element occurs last in list

(true, false)

Step 3 : Modeling the Input Domain

Partitioning characteristics into blocks and values is a very creative engineering step

More blocks means more tests

The partitioning often flows directly from the definition of **characteristics** and both steps are sometimes done together

Should **evaluate** them separately – sometimes fewer characteristics can be used with more blocks and vice versa

Strategies for identifying values :

- Include valid, invalid and special values

- Sub-partition some blocks

- Explore boundaries of domains

- Include values that represent “normal use”

- Try to balance the number of blocks in each characteristic

- Check for completeness and disjointness

Using More than One IDM

Some programs may have dozens or even hundreds of parameters

Create several small IDMs

A divide-and-conquer approach

Different parts of the software can be tested with different amounts of rigor

For example, some IDMs may include a lot of invalid values

It is okay if the different IDMs overlap

The same variable may appear in more than one IDM

Step 4 – Choosing Combinations of Values

Once characteristics and partitions are defined, the next step is to choose test values

We use criteria – to choose effective subsets

The most obvious criterion is to choose all combinations ...

Step 4 – Choosing Combinations of Values

Once characteristics and partitions are defined, the next step is to choose test values

We use criteria – to choose effective subsets

The most obvious criterion is to choose all combinations ...

All Combinations (ACoC) : All combinations of blocks from all characteristics must be used.

Step 4 – Choosing Combinations of Values

Once characteristics and partitions are defined, the next step is to choose test values

We use criteria – to choose effective subsets

The most obvious criterion is to choose all combinations ...

All Combinations (ACoC) : All combinations of blocks from all characteristics must be used.

- Number of tests is the product of the number of blocks in each characteristic : $\prod_{i=1}^Q (B_i)$

Step 4 – Choosing Combinations of Values

Once characteristics and partitions are defined, the next step is to choose test values

We use criteria – to choose effective subsets

The most obvious criterion is to choose all combinations ...

All Combinations (ACoC) : All combinations of blocks from all characteristics must be used.

- Number of tests is the product of the number of blocks in each characteristic : $\prod_{i=1}^Q (B_i)$
- The second characterization of TriTyp results in $4*4*4 =$ 64 tests – too many ?

ISP Criteria – Each Choice

64 tests for TriTyp is almost certainly way too many

One criterion comes from the idea that we should try at least one value from each block

ISP Criteria – Each Choice

64 tests for TriTyp is almost certainly way too many

One criterion comes from the idea that we should try at least one value from each block

Each Choice (EC) : One value from each block for each characteristic must be used in at least one test case.

ISP Criteria – Each Choice

64 tests for TriTyp is almost certainly way too many

One criterion comes from the idea that we should try at least one value from each block

Each Choice (EC) : One value from each block for each characteristic must be used in at least one test case.

- Number of tests is the number of blocks in the **largest** characteristic

ISP Criteria – Each Choice

64 tests for TriTyp is almost certainly way too many

One criterion comes from the idea that we should try at least one value from each block

Each Choice (EC) : One value from each block for each characteristic must be used in at least one test case.

- Number of tests is the number of blocks in the **largest** characteristic

$$\text{Max}_{i=1}^Q (B_i)$$

ISP Criteria – Each Choice

64 tests for TriTyp is almost certainly way too many

One criterion comes from the idea that we should try at least one value from each block

Each Choice (EC) : One value from each block for each characteristic must be used in at least one test case.

- Number of tests is the number of blocks in the **largest** characteristic

$$\text{Max}_{i=1}^Q (B_i)$$

For TriTyp: 2, 2, 2
1, 1, 1
0, 0, 0
-1, -1, -1

ISP Criteria – Pair-Wise

Each choice yields few tests – **cheap** but perhaps ineffective

Another approach asks values to be **combined** with other values

ISP Criteria – Pair-Wise

Each choice yields few tests – **cheap** but perhaps ineffective

Another approach asks values to be **combined** with other values

Pair-Wise (PW) : A value from each block for each characteristic must be combined with a value from every block for each other characteristic.

ISP Criteria – Pair-Wise

Each choice yields few tests – **cheap** but perhaps ineffective

Another approach asks values to be **combined** with other values

Pair-Wise (PW) : A value from each block for each characteristic must be combined with a value from every block for each other characteristic.

- Number of tests is at least the product of two largest characteristics

ISP Criteria – Pair-Wise

Each choice yields few tests – **cheap** but perhaps ineffective

Another approach asks values to be **combined** with other values

Pair-Wise (PW) : A value from each block for each characteristic must be combined with a value from every block for each other characteristic.

- Number of tests is at least the product of two largest characteristics

$$(\text{Max}_{i=1}^Q (B_i)) * (\text{Max}_{j=1, j \neq i}^Q (B_j))$$

ISP Criteria – Pair-Wise

Each choice yields few tests – **cheap** but perhaps ineffective

Another approach asks values to be **combined** with other values

Pair-Wise (PW) : A value from each block for each characteristic must be combined with a value from every block for each other characteristic.

- Number of tests is at least the product of two largest characteristics

$$(\text{Max}_{i=1}^Q (B_i)) * (\text{Max}_{j=1, j \neq i}^Q (B_j))$$

For TriTyp:	2, 2, 2	2, 1, 1	2, 0, 0	2, -1, -1
	1, 2, 1	1, 1, 0	1, 0, -1	1, -1, 2
	0, 2, 0	0, 1, -1	0, 0, 2	0, -1, 1
	-1, 2, -1	-1, 1, 2	-1, 0, 1	-1, -1, 0

ISP Criteria–T-Wise

A natural extension is to require combinations of t values instead of
2

ISP Criteria–T-Wise

A natural extension is to require combinations of t values instead of 2

t-Wise (TW) : A value from each block for each group of t characteristics must be combined.

ISP Criteria–T-Wise

A natural extension is to require combinations of t values instead of 2

t-Wise (TW) : A value from each block for each group of t characteristics must be combined.

- Number of tests is at least the product of t largest characteristics
- If all characteristics are the same size, the formula is

ISP Criteria–T-Wise

A natural extension is to require combinations of t values instead of 2

t-Wise (TW) : A value from each block for each group of t characteristics must be combined.

- Number of tests is at least the product of t largest characteristics
- If all characteristics are the same size, the formula is

$$\left(\text{Max}_{i=1}^Q (B_i) \right)^t$$

ISP Criteria–T-Wise

A natural extension is to require combinations of t values instead of 2

t-Wise (TW) : A value from each block for each group of t characteristics must be combined.

- Number of tests is at least the product of t largest characteristics
- If all characteristics are the same size, the formula is

$$\left(\text{Max}_{i=1}^Q (B_i) \right)^t$$

- If t is the number of characteristics Q , then all combinations

ISP Criteria–T-Wise

A natural extension is to require combinations of t values instead of 2

t-Wise (TW) : A value from each block for each group of t characteristics must be combined.

- Number of tests is at least the product of t largest characteristics
- If all characteristics are the same size, the formula is

$$\left(\text{Max}_{i=1}^Q (B_i) \right)^t$$

- If t is the number of characteristics Q , then all combinations
- That is ... *Q -wise = AC*

ISP Criteria–T-Wise

A natural extension is to require combinations of t values instead of 2

t-Wise (TW) : A value from each block for each group of t characteristics must be combined.

- Number of tests is at least the product of t largest characteristics
- If all characteristics are the same size, the formula is

$$\left(\text{Max}_{i=1}^Q (B_i) \right)^t$$

- If t is the number of characteristics Q , then all combinations
- That is ... *Q -wise* = *AC*
- t -wise is **expensive** and benefits are not clear

ISP Criteria – Base Choice

Testers sometimes recognize that certain values are important

This uses domain knowledge of the program

ISP Criteria – Base Choice

Testers sometimes recognize that certain values are important

This uses domain knowledge of the program

Base Choice (BC) : A base choice block is chosen for each characteristic, and a base test is formed by using the base choice for each characteristic. Subsequent tests are chosen by holding all but one base choice constant and using each non-base choice in each other characteristic.

ISP Criteria – Base Choice

Testers sometimes recognize that certain values are important

This uses domain knowledge of the program

Base Choice (BC) : A base choice block is chosen for each characteristic, and a base test is formed by using the base choice for each characteristic. Subsequent tests are chosen by holding all but one base choice constant and using each non-base choice in each other characteristic.

- Number of tests is one base test + one test for each other block

ISP Criteria – Base Choice

Testers sometimes recognize that certain values are important

This uses domain knowledge of the program

Base Choice (BC) : A base choice block is chosen for each characteristic, and a base test is formed by using the base choice for each characteristic. Subsequent tests are chosen by holding all but one base choice constant and using each non-base choice in each other characteristic.

- Number of tests is one base test + one test for each other block

$$1 + \sum_{i=1}^Q (B_i - 1)$$

ISP Criteria – Base Choice

Testers sometimes recognize that certain values are important

This uses domain knowledge of the program

Base Choice (BC) : A base choice block is chosen for each characteristic, and a base test is formed by using the base choice for each characteristic. Subsequent tests are chosen by holding all but one base choice constant and using each non-base choice in each other characteristic.

- Number of tests is one base test + one test for each other block

$$1 + \sum_{i=1}^Q (B_i - 1)$$

For TriTyp: Base	2, 2, 2	2, 2, 1	2, 1, 2	1, 2, 2
		2, 2, 0	2, 0, 2	0, 2, 2
		2, 2, -1	2, -1, 2	-1, 2, 2

ISP Criteria – Multiple Base Choice

Testers sometimes have more than one logical base choice

ISP Criteria – Multiple Base Choice

Testers sometimes have more than one logical base choice

Multiple Base Choice (MBC) : One or more base choice blocks are chosen for each characteristic, and base tests are formed by using each base choice for each characteristic. Subsequent tests are chosen by holding all but one base choice constant for each base test and using each non-base choices in each other characteristic.

ISP Criteria – Multiple Base Choice

Testers sometimes have more than one logical base choice

Multiple Base Choice (MBC) : One or more base choice blocks are chosen for each characteristic, and base tests are formed by using each base choice for each characteristic. Subsequent tests are chosen by holding all but one base choice constant for each base test and using each non-base choices in each other characteristic.

- If there are M base tests and m_i base choices for each characteristic:

ISP Criteria – Multiple Base Choice

Testers sometimes have more than one logical base choice

Multiple Base Choice (MBC) : One or more base choice blocks are chosen for each characteristic, and base tests are formed by using each base choice for each characteristic. Subsequent tests are chosen by holding all but one base choice constant for each base test and using each non-base choices in each other characteristic.

- If there are M base tests and m_i base choices for each characteristic: $M + \sum_{i=1}^Q (M * (B_i - 1))$

ISP Criteria – Multiple Base Choice

Testers sometimes have more than one logical base choice


Multiple Base Choice (MBC) : One or more base choice blocks are chosen for each characteristic, and base tests are formed by using each base choice for each characteristic. Subsequent tests are chosen by holding all but one base choice constant for each base test and using each non-base choices in each other characteristic.

- If there are M base tests and m_i base choices for each characteristic: $M + \sum_{i=1}^Q (M * (B_i - 1))$

For TriTyp: Base

2, 2, 2	2, 2, 0	2, 0, 2	0, 2, 2
	2, 2, -1	2, -1, 2	-1, 2, 2
	2, 2, 1	2, 1, 2	1, 2, 2
1, 1, 1	1, 1, 0	1, 0, 1	0, 1, 1
	1, 1, -1	1, -1, 1	-1, 1, 1
	1, 1, 2	1, 2, 1	2, 1, 1

ISP Coverage Criteria Subsumption



Constraints Among Characteristics

Some combinations of blocks are **infeasible**

“less than zero” and “scalene” ... not possible at the same time

These are represented as constraints among blocks

Two general types of constraints

A block from one characteristic cannot be combined with a specific block from another

A block from one characteristic can ONLY BE combined with a specific block from another characteristic

Handling constraints depends on the criterion used

AC, PW, TW : Drop the infeasible pairs

BC, MBC : Change a value to another non-base choice to find a feasible combination

Example Handling Constraints

Sorting an array

Input : variable length array of arbitrary type

Outputs : sorted array, largest value, smallest value

Example Handling Constraints

Sorting an array

Input : variable length array of arbitrary type

Outputs : sorted array, largest value, smallest value

Characteristics:

- Length of array
- Type of elements
- Max value
- Min value
- Position of max value
- Position of min value

Example Handling Constraints

Sorting an array

Input : variable length array of arbitrary type

Outputs : sorted array, largest value, smallest value

Characteristics:

- Length of array { 0, 1, 2..100, 101..MAXINT }
- Type of elements { int, char, string, other }
- Max value Max { ≤ 0 , 1, > 1 , 'a', 'Z', 'b', ..., 'Y' }
- Min value Min { ... }
- Position of max value Max Pos { 1, 2 .. Len-1, Len }
- Position of min value Min Pos { 1, 2 .. Len-1, Len }

Example Handling Constraints

Sorting an array

Input : variable length array of arbitrary type

Outputs : sorted array, largest value, smallest value

Blocks from other characteristics are irrelevant

Characteristics:

- Length of array { 0, 1, 2..100, 101..MAXINT }
- Type of elements { int, char, string, other }
- Max value Max { ≤ 0 , 1, > 1 , 'a', 'Z', 'b', ..., 'Y' }
- Min value Min { ... }
- Position of max value Max Pos { 1, 2 .. Len-1, Len }
- Position of min value Min Pos { 1, 2 .. Len-1, Len }

Example Handling Constraints

Sorting an array

Input : variable length array of arbitrary type

Outputs : sorted array, largest value, smallest value

Blocks from other characteristics are irrelevant

Characteristics:

- Length of array { 0, 1, 2..100, 101..MAXINT }
- Type of elements { int, char, string, other }
- Max value { $\leq 0, 1, > 1, 'a', 'Z', 'b', \dots, 'Y' \}$
- Min value { ... }
- Position of max value { 1, 2 .. Len-1, Len }
- Position of min value { 1, 2 .. Len-1, Len }

Blocks must be combined

Example Handling Constraints

Sorting an array

Input : variable length array of arbitrary type

Outputs : sorted array, largest value, smallest value

Blocks from other characteristics are irrelevant

Characteristics:

- Length of array { 0, 1, 2..100, 101..MAXINT }
- Type of elements { int, char, string, other }
- Max value { ≤ 0 , 1, > 1 , 'a', 'Z', 'b', ..., 'Y' }
- Min value { ... }
- Position of max value { 1, 2 .. Len-1, Len }
- Position of min value { 1, 2 .. Len-1, Len }

Blocks must be combined

Blocks must be combined

Input Space Partitioning Summary

Input Space Partitioning Summary

Fairly easy to apply, even with no automation

Convenient ways to add more or less testing

Input Space Partitioning Summary

Fairly easy to apply, even with no automation

Convenient ways to add more or less testing

Applicable to all levels of testing – unit, class, integration, system, etc.

Input Space Partitioning Summary

Fairly easy to apply, even with no automation

Convenient ways to add more or less testing

Applicable to all levels of testing – unit, class, integration, system, etc.

Based only on the input space of the program, not the implementation

پایان