

Premier

COATING | ADHESIVE | SEALANTS



PREMIER 30-36

CANVAS DUCT COATING

PREMIER 30-36 is a tough yet flexible abrasion resistant interior duct coating to protect thermal insulation. It can be used as a lagging adhesive for canvas cloth. **PREMIER 30-36** has very good 'uniform spread' properties, which can give an excellent finish in application even by brush. **PREMIER 30-36** has an intrinsic quality of being 'non- yellowing' **PREMIER 30-36** provides a very good protective coating on air-conditioning ducts and chilled water piping when applied in two coats with reinforced canvas cloth or equivalent embedded coats.

USES

Ideal for use over Internal HVAC duct, ASJ, FRK, and FSK (jackets and board) facings to give a vapour barrier seal at joints, laps, and weld pin punctures. It is used for sealing and fitting of piping, vessel ducts and equipment operating between 0°C and ambient temperatures. It is used on mineral wool, glass fiber, and polyurethane foam.

FEATURES & ADVANTAGES

- Due to excellent coating characteristics it has very good coverage and uniform spread.
- It does not change colour with age
- It does not contain asbestos, lead, mercury or mercury compounds
- Shield to ultraviolet radiations
- Smooth finish on almost all substrates

COVERAGE

Theoretical coverage of **PREMIER 30-36** is 2.5 m²/lt at 300-350 microns WFT (Wet Film Thickness).

APPLICATION METHOD

The surface must be clean and free from any dust, dirt, oil, grease and loose particles.

Apply an even tack coat of **PREMIER 30-36** on the surface at 1.50 m²/lt with brush or airless spray machine. After applying tack coat immediately embed the selected lagging fabric smoothly (avoid wrinkles and overlaps) in to the tack coating. Within 4 hours apply two finishing coats of undiluted **PREMIER 30-36** at ~1m²/lt. It is very important to ensure that each coat of **PREMIER 30-36** is totally **cured** before the next coat is applied.

HEALTH & SAFETY

As with all chemicals, caution should always be exercised. Protective clothing such as gloves and goggles should be worn.

INHALATION: Inhalation of vapor or mist should be avoided. Symptoms include coughing, wheezing, laryngitis, and shortness of breath, headache, nausea, and vomiting. Immediately shift victim to fresh air, and, if needed immediately start artificial respiration. Give oxygen if breathing is labored. Get emergency medical help.

EYE CONTACT: Flush eyes with water for 15 minutes and call for medical help.

INGESTION: Causes nausea, vomiting, and loss of consciousness. If accidentally swallowed call for medical help immediately.

SKIN CONTACT: Flush with water or soap and water until all traces have been removed. Seek medical attention if required.

STORAGE

Store under cover, protect from direct sunlight and high temperature (>40°C). Shelf life is up to 18 months when stored as directed.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.

PACKING

PREMIER 30-36 is supplied in 5 US Gallon plastic pails.

T E C H N I C A L D A T A	
Colour	White
Density (gm/cc)	1.30 ± 0.05
Viscosity	70000-80000 cps @30°C rpm 15
Service temp.	Up to 234°F (112°C)
Application temp.	5°C to + 45°C
Sealing property	Good
Drying time:	(at 30°C and 50% RH)
To touch	3 hours
Thorough	24 hours



PREMIER 81-10

DUCT GLUE

DESCRIPTION

PREMIER 81-10 is inflammable, heat resistant, single component adhesive purely on POLYCHLOROPRENE with special tackifying agents and additives. It is specially developed to adhere to fibrous glass wool and metals. It can be used to bond most porous or non-porous surfaces.

PROPERTIES

PREMIER 81-10 has a correct balance of wet and dry tack with 'smooth flow' properties which are uniform and fast drying in nature. On curing **PREMIER 81-10** has very good heat and fire retardant properties.

APPLICATION

PREMIER 81-10 has excellent adhesion to most porous and non porous surfaces. It is compatible with range of metal substrates as well.

APPLICATION METHOD

Before applying, the surface should be made clean and even, free from dust, loose shavings, oil and grease.

Apply **PREMIER 81-10** either with brush or pressure feeding equipment to form a uniform coat.

Allow 10-15 minutes to evaporate the complete solvent, and then apply normal hand pressure to give strong bond.

Surface setting time varies from 10 minutes to 20 minutes depending on thickness of layers of adhesive, type of substrate, moisture and temperature.

PREMIER - VB

VAPOUR BARRIER DUCT COATING

PREMIER-VB is a synthetic resin, water based vapour barrier coating specially manufactured for all types of internal and external thermal insulation duct systems. It is formulated for increased vapour barrier protection and for heavy duty commercial or industrial use.

USES

Ideal for use over Internal and External HVAC duct, ASJ, FRK, and FSK jackets and board facings to give a vapour barrier seal at joints, laps, and weld pin punctures.

It is used for sealing and fitting of piping, vessel ducts and equipment operating between 0°C and ambient temperatures.

It is used on mineral wool, glass fiber, and polyurethane foam.

T E C H N I C A L D A T A

Colour	White
Density (gm/cc)	1.30 ± 0.05
Viscosity	50000-70000 cps @30°C rpm 15
Service temp.	-25°C to +120°C)
Application temp.	5°C to + 45°C
Water permeability	Almost Zero
Drying time:	(at 30°C and 50% RH)
To touch	3 hours
Thorough	18 - 20 hours

FEATURES & ADVANTAGES

- Due to excellent coating characteristics it has very good coverage and spreads uniformly.
- It does not change colour with age
- It does not contain asbestos, lead, mercury or mercury compounds
- Resistant to water and moisture
- Shield to ultra violet radiations
- Smooth finish on almost all substrates



COVERAGE

Primer coat 2.5 to 3.5 m²/lt

First coat 1.5 to 1.8 m²/lt

Final coat 1.5 to 2 m²/lt

APPLICATION METHOD

Dilute PREMIER -VB with 5-10% soft water with suitable mixing equipment at not more than 10 rpm to avoid forming bubbles, and apply as a tack coat. The surface must be clean and free from any dust, dirt, oil, grease and loose particles. Apply an even tack coat of PREMIER -VB on the surface at 1.50 m²/lt with brush or airless spray machine. After applying tack coat immediately embed the selected lagging fabric smoothly (avoid wrinkles and overlaps) into the tack coating. Within 4 hours apply two finishing coats of undiluted PREMIER - VB at ~1.50 m²/lt. It is very important to ensure that each coat of PREMIER -VB is totally **cured** before the next coat is applied.

HEALTH & SAFETY

As with all chemicals, caution should always be exercised. Protective clothing such as gloves and goggles should be worn.

INHALATION: Inhalation of vapour or mist should be avoided. Symptoms include coughing, wheezing, laryngitis, and shortness of breath, headache, nausea, and vomiting. Immediately shift victim to fresh air, and, if needed immediately start artificial respiration. Give oxygen if breathing is labored. Get emergency medical help. **EYE**

CONTACT: Flush eyes with water for 15 minutes and call for medical help. **INGESTION:** Causes nausea, vomiting, and loss of consciousness. If accidentally swallowed call for medical help immediately.

SKIN CONTACT: Flush with water or soap and water until all traces have been removed. Seek medical attention if required.

STORAGE

Store under cover, protect from direct sunlight and high temperature (>40° C). Shelf life is up to 18 months when stored as directed.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.

PACKING

PREMIER -VB is supplied in 25 kg plastic pails.

PREMIER - AF

ANTI FUNGAL DUCT COATING

PREMIER - AF is a flexible adhesive and sealant, forming a durable seal against air leakage. Due to its excellent resistance to water, U.V. and fungi, it can be used outdoors as well as indoors of thermal insulation on metal ducts. **PREMIER- AF** can be used where the humidity level has to be sustained at or above 90%.

APPLICATION METHOD

The surface should be clean, dry and free from oil, grease and loose particles.

Dilute **PREMIER - AF** with 20% soft water and apply as a primer coat at 2.5 to 3 m²/lt. After applying primer coat immediately embed the selected lagging fabric smoothly in to the wet primer coating. Apply two finishing coats of undiluted **PREMIER - AF** at rate of 3 to 3.5 m²/lt. It is very important to ensure that each coat of **PREMIER - AF** is totally **cured** before the next coat is applied.



ADVANTAGES

- Good adhesion
- Water resistant
- Non-toxic & non-flammable
- Ultra-violet resistance
- Chemical resistance
- Antifungal & antibacterial
- Suitable to Middle East climatic conditions

CLEANING

Clean all the tools immediately with clean water

T E C H N I C A L D A T A	
Base	Selective synthetic resin
No. of components	One
Colour	White
Consistency	Thixotropic like paste
Solid content	62%± 1%
Viscosity	50000 to 65000 cps (Brookfield)
Specific gravity	1.26 ± 1
Bonding time	45 minutes (at 20°C, 50% relative humidity)
Drying time	3 to 5 hours depending on ambient temperature
Service temperature	Up to 234F (112°C)
Flash Point	Non flammable
Cured Film	Flexible
Storage	Not below 5°C, protect from high temp., shelf life is 18 months from date of manufacture in an unopened container
Coverage	Approx 4m ² /lt (200 mic. WFT)
Water tightness	Excellent
Chemical resistance	Good
Insulation properties	Excellent
Solar reflection	Excellent
Water permeability resistance	Excellent
Application tools	Brush, Roller and Airless spray
Solubility	Water

PREMIER 32 - 17

ANTIBACTERIAL DUCT SEALANT

DESCRIPTION

Premier 32-17 is a fire retardant, aqua based, vapour barrier sealant for low, medium, and high velocity heating and air conditioning air ducts. It is specially formulated to meet Middle Eastern weather conditions. It is highly elastic in nature. It has excellent adhesion to metal, aluminum, etc. It acts as tough yet flexible adhesive and sealant, forming a durable seal against air leakage. Due to high ultra violet resistance Premier 32-17 can be used indoor as well as outdoor.

Premier 32-17 does not contain asbestos, lead, mercury or mercury compounds



PREMIER 32 - 17

ANTIBACTERIAL DUCT SEALANT

DESCRIPTION

Premier 32-17 is a duct sealant widely used in duct assembly of A/C Ducts

APPLICATION METHOD

Premier 32-17 should be applied to clean, dry, oil-free surface, either by power extrusion or by trowel. A 2" uniformly wide coat should be applied at 2 to 2.2 gallon/100 ft². Total coverage 40-55 ft²/gallon. Allow the completed joint to dry at least 24 hours above 25°C before pressure testing. High humidity (over 70%) and/or cooler temperature may retard drying. Total WFT (Wet Film Thickness) to be 30-35 mils.

POWER EXTRUSION

Premier 32-17 may be applied using a wide variety of power extrusion equipment which is suitable for use with water based sealants. It is soft and creamy with a typical viscosity. Always use corrosion resistant equipments.

CLEANING

All the tools must be cleaned immediately after use with fresh water

WARNING

Premier 32-17 is recommended only for industrial uses. Please keep out of reach of children. It contains Crystalline Silica which could cause irritation with eye contact. Prolonged skin contact may cause irritation too. Long-term vapour inhalation may affect lungs.

STORAGE Store in cool, dry place, preferably at 20°C.

T Y P I C A L P R O P E R T I E S

Base	Selective synthetic resin
Colour	White
Solid content	77% +/- 1.5%
Specific gravity	1.6 +/- 1
Application temperature	Min 5°C
Service temperature	-10 to 120°C
Flash Point	Non flammable
Water resistance	Excellent
UV resistance	Excellent
Chemical resistance	Excellent
Insulation properties	Excellent
Brush ability	Good
Odor	Mild
Shelf life	18 months in closed container
Solubility	Water
Packing	455 gram/cartridge



PREMIER R 242

CLOSED CELL NITRILE FOAM GLUE

DESCRIPTION

Premier-R242 is inflammable, heat resistant, single component adhesive made purely on POLYCHLOROPRENE with special tackyfier and additives. It is specially developed for Closed Cell Nitrile Foam Insulation systems.

PROPERTIES

Premier-R242 has correct balance of wet and dry tack with 'smooth flow' properties and slow uniform drying characteristics. Premier-R242 has very good heat and fire retardant properties.

APPLICATION

Premier-R242 has excellent adhesion and good compatibility with Closed Cell Nitrile foam insulation with range of metal substrate.

Used for Pre Insulated Air Duct System, Pre Insulated Pipe sections, Pre Insulated slabs etc..

APPLICATION METHOD

Before applying, the surface should be prepared clean and even, free from dust, loose shavings, oil and grease.

Apply Premier-R242 on both surfaces, either with brush or pressure feeding equipment to form a uniform coat.

Allow 20-30 minutes to evaporate the complete solvent, and then apply normal hand pressure to give strong bond.

Surface setting time varies from 20 minutes to 35 minutes depending on thickness of layers of adhesive, substrate type, moisture and temperature.

TYPICAL PROPERTIES

Base	Synthetic rubber
No.of components	One
Solid	22 ± 2
Colour	Black
Viscosity	8000 cps (Brookfield)
Density	0.83 ± 0.02
Open time	12 to 15 minutes (at 25°C, 50% rel. humidity)
Service temperature	-20°C to + 120°C
Flash point	22°C
Coverage	6 m ² /kg at 100 microns (approx.)
Storage	Keep away from direct sunlight and heat. Shelf life is 18 months from date of manufacture in an unopened container.
Water resistance	Excellent
Chemical resistance	Good
Application tools	Brush, Roller and Airless spray
Solubility	Toluene



Warranty:

All information is given in good faith on the result gained from testing and experience. However, all recommendations or suggestions are made without guarantee, since manufacturer does not have any control over / on site conditions and its uses.





CENTURY MECHANICAL SYSTEMS FACTORY L.L.C

P.O. BOX: 60270, DUBAI, UAE, TEL.: 04 347 4858, FAX: 04 347 4656
Email: cmsdubai@emirates.net.ae