

Type

UL Listed Duct Adhesive.

Description

PREMIER 81-10 UL is an UL listed premium quality, single component, synthetic rubber based adhesive with special additives and tackifier. It is specially formulated for porous and non porous surfaces in humid and hot climatic conditions. It has excellent water and alkali resistance and is inflammable. PREMIER 81-10 UL is produced under the classification and follow up service of Underwriters Laboratory, Inc.

Recommended Use

PREMIER 81-10 UL is recommended in applications where fibrous glass and other type of insulation are bonded to the interior or exterior of metal duct system.

Features

- Fire resistant
- Excellent Adhesion and high strength
- Low smell
- Excellent open time & Wet tack
- Excellent bonding to porous and non porous surface Chemical resistant
- Non-toxic
- UV resistant

Form Supplied

Liquid

DATA REPRODUCED FROM UNDERWRITERS LABORATORIES, INC. BUILDING MATERIALS DIRECTORY

COATING GENERAL PURPOSE	R-27945
	Surface Burning Inorganic Characteristics 14inch (6.4 mm) Reinforced cement board
Surface Flame Spread	0
Smoke Developed	0
Number of Coats	1
Rate per coat (sq.ft.per gal.)	200

Specification

PROPERTY	Value	Unit of Measurement	Method
Specific Gravity	0.85±.10	kg/l	ASTM D 1475-98
Solid	28±2	%	ASTM D 1644-01
Viscosity	800-1500	cps	ASTM D 2196
Flash point	>10	°C	ASTM D 92

Other Data*

Appearance	Green Color
Service Temperature	-25°C to 90°C
Chemical Resistance	Excellent
Cure Film	Flexible & tough
UV Resistivity	Excellent
Insulation Properties	Excellent
Coverage	6 to 9 m2/per liter



Surface Preparation

The surface should be structurally sound, clean, dry, leveled and free from dust curing compounds grease and other loose debris.

Application Procedure

Apply PREMIER 81-10 UL @ 6 - 9 m²/liter (subject to surface condition). It is very important to ensure that each coat of PREMIER 81-10 UL is totally cured before the next coat is applied. The dry film thickness will vary with fabric selected.

Packaging

5 USG Pails

Shelf life Storage

18 months from date of manufacturing in an original unopened container. Store product 10°C - 40°C for maximum storage life. Higher temperatures reduce normal storage life. Lower temperatures may cause increased viscosity of a temporary nature. Rotate stock on a "First in First out" basis.

Cleaning

Tools : Clean immediately after use with water or white spirit if the material has dried.

Clean : Immediately removed any adhesive from the surface of the floor covering with a damp Cloth.

Health & Safety

Please refer to the MSDS.



This Information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility.