

Passive fire protection with innovative ideas

EXCELAIR

AIRFILTERS ■ AIROUTLETS ■ HVAC DUCTING ■ ADHESIVE TAPES ■ MEP ACCESSORIES ■ FLANGING SYSTEMS ■ LAUNDRY SOLUTIONS

FIRE DAMPER

(suitable for both static and dynamic systems.)



MULTI BLADE (Motorized/Spring Actuated)

1.5 hr Fire Rated

- V-locking blades
- Airfoil blades

Catalogues

EFD - 140

EFD - 150

Certification

UL certification

UL certification

3 hr Fire Rated

- V-locking blades
- Airfoil blades

EFD - 340

EFD - 350

UL certification

UL certification

Velocity Rating 2000 to 4000 FPM | Pressure Rating 4"wg to 8"wg

FIRE SMOKE DAMPER

(suitable for both static and dynamic systems.)

COMBINATION FIRE & SMOKE

Catalogues

Certification

1.5 hr Fire Rated, (with V - Lock Blade)

- Class-I leakage
- Class-II leakage
- Class-III leakage

EFSD - 141

EFSD - 142

EFSD - 143

UL certification

UL certification

UL certification

1.5 hr Fire Rated, (with Airfoil Blade)

- Class-I leakage
- Class-II leakage

EFSD - 151

EFSD - 152

UL certification

UL certification

3 hr Fire Rated, (with V - Lock Blade)

- Class-I leakage
- Class-II leakage
- Class-III leakage

EFSD - 341

EFSD - 342

EFSD - 343

UL certification

UL certification

UL certification

3 hr Fire Rated, (with Airfoil Blade)

- Class-I leakage
- Class-II leakage

EFSD - 351

EFSD - 352

UL certification

UL certification

Velocity Rating 2000 to 4000 FPM | Pressure Rating 4"wg to 8"wg | Temperature Rating 250 Deg F & 350 Deg F



Passive fire protection with innovative ideas

EXCELAIR

AIRFILTERS ■ AIROUTLETS ■ HVAC DUCTING ■ ADHESIVE TAPES ■ MEP ACCESSORIES ■ FLANGING SYSTEMS ■ LAUNDRY SOLUTIONS

SMOKE DAMPER

(suitable for both static and dynamic systems.)

SMOKE DAMPER

Catalogues

Certification

V - Lock Blade

- Class-I leakage rated
- Class-II leakage rated
- Class-III leakage rated

ESD - 141

UL certification

ESD - 142

UL certification

ESD - 143

UL certification

Airfoil Blade

- Class-I leakage rated
- Class-II leakage rated

ESD - 151

UL certification

ESD - 152

UL certification

Velocity Rating 2000 to 4000 FPM | Pressure Rating 4"wg to 8"wg | Temperature Rating 250 Deg F & 350 Deg F



CURTAIN DAMPER

CURTAIN TYPE FIRE DAMPER

Catalogues

Certification

1.5 hr Fire Rated (Static Sytem)

- Style-A
- Style-B
- Style-C

EVFD - 10 - A

UL certification

EVFD - 10 - B

UL certification

EVFD - 10 - C

UL certification

1.5 hr Fire Rated (Dynamic Sytem)

- Style-A
- Style-B
- Style-C

EVFD - 10 D - A

UL certification

EVFD - 10 D - B

UL certification

EVFD - 10 D - C

UL certification

3 hr Fire Rated (Static Sytem)

- Style-A
- Style-B
- Style-C

EVFD - 30 - A

UL certification

EVFD - 30 - B

UL certification

EVFD - 30 - C

UL certification

3 hr Fire Rated (Dynamic Sytem)

- Style-A
- Style-B
- Style-C

EVFD - 30 D - A

UL certification

EVFD - 30 D - B

UL certification

EVFD - 30 D - C

UL certification



Velocity Rating 2000 to 4000 FPM | Pressure Rating 4"wg

Passive fire protection with innovative ideas

EXCELAIR

AIRFILTERS ■ AIROUTLETS ■ HVAC DUCTING ■ ADHESIVE TAPES ■ MEP ACCESSORIES ■ FLANGING SYSTEMS ■ LAUNDRY SOLUTIONS

STAINLESS STEEL FIRE / SMOKE

(suitable for both static and dynamic systems, Stainless Steel Construction.)

MOTORIZED FIRE DAMPER

Catalogues

Certification

V - Lock Blade

- 1.5hr Fire Rated
- 3hr Fire Rated

EFD - 140-SS

UL certification

EFD - 340-SS

UL certification

COMBINATION FIRE & SMOKE DAMPER

V - Lock Blade

- 1.5hr fire rated, Class-II leakage
- 1.5hr fire rated, Class-III leakage
- 3 hr fire rated, Class-II leakage

EFSD - 142-SS

UL certification

EFSD - 143-SS

UL certification

EFSD - 342-SS

UL certification

SMOKE DAMPER

V - Lock Blade

- Class-II leakage rated
- Class-III leakage rated

ESD - 142-SS

UL certification

ESD - 143-SS

UL certification

Velocity Rating 2000 FPM | Pressure Rating 4"wg | Temperature Rating 250Deg F



TRUE ROUND

(suitable for both static and dynamic systems.)

TRUE ROUND FIRE SMOKE

Catalogues

Certification

Fire damper

- 1.5 Hr Fire Rated

EFD 125 R

UL certification

Combination fire and smoke damper

- 1.5hr fire rated, Class-I leakage

EFSD 125 R

UL certification

Smoke damper

- Class-I leakage rated

ESD 25 R

UL certification

Velocity Rating 2000 FPM | Pressure Rating 4"wg | Temperature Rating 250Deg F or 30 Deg F



Products from



Century Mechanical Systems Factory LLC
Al Quoz Industrial Area 4,
Dubai, United Arab Emirates
Tel: +971 4 3474858
E mail: info@cmglobal.com | cmglobal.com

