



EXCELAIR
HEPA HT-900

EXCELAIR

Air Filters

Since 1982

HEPA HT-900

DEEP PLEAT CONSTRUCTION | HEPA

Features & Benefits | HEPA HT-900

- Standard capacity deep pleated High Temperature HEPA Filter.
- HEPA HT-900 filter utilizes micro glass fiber paper media arranged in deep pleat construction
- The filters feature a reinforced stainless steel frame, providing exceptional stability.
- Each filter is scan tested individually per EN 1822, ensuring a leak proof performance. Test results are affixed by label to each filter.
- HEPA HT-900 filters are suitable for use in high temperature applications of up to 900 °F / 482°C
- The filters specifically designed to meet the requirements of the pharmaceutical industry for dehydrogenation tunnels and ovens.

Specifications | HEPA HT-900

Type	Deep pleat construction
Filter Grades (EN 1822)	E12 / H13 / H14
MPPS Efficiency	≤ 99.5% / ≤ 99.95% / ≤ 99.995%
Efficiency @ 0.3μ	≤ 99.97% / ≤ 99.99% / 99.999%
Filter Media	Micro glass fiber paper media
Media Separator	Corrugated Aluminium / Corrugated Stainless steel
Frame	Stainless steel
Media Sealant	Ceramic Cement
Gasket	Ceramic Fiberglass
Maximum Temperature	900°F / 482°C
Final Pressure Drop	2.00" wg (Recommended)

Applications | HEPA HT-900



Hospital



Biomedical



Pharmaceutical



Laboratories



Food Processing



Hospitality Industry



Selection Chart

Model Reference	Actual Dimensions (inches)			Filter Classification as per EN 1822	Airflow		Initial Pressure Drop	Media Area
	Width	Height	Depth		CFM	CMH	(Inch W.G)	(Sq.ft.)
EHHT900-12x24x6-(DTF/BX)-H14	12	24	5.90	H14	240	410	1.10	39
EHHT900-24x24x6-(DTF/BX)-H14	24	24	5.90	H14	525	890	1.10	83
EHHT900-12x12x12-(DTF/BX)-H14	11.30	11.30	11.50	H14	215	365	1.10	33
EHHT900-12x12x12-(DTF/BX)-H14	12	12	11.50	H14	240	410	1.10	38
EHHT900-12x24x12-(DTF/BX)-H14	12	24	11.50	H14	475	805	1.10	77
EHHT900-24x24x12-(DTF/BX)-H14	23.30	23.30	11.50	H14	950	1615	1.10	155
EHHT900-18x18x12-(DTF/BX)-H14	18	18	11.50	H14	565	960	1.10	91
EHHT900-24x24x12-(DTF/BX)-H14	24	24	11.50	H14	1000	1700	1.10	166
EHHT900-30x24x12-(DTF/BX)-H14	30	24	11.50	H14	1270	2160	1.10	210
EHHT900-12x24x6-(DTF/BX)-H13	12	24	5.90	H13	295	500	1.10	39
EHHT900-24x24x6-(DTF/BX)-H13	24	24	5.90	H13	635	1080	1.10	83
EHHT900-12x12x12-(DTF/BX)-H1	11.30	11.30	11.50	H13	260	440	1.10	33
EHHT900-12x12x12-(DTF/BX)-H13	12	12	11.50	H13	285	485	1.10	38
EHHT900-12x24x12-(DTF/BX)-H13	11.30	23.30	11.50	H13	540	915	1.10	69
EHHT900-12x24x12-(DTF/BX)-H13	12	24	11.50	H13	570	970	1.10	77
EHHT900-24x24x12-(DTF/BX)-H13	23.30	23.30	11.50	H13	1100	1870	1.10	155
EHHT900-18x18x12-(DTF/BX)-H13	18	18	11.50	H13	650	1105	1.10	91
EHHT900-24x24x12-(DTF/BX)-H13	24	24	11.50	H13	1200	2040	1.10	166
EHHT900-24x12x12-(DTF/BX)-H13	24	12	11.50	H13	600	1020	1.10	81
EHHT900-30x24x12-(DTF/BX)-H13	30.00	24.00	11.50	H13	1525	2590	1.10	210
EHHT900-12x12x12-(DTF/BX)-E12	12	12	11.50	E12	285	485	1.10	38
EHHT900-12x24x12-(DTF/BX)-E12	12	24	11.50	E12	570	970	1.10	77
EHHT900-24x24x12-(DTF/BX)-E12	24	24	11.50	E12	1200	2040	1.10	166

Model Ref.Numbering Scheme & Size Selection | HEPA HT-900

- EHHT900 - 12x12x12-E12
- E

:

Excelair
- HHT900

:

HEPA High Temperature 900°F
- 12x12x12

:


Width x Height x Depth
- DTF / BX

:

Double Turn Flange
- E12

:

Grade



General Isometric view

Note: The photos shown are only for illustration purpose. The actual product may vary. Please contact the technical/sales department for more information. As a part of continuous improvement, CMS reserve the right to make technical modifications without prior notice. All non-standard sizes are available upon request. Please contact factory for details.

EXCELAIR

Air Filters



Products from



Manufacturer:

Century Mechanical Systems Factory LLC
Tel: +971 4 3474858, Fax: +971 4 3474656
P.O Box: 60270, Dubai, United Arab Emirates
E mail: info@cmsglobal.com

