Common Errors in Dimple Coding

Common Errors to Avoid in Prompts

CRITICAL 🔴 **-** Having this issue will automatically lower your task score to 2
IMPORTANT 🟡 **-** Having this issue will lower your task score with the risk of getting a 2

Status	Common Error	Example
IMPORTANT 🟡	**Lacking Naturalness** These prompts are being described as “not natural,” “contrived,” or “too simple.” There should be a realistic user need.	⛔ **Bad Prompt** *Show details of famous tourist places in Telangana in a customized schema. It should include the name of the place, city, specialty, main attractions, and entry fee. Example:* *[{* *"Name" : "Ramappa Temple",* *"Region" : "Mulugu",* *"Speciality" : "UNESCO Heritage Site",* *"Main attractions" : ["Sculpture", "Cleanliness"],* *"Entry fee" : "30 Rs"* *}]*
CRITICAL 🔴	**Feasibility** These are prompts that contain impractical or impossible requests that can't be answered by an LLM in a single response. They can have conflicting or contradicting instructions that can't be fulfilled simultaneously or are incoherent.	⛔ **Bad Prompt** *Create an XML structure containing information about cultural event programs in Moldova for 2026. It also necessarily includes the event name, date, location, type and description.*

CONFIDENTIAL | gamermada2@gmail.com+outlier | 2026-02-13T13:50:00.697Z

Status	Common Error	Example
CRITICAL 🔴	**Scope Misalignment** Many prompts fall outside the expected task category, for example, requesting code generation instead of structured data. Output should be a data structure, not code or analysis.	⛔ **Bad Prompt** *Create a Kubernetes deployment YAML file for my web app lounge_app. This app should expose port 8080, run with 3 replicas, and use Canary as the deployment strategy. Structure this YAML file so that it is suitable for use in a CI/CD pipeline.*
IMPORTANT 🟡	**Missing Structure** Prompts often lack real-world data complexity or fail to provide example inputs, making them ambiguous or underspecified.	⛔ **Bad Prompt** *For a monitoring system for a Java project with Spring Boot, I need to document how internal notifications are handled. Create 5 examples using the custom schema -notification_name, *trigger_event*, #description# %priority%. Each notification should reflect a realistic scenario in an enterprise project.*
CRITICAL 🔴	**Lacking Specificity** There are frequent one-sentence prompts that don't give the model enough detail to generate a useful or targeted data structure.	–
CRITICAL 🔴	**Incorrect Category Use**	⛔ **Bad Prompt** For example, if the category is `YAML`, the expected output must be in a YAML-like structure, not JSON

CONFIDENTIAL | gamermada2@gmail.com+outlier | 2026-02-13T13:50:00.697Z

Status	Common Error	Example
CRITICAL 🔴	**Misuse of "Customized Schema"**	A truly customized schema must represent a unique or unconventional format that doesn't already exist in standard serialization formats.
CRITICAL 🔴	**Array Ambiguity**	Some CBs, for the Array tasks, wrongfully request for a JSON array, which fits into the JSON category but not into the Array category. Also, avoid requesting "Python arrays" as this is not an in-built data type.
CRITICAL 🔴	**Non-code Lists**	⛔ **Bad Prompt** *I'm currently preparing packages for a group of tourists coming from outside Egypt, and the trip starts in Alexandria. So I need an organized list of 10 hotels located in popular areas like Raml Station, Stanley, Bahri, and Maamoura. Each hotel should include the name, number of stars, daily price in Egyptian pounds, whether breakfast is included, address, mobile number or other contact information, and if there are current offers. It's preferable to arrange them from most expensive to cheapest so I can choose the most suitable one according to the budget.*

CONFIDENTIAL | gamermada2@gmail.com+outlier | 2026-02-13T13:50:00.697Z