Mohammed Nagi

Cairo, Egypt
mo.nagi017@gmail.com +27 707 466 350 LinkedIn GitHub

RESEARCH PROFILE

Graduate DeepMind Scholar from the AIMS MSc in Artificial Intelligence for Science, with a background in electrical and electronics engineering. I use mechanistic interpretability techniques to study the internal representations of models trained on instrument data rather than text, and build Human-AI collaboration systems that learn when a model should defer to a human expert.

EDUCATION

MSc Mathematical Sciences, specialisation in Artificial Intelligence for Science Sep 2025 – July 2026
African Institute for Mathematical Sciences (AIMS) South Africa *Cape Town*

- **Overall mark:** 84 (Distinction).
- **Relevant coursework:** Applied Machine Learning at Scale, Bayesian Inference, Monte Carlo Methods for Machine Learning, Explainable AI (XAI), Reinforcement Learning, Responsible AI, CUDA Programming for NVIDIA GPUs, Natural Language Processing and Large Language Models.

BSc (Honours) Electrical and Electronics Engineering 2017 – Aug 2025
University of Khartoum *Sudan*

- **Grade:** First Class Honours.
- **Relevant coursework:** Calculus, Linear Algebra, Systems Modelling and Simulation, Signal Processing, Real-Time Embedded Systems.

RESEARCH & TECHNICAL PROJECTS

MSc Thesis: Sparse Autoencoders for Interpretability of InstaNovo | *Python, PyTorch* July 2026

- First sparse autoencoder analysis of a de novo peptide sequencing model: trained SAEs at four encoder depths of InstaNovo over 639,286 spectra, recovering more than 99.5% of sequencing loss at every layer, with chemical properties emerging at the depths fragmentation theory predicts.
- Labelled every peak with 50 concepts computed from fragment-ion theory, then showed the limits of that vocabulary: theory labels only 38% of peaks, and features responding to the rest are described *better* than the strongest concept-associated ones (median r 0.82 against 0.65), recovering real chemistry the annotation omits.
- Two masses recovered from unlabelled peaks match modified-residue immonium ions to within a millidalton, chemistry the annotation could not express; the remaining recurring masses are open candidates for mass-spectrometry validation.

Fairness-Constrained Bandit Routing for Human-AI Triage | *PyTorch, SHAP, Fairlearn* 2026

- Architected PsychRoute, a fairness-constrained human-AI collaboration framework for psychiatric triage (Bipolar Disorder vs Major Depressive Disorder), wrapping a fine-tuned MentalBERT classifier in a LinUCB contextual bandit that routes each encounter across four governance-anchored actions mapped to the Fabric AI governance taxonomy (*Jorgensen et al., 2025*).
- Reduced diagnostic error rate by 35% (0.017 vs 0.026 AI-only and 0.070 human-only) on 3,626 held-out encounters, with formal verification of human-AI complementarity in both directions (*Mozannar & Sontag, 2020*), i.e. the combined system outperforms either party alone rather than merely deferring.

Multilingual Polarisation Detection (SemEval-2026) | *Python, PyTorch, Hugging Face* 2025

- Engineered a two-stage training framework for multilingual classification under extreme 16:1 class imbalance, optimising DeBERTa and MARBERTv2 (Arabic) backbones with Focal Loss to correct distributional skew in low-resource settings.
- Developed dynamic per-class thresholding to maximise Macro-F1, demonstrating that loss-function engineering lifts minority-class recall considerably more than simply scaling the model.

AI-Driven Discovery in Spectral Graph Theory | ***Python, PyTorch, RL, GNNs*** 2026

– Extended the Cross-Entropy Method (*Wagner, 2021*) with graph neural network policy approximators to discover counterexamples to open conjectures in spectral graph theory, automating search through discrete combinatorial spaces (graphs up to $N = 35$) to surface structural violations of established mathematical bounds.

Explainable AI & Mechanistic Interpretability | ***PyTorch, SHAP, LIME, TCAV*** 2026

– Implemented axiomatic Shapley decomposition, LIME, and counterfactual explanations from scratch, then contrasted their correlational attributions against Integrated Gradients and Testing with Concept Activation Vectors on Vision Transformers and sequence models, mapping where attribution-based and causal/mechanistic methods agree and diverge.

High-Performance Recommender System (32M MovieLens) | ***Python, Numba, NumPy*** 2026

– Built a hardware-aware Alternating Least Squares pipeline achieving an 8,767× speedup over the Python baseline via JIT compilation and a synchronised CSR/CSC sparse architecture, cutting per-epoch latency from 3.5 hours to 1.46 seconds.

– Verified through latent-manifold analysis that the model autonomously recovers interpretable semantic structure.

TECHNICAL SKILLS

Languages: Python, CUDA, SQL, MATLAB, LaTeX
ML & Interpretability: PyTorch, Scikit-learn, TransformerLens, Sparse Autoencoders, SHAP, LIME, Integrated Gradients.
Causal & Statistical Methods: Causal Interventions, Feature Ablation, Bayesian Inference, Monte Carlo Methods
Safety, Alignment & Fairness: MC-Dropout Uncertainty, Temperature Calibration, Fairlearn Auditing, Contextual Bandits.
Tools & Platforms: Git, Docker, Google Cloud Platform (GCP)
Research Interests: Mechanistic Interpretability, Machine Learning for the Sciences, Human-AI Collaboration, AI Safety
Natural Languages: Arabic (Native), English (Fluent), French (Beginner)