

Semi-Humanoid Robotics: Strategic Research Implementation Plan and Market Analysis

Implementation Plan for Structuring Modular Semi-Humanoid Research

Evaluating and deploying a modular semi-humanoid robotic system requires a systematic engineering strategy that integrates dynamic stabilization, thermal structural modeling, low-inertia actuation, real-time control, and total cost of ownership (TCO) benchmarks. The proposed semi-humanoid platform—combining a compliant anthropomorphic upper body, a 3-degree-of-freedom (DOF) stabilized perception head, two 7-DOF proximally actuated arms, under-actuated compliant hands, and a wheeled mobile base—addresses the operational limitations of stationary industrial cobots and complex bipedal humanoid¹. To execute this evaluation, the research roadmap is structured across five sequential engineering and analytical phases.

Kinematic Synthesis and Dynamic Stability Modeling

The hybrid kinematic form factor trades the mechanical friction and power expenditure of bipedal gait control for a wheeled mobile platform while retaining upper-body anthropomorphic reach². Research begins by modeling static and dynamic tipping boundaries under cantilevered arm loads.

Static balance for a wheeled platform bearing a cantilevered dual-arm payload is governed by projecting the global center of mass ($\mathbf{P}_{\text{CoM}}$) into the ground plane support polygon ($\mathcal{P}_{\text{support}}$) bounded by wheel contact points. The system center of mass is derived as:

$$\mathbf{P}_{\text{CoM}} = \frac{m_b \mathbf{r}_b + m_t \mathbf{r}_t + \sum_{i=1}^N m_i \mathbf{r}_i(\mathbf{q})}{M_{\text{total}}} \in \mathcal{P}_{\text{support}}$$

where m_b , m_t , and m_i represent the masses of the base, torso, and individual arm links; $\mathbf{r}$ denotes their spatial vectors as a function of joint configuration $\mathbf{q}$; and M_{total} is the aggregate system mass⁴. Kinematic modeling must establish the operational payload envelope such that dynamic accelerations during dual-arm manipulation do not shift the Zero Moment Point (ZMP) outside $\mathcal{P}_{\text{support}}$.

Thermal and Structural Chassis Engineering

The torso framework serves as both the primary load-bearing structural spine and a passive thermal dissipation system⁵. Research evaluates open and closed structural aluminum profiles (e.g., 6061-T6 alloy) to optimize torsional rigidity under cantilever arm torque.

To avoid active cooling fans—which draw parasitic power, produce acoustic noise that degrades speech recognition, and ingest airborne particulates—the structural design integrates a distributed passive cooling strategy⁵. By thermal coupling of the primary onboard graphics processing units (GPUs), central processing units (CPUs), and Power Distribution Units

(PDUs) to the structural aluminum chassis ($k \approx 167 \text{ W/m} \cdot \text{K}$), the framework acts as a conductive heat sink, dissipating thermal energy passively via natural convection⁵.

Actuation Mechanics and Low-Inertia Distal Design

Safe physical Human-Robot Interaction (HRI) requires low distal limb inertia¹. The research framework focuses on a proximal actuation model:

- **Proximal Actuator Placement:** Heavy prime movers—high-torque zero-backlash Harmonic Drives (Strain Wave Gearing) supported by cross-roller bearings—are housed inside the upper shoulder and torso structures⁵.
- **Remote Tendon Transmission:** Distal joints (elbow, wrist) are actuated remotely using high-tensile Dyneema or Kevlar tendon cable networks routed through low-friction conduits inside hollow structural links⁴.
- **Under-Actuated Grasping:** End-effector evaluation leverages passively compliant mechanisms, such as Yale OpenHand variants, where single prime movers actuate multi-jointed flexure fingers, allowing compliant adaptation around unmodeled object geometries without joint-by-joint inverse kinematics⁶.

Perception, Control, and Software Orchestration Architecture

The system software stack decouples high-level cognitive task planning from low-level deterministic motor execution:

- **High-Level Cognitive Layer:** Heterogeneous onboard compute (e.g., NVIDIA Jetson / Intel NUC) executes Robot Operating System 2 (ROS 2), Nav2 for dynamic obstacle avoidance, MoveIt 2 for 7-DOF trajectory generation, and Vision-Language-Action (VLA) pipelines for verbal command parsing².
- **Low-Level Deterministic Execution:** Dedicated microcontrollers run deterministic control loops ($\geq 1 \text{ kHz}$) over real-time fieldbuses (CAN-FD or EtherCAT) for motor commutation, active impedance control, and safety watchdogs⁸.
- **Perception & Audio Array:** A 3-DOF low-inertia neck decouples vision from base motion³. Sensor suites integrate wide-baseline stereo RGB-D cameras (Orbbec Gemini 336 / Luxonis ToF) with lateral microphone arrays using Time-Difference-of-Arrival (TDOA) algorithms for Sound Source Localization (SSL)⁵.

Economic Feasibility and Benchmark Validation

The evaluation pipeline cross-references open-source hardware modules (e.g., Pollen Robotics Reachy 2, Hello Robot Stretch, Yale OpenHand) against commercial platforms². Quantitative metrics evaluate capital expenditure, assembly reproducibility, serviceability, and maintenance downtime¹.

Market Landscape and Macroeconomic Growth Drivers

The global market for semi-humanoid robotics, mobile manipulators, and autonomous mobile manipulator robots (AMMRs) is expanding rapidly¹. Historically, industrial facilities separated autonomous navigation (Autonomous Mobile Robots / Automated Guided Vehicles) from object manipulation (stationary robotic arms)¹. The integration of these capabilities into unified mobile manipulators is redefining workflow economics in logistics, electronics assembly, healthcare, and research laboratories¹.

Global Market Valuation and Segment Forecasts

Market studies across mobile manipulation and semi-humanoid sub-sectors reveal strong compound growth trajectories:

Market Category / Report Scope	Base Valuation	Base Year	Forecast Valuation	Target Year	Forecast CAGR	Primary Growth Drivers	Citation
Global Mobile Manipulator Market	\$1.52 Billion	2025	\$3.95 Billion	2032	14.7%	AMR/Arm convergence, e-commerce automation, whole-body AI control	¹
Mobile Manipulators	\$0.89 Billion	2025	\$3.74 Billion	2034	17.3%	Repetitive task automa	¹⁰

(Broad er Scope)						tion (65% adoptio n), line feeding, safety compliance	
Autonomous Mobile Manipulator Robots (AMMR)	\$385.9 Million	2023	\$1.699 Billion	2030	23.9%	AI/ML sensor integration, labor shortages, high-precision picking	11
Extended Mobile Manipulator Industry	\$4.70 Billion	2025	\$14.10 Billion	2033	13.0%	Elimination of non-value walking, battery swapping, 24/7 duty cycles	13
Autonomous Mobile Robots (AMR Baseline)	\$3.10 Billion	2025	\$17.00 Billion	2035	19.5%	Goods-to-person picking, agricultural auto-steering, pharmalogistics	14

Global Mobile Robots Sector (Total Systems)	\$20.79 Billion	2025	\$63.28 Billion	2035	11.83%	Software/services dominant (67.17%), SME expansion, modular platforms	¹²
--	-----------------	------	-----------------	------	--------	---	---------------

Variations in base market valuations stem from scope boundaries: focused definitions isolate standalone AMMR units with integrated articulated arms¹¹, whereas broader evaluations include heavy industrial conveyor-replacing mobile platforms, commercial package-handling systems, and semi-humanoid service platforms¹². Across all definitions, mobile manipulation significantly outpaces stationary industrial robotics, driven by the demand for flexible, unanchored automation¹.

Geographic Dynamics and End-User Vertical Distribution

North America holds a leading position in global revenue share, representing 33.5% to 35.0% of the market¹⁰. This footprint is supported by capital investments in e-commerce fulfillment infrastructure, automated logistics centers, and advanced manufacturing in automotive and semiconductor sectors¹.

The Asia-Pacific region represents the fastest-growing market, commanding a 39.3% revenue share in specialized categories like AMMRs¹¹. Rapid industrial adoption in China, Japan, South Korea, and India—driven by electric vehicle (EV) battery production, cleanroom electronics manufacturing (which accounts for 22.70% of total mobile robot deployments), and government-backed automation initiatives—accelerates regional expansion¹. In Europe, adoption is shaped by strict safety compliance frameworks, including ISO/TS 15066 and the EU Machinery Regulation 2023/1230¹.

From an industry perspective, manufacturing and warehouse logistics represent over 70% of total mobile manipulator deployments¹⁰. Primary application areas include:

- **Warehouse Logistics & E-Commerce:** Package sorting, trailer unloading (e.g., Boston Dynamics Stretch handling 25 kg containers)¹³, and goods-to-person picking (\$1.3 Billion market segment)¹⁴.
- **Electronics & Semiconductor Fabrication:** Cleanroom material transport, silicon wafer cassette handling, and assembly line feeding¹².
- **Healthcare & Clinical Laboratories:** Automated specimen transport, sterile equipment

handling, and assistive care tasks².

Competitive Benchmarking and Architectural Archetypes

Commercially available mobile manipulators and semi-humanoids fall into three structural archetypes:

1. **Telescoping Single-Arm Platforms:** Systems designed for lightweight Cartesian reach in narrow domestic and clinical spaces (e.g., Hello Robot Stretch)².
2. **Bimanual Bio-Inspired Semi-Humanoids:** Platforms featuring dual-arm upper bodies mounted on holonomic bases, combining anthropomorphic kinematics with expressive HRI interfaces (e.g., Pollen Robotics Reachy 2)³.
3. **Heavy Industrial Mobile Manipulators:** Heavy-payload cobot arms mounted on differential AMR bases, built for industrial line-feeding and high-rigidity operations (e.g., PAL Robotics TIAGo, Toyota HSR, legacy Willow Garage PR2)¹⁷.

Platform Specification Benchmark


Rob ot Platf orm	Dev elop er / Pare nt Com pan y	List Unit Pric e (US D)	Tota l Mas s	Max Wor king Heig ht / Rea ch	Sing le Arm Payl oad	Deg rees of Free dom (Do F)	Onb oard Proc essi ng Stac k	Bas e Kine mati cs & Ope ratin g Runt ime	Mid dle war e & Ecos yste m Com pati bilit y	Cita tion
Stre tch 3 / 4	Hell o Rob ot	\$19, 950 – \$29, 950	46 kg (33 kg unba llast ed)	160 cm heig ht; 71 cm reac h	2.5 kg (exte nde d) / 4.0 kg (retr acte d)	5 DoF (Tele scop ing arm + 2-D OF Dex Wris	Intel NUC 15 + NVI DIA Jets on Orin NX	Diffe renti al / Om nidir ecti onal; 8h runti me	Ope n-so urce ROS 2, Pyth on SDK, Nav 2, VLM gras	²

						t)			ping	
Rea chy 2	Polle n Rob otics / Hug ging Face	\$70, 000 – \$78, 000	50 kg syst em; 20– 25 kg upp er tors o	136– 166 cm (adju stabl e)	~3.0 kg per arm (Dua l arms)	17 DoF (2x 7-D OF arms + 3-D OF neck) + base	Onb oard CPU + Exte rnal GPU supp ort	3-W heel Holo nomi c Om nidir ecti onal; 8h runti me	ROS 2, Pyth on SDK, Ethe rCAT (500 Hz), VR Tele op	³
TIA Go	PAL Rob otics	~\$56 ,000 – \$70, 000	70 kg	145 cm heig ht	3.0 kg – 6.0 kg (sing le/du al arm opti ons)	7 to 14 DoF (Arm dep end ent) + lift	Onb oard Indu strial PC (Intel i7)	Diffe renti al Driv e AMR ; 8–10 h runti me	ROS / ROS 2, Mov elt, C++ APIs	¹⁷
HSR (Hu man Sup port Rob ot)	Toyo ta	Prop rieta ry / Leas e	37 kg	100 –135 cm heig ht	~1.2 kg	4 DoF arm + pitch /roll wrist + base	Inte grat ed Onb oard Indu strial Com pute	Om nidir ecti onal; ~2–4 h runti me	ROS / Toyo ta Rese arch Soft ware Stac k	¹⁷
PR2	Willo w Gara	~\$4 00,0	220 kg	140 cm heig	~2.0 kg per	16 DoF (Dua	Dual Xeo n	Om nidir ecti	ROS (Ori ginal	¹⁷

	ge (Leg acy)	00		ht	arm	I 7-D OF arms + neck + spin e)	Serv ers onb oard	onal Cast er Base ; ~2h runti me	Rese arch Base line)	
--	--------------------	----	--	----	-----	--	----------------------------	--	-------------------------------	--

Architectural Analysis

The historical evolution of mobile manipulation highlights a shift in cost structures and mechanical complexity. Early research platforms like the Willow Garage PR2 relied on heavy counter-weighted frames (220 kg) at high price points (~\$400,000), limiting enterprise deployment¹⁷. Modern commercial and research platforms concentrate in two cost-to-capability brackets:



Lightweight single-arm architectures, exemplified by Hello Robot Stretch, prioritize mechanical simplicity and low mass². Using a single vertical lift column and a carbon-fiber telescoping arm, Stretch achieves Cartesian translation while keeping total mass at 46 kg (33 kg with transport ballast removed)². With a base width of 34 cm—matching human hip dimensions—it navigates constrained domestic and clinical settings safely⁴. However, its limited payload (2.5 kg extended) and single-arm configuration restrict its performance in heavy industrial handling or bimanual coordination tasks².

Bimanual bio-inspired semi-humanoids, such as Pollen Robotics Reachy 2, focus on anthropomorphic HRI and dexterous bimanual manipulation³. Reachy 2 incorporates dual 7-DOF arms driven by parallel joint mechanisms (Orbita actuators), lifting 3.0 kg per arm at a system mass of 50 kg³. The acquisition of Pollen Robotics by Hugging Face in April 2025 illustrates a major trend: using open-source modular hardware platforms to collect teleoperation datasets for training foundational Embodied AI models⁹.

Technical Subsystem Engineering and Embodied AI Integration

Combining lightweight mobility with multi-DOF upper-body dexterity requires coordination across five core mechanical and software subsystems².

Torso Infrastructure and Passive Thermal Dissipation

The central torso forms the load-bearing spine of the semi-humanoid robot⁵. It supports dynamic cantilever forces generated during dual-arm motion while housing the primary power storage, power distribution units, and high-performance compute hardware⁵.

In place of active cooling fans, the chassis implements a passive thermal dissipation design⁵. Compute units (NVIDIA Jetson / Intel NUC) and PDUs are thermally bonded directly to structural aluminum plates². Heat generated during computer vision processing and trajectory calculation conducts into the aluminum framework and dissipates through natural convection⁵. This open-structure convective pathway lowers parasitic battery drain, reduces acoustic noise during voice interaction, and eliminates fan dust draw into joint mechanics⁵.

Perception Suite and Neck Gimbal Kinematics

Decoupling perception from base motion requires a low-inertia neck assembly³. The neck uses a 3-DOF gimbal (Pitch, Yaw, Roll) driven by parallel brushless motors (e.g., Orbita 3D technology)³.

To minimize head inertia and enable rapid saccadic tracking ($I = \sum m_i r_i^2$), compute hardware is offloaded to the torso, leaving only raw sensor modules in the head⁵:


- **Stereo RGB-D Vision:** Dual global shutter RGB cameras (e.g., Sony IMX296) provide wide-baseline stereo imaging, paired with depth sensors (e.g., Orbbec Gemini 336 or Luxonis OAK ToF) for 3D point-cloud generation across a 0.2 m to 5.0 m operational range⁵.
- **Acoustic Localization:** Lateral microphone arrays perform Sound Source Localization (SSL) using Time-Difference-of-Arrival (TDOA) algorithms⁵. The sound source angle (θ) relative to microphone spacing (d) is determined real-time via:

$$\Delta t_{ij} = \frac{\mathbf{P}_s - \mathbf{P}_i}{c} - \frac{\mathbf{P}_s - \mathbf{P}_j}{c} \implies \theta = \arcsin \left(\frac{c \cdot \Delta t_{ij}}{d} \right)$$

where c is the speed of sound, allowing the neck to turn toward a human speaker before natural language processing completes⁵.

Proximal Actuation and Remote Tendon Drive Kinematics

Safety during physical HRI requires minimizing moving limb inertia¹. Positioning high-mass drive motors in distal elbow or wrist joints increases rotational inertia, raising collision impact forces during unexpected contact¹.



To eliminate this dynamic risk, the arms utilize proximal actuation:

1. **Proximal Actuator Placement:** High-torque prime movers—such as zero-backlash Harmonic Drives (Strain Wave Gearing) backed by cross-roller bearings—are housed inside the upper shoulder and torso frame⁵.
2. **Tendon-Driven Transmission:** Motion to distal joints (1-DOF elbow, 2–3 DOF wrist) is transferred via closed-loop Dyneema or Kevlar cable tendons routed through conduits inside hollow carbon-fiber or 3D-printed structural links⁴.
3. **Active Impedance Control:** Joint torque control operates at $\geq 500 \text{ Hz}$ ⁸. If external contact forces exceed safety limits, joint impedance scales down within milliseconds to prevent physical harm¹.

Under-Actuated Adaptive End-Effectors

Handling varied everyday objects without complex trajectory planning relies on mechanically compliant end-effectors⁶. Adapting concepts from the Yale OpenHand framework:

- Single prime movers actuate tendon loops across multi-jointed flexure fingers⁶.
- When contacting unmodeled object geometries (e.g., tools, soft containers, produce), the fingers passively conform around the object boundary⁶.
- Tactile feedback arrays—such as force-sensing resistors (FSRs) or capacitive skin sensors on fingertips—provide closed-loop force regulation to manipulate delicate items without slippage or crushing⁶.

Software Architecture, VR Teleoperation, and Embodied AI

The computational framework layers high-level cognitive decision-making over deterministic hardware execution²:

- **Software Middleware:** High-level task orchestration runs on ROS 2 (Humble/Jazzy) with DDS communications, leveraging micro-services deployed in Docker containers for modular updates². Nav2 manages dynamic obstacle avoidance, MoveIt 2 generates inverse kinematics (IK) trajectories, and multimodal pipelines (Whisper Speech-to-Text → LLM/VLM Task Planner) convert human verbal prompts into ROS 2 action primitives².
- **Imitation Learning via VR Teleoperation:** Leveraging pipelines developed by Pollen Robotics and Hugging Face, human operators wearing Virtual Reality (VR) headsets control the robot's dual arms, hands, and stereo visual hub with low glass-to-glass latency ($\leq 125 \text{ ms}$)¹⁶. Visual observations and motor command trajectories $(\mathbf{o}_t, \mathbf{a}_t)$ recorded during teleoperation stream into neural network policies (e.g., Diffusion Policy, Action Chunking Transformers), training autonomous behaviors for real-world execution⁹.

Industry Integration Challenges and Strategic Market Insights

While technical adoption of semi-humanoid platforms is accelerating, enterprise integration faces operational and economic bottlenecks¹.

System Commissioning Friction and TCO Analysis

Deploying mobile manipulators in enterprise environments involves costs beyond initial hardware procurement¹:

[Total Cost of Ownership Breakdown]

+-----+
Base Hardware Purchase Price (~45% - 50%)
+-----+
Workflow Customization & Safety Certification (~35%)
+-----+
Software Licensing, Fleet Integration & Maintenance (~15%
+-----+

1. **Custom Commissioning Overhead:** Fully integrated industrial-grade mobile manipulators often represent a six-figure investment per unit once custom engineering, software licensing, and facility integration are included¹.
2. **Workflow and Interoperability Friction:** Approximately 35% of industrial enterprise buyers cite difficulties integrating mobile manipulators into existing workflows, legacy WMS/ERP databases, and mixed-vendor fleets¹⁰.
3. **Dexterity Restraints:** Nearly 40% of prospective industrial adopters report that limited end-effector dexterity and precision in unstructured environments remain significant obstacles to replacing manual labor¹⁰.

Strategic Insights

Open-Source Hardware Offloading and Cost Reduction

The robotics industry is shifting away from monolithic proprietary systems toward modular open-source architectures². Platforms such as Hello Robot Stretch (\$19,950–\$29,950) and open projects like Pollen Robotics Reachy 2 demonstrate how publishing open CAD schematics, ROS 2 middleware, and standardized electrical interfaces lowers baseline R&D costs². This open approach allows Small and Medium Enterprises (SMEs) to adopt adaptable robotics platforms previously restricted to high-capital industrial facilities¹².

Kinematic Efficiency: Wheeled vs. Bipedal Form Factors

Although bipedal humanoids draw public interest, wheeled semi-humanoid platforms offer superior operational efficiency in structured indoor environments (e.g., warehouses, hospital hallways, manufacturing floors)¹. Bipedal humanoids expend continuous electrical energy maintaining active balance, resulting in runtimes of 1.5 to 2 hours. In contrast, wheeled semi-humanoid platforms limit gravity-resisting energy draw to vertical lift joints and rolling base motors². This yields continuous operational runtimes of up to 8 hours on a single charge while supporting larger payload capacities².

Performance Dimension	Wheeled Semi-Humanoid System	Bipedal Humanoid Platform
Continuous Runtime	High (Up to 8 hours per charge) ²	Limited (1.5 to 2.5 hours average)

Payload Stability	High (Static equilibrium over fixed support footprint) ⁴	Variable (Requires dynamic ZMP compensation)
Control Complexity	Moderate (Standard ROS 2 Nav2 & MoveIt 2 stacks) ²	Extreme (Whole-body gait and fall recovery)
Regulatory Path	Established (ISO/TS 15066 & standard AMR vehicle codes) ¹	Emerging (Unsettled dynamic stability standards)
Facility Requirements	Flat floors, ramps, standard ADA doorways ⁴	Capable of navigating stairs and vertical obstacles

Embodied AI and Foundation Model Generalization

The acquisition of Pollen Robotics by Hugging Face highlights an industry-wide realignment: physical robotic hardware is increasingly engineered as a data-collection pipeline for training machine learning models⁹. The long-term value of semi-humanoid robotics lies in foundational Vision-Language-Action (VLA) models trained on teleoperation datasets². As VLA models improve at generalizing motor skills across unmodeled environments, semi-humanoid systems will transition from pre-programmed task execution to general-purpose assistance².

Strategic Implementation Directives

To maximize operational performance, system reliability, and deployment velocity, modular semi-humanoid development should align with four system engineering directives:

1. **Implement Proximal Tendon Actuation:** Concentrate primary drive motors within the upper torso and shoulder housing⁵. Use conduit-routed tendon networks to drive distal joints, reducing arm inertia to ensure inherently safe physical HRI¹.
2. **Integrate Chassis Passive Cooling:** Use high-thermal-conductivity structural aluminum frameworks as distributed heat radiators⁵. Eliminating active cooling fans reduces parasitic power draw, lowers noise for speech interfaces, and protects internal mechanics from airborne debris⁵.
3. **Separate High-Level AI from Deterministic Control:** Deploy ROS 2 middleware for high-level perception, navigation, and VLA planning while isolating low-level motor commutation and active impedance loops on dedicated real-time microcontrollers ($\geq 1 \text{ kHz}$) using CAN-FD or EtherCAT fieldbuses⁸.
4. **Leverage Open Data & VR Teleoperation Workflows:** Integrate VR-based teleoperation pipelines to collect demonstration data¹⁶. Aligning hardware interfaces with open-source Embodied AI frameworks accelerates policy training and autonomous manipulation capabilities⁹.

By combining mechanical compliance, modular sub-assemblies, open-source software, and proximal weight reduction, this semi-humanoid architecture offers a scalable path toward general-purpose automation across research, service, and industrial environments¹.

Works cited

1. Mobile Manipulator Market Size, Share & Latest Trends - MarketsandMarkets, <https://www.marketsandmarkets.com/Market-Reports/mobile-manipulator-market-167435958.html>
2. Stretch 4 by Hello Robot - ui44, <https://ui44.com/robots/hello-robot-stretch-4>
3. Reachy 2 - Specifications & Quote - RoboZaps, <https://robozaps.com/products/reachy-2>
4. The Design of Stretch: A Compact, Lightweight Mobile Manipulator for Indoor Human Environments - ResearchGate, https://www.researchgate.net/publication/354776839_The_Design_of_Stretch_A_Compact_Lightweight_Mobile_Manipulator_for_Indoor_Human_Environments
5. Reachy 2 - Pollen Robotics, <https://www.pollen-robotics.com/wp-content/uploads/2025/02/Reachy2-Single-Arm-Datasheet.pdf>
6. Two-Finger Gripper | Details - Hackaday.io, <https://hackaday.io/project/181205/log/200416-two-finger-gripper>
7. [Release information] Stretch 3 | Latest model of mobile manipulator made by Hello Robot, <https://www.tegakari.net/en/2024/03/stretch3/>
8. Reachy 2 Humanoid Robot Overview | PDF - Scribd, <https://www.scribd.com/document/839112213/Reachy2-Dual-arms-Datasheet>
9. Gemini 336 Powers Reachy 2 Embodied AI Robot - ORBBEC, <https://www.orbbec.com/news/bringing-vision-to-embodied-ai-how-orbbecs-gemini-336-powers-reachy-2s-real-world-perception-across-top-global-research-labs/>
10. Mobile Manipulators Market Size | Growth Forecast To 2034 - Business Research Insights, <https://www.businessresearchinsights.com/market-reports/mobile-manipulators-market-112460>
11. Autonomous Mobile Manipulator Robots Market Report, 2024-2030 - Grand View Research, <https://www.grandviewresearch.com/industry-analysis/autonomous-mobile-manipulator-robots-ammr-market-report>
12. Mobile Robots Market Size, Trends & Forecast 2035 - Roots Analysis, <https://www.rootsanalysis.com/mobile-robots-market>
13. Mobile Manipulator Robots Industry Observing Fabulous Growth - HTF Market Insights, <https://www.htfmarketinsights.com/report/4422276-mobile-manipulator-robots-market>
14. Autonomous Mobile Robots (AMR) Market Size & Share 2026 - 2035, <https://www.gminsights.com/industry-analysis/autonomous-mobile-robots-market>

[et](#)

15. Stretch 3 from Hello Robot designed for open-source mobile manipulation - JobToRob,
<https://jobtorob.com/stretch-3-from-hello-robot-designed-for-open-source-mobile-manipulation>
16. Reachy 2: The Open-Source Humanoid Robot Redefining Human-Machine Interaction,
<https://www.maxongroup.com/en-us/knowledge-and-support/blog/reachy-2-the-open-source-humanoid-robot-257768>
17. The Design of Stretch: A Compact, Lightweight Mobile Manipulator for Indoor Human Environments - PMC, <https://pmc.ncbi.nlm.nih.gov/articles/PMC10710733/>
18. PAL Robotics TIAGo — New Unit - BotMarket,
<https://botmarket24.com/en/humanoid-robots/pal-robotics/pal-robotics-tiago/listing-9f4ae53a-5557-4b41-8102-cf0073dd2f4b/>
19. Hello Robot : Simply Useful Robots, <https://teal-blue-zpt3.squarespace.com/>
20. Pollen Robotics Reachy 2 Specs & Price | Humanoid.guide,
<https://humanoid.guide/product/reachy-2/>