Classic Mystique PUR Pure Colours

POLYFLOR™ COVERING THE WORLD

PRODUCT SPECIFICATION

Key Features

> Tonal non-directional heavy-duty homogeneous flooring
> Broad palette of stylish colours
> 100% recyclable & 25% recycled content
> Low cost, polish-free maintenance
> Healthcare & education interiors



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Total Weight	ISO 23997 (EN 430)	3250g/m²
Finish		PUR

Sheet & Tile Sizes	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	15	-	40m²

Performance Requirements	Standard	Result
General Performance	ISO 10581 ASTM F1913 ASTM F1700	Conforms Conforms Class I, Type A
Use Area	ISO 10874 (EN 685)	23, 34, 43
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 Appendix D ASTM D2047	Class DS R9 R9 SCOF ≥0.6
Binder Content	ISO 10581	Type I
Reaction to Fire	EN 13501-1 ASTM E648 ASTM E662 CAN/ULC 102.2 BCA Spec C1.10 Clause 3 AS ISO 9239-1	Class Bfl-S1 Class 1 <450 FSR ≤ 300, SDC ≤ 500 Complies >8.0 kW/m²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ASTM F970 (Modified) ISO 24343-1	≤0.005" (750psi) ≤0.10mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Flexibility	ASTM F137 ISO 24344 (EN 435)	Pass (Method A) Pass 20mm ø
Underfloor Heating		Suitable, max 27°C
Light Fastness	ISO 105-B02 (Method 3)	≥6
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

Sustainability	Standard	Result
BRE Green Guide		A+ ENP 472
GreenTag	GreenRate™	Level A
Singapore Green Building Product (SGBP)		Leader
Product Specific EPD	EN 15804+A2	Available
Recyclable		100%
Recycled Content		25%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
VOC Emissions	TVOC after 28 days	≤ 10µg/m³
Responsible Sourcing	BES 6001	Excellent

Acoustic Performance	Standard	Result
Impact Sound Reduction	ISO 10140-3	4dB

Maintenance Performance	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Excellent Excellent
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection. Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.

Hygiene	Standard	Result
Bacterial Resistance	ISO 846 Part C	Does not favour growth
Ease of Radioactive Decontamination	ISO 8690	Excellent

BS EN 14041 EN 14041

Polyflor Ltd. Head Office
PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • **www.polyflor.com**
© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

Classic Mystique PUR
Pure Colours

POLYFLOR™
COVERING THE WORLD

RANGE SHADES

Linen Drift **7809** w/r 7809
NCS S 1505-Y20R LRV 65



Fossil Shell **7813** w/r 7813
NCS S 2005-Y20R LRV 60



Silken Sand **7801** w/r 7801
NCS S 2005-Y40R LRV 53



Urban Silt **7812** w/r 7812
NCS S 5005-Y20R LRV 25



Ashen Path **7804** w/r 7804
NCS S 7005-Y50R LRV 13



Silver Habitat **7814** w/r 7814
NCS S 3000-N LRV 45




Pale Cement **7815** w/r 7815
NCS S 2502-Y LRV 44



Morning Ash **7818** w/r 7818
NCS S 3502-Y LRV 30



Shadow Quarry **7819** w/r 7819
NCS S 4005-Y20R LRV 30



Iron Clay **7820** w/r 7820
NCS S 5500-N LRV 19



Glacier Haze **7805** w/r 7805
NCS S 2005-R90B LRV 58



Butter Cup **7808** w/r 7808
NCS S 1030-Y20R LRV 59



Harbour Current **7802** w/r 7802
NCS S 4020-R90B LRV 29



Smoked Flint **7817** w/r 7817
NCS S 5502-Y LRV 20



Basalt Veil **7816** w/r 7816
NCS S 7000-N LRV 14

w/r - Weld Rod LRV - Light Reflectance Value NCS - Natural Colour System

Polyflor Ltd. Head Office
PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • **www.polyflor.com**

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.