

Introspection Headers

- Purpose: Used when Tyk Dashboard sends an introspection query to fetch the upstream GraphQL schema.
- Usage scenario: Required when upstream GraphQL APIs are protected and require authorization for schema discovery.
- Key Points:
 - Headers are only used during schema introspection from the Dashboard.
 - These headers are not forwarded during runtime API requests from consumers.
 - Configurable in the Advanced Options tab or via raw API definition:

Introspection Headers

```
"graphql": {  
  "execution_mode": "proxyOnly",  
  "proxy": {  
    "auth_headers": {  
      "admin-auth": "token-value"  
    }  
  }  
}
```

Request Headers

- Purpose: Used to inject additional headers into runtime requests proxied through Tyk Gateway.
- Usage scenario: Add metadata, tokens, or dynamic values to upstream requests.
- Key Points:
 - Only active during actual API requests, not during introspection.
 - Supports static values or dynamic context variables like `$tyk_context.*`.
 - Configurable in the Advanced Options tab or raw API definition:

Request Headers

```
"graphql": {  
  "execution_mode": "proxyOnly",  
  "proxy": {  
    "request_headers": {  
      "context-vars-metadata": "$tyk_context.path",  
      "static-metadata": "static-value"  
    }  
  }  
}
```