

Dynamic Variables

You can pass dynamic variables to your persisted GraphQL queries.

- Supported sources:
 - Request headers
 - URL path parameters
- Use Tyk context variables to reference them.
- Ideal for flexible query inputs without hardcoding values.

Dynamic Variables

Example: Extract countryCode from request header code

Request Header:

code: UK

```
{
  "method": "GET",
  "path": "/getCountryByCode",
  "operation": "query ($countryCode: ID!) {\n
country(code: $countryCode) {\n          code\n
name\n    }\n}",
  "variables": {
    "countryCode": "$tyk_context.headers_code"
  }
}
```

Dynamic Variables

Response:

```
{  
  "data": {  
    "country": {  
      "code": "UK",  
      "name": "United Kingdom"  
    }  
  }  
}
```

Dynamic Variables

Example: Extract countryCode from the URL

```
{
  "method": "GET",
  "path": "/getCountryByCode/{countryCode}",
  "operation": "query ($countryCode: ID!) {\n
country(code: $countryCode) {\n          code\n
name\n    }\n}",
  "variables": {
    "countryCode": "$path.countryCode"
  }
}
```

Request URL:

/getCountryByCode/NG

Dynamic Variables

Response:

```
{  
  "data": {  
    "country": {  
      "code": "NG",  
      "name": "Nigeria"  
    }  
  }  
}
```