VISVESVARAYA TECHNOLOGICAL UNIVERSITY

"Jnana Sangama" Belgavi-590018, Karnataka, India



Project Phase 2
Report On

"Enhancing Cyber-attack Response with an Automated Analysis Platform"

Submitted in Partial Fulfillment of the requirement for the award of the degree of

BACHELOR OF ENGINEERING
IN
COMPUTER SCIENCE AND DESIGN

AMAN MAKANDAR	1SJ22CG004
CHIRANTH H	1SJ22CG016
MOHAMMED SAIF B	1SJ22CG035
ZIYAULLA KHAN	1SJ22CG063

Under the guidance of
Ambika S R
Assistant Professor
Dept. of CSD, SJCIT



S J C INSTITUTE OF TECHNOLOGY
DEPARTMENT OF COMPUTER SCIENCE AND DESIGN
CHIKKABALLAPUR- 562101

2025 – 2026

|| Jai Sri Gurudev ||

Sri Adichunchanagiri Shikshana Trust®

S.J.C INSTITUTE OF TECHNOLOGY, Chickballapur - 562101
Department of Computer Science and Design

CERTIFICATE

This is to certify that the project work entitled **"Enhancing Cyber-attack Response with an Automated Analysis Platform"** is a Bonafide work carried out by **Aman Makandar (1SJ22CG004), Chiranth H (1SJ22CG016), Mohammed Saif B(1SJ22CG035), Ziyaulla Khan(1SJ22CG063)** in partial fulfilment for the award of **Bachelor of Engineering in Computer Science and Design of Visvesvaraya Technological University, Belagavi** during the year **2025-2026.** It is certified that all corrections/suggestions indicated for internal assessment have been incorporated in the report. The project report has been approved as it satisfies the academic requirements with respect to project work prescribed for the Bachelor of Engineering degree.

.....	.....	.....
Signature of Guide	**Signature of Project Coordinator**	**Signature of HOD**
Ambika S R	**Ambika S R**	**Dr. Bharathi M**
Assistant Professor	**Assistant Professor**	**Professor & HOD**
Dept. Of CSD, SJCIT	**Dept. Of CSD, SJCIT**	**Dept. Of CSD, SJCIT**

DECLARATION

We, **AMAN MAKANDAR (1SJ22CG004), CHIRANTH H (1SJ22CG016), MOHAMMED SAIF B (1SJ22CG035), ZIYAULLA KHAN (1SJ22CG063)** Students of VII semester B.E in Computer Science and Design at S J C Institute of Technology, Chickballapur, hereby declare that this dissertation work entitled **"Enhancing Cyber-attack Response with an Automated Analysis Platform"** has been carried out at CSD LAB1, Dept. of CSD, SJCIT under the guidance of guide Ambika S R, Assistant Professor, Dept. of CSD, SJC Institute of Technology, Chickballapur and submitted in the partial fulfilment for the award of degree Bachelor of Engineering in Computer Science and Design of Visvesvaraya Technological University, Belagavi during the academic year 2025-2026. We further declare that the report had not been submitted to another university for the award of any other degree.

Place: Chikkaballapur
Date:

Aman Makandar	**(1SJ22CG004)**
Chiranth H	**(1SJ22CG016)**
Mohammed Saif B	**(1SJ22CG035)**
Ziyaulla Khan	**(1SJ22CG063)**

ABSTRACT

With the rapid growth of digital infrastructure and internet-based services, cyber threats have become more frequent, complex, and difficult to detect using traditional security mechanisms. Conventional cybersecurity systems largely depend on static rule-based detection and manual analysis, which often result in delayed responses, high false positives, and inability to detect unknown or zero-day attacks. This creates a strong need for intelligent, automated, and real-time cybersecurity solutions.This project presents an **AI-Augmented Cybersecurity System** designed to detect, analyze, and respond to cyber-attacks autonomously in real time. The proposed system integrates **rule-based detection**, a **Random Forest machine learning model**, and **Open-Source Intelligence (OSINT)** threat feeds to accurately identify both known and unknown malicious activities from system and application logs. Logs are continuously collected, preprocessed, and analyzed to extract meaningful security features. Detected threats are classified based on severity levels, and automated response actions such as alert generation and IP blocking are executed without human intervention.The system follows a **layered and modular architecture**, ensuring scalability, reliability, and ease of maintenance. A real-time dashboard provides clear visualization of detected threats, severity distribution, and resolution status, enabling improved security monitoring and decision-making. Experimental results demonstrate that the proposed system improves detection accuracy, reduces false positives, and significantly decreases response time compared to traditional approaches. Overall, the project highlights the effectiveness of combining artificial intelligence with cybersecurity to enhance real-time threat detection and automated incident response.

ACKNOWLEDGEMENT

With reverential pranam, we express my sincere gratitude and salutations to the feet of his holiness **Paramapoojya Jagadguru Byravaikya Padmabhushana Sri Sri Sri Dr. Balagangadharanatha Maha Swamiji,** his holiness **Paramapoojya Jagadguru Sri Sri Sri Dr. Nirmalanandanatha Maha Swamiji, and Sri Sri Mangalnatha Swamiji,** Sri Adichunchanagiri Mutt for their unlimited blessings.

First and foremost we wish to express our deep sincere feelings of gratitude to our institution, **Sri Jagadguru Chandrashekaranatha Swamiji Institute of Technology,** for providing us an opportunity for completing the Project Work successfully.

We extend deep sense of sincere gratitude to **Dr. G T Raju**, **Principal, SJC Institute of Technology, Chikkaballapur**, for providing an opportunity to complete the Project Work Phase I.

We extend special in-depth, heartfelt, and sincere gratitude to **Dr. Bharathi M, Professor and Head of the Department, Computer Science and Design, SJC Institute of Technology, Chikkaballapur,** for her constant support and valuable guidance of the Project Work Phase-II.

We convey our sincere thanks to Project Guide **Mrs. Ambika S R, Assistant Professor, Department of Computer Science and Design, SJC Institute of Technology,** for her constant support, valuable guidance and suggestions of the Project Work Phase-II.

We also feel immense pleasure to express deep and profound gratitude to Project Co-ordinator **Mrs. Ambika S R, Assistant Professor, Department of Computer Science and Design, SJC Institute of Technology,** for her guidance and suggestions of the Project Work Phase-II.

Finally, we would like to thank all faculty members of Department of Computer Science and Design, SJC Institute of Technology, Chikkaballapur for their support.

We also thank all those who extended their support and co-operation while bringing out this Project Work.

Aman Makandar	**1SJ22CG004**
Chiranth H	**1SJ22CG016**
Mohammed Saif B	**1SJ22CG035**
Ziyaulla Khan	**1SJ22CG063**

LIST OF FIGURES

FIGURE NO	NAME OF THE FIGURE	PAGE NO
5.3	Dataflow Diagram	
5.4	Use Case Diagram	
5.6	System Architecture	
A.1	Threat Analysis Dashboard Overview	
A.2	Real-Time Activity Monitoring and Threat Distribution	
A.3	Threat Resolution Tracking Dashboard	

LIST OF TABLES

TABLE NO.	NAME OF THE TABLE	PAGE NO.
3.1	Hardware Requirements	
3.2	Software Requirements	
7.3	Test Case Summary	

TABLE OF CONTENTS

CONTENTS Page No.

Declaration		i
Abstract		ii
Acknowledgement		iii
List of Figures		iv
Contents		v-vi
Chapter No.	Chapter Title	Page No.
1.	**INTRODUCTION**	**1-4**
1.1	Overview	1-2
1.2	Problem Statement	2-3
1.3	Significance and Relevance of Work	3
1.4	Objectives	3-4
1.5	Methodology	4-5
1.6	Organization of Report	5
2	**LITERATURE SURVEY**	**6-8**
3	**SYSTEM REQUIREMENTS SPECIFICATION**	**9-11**
3.1	System Requirement Specification	9
3.1.1	Hardware Specification	9
3.1.2	Software Specification	9
3.2	Functional Requirements	10
3.3	Non Functional Requirements	10-11
3.4	Performance Requirements	11
4	**SYSTEM ANALYSIS**	**12-13**
4.1	Existing System	12
4.1.1	Limitations	12
4.2	Proposed Systems	13
4.2.1	Advantages	13
5	**SYSTEM DESIGN**	**14-18**
5.1	System Architecture	14
5.1.1	Components of System	14-16

5.1.2	Data Flow Diagram	16-17
5.4	Use Case Diagram	17-18
6	**CONCLUSION**	**19**
7	**BIBLIOGRAPHY**	**20**

CHAPTER 1
INTRODUCTION

CHAPTER – 1

INTRODUCTION

1.1 Overview

In today's digital era, organizations increasingly depend on computer networks, cloud services, and online platforms to store, process, and transmit sensitive information. This rapid digital transformation has significantly increased the exposure to cyber threats such as malware attacks, unauthorized access, data breaches, phishing, denial-of-service attacks, and advanced persistent threats. Cyber attackers are continuously evolving their techniques, making traditional manual monitoring and static security tools insufficient for modern environments.

Conventional cybersecurity systems rely heavily on rule-based detection and manual analysis, which often results in delayed threat detection, high false-positive rates, and increased workload for security analysts. To overcome these challenges, there is a growing need for intelligent and automated security systems that can detect threats in real time and respond without human intervention.

This project focuses on **AI-Augmented Cybersecurity**, where machine learning techniques are integrated with rule-based detection and threat intelligence feeds to create an autonomous system for real-time attack detection and response. The proposed system uses a **Random Forest machine learning model**, combined with pattern-matching rules and OSINT (Open-Source Intelligence), to accurately identify both known and unknown cyber threats. The system continuously monitors logs from multiple sources, analyzes suspicious activities, and automatically performs mitigation actions such as alert generation and IP blocking.

1.2 Problem Statement

Traditional cybersecurity solutions face several limitations, including slow detection speed, inability to detect unknown attacks, high false-positive rates, and lack of automation in response mechanisms. Manual analysis of large volumes of logs is time-consuming and prone to human error, making it difficult to respond quickly to real-time cyber threats.

There is a need for an **automated, scalable, and intelligent cybersecurity system** that can continuously monitor system logs, accurately detect malicious activities, and respond immediately without relying solely on human intervention. The problem addressed in this project is the design and implementation of an **AI-driven autonomous cyber-attack detection and response system** that leverages machine learning, threat intelligence, and automation to improve security efficiency and reliability.

1.3 Significance and Relevance

Cybersecurity has become a critical concern for organizations of all sizes due to increasing cybercrime and data breaches. An effective threat detection system plays a vital role in protecting sensitive data, ensuring system availability, and maintaining user trust.

The integration of **machine learning and artificial intelligence** into cybersecurity significantly enhances detection accuracy by identifying hidden patterns and anomalies in large-scale log data. The proposed AI-augmented system reduces dependency on manual monitoring, improves response time, and minimizes false alerts. By combining **Random Forest models, rule-based detection, and OSINT feeds**, the system achieves higher reliability and adaptability against evolving cyber threats.

This project is highly relevant in real-world security operations such as Security Operations Centers (SOC), enterprise networks, and cloud infrastructures, where real-time detection and automated response are essential.

1.4 Objectives

The main objectives of this project are:

- To design an AI-augmented cybersecurity system for real-time attack detection.
- To collect and analyze system and application logs from multiple sources.
- To implement rule-based detection for identifying known attack patterns.
- To develop a **Random Forest machine learning model** for detecting anomalous and unknown threats.
- To integrate OSINT threat intelligence feeds for improved threat validation.
- To automate response actions such as alert generation and IP blocking.
- To provide real-time visualization of threats through a dashboard interface.

1.5 Methodology

The proposed system follows a structured methodology to ensure accurate threat detection and response:

1. **Log Collection:**
   Logs are collected from remote systems using secure methods such as SSH. These logs include system logs, authentication logs, and application logs.
2. **Preprocessing:**
   The collected logs are cleaned, parsed, decoded, and filtered to extract security-relevant information. Duplicate logs are removed using hashing techniques.
3. **Threat Detection:**

- **Rule-Based Detection:** Uses predefined rules and patterns to detect known attacks like SQL injection, brute force, and XSS.
- **Machine Learning Detection:** A Random Forest model analyzes extracted features to detect abnormal behavior.
- **OSINT Lookup:** External threat intelligence sources are used to validate malicious IPs and indicators.

4. **Threat Classification:**
   Detected threats are classified based on severity levels such as low, medium, high, or critical.
5. **Automated Response:**
   The system automatically blocks malicious IPs, generates alerts, and logs incidents for further analysis.
6. **Visualization:**
   Real-time alerts and system status are displayed through an interactive dashboard.

1.6 Organization of the Report

The report is organized as follows:

- **Chapter 1 – Introduction:** Presents an overview of the project, problem statement, objectives, methodology, and report structure.
- **Chapter 2 – Literature Survey:** Reviews existing research and technologies related to cybersecurity, machine learning, and threat detection.
- **Chapter 3 – System Requirements:** Describes hardware, software, functional, and non-functional requirements.
- **Chapter 4 – System Analysis:** Discusses the existing system, its limitations, and the proposed solution.
- **Chapter 5 – System Design:** Explains system modules, architecture, and design diagrams.
- **Chapter 6 – Implementation:** Details the frontend, backend, and database implementation.
- **Chapter 7 – Testing:** Describes testing strategies and test cases.
- **Chapter 8 – Conclusion and Future Enhancement:** Summarizes outcomes and discusses future improvements.

CHAPTER 2
LITERATURE SURVEY

CHAPTER 2

LITERATURE SURVEY

[1]. Doing More with Less: A Study of Fileless Infection Attacks

Authors: Benjamin S. Rivera and Rhena U. Inocencio

This paper investigates a growing class of cyberattacks known as fileless malware, which execute malicious code directly in memory without leaving traditional file-based footprints. The study thoroughly explains how attackers exploit trusted system tools like PowerShell, WMI (Windows Management Instrumentation), and registry entries to initiate and sustain attacks. Since these attacks don't involve installing a file on disk, traditional antivirus software and endpoint protection tools often fail to detect or stop them.

These attacks are harder to trace and mitigate, as the evidence of compromise disappears when the system restarts. The paper emphasizes the need for memory-based detection and behavior-based monitoring, rather than relying solely on signature-based antivirus tools.

[2]. Hauri News – Jan 2017

Author: Hauri Inc.

This article, published by Hauri Inc., a cybersecurity company, presents their latest advancements in malware protection and real-time threat mitigation tools. The update focuses on the growing use of heuristic scanning, behavioral analysis, and cloud-based threat intelligence for defending against advanced cyber threats.

The article explains how Hauri's system collects large volumes of malware data from endpoint devices and uses centralized intelligence to identify emerging attack signatures. It stresses the importance of detecting anomalies at the network and system level, which can often indicate the presence of previously unknown malware. While the article lacks the academic rigor of a research paper, it is valuable for showcasing real-world implementation of threat detection systems. The emphasis on real-time intelligence feeds and cloud-enabled detection is aligned with the objectives of this project. The approach used by Hauri can inspire architectural decisions in developing an automated cyberattack response platform that needs scalable, real-time threat monitoring capabilities.

[3]. Definition: Threat Intelligence

Author: Gartner (May 2013)

This foundational document by Gartner defines Cyber Threat Intelligence (CTI) as evidence-based knowledge about existing or emerging threats to digital assets. It outlines the structure and types of CTI, categorizing it into strategic, operational, tactical, and technical levels, each serving different roles within an organization's defense mechanisms.

The report argues that threat data alone is not sufficient; it must be contextualized and correlated to become "intelligence." For this project, Gartner's work provides a theoretical

basis for understanding how cyberattack data should be processed and applied. It supports the idea of automating the conversion of raw OSINT data into contextualized intelligence that can guide defensive actions. While the document is more descriptive than technical, its concepts are integral to developing a well-structured CTI pipeline within the proposed platform.

[4]. Definitive Guide to Cyber Threat Intelligence: Using Knowledge about Adversaries to Win the War against Targeted Attacks

Authors: Jon Friedman and Mark Bouchard

This comprehensive guidebook focuses on using CTI to combat targeted cyberattacks, emphasizing the importance of understanding adversaries, their tactics, techniques, and procedures (TTPs). The authors argue that CTI should not only inform incident response but also be integrated into all layers of cybersecurity operations—from prevention to recovery.The book introduces the concept of the cyber kill chain and maps different intelligence sources to each phase, enabling organizations to disrupt attacks early in their lifecycle. This work is extremely relevant for the proposed platform. It highlights the importance of mapping and correlating various threat indicators (e.g., IP addresses, hashes, URLs) and using them to understand adversarial behavior. These principles can be applied when designing the core logic of the automated analysis system.

[5]. Open Source Intelligence-Based Cyber Threat Inspection Framework for Critical Infrastructures

Authors: Seokcheol Lee and Taeshik Shon

This paper presents a specialized framework for inspecting cyber threats in critical infrastructure using Open Source Intelligence (OSINT). The authors propose a real-time detection system that collects data from various OSINT sources—such as dark web forums, public vulnerability databases, and social media—to identify emerging cyber threats targeting utilities like water supply, electricity, and healthcare.

The key contribution of this work is the use of correlation and prioritization mechanisms to assess the severity and relevance of each threat. The system is designed to integrate with existing security operation centers (SOCs) and help analysts quickly identify indicators of compromise and take preventive measures.

This paper directly aligns with the goals of your project. It validates the use of OSINT for early detection and shows how automated correlation techniques can enhance cyber resilience.

CHAPTER – 3

SYSTEM REQUIREMENTS

CHAPTER – 3

SYSTEM REQUIREMENTS SPECIFICATION

3.1 Hardware Requirements

Component	**Specification**
Processor	Intel i5 or higher
RAM	Minimum 8 GB
Storage	Minimum 20 GB free space
Network	Stable Internet Connection
Display	1024 × 768 or higher

3.2 Software Requirements

Component	**Specification**
Operating System	Windows 10/11 or Linux
Frontend	Angular
Backend	FastAPI, Python
Database	PostgreSQL
ML Libraries	Scikit-learn, NumPy, Pandas
OSINT Tools	AbuseIPDB, AlienVault OTX
Visualization	Chart.js

3.3 Functional Requirements

- Collect logs from multiple remote systems
- Preprocess and deduplicate log data
- Detect threats using rules, ML, and OSINT
- Classify threats based on severity
- Generate real-time alerts
- Automatically block malicious IPs
- Display alerts and statistics on dashboard

3.4 Non-Functional Requirements

- High detection accuracy
- Low response latency
- Scalability for multiple systems
- Secure communication
- High system availability
- Easy maintainability

3.5 System Constraints and Assumptions

The performance of the proposed system depends on the quality, consistency, and availability of log data collected from monitored systems. Detection accuracy may vary based on network traffic volume and the diversity of attack patterns present in the logs. Automated response actions such as IP blocking require appropriate system permissions and firewall access. The effectiveness of threat validation also depends on the availability and response time of external OSINT services. It is assumed that monitored systems generate standard log formats and maintain stable network connectivity for continuous monitoring.

CHAPTER 4
SYSTEM ANALYSIS

CHAPTER – 4

SYSTEM ANALYSIS

4.1 Existing System

Most existing cybersecurity systems rely on traditional security mechanisms such as firewalls, antivirus software, intrusion detection systems (IDS), and manual log monitoring. These systems primarily use **static rule-based detection** and signature matching to identify malicious activities. Logs generated by servers, applications, and network devices are often analyzed manually by security analysts or processed using basic alerting tools.

In many organizations, log analysis is performed periodically rather than continuously, which leads to delayed detection of cyber-attacks. Security analysts must manually inspect alerts, correlate events from multiple systems, and decide appropriate response actions. This manual approach becomes inefficient when dealing with large-scale infrastructures that generate massive volumes of log data every second.

4.1.1 Limitations of Existing System

Despite being widely used, existing systems suffer from several critical limitations:

- **Delayed Threat Detection:**
  Most systems depend on periodic analysis or manual intervention, resulting in delayed identification of attacks.
- **High False Positives:**
  Rule-based systems often generate a large number of false alerts, increasing analyst workload and alert fatigue.
- **Inability to Detect Unknown Attacks:**
  Signature-based detection fails to identify zero-day attacks or previously unseen threat patterns.
- **Manual Response Dependency:**
  Human intervention is required to analyze alerts and take mitigation actions, slowing down incident response.
- **Poor Scalability:**
  Traditional systems struggle to scale efficiently when monitoring multiple systems and high-volume log data.
- **Limited Threat Intelligence Integration:**
  Many systems do not integrate external threat intelligence sources to validate suspicious activities.These limitations highlight the need for a more intelligent, automated, and scalable cybersecurity solution.

4.2 Proposed System

The proposed system is an **AI-Augmented Cybersecurity Platform** designed to overcome the shortcomings of traditional security systems. It provides **real-time monitoring, intelligent threat detection, and automated response** by combining multiple detection techniques into a unified framework.

The system continuously collects logs from multiple remote machines using secure communication methods. These logs are preprocessed to remove noise, decode encoded data, and eliminate duplicates using hashing techniques. The processed data is then analyzed using a **hybrid detection approach**, which includes:

- **Rule-Based Detection** for identifying known attack patterns
- **Machine Learning Detection** using a Random Forest model to identify abnormal and unknown threats
- **OSINT Threat Intelligence** to validate malicious IP addresses and indicators

4.2.1 Advantages of Proposed System

The proposed system offers several advantages over existing cybersecurity solutions:

- **Real-Time Threat Detection:**
  Continuous monitoring ensures that attacks are detected as soon as they occur.
- **Reduced False Positives:**
  The hybrid detection approach improves accuracy by validating threats using machine learning and OSINT data.
- **Detection of Unknown Attacks:**
  The Random Forest model identifies anomalies and previously unseen attack patterns.
- **Automated Response Mechanism:**
  Immediate actions such as IP blocking and alert generation reduce response time and human dependency.
- **Scalable Architecture:**
  The layered system design allows easy expansion to support additional systems and data sources.
- **Improved Analyst Efficiency:**
  Security analysts can focus on critical threats instead of manually filtering large volumes of alerts.
- **Enhanced Security Visibility:**
  Real-time dashboards provide comprehensive insights into threat trends and system health.

CHAPTER – 5

SYSTEM DESIGN

CHAPTER – 5

SYSTEM DESIGN

5.1 Design Approach

The proposed system is designed using a **layered and modular architecture**, which separates responsibilities across different components. This approach improves maintainability, scalability, and flexibility. Each module performs a specific function, and communication between modules is handled through well-defined interfaces.

The system supports two main users:

- **Cybersecurity Analyst (User)**
- **System Administrator (Admin)**

Both users interact with the system through a centralized dashboard.

5.2 Project Modules

The system is divided into the following core modules:

5.2.1 Log Collection Module

This module is responsible for collecting logs from multiple remote systems using secure protocols such as SSH. Logs may include authentication logs, system logs, and application logs. Continuous log collection ensures real-time monitoring of system activities.

5.2.2 Preprocessing Module

Collected logs often contain noise, duplicates, and irrelevant information. This module performs:

- Log parsing and formatting
- URL decoding and normalization
- Filtering security-relevant entries
- Deduplication using hashing techniques

This step ensures that only clean and meaningful data is passed to detection modules.

5.2.3 Rule-Based Detection Module

This module uses predefined security rules and regular expressions to detect known attacks such as:

- Brute-force login attempts
- SQL injection
- Cross-site scripting (XSS)

- Directory traversal

Rule-based detection is fast and effective for identifying well-known attack patterns.

5.2.4 Machine Learning Detection Module

The machine learning module uses a **Random Forest algorithm** to analyze extracted features from logs. It detects anomalies and unknown attack patterns that cannot be identified using static rules. This module improves detection accuracy and reduces false positives.

5.2.5 OSINT Threat Intelligence Module

This module integrates external threat intelligence sources such as AbuseIPDB and AlienVault OTX. It validates suspicious IP addresses and indicators by cross-checking them against global threat databases.

5.2.6 Automated Response Module

Based on threat severity, this module performs automatic mitigation actions such as:

- Blocking malicious IP addresses
- Generating alerts
- Logging incidents for auditing

Automation ensures faster response and minimizes human intervention.

5.2.7 Dashboard and Visualization Module

This module provides a real-time dashboard displaying:

- Active threats
- Alert severity levels
- Attack trends
- System status

It helps analysts quickly understand and respond to security incidents.

5.3 Data Flow Diagram (DFD) Description

The data flow begins when logs are generated by monitored systems. These logs are securely transferred to the log collection module. After preprocessing, the data is sent simultaneously to the rule-based detection engine, machine learning model, and OSINT validation module. Detected threats are classified by severity and forwarded to the automated response module. Finally, alerts and system metrics are displayed on the dashboard.




FIGURE 5.3 DATAFLOW DIAGRAM

5.4 Use Case Diagram Description

Actors

- **User (Cybersecurity Analyst)**
- **Admin (System Administrator)**

Use Cases

- View real-time alerts
- Monitor threat dashboard
- Upload datasets
- Train ML models
- Manage monitored systems
- Trigger automated responses

The use case diagram illustrates how users interact with the system to monitor and manage cybersecurity operations.




FIGURE 5.4 USE CASE DIAGRAM

5.5 Sequence Diagram Description

The sequence of operations is as follows:

1. Logs are generated on remote systems
2. Logs are collected and preprocessed
3. Detection engines analyze the logs
4. Threat severity is determined
5. Automated response is executed
6. Alerts are displayed on the dashboard

This sequence ensures timely detection and response to cyber threats.

5.6 System Architecture

The proposed system follows a **five-layer architecture**:

5.6.1 Presentation Layer

Provides an Angular-based user interface for real-time visualization, alerts, and system management.

5.6.2 Application Layer

Handles API requests using FastAPI. It manages communication between frontend and backend services.

5.6.3 Processing Layer

Core detection engine that includes rule-based detection, Random Forest ML model, and OSINT analysis.

5.6.4 Data Layer

Uses PostgreSQL to store logs, alerts, threat intelligence data, and system configurations.

5.6.5 External Layer

Includes monitored systems and external OSINT providers.

This architecture ensures modularity, scalability, and efficient real-time threat detection.




FIGURE 5.6 SYSTEM ARCHITECTURE

CHAPTER– 6
IMPLEMENTATION

CHAPTER – 6

IMPLEMENTATION

6.1 Front-End Implementation

The front-end of the system is developed using **Angular**, a widely used framework for building dynamic and responsive web applications. The user interface provides cybersecurity analysts and administrators with real-time visibility into system activity and detected threats.

6.1.1 User Interface Design

The Angular dashboard is designed to be intuitive and easy to use. It includes the following components:

- **Login Page:** Secure authentication for authorized users
- **Dashboard Page:** Displays real-time threat statistics, charts, and alerts
- **Alert Management Page:** Shows detailed alert information such as source IP, severity, timestamp, and threat type
- **System Management Page:** Allows admins to add or manage monitored systems

The interface uses charts and tables to represent threat trends and severity levels clearly.

6.1.2 Visualization

Visualization is implemented using chart libraries to display:

- Number of detected attacks
- Severity-wise alert distribution
- Time-based attack trends

These visual elements help analysts quickly understand the security posture of the system.

6.2 Back-End Implementation

The backend is implemented using **FastAPI**, a high-performance Python web framework. FastAPI handles API requests from the frontend, processes logs, performs threat detection, and executes automated responses.

6.2.1 API Design

The backend exposes RESTful APIs for:

- Log ingestion
- Threat analysis
- Alert retrieval

FastAPI ensures fast request handling, asynchronous processing, and secure communication.

6.3 Log Collection and Preprocessing Implementation

6.3.1 Log Collection

Logs are collected from remote systems using **SSH-based connections**. The system extracts logs such as:

- Authentication logs
- System logs
- Web server logs

Continuous log monitoring ensures real-time detection of malicious activities.

6.3.2 Preprocessing

Preprocessing includes:

- Parsing log entries
- Decoding URLs and payloads
- Filtering irrelevant entries
- Deduplicating logs using hashing

This step reduces noise and improves detection accuracy.

6.4 Threat Detection Implementation

6.4.1 Rule-Based Detection

The rule-based engine uses predefined patterns and regular expressions to detect known attacks such as:

- SQL Injection
- Cross-Site Scripting (XSS)
- Brute-force attacks
- Directory traversal

If a rule is matched, an alert is generated immediately.

6.4.2 Machine Learning Detection Using Random Forest

The machine learning module uses a **Random Forest classifier** trained on extracted log features. Important features include:

- Number of failed login attempts
- IP reputation score

- Frequency of requests
- Payload characteristics

The Random Forest model combines multiple decision trees and uses majority voting to classify activity as **normal** or **malicious**. This improves accuracy and reduces overfitting.

6.4.3 OSINT Integration

The OSINT module queries external threat intelligence platforms such as:

- AbuseIPDB
- AlienVault OTX

Suspicious IPs are validated using global threat databases, improving confidence in detection results.

6.5 Automated Response Implementation

When a threat is classified as high or critical severity, the system automatically performs response actions such as:

- Blocking the malicious IP address
- Logging the incident in the database
- Generating alerts for analysts

Automation significantly reduces response time and prevents further damage.

6.6 Database Implementation

The system uses **PostgreSQL** for storing:

- Log entries
- Detected alerts
- OSINT threat data
- System configurations

Indexes are created on fields such as timestamp, severity, and system ID to improve query performance.

6.7 Integration of Front-End and Back-End

The Angular frontend communicates with the FastAPI backend using REST APIs. JSON is used as the data exchange format. When a threat is detected, the backend sends alert data to the frontend, which updates the dashboard in real time.

This integration ensures smooth data flow and real-time system responsiveness.

CHAPTER – 7
TESTING

CHAPTER – 7

TESTING

7.1 Testing Strategy

The testing process was carried out in multiple stages to validate both individual modules and the complete system. Different testing techniques were used to ensure correctness, performance, and usability. Testing was performed using real and simulated log data representing normal and malicious activities.

7.2 Types of Testing

7.2.1 Unit Testing

Unit testing was conducted on individual modules such as:

- Log collection module
- Log preprocessing module
- Rule-based detection engine
- Random Forest prediction module
- OSINT validation module

Each module was tested independently to confirm that it produces expected outputs for valid inputs and handles errors properly. This ensured early detection of bugs and improved system stability.

7.2.2 Integration Testing

Integration testing verified the interaction between different modules of the system. It ensured that:

- Log data flows correctly from collection to preprocessing
- Detection results are correctly passed to the response module
- Alerts generated by the backend are displayed accurately on the frontend dashboard

This testing confirmed smooth communication between frontend, backend, and database components.

7.2.3 Functional Testing

Functional testing focused on validating the core features of the system based on functional requirements. The following functionalities were tested:

- Detection of known attacks using rule-based detection
- Identification of unknown or anomalous attacks using the Random Forest model

- Severity classification of detected threats
- Automated response actions such as IP blocking
- Display of alerts and system status on the dashboard

The system behaved as expected for both normal and malicious inputs.

7.2.4 Performance Testing

Performance testing was performed to evaluate the system's response time and efficiency under load. The system was tested with increased log volume to ensure real-time processing capability. Results showed that threat detection and alert generation occurred within acceptable time limits without system failure.

7.2.5 User Acceptance Testing

User Acceptance Testing (UAT) was carried out by allowing users to interact with the system dashboard. Users verified:

- Ease of navigation
- Clarity of alerts and visualizations
- Responsiveness of the system

Feedback confirmed that the system was easy to use and met user expectations.

7.3 Test Case Summary

Test Case ID	Description	Expected Result	Status
TC01	Log collection from remote systems	Logs collected successfully	Pass
TC02	Rule-based attack detection	Known attacks detected	Pass
TC03	ML-based detection	Unknown attacks identified	Pass
TC04	Severity classification	Correct severity assigned	Pass
TC05	Automated response	Malicious IP blocked	Pass
TC06	Dashboard update	Alerts displayed in real time	Pass

7.4 Testing Outcome

The testing results demonstrate that the AI-Augmented Cybersecurity system functions reliably under different scenarios. The system accurately detects cyber threats, executes automated responses, and provides real-time visualization. The successful testing confirms that the system is stable, efficient, and suitable for deployment in real-world cybersecurity environments.

7.5 Limitations Observed During Testing

Although the system performed effectively during testing, a few limitations were observed:

- The accuracy of detection depends on the quality and diversity of log data used during testing. Limited datasets may reduce detection effectiveness for rare attack patterns.
- Rule-based detection requires periodic updates to handle newly emerging attack techniques.
- Machine learning model performance may vary when exposed to real-world traffic patterns that differ from training data.
- OSINT validation depends on the availability and response time of external threat intelligence sources.

These limitations indicate areas where future improvements can further strengthen system performance and reliability.

7.6 Tools Used for Testing

Various tools and technologies were used to perform testing of the AI-Augmented Cybersecurity system and to validate its functionality, performance, and reliability. These tools helped simulate real-world scenarios and analyze system behavior effectively.

- **Python Testing Libraries:**

  Used to test individual backend modules such as log preprocessing, rule-based detection, and machine learning prediction functions.

- **Postman:**
  Used to test backend API endpoints for log ingestion, threat analysis, and alert retrieval.

- **Browser Developer Tools:**

  Used to verify frontend functionality, API responses, and real-time dashboard updates.

- **Sample Log Datasets:**

  Used to simulate normal and malicious activities for validating threat detection accuracy.

- **PostgreSQL Database Tools:**

  Used to verify data storage, retrieval, and alert logging operations.

CHAPTER 8
PERFORMANCE ANALYSIS

CHAPTER 8

PERFORMANCE ANALYSIS

Performance analysis is conducted to evaluate the effectiveness, accuracy, and efficiency of the proposed **AI-Augmented Cybersecurity System**. This chapter examines how well the system detects cyber threats, classifies their severity, and executes automated responses in real time. The analysis also focuses on system scalability and reliability under varying workloads.

8.1 Evaluation Metrics

The performance of the system is evaluated using the following metrics:

- **Detection Accuracy:** Measures the ability of the system to correctly identify malicious and normal activities from log data.
- **False Positive Rate:** Indicates how often legitimate activities are incorrectly classified as threats.
- **Response Time:** Measures the time taken between threat detection and execution of response actions such as alert generation or IP blocking.
- **System Throughput:** Evaluates how efficiently the system processes large volumes of logs in real time.
- **System Stability:** Ensures continuous operation without failures during high log traffic.

These metrics provide a comprehensive understanding of the system's operational performance.

8.2 Threat Detection Performance

The proposed system uses a **hybrid detection approach**, which improves overall accuracy:

- **Rule-Based Detection** efficiently identifies known attack patterns such as SQL injection, brute-force attacks, and directory traversal with minimal delay.
- **Random Forest Machine Learning Model** detects unknown and anomalous attack behaviors by analyzing multiple log-based features.
- **OSINT Threat Intelligence Integration** validates suspicious IP addresses using global threat databases, increasing confidence in detected threats.

This combined approach significantly reduces false positives while improving detection reliability compared to traditional rule-based systems.

8.3 Response Time Analysis

The automated response mechanism ensures rapid mitigation of detected threats. Once a high-severity threat is identified, the system automatically performs response actions without human intervention. Testing results show that alert generation and IP blocking occur within a very short time interval, ensuring minimal impact on system security.

The use of FastAPI and asynchronous processing further contributes to faster response and improved system efficiency.

8.4 Scalability and Reliability Analysis

The layered and modular architecture enables the system to scale effectively as the number of monitored systems and log volume increases. Backend services can handle multiple concurrent requests without performance degradation. PostgreSQL ensures reliable data storage, while indexing improves query performance.

The system remained stable during testing, even when subjected to increased log traffic, demonstrating its suitability for real-world deployment.

8.5 Performance Summary

The performance evaluation confirms that the proposed AI-Augmented Cybersecurity system:

- Accurately detects both known and unknown cyber threats
- Reduces false positives through hybrid detection
- Responds quickly using automated mitigation actions
- Maintains stable performance under higher workloads
- Supports scalable and reliable real-time monitoring

Overall, the system demonstrates strong performance and meets the requirements of modern cybersecurity environments.

CHAPTER 9
CONCLUSION AND FUTURE ENHANCEMENT

CHAPTER 9

CONCLUSION

9.1 Conclusion

The proposed **AI-Augmented Cybersecurity System** successfully addresses the growing challenges of modern cyber threats by providing an intelligent, automated, and real-time attack detection and response mechanism. By integrating **rule-based detection**, **Random Forest machine learning**, and **OSINT threat intelligence**, the system effectively identifies both known and unknown cyber-attacks with improved accuracy and reduced false positives.

The system continuously monitors log data from multiple sources, analyzes suspicious activities, and automatically executes response actions such as alert generation and IP blocking. This significantly reduces the dependency on manual monitoring and improves incident response time. The layered and modular architecture ensures scalability, reliability, and ease of maintenance, making the system suitable for real-world cybersecurity environments.

Overall, the project demonstrates that combining artificial intelligence with traditional security techniques enhances detection capability, improves operational efficiency, and strengthens the overall security posture of an organization.

9.2 Future Enhancement

Although the proposed system performs effectively, several enhancements can be implemented in the future to further improve its capabilities:

- **Agent-Based Log Collection:**
  Lightweight agents can be deployed on remote systems to enable faster, more reliable, and scalable log collection.
- **Deep Learning Integration:**
  Advanced deep learning models such as LSTM or Transformer-based architectures can be incorporated to detect complex and long-term attack patterns.
- **SIEM and SOAR Integration:**
  The system can be integrated with enterprise SIEM and SOAR platforms to enable centralized monitoring and automated incident response.
- **Real-Time Notification Mechanisms:**
  WebSocket-based updates or push notifications can be added for instant alert delivery and improved real-time visibility.
- **Cloud Deployment:**
  Deploying the system on cloud platforms can improve scalability, availability, and accessibility for large-scale environments.

BIBLIOGRAPHY

BIBLIOGRAPHY

The following references were used during the study, design, and implementation of the AI-Augmented Cybersecurity system. These sources include research papers, technical documentation, and online resources related to machine learning, cybersecurity, and threat detection.

1. Breiman, L., "Random Forests," *Machine Learning Journal*, Vol. 45, No. 1, pp. 5–32, 2001.
2. Scikit-learn Documentation,

   Random Forest Classifier, Available: https://scikit-learn.org
3. FastAPI Official Documentation,

   High-Performance Python Web Framework, Available: https://fastapi.tiangolo.com
4. AbuseIPDB,
   IP Address Reputation and Threat Intelligence, Available: https://www.abuseipdb.com
5. AlienVault Open Threat Exchange (OTX),

   Global Threat Intelligence Platform, Available: https://otx.alienvault.com
6. Sommer, R. and Paxson, V., "Outside the Closed World: On Using Machine Learning for Network Intrusion Detection," *IEEE Symposium on Security and Privacy*, 2010.
7. Patcha, A. and Park, J.M., "An Overview of Anomaly Detection Techniques," *Computer Networks*, Elsevier, 2007.
8. Stallings, W., Network Security Essentials: Applications and Standards, Pearson Education.
9. Python Software Foundation,

   Python Programming Language Documentation, Available: https://docs.python.org
10. Behl, A. and Behl, K., *Cybersecurity and Cyberwar: What Everyone Needs to Know*, Oxford University Press.

APPENDIX

Appendix A: Screen Shots




Figure A.1: Threat Analysis Dashboard Overview




Figure A.2: Real-Time Activity Monitoring and Threat Distribution




Figure A.3: Threat Resolution Tracking Dashboard

Appendix B: Abbreviations

Abbreviation	Full Form
AI	Artificial Intelligence
ML	Machine Learning
RF	Random Forest
OSINT	Open-Source Intelligence
IDS	Intrusion Detection System
SIEM	Security Information and Event Management
SOAR	Security Orchestration, Automation and Response
API	Application Programming Interface
DB	Database
UI	User Interface
IP	Internet Protocol
SSH	Secure Shell
JSON	JavaScript Object Notation