

Mid Exam

Section 1: File and Directory Management

1. Display the current working directory.

```
File Actions Edit View Help
(kali@kali)-[~/Desktop]
$ pwd
/home/kali/Desktop
```

2. List all the contents of your current directory, including hidden files.

```
(kali@kali)-[~]
$ ls -a
. .bash_logout .cache directory .face file2 .gnupg .mozilla 'New Folder' .pki Templates .xsession-errors
. .bashrc .child .dmrc .face.icon filename .ICEauthority Music p .profile .xsession-errors.old
. .bashrc.original .config Documents file folder .java .parent Public .viminfo .zsh_history
. .BurpSuite Desktop Downloads file1 folder1 .local new Pictures .sudo_as_admin_successful .Xauthority .zshrc

(kali@kali)-[~]
$
```

3. Change your directory to the `Desktop`.

```
(kali@kali)-[~]
$ cd Desktop

(kali@kali)-[~/Desktop]
$
```

4. Create two directories named `dir1` and `dir2` on the Desktop.

```
(kali@kali)-[~/Desktop]
$ mkdir ahmed1
mkdir: cannot create directory 'ahmed1': File exists

(kali@kali)-[~/Desktop]
$ mkdir ahmed
mkdir: cannot create directory 'ahmed': File exists

(kali@kali)-[~/Desktop]
$
```

5. Inside `dir1`, create a file named `file1.txt`.

```
(kali@kali)-[~/Desktop]
$ cd ahmed

(kali@kali)-[~/Desktop/ahmed]
$ touch ahmed2.txt
```

6. Inside `dir2`, create a file named `file2.txt`.

```
(kali@kali)-[~/Desktop]
$ cd ahmed

(kali@kali)-[~/Desktop/ahmed]
$ touch ahmed2.txt
```

7. Using nano or vim Write the numbers 1 to 9 into `file1.txt`.

```
(kali㉿kali)-[~/Desktop/ahmed]  
$ nano ahmed1.txt
```

8. From the home directory Copy the contents of `file1.txt` into `file2.txt`.

```
(kali㉿kali)-[~/Desktop]  
$ cp ahmed1/ahmed2.txt ahmed/ahmed1.txt
```

9. From the home directory, delete `file1.txt` inside `dir1`.

```
(kali㉿kali)-[~/Desktop]  
$ rm ahmed/ahmed1.txt  
  
(kali㉿kali)-[~/Desktop]  
$
```

10. Remove the directory `dir1` from the Desktop.

```
(kali㉿kali)-[~/Desktop]  
$ rmdir ahmed
```

11. Redirect the output of the network configuration command to a file named `network_info.txt` on the Desktop.

```
(kali㉿kali)-[~/Desktop]  
$ ifconfig >ahmed2.txt
```

12. Open the Desktop folder and show all files with detailed information.

```
(kali㉿kali)-[~/Desktop]  
$ ls -all  
total 20  
drwxr-xr-x  3 kali kali 4096 Aug 31 13:19 .  
drwx----- 26 kali kali 4096 Aug 31 12:46 ..  
drwxr-xr-x  2 kali kali 4096 Aug 31 11:59 ahmed1  
-rw-r--r--  1 kali kali  874 Aug 31 13:24 ahmed2.txt  
-rw-r--r--  1 kali kali    0 Aug 21 11:14 folder.folder  
-rw-----  1 kali kali 3643 Aug 24 19:13 quiz02.sh
```

Section 2: Users and Groups Management

13. Create a new user with your name.

```
(kali㉿kali)-[~/Desktop]
$ sudo adduser ahmed
info: Adding user `ahmed' ...
info: Selecting UID/GID from range 1000 to 59999 ...
info: Adding new group `ahmed' (1001) ...
info: Adding new user `ahmed' (1001) with group `ahmed (1001)' ...
info: Creating home directory `/home/ahmed' ...
info: Copying files from `/etc/skel' ...
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for ahmed
Enter the new value, or press ENTER for the default
  Full Name []: ahmed abotalip
  Room Number []:
  Work Phone []:
  Home Phone []:
  Other []:
Is the information correct? [Y/n] y
info: Adding new user `ahmed' to supplemental / extra groups `users' ...
info: Adding user `ahmed' to group `users' ...
```

14. Set a password for your user.

```
(kali㉿kali)-[~]
$ sudo passwd ahmed
New password:
Retype new password:
passwd: password updated successfully
```

15. Open the file that contains user information and verify that your user has been added.

```
(kali㉿kali)-[~]
$ /home
```

```
(kali㉿kali)-[/home]
$ net ahmed
Invalid command: net ahmed
Usage:
net rpc          Run functions using RPC transport
net rap          Run functions using RAP transport
net ads          Run functions using ADS transport
net file         Functions on remote opened files
net share        Functions on shares
net session      Manage sessions
net server       List servers in workgroup
net domain       List domains/workgroups on network
net printq       Modify printer queue
```

16. Add your user to the file that gives administrative privileges.

```
(kali㉿kali)-[/home]
$ sudo usermod -ag sudo ahmed
usermod: -a flag is only allowed with the -G flag
Usage: usermod [options] LOGIN

Options:
  -a, --append          append the user to the supplementa
  l GROUPS              mentioned by the -G option without
  removing              the user from other groups
  -b, --badname          allow bad names
  -c, --comment COMMENT new value of the GECOS field
```

```
(kali㉿kali)-[/home]
$ groups ahmed
ahmed : ahmed sudo users
```


17. Switch to your user and confirm the user identity.

```
(kali㉿kali)-[~]  
$ su cyber  
Password: █
```

18. Create a new group named `testgroup`.

```
(kali㉿kali)-[~]  
$ sudo addgroup testgroup  
[sudo] password for kali:  
info: Selecting GID from range 1000 to 59999 ...  
info: Adding group `testgroup' (GID 1002) ...
```

19. Add your user to `testgroup`.

```
(kali㉿kali)-[~]  
$ usermod -ag testgroup cyber  
usermod: -a flag is only allowed with the -G flag  
Usage: usermod [options] LOGIN  
  
Options:  
-a, --append                append the user to the supplemental GROUPS  
                             mentioned by the -G option without removing  
                             the user from other groups  
-b, --badname                allow bad names  
-c, --comment COMMENT       new value of the GECOS field  
-d, --home HOME_DIR         new home directory for the user account  
-e, --expiredate EXPIRE_DATE set account expiration date to EXPIRE_DATE  
-f, --inactive INACTIVE     set password inactive after expiration  
                             to INACTIVE  
-g, --gid GROUP              force use GROUP as new primary group  
-G, --groups GROUPS          new list of supplementary GROUPS  
-h, --help                   display this help message and exit  
-l, --login NEW_LOGIN        new value of the login name  
-L, --lock                   lock the user account  
-m, --move-home              move contents of the home directory to the  
                             new location (use only with -d)  
-o, --non-unique              allow using duplicate (non-unique) UID  
-p, --password PASSWORD      use encrypted password for the new password  
-P, --prefix PREFIX_DIR      prefix directory where are located the /etc/* files  
-r, --remove                  remove the user from only the supplemental GROUPS  
                             mentioned by the -G option without removing  
                             the user from other groups  
-R, --root CHROOT_DIR        directory to chroot into  
-s, --shell SHELL            new login shell for the user account  
-u, --uid UID                 new UID for the user account  
-U, --unlock                  unlock the user account  
-v, --add-subuids FIRST-LAST add range of subordinate uids  
-V, --del-subuids FIRST-LAST remove range of subordinate uids  
-w, --add-subgids FIRST-LAST add range of subordinate gids  
-W, --del-subgids FIRST-LAST remove range of subordinate gids  
-Z, --selinux-user SEUSER    new SELinux user mapping for the user account
```

20. Add the group `testgroup` to the file that gives administrative privileges.

```
(kali㉿kali)-[~/Desktop]  
$ sudo visudo
```

21. Remove your user from the file that gives administrative privileges.

```
(kali㉿kali)-[~/Desktop]  
$ sudo visudo
```

22. Check if your user still have administrative privileges.

```
(kali㉿kali)-[~/Desktop]  
$ sudo visudo
```

23. Check which groups your user belongs to.

```
(kali㉿kali)-[~/Desktop]  
$ testgroup cyber  
testgroup: command not found  
  
(kali㉿kali)-[~/Desktop]  
$ sudo testgroup cyber  
sudo: testgroup: command not found
```

Section 3: Permissions and Ownership

24. Set the permissions of `file2.txt` on the Desktop to allow the owner to read, write, and execute; the group to read and execute; and others to read .

```
(kali㉿kali)-[~/Desktop]
$ chmod u+rw,g+rw,o+r folder.folder
```

25. Check the permissions of `file2.txt` to verify the change.

```
(kali㉿kali)-[~/Desktop]
$ ls -l folder.folder
-rwxrw-r-- 1 kali kali 0 Aug 21 11:14 folder.folder
```

26. Change the ownership of `file2.txt` to your user.

```
(kali㉿kali)-[~/Desktop]
$ sudo chown cyber:cyber folder.folder
```

27. verify the ownership of `file2.txt`.

```
(kali㉿kali)-[~/Desktop]
$ ls -l folder.folder
-rwxrw-r-- 1 cyber cyber 0 Aug 21 11:14 folder.folder
```

28. Change back the ownership of a file `file2.txt` .

```
(kali㉿kali)-[~/Desktop]
$ sudo chown kali:kali folder.folder
```

29. Grant write permission to everyone for `file2.txt`.

```
(kali㉿kali)-[~/Desktop]
$ chmod u+w,g+w,o+w folder.folder
```

30. Remove the write permission for the group and others for `file2.txt`.

```
(kali㉿kali)-[~/Desktop]
$ chmod u+~w-,g+~,o+~ folder.folder
```

31. Delete `file2.txt` after making the necessary ownership and permission changes.

```
(kali㉿kali)-[~/Desktop]
$ rm folder.folder
rm: remove write-protected regular empty file 'folder.folder'? y
```

32. What command would you use to recursively change the permissions of all files and directories inside a folder named `project` to `755`.

```
(kali㉿kali)-[~/Desktop]
$ sudo chown -R 755 ahmed1
```

Section 4: Process Management

33. Install a system monitor tool that provides an interactive process viewer(htop).

```
(kali㉿kali)-[~]
└─$ sudo apt install httpd
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
E: Unable to locate package httpd
```

34. Display all running processes.

```

[~](kali@kali)~$ ps aux
USER      PID CPU MEM     VSZ    RSS TTY      STAT START   TIME COMMAND
root      1  0.0  0.0  28784 12492 ?        Ss   16:29   0:01 /sbin/init splash
root      2  0.0  0.0  0 0 ?        Ss   16:29   0:00 [kthreadd]
root      3  0.0  0.0  0 0 ?        Ic   16:29   0:00 [rcu_sgl]
root      4  0.0  0.0  0 0 ?        Ic   16:29   0:00 [rcu_gp]
root      5  0.0  0.0  0 0 ?        Ic   16:29   0:00 [slub_flushwq]
root      6  0.0  0.0  0 0 ?        Ic   16:29   0:00 [netns]
root      7  0.0  0.0  0 0 ?        Ic   16:29   0:00 [kworker/0:0m-events_h]
root      8  0.0  0.0  0 0 ?        Ic   16:29   0:00 [rcu_gp]
root      9  0.0  0.0  0 0 ?        I   16:29   0:00 [rcu_tasks_kthreadd]
root     10  0.0  0.0  0 0 ?        I   16:29   0:00 [rcu_tasks_rude_kthrea]
root     11  0.0  0.0  0 0 ?        Ic   16:29   0:00 [rcu_tasks_rude_kthrea]
root     12  0.0  0.0  0 0 ?        I   16:29   0:00 [ksfoidirq/0]
root     13  0.0  0.0  0 0 ?        I   16:29   0:00 [ksfoidirq/0]
root     14  0.0  0.0  0 0 ?        I   16:29   0:00 [ksfoidirq/0]
root     15  0.0  0.0  0 0 ?        I   16:29   0:05 [rcu_preempt]
root     16  0.0  0.0  0 0 ?        S   16:29   0:00 [migration/0]
root     17  0.0  0.0  0 0 ?        S   16:29   0:00 [idle_inject/0]
root     18  0.0  0.0  0 0 ?        S   16:29   0:00 [cpuhp/0]
root     19  0.0  0.0  0 0 ?        S   16:29   0:00 [cpuhp/1]
root     20  0.0  0.0  0 0 ?        S   16:29   0:00 [idle_inject/1]
root     21  0.0  0.0  0 0 ?        S   16:29   0:00 [migration/1]
root     22  0.0  0.0  0 0 ?        S   16:29   0:00 [ksfoidirq/1]
root     23  0.0  0.0  0 0 ?        Ic   16:29   0:00 [rcu_gp]
root     24  0.0  0.0  0 0 ?        Ic   16:29   0:00 [rcu_gp:1:mh-events_h]
root     25  0.0  0.0  0 0 ?        S   16:29   0:00 [cpuhp/2]
root     26  0.0  0.0  0 0 ?        S   16:29   0:00 [idle_inject/2]
root     27  0.0  0.0  0 0 ?        S   16:29   0:00 [migration/2]
root     28  0.0  0.0  0 0 ?        S   16:29   0:00 [cpuhp/3]

```

35. Display a tree of all running processes.

```

[~(setenv klog): [-]
  - ps1rew -p
  systemd(1)
    - ModeManager(749)
      - [ModeManager(78a)
        - [ModeManager(789)
          - [ModeManager(782)
            - [NetworkManager(788)
              - [NetworkManager(718)
                - [NetworkManager(712)
          - [NetworkManager(593)
        - [getty(951)
      - colord(3489)
        - [colorctl(1511)
          - [colorctl(1512)
            - [colorctl(1516)
        - [cron(618)
      - dbus-daemon(524)
      - hwsd(516)
      - lightdm(877)
        - [Xorg(930)
          - [Xorg(1825)
            - [lightdm(1108)
              - [xco-session(1214)
                - [Thunar(1354)
                  - [Thunar(1355)
                    - [Thunar(1356)
                    - [Thunar(1357)
                  - [agent(1457)
                    - [agent(1457)
                    - [agent(1458)
                    - [agent(1468)
                  - [blueman-applet(1452)
                    - [blueman-applet(1082)
                    - [blueman-applet(1683)
                    - [blueman-applet(1687)
                    - [blueman-applet(1702)
                  - [light-locker(1454)
                    - [light-locker(1324)
                    - [light-locker(1553)
                    - [light-locker(1554)
                    - [light-locker(1565)
                  - [nm-applet(1472)
                    - [nm-applet(1527)
                    - [nm-applet(1528)
                    - [nm-applet(1537)
                    - [nm-applet(1628)
                  - [polkit-gnome-aut(1453)
                    - [polkit-gnome-aut(1593)
                    - [polkit-gnome-aut(1594)
                    - [polkit-gnome-aut(1688)
                  - [ssh-agent(1762)
                - [xfce-panel(1349)
                  - [panel-1-whisker(1361)
                    - [panel-1-whisker(1362)

```

36. Open the interactive process viewer and identify a process by its PID.

```

kali@kali:~$ top
top - 18:07:40 up 5 min, 1 user, load average: 0.01, 0.08, 0.05
Tasks: 200 total, 1 running, 199 sleeping, 0 stopped, 0 zombie
%Cpu(s): 0.6 us, 1.7 sy, 0.0 ni, 97.7 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
MiB Mem : 1958.2 total, 987.2 free, 745.1 used, 458.9 buff/cache
MiB Swap: 1024.0 total, 1024.0 free, 0.0 used. 1213.2 avail Mem

  PID USER      PR  NI    VIRT    RES    SHR  S  %CPU  %MEM     TIME+ COMMAND
  888 root        20   0    383360 118092 55884  S   3.3   5.9   0:06.45 Xorg
2192 kali        20   0    448604 104704 85816  S   1.7   5.2   0:01.14 qterminal
1661 kali        20   0    1314812 107060 76964  S   0.7   5.3   0:02.96 xfwm4
1723 kali        20   0    423672 29796 20440  S   0.7   1.5   0:01.92 panel15-geommon
1817 kali        20   0    362184 41024 29980  S   0.7   2.0   0:01.23 vmtoolsd
4529 kali        20   0    11724 5376 3328 R   0.7   0.3   0:00.10 top
1721 kali        20   0    283732 25296 18816  S   0.3   1.3   0:01.56 panel-13-cpugra
   1 root         0    0    21048 12144 9072  S   0.0   0.6   0:03.02 systemd
   2 root         0    0         0 0 0  S   0.0   0.0   0:00.01 kthreadd
   3 root         0 -20    0 0 0  I   0.0   0.0   0:00.00 rcu_gp
   4 root         0 -20    0 0 0  I   0.0   0.0   0:00.00 rcu_par_gp

```


37. Kill a process with a specific PID.

```
(kali㉿kali)-[~]  
$ kill [4529]  
kill: illegal pid: [4529]
```

```
(kali㉿kali)-[~]  
$
```

38. Start an application and stop it using a command that kills processes by name(exeyes).

```
(kali㉿kali)-[~]  
$ exeyes &  
[1] 123896  
  
(kali㉿kali)-[~]  
$ Command 'exeyes' not found, did you mean:  
command 'expeyes' from deb expeyes  
command 'xeyes' from deb x11-apps  
Try: sudo apt install <deb name>  
  
[1] + exit 127 exeyes  
(kali㉿kali)-[~]  
$ pkill exeyes  
  
(kali㉿kali)-[~]  
$
```

39. Restart the application, then stop it using the interactive process viewer.

```
(kali㉿kali)-[~]  
$ exeyes &  
[1] 124891  
  
(kali㉿kali)-[~]  
$ Command 'exeyes' not found, did you mean:  
command 'xeyes' from deb x11-apps  
command 'expeyes' from deb expeyes  
Try: sudo apt install <deb name>  
  
[1] + exit 127 exeyes  
(kali㉿kali)-[~]  
$ htop  
Command 'htop' not found, but can be installed with:  
sudo apt install htop  
Do you want to install it? (N/y)y  
sudo apt install htop  
Reading package lists... Done  
Building dependency tree... Done  
Reading state information... Done  
E: Unable to locate package htop
```

40. Run a command in the background, then bring it to the foreground(exeyes).

```
(kali㉿kali)-[~]  
$ sudo exeyes &  
[1] 127334  
  
sudo: exeyes: command not found  
[1] + exit 1 sudo exeyes  
(kali㉿kali)-[~]  
$ fg  
fg: no current job
```

41. Check how long the system has been running.

```
(kali㉿kali)-[~]  
$ uptime  
21:03:42 up 4:34, 1 user, load average: 0.09, 0.13, 0.12
```

42. List all jobs running in the background.

```
(kali㉿kali)-[~]  
$ sleep 100 &  
[1] 130678  
  
(kali㉿kali)-[~]  
$ jobs  
[1] + running sleep 100
```

Section 5: Networking Commands

43. Display the network configuration

```
(kali㉿kali)-[~]  
$ ifconfig  
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500  
    inet 192.168.38.129 netmask 255.255.255.0 broadcast 192.168.38.255  
    inet6 fe80::45f6:5a1f:1b84:e30f prefixlen 64 scopeid 0x20<link>  
    ether 00:0c:29:6d:ec:77 txqueuelen 1000 (Ethernet)  
    RX packets 408 bytes 41928 (40.9 KiB)  
    RX errors 0 dropped 0 overruns 0 frame 0  
    TX packets 69 bytes 10888 (10.6 KiB)  
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0  
  
lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536  
    inet 127.0.0.1 netmask 255.0.0.0  
    inet6 ::1 prefixlen 128 scopeid 0x10<host>  
    loop txqueuelen 1000 (Local Loopback)  
    RX packets 4 bytes 240 (240.0 B)  
    RX errors 0 dropped 0 overruns 0 frame 0  
    TX packets 4 bytes 240 (240.0 B)  
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

44. Check the IP address of your machine.

```
(kali㉿kali)-[~]  
$ hostname -i  
127.0.1.1
```

45. Test connectivity to an external server.


```
(kali@kali)-[~]
$ ping 192.168.1.10
PING 192.168.1.10 (192.168.1.10) 56(84) bytes of data:
From 192.168.1.3 icmp_seq=3 Destination Host Unreachable
From 192.168.1.3 icmp_seq=6 Destination Host Unreachable
From 192.168.1.3 icmp_seq=9 Destination Host Unreachable
From 192.168.1.3 icmp_seq=12 Destination Host Unreachable
From 192.168.1.3 icmp_seq=15 Destination Host Unreachable
From 192.168.1.3 icmp_seq=18 Destination Host Unreachable
From 192.168.1.3 icmp_seq=21 Destination Host Unreachable
From 192.168.1.3 icmp_seq=24 Destination Host Unreachable
From 192.168.1.3 icmp_seq=27 Destination Host Unreachable
From 192.168.1.3 icmp_seq=30 Destination Host Unreachable
From 192.168.1.3 icmp_seq=33 Destination Host Unreachable
From 192.168.1.3 icmp_seq=36 Destination Host Unreachable
From 192.168.1.3 icmp_seq=39 Destination Host Unreachable
From 192.168.1.3 icmp_seq=42 Destination Host Unreachable
From 192.168.1.3 icmp_seq=45 Destination Host Unreachable
From 192.168.1.3 icmp_seq=48 Destination Host Unreachable
From 192.168.1.3 icmp_seq=51 Destination Host Unreachable
From 192.168.1.3 icmp_seq=54 Destination Host Unreachable
From 192.168.1.3 icmp_seq=57 Destination Host Unreachable
From 192.168.1.3 icmp_seq=60 Destination Host Unreachable
From 192.168.1.3 icmp_seq=63 Destination Host Unreachable
From 192.168.1.3 icmp_seq=66 Destination Host Unreachable
From 192.168.1.3 icmp_seq=69 Destination Host Unreachable
From 192.168.1.3 icmp_seq=72 Destination Host Unreachable
From 192.168.1.3 icmp_seq=75 Destination Host Unreachable
From 192.168.1.3 icmp_seq=78 Destination Host Unreachable
```

46. Display the routing table.

```
(kali@kali)-[~]
$ route -n
Kernel IP routing table
Destination      Gateway         Genmask         Flags Metric Ref    Use Iface
0.0.0.0          192.168.38.2   0.0.0.0         UG    100    0      0 eth0
192.168.38.0     0.0.0.0        255.255.255.0   U     100    0      0 eth0
```

active

47. Check the open ports and connections.

```
(kali@kali)-[~]
$ netstat -tuln
Active Internet connections (only servers)
Proto Recv-Q Send-Q Local Address           Foreign Address         State
```

48. Show the IP address of the host machine and the VM, and verify if they are on the same network.

```
(kali@kali)-[~]
$ hostname -i
127.0.1.1
```

49. Trace the route to an external server.

```
(kali@kali)-[~]
$ traceroute 192.168.1.10
traceroute to 192.168.1.10 (192.168.1.10), 30 hops max, 60 byte packets
 1 192.168.38.2 (192.168.38.2) 0.570 ms 0.676 ms 0.862 ms
 2 * * *
 3 * * *
 4 * * *
 5 * * *
 6 *
 *
 7 * * *
 8 * * *
 9 * * *
10 * * *
11 * * *
12 * * *
13 * * *
14 * * *
15 * * *
16 * * *
17 * * *
18 * * *
19 * * *
20 * * *
21 * * *
22 * * *
23 * * *
24 * * *
25 * * * "the quieter you become, the more you are able to hear"
26 * * *
27 * * *
28 * * *
29 * * *
30 * * *
```

50. Find out the default gateway.

```
(kali㉿kali)-[~]  
$ arp -a  
? (192.168.38.254) at 00:50:56:eb:e3:ab [ether] on eth0  
? (192.168.38.2) at 00:50:56:f8:13:20 [ether] on eth0
```

51. Check the MAC address of your network interface.

```
(kali㉿kali)-[~]  
$ ip link show  
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN mode DEFAULT group default qlen 1000  
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00  
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP mode DEFAULT group default qlen 1000  
    link/ether 00:0c:29:6d:ec:77 brd ff:ff:ff:ff:ff:ff
```

52. Ensure that the VM can access external networks.

```
(kali㉿kali)-[~]  
$ ping 192.168.1.10  
PING 192.168.1.10 (192.168.1.10) 56(84) bytes of data:  
From 192.168.1.3 icmp_seq=3 Destination Host Unreachable  
From 192.168.1.3 icmp_seq=6 Destination Host Unreachable
```

Section 6: UFW Firewall

53. Enable the firewall.

```
File Actions Edit View Help  
(kali㉿kali)-[~]  
$ sudo ufw enable  
[sudo] password for kali:  
sudo: ufw: command not found
```

54. Allow SSH connections through the firewall.

```
(kali㉿kali)-[~]  
$ sudo ufw deny ssh  
sudo: ufw: command not found
```

55. Deny all incoming traffic by default.

```
(kali㉿kali)-[~]  
$ sudo ufw default deny incoming  
sudo: ufw: command not found
```

56. Allow HTTP and HTTPS traffic.

```
(kali㉿kali)-[~]  
$ sudo ufw allow http  
sudo: ufw: command not found
```

57. Allow port 20

```
(kali㉿kali)-[~]  
$ sudo ufw allow 20  
sudo: ufw: command not found
```

58. Reset the firewall settings.

```
(kali㉿kali)-[~]
$ sudo ufw disable
sudo: ufw: command not found

(kali㉿kali)-[~]
$ sudo ufw reset
sudo: ufw: command not found
```

59. Delete a rule from the firewall.

```
(kali㉿kali)-[~]
$ sudo ufw status numbered
sudo: ufw: command not found

(kali㉿kali)-[~]
$ sudo ufw delete 1
```

60. Disable the firewall.

```
(kali㉿kali)-[~]
$ sudo ufw disable
sudo: ufw: command not found
```

61. View the status of the firewall.

```
(kali㉿kali)-[~]
$ sudo ufw status
sudo: ufw: command not found
```

62. Log firewall activity and view it.

```
(kali㉿kali)-[~]
$ sudo cat /var/log/ufw.log
cat: /var/log/ufw.log: No such file or directory
```

Section 7: Searching and System Information

63. Delete the command history.

```
(kali㉿kali)-[~]
$ bash history -c
```

64. Search for a kali in the `/etc/passwd` file.

```
(kali㉿kali)-[~]
$ bash grep kali /etc/passwd
/usr/bin/grep: /usr/bin/grep: cannot execute binary file
```

65. Search for a kali in the `/etc/group` file.

```
(kali㉿kali)-[~]
$ bash grep kali /etc/group
/usr/bin/grep: /usr/bin/grep: cannot execute binary file
```


66. Locate the `passwd` file.

```
(kali@kali)-[~]
$ locate passwd
/etc/passwd
/etc/passwd-
/etc/alternatives/vncpasswd
/etc/alternatives/vncpasswd.1.gz
/etc/pam.d/chpasswd
/etc/pam.d/passwd
/etc/security/opasswd
/usr/bin/autopasswd
/usr/bin/expect_autompasswd
/usr/bin/expect_mkpasswd
/usr/bin/expect_tkpasswd
/usr/bin/gpasswd
/usr/bin/grub-mkpasswd-pbkdf2
/usr/bin/httpasswd
/usr/bin/impacket-smbpasswd
/usr/bin/ldappasswd
/usr/bin/mkpasswd
/usr/bin/mosquitto_passwd
/usr/bin/passwd
/usr/bin/smbpasswd
/usr/bin/tightvncpasswd
/usr/bin/tkpasswd
/usr/bin/vncpasswd
/usr/include/rpcsvc/yppasswd.h
/usr/include/rpcsvc/yppasswd.x
/usr/lib/python3/dist-packages/future/backports/test/keycert.passwd.pem
/usr/lib/python3/dist-packages/future/backports/test/ssl_key.passwd.pem
/usr/lib/python3/dist-packages/impacket/krb5/_pycache_/kpasswd.cpython-311.pyc
/usr/lib/python3/dist-packages/samba/tests/krb5/kpasswd_tests.py
/usr/lib/python3/dist-packages/samba/tests/krb5/_pycache_/kpasswd_tests.cpython-311.pyc
/usr/lib/tmpfiles.d/passwd.conf
/usr/lib/x86_64-linux-gnu/samba/libmbpasswdparser-samba4.so.0
/usr/sbin/chpasswd
/usr/sbin/chpasswd
```

67. Locate the shadow file and open it.

```
(kali@kali)-[~]
$ sudo cat /etc/shadow
root:!:19590:0:99999:7:::
daemon:!:19590:0:99999:7:::
bin:!:19590:0:99999:7:::
sys:!:19590:0:99999:7:::
sync:!:19590:0:99999:7:::
games:!:19590:0:99999:7:::
man:!:19590:0:99999:7:::
lp:!:19590:0:99999:7:::
mail:!:19590:0:99999:7:::
news:!:19590:0:99999:7:::
uucp:!:19590:0:99999:7:::
proxy:!:19590:0:99999:7:::
www-data:!:19590:0:99999:7:::
backup:!:19590:0:99999:7:::
list:!:19590:0:99999:7:::
irc:!:19590:0:99999:7:::
_apt:!:19590:0:99999:7:::
nobody:!:19590:0:99999:7:::
systemd-network:!:19590:0:99999:7:::
systemd-timesync:!:19590:0:99999:7:::
messagebus:!:19590:0:99999:7:::
tss:!:19590:0:99999:7:::
strongswan:!:19590:0:99999:7:::
tcpdump:!:19590:0:99999:7:::
usbmux:!:19590:0:99999:7:::
sshd:!:19590:0:99999:7:::
dnsmasq:!:19590:0:99999:7:::
avahi:!:19590:0:99999:7:::
speech-dispatcher:!:19590:0:99999:7:::
pulse:!:19590:0:99999:7:::
lightdm:!:19590:0:99999:7:::
saned:!:19590:0:99999:7:::
polkitd:!:19590:0:99999:7:::
rtkit:!:19590:0:99999:7:::
colord:!:19590:0:99999:7:::
nm-openvpn:!:19590:0:99999:7:::
nm-openconnect:!:19590:0:99999:7:::
mysql:!:19590:0:99999:7:::
```

68. Search for all configuration files in the `/etc` directory.

```
(kali㉿kali)-[~]
$ find /etc -type f
/etc/python2.7/sitecustomize.py
/etc/macchanger/ifupeown.sh
/etc/alternatives/README
/etc/stunnel/README
/etc/mysql/my.cnf.fallback
/etc/mysql/conf.d/mysql.cnf
/etc/mysql/conf.d/mysqldump.cnf
/etc/mysql/debian.cnf
/etc/mysql/mariadb.cnf
/etc/mysql/mariadb.conf.d/50-mysql-clients.cnf
/etc/mysql/mariadb.conf.d/50-mysqld_safe.cnf
/etc/mysql/mariadb.conf.d/provider_lzo.cnf
/etc/mysql/mariadb.conf.d/provider_lz4.cnf
/etc/mysql/mariadb.conf.d/provider_lzma.cnf
/etc/mysql/mariadb.conf.d/provider_bzip2.cnf
/etc/mysql/mariadb.conf.d/50-client.cnf
/etc/mysql/mariadb.conf.d/provider_snappy.cnf
/etc/mysql/mariadb.conf.d/50-server.cnf
/etc/mysql/mariadb.conf.d/60-galera.cnf
/etc/mysql/debian-start
/etc/reader.conf.d/libccidtwi
/etc/ts.conf
/etc/smartd.conf
/etc/init.d/plymouth
/etc/init.d/udev
/etc/init.d/samba-ad-dc
/etc/init.d/nginx
/etc/init.d/pcscd
/etc/init.d/nfs-common
/etc/init.d/ntpsec
/etc/init.d/saned
/etc/init.d/procps
/etc/init.d/apache2
/etc/init.d/haveged
/etc/init.d/rsync
```

69. Search recursively for a specific word in

the `/var/log` directory.

```
(kali㉿kali)-[~]
$ grep -r "ah" /var/log
grep: /var/log/vmware-vmtoolsd-root.1.log: Permission denied
grep: /var/log/apt/term.log.1.gz: binary file matches
grep: /var/log/apt/eipp.log.xz: binary file matches
grep: /var/log/boot.log: Permission denied
grep: /var/log/private: Permission denied
grep: /var/log/vmware-vmtoolsd-root.3.log: Permission denied
grep: /var/log/boot.log.2: Permission denied
grep: /var/log/btmp: Permission denied
grep: /var/log/boot.log.1: Permission denied
grep: /var/log/speech-dispatcher: Permission denied
grep: /var/log/vmware-vmtoolsd-root.2.log: Permission denied
/var/log/dpkg.log.1:2023-08-21 14:52:02 install libavahi-common-data:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status half-installed libavahi-common-data:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status unpacked libavahi-common-data:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 install libavahi-common3:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status half-installed libavahi-common3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status unpacked libavahi-common3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 install libavahi-client3:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status half-installed libavahi-client3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status unpacked libavahi-client3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 install libavahi-core7:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 status half-installed libavahi-core7:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 status unpacked libavahi-core7:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 install avahi-daemon:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 status half-installed avahi-daemon:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 status unpacked avahi-daemon:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:42 install libavahi-glib1:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:42 status half-installed libavahi-glib1:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:42 status unpacked libavahi-glib1:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:11 configure libavahi-common-data:amd64 0.8-10 <none>
/var/log/dpkg.log.1:2023-08-21 14:53:11 status unpacked libavahi-common-data:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:11 status half-configured libavahi-common-data:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:11 status installed libavahi-common-data:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:15 configure libavahi-common3:amd64 0.8-10 <none>
/var/log/dpkg.log.1:2023-08-21 14:53:15 status unpacked libavahi-common3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:15 status half-configured libavahi-common3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:15 status installed libavahi-common3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:16 configure libavahi-glib1:amd64 0.8-10 <none>
/var/log/dpkg.log.1:2023-08-21 14:53:16 status unpacked libavahi-glib1:amd64 0.8-10
```


70. View the system's kernel version.

```
(kali㉿kali)-[~]  
$ uname -r  
6.3.0-kali1-amd64
```

71. Display the system's memory usage.

```
(kali㉿kali)-[~]  
$ free -h
```

	total	used	free	shared	buff/cache	available
Mem:	1.9Gi	760Mi	665Mi	6.6Mi	685Mi	1.2Gi
Swap:	1.0Gi	0B	1.0Gi			

72. Show the system's disk usage.

```
(kali㉿kali)-[~]  
$ df -f  
df: invalid option -- 'f'  
Try 'df --help' for more information.
```

73. Check the system's uptime and load average.

```
(kali㉿kali)-[~]  
$ uptime  
16:19:26 up 1:05, 1 user, load average: 0.16, 0.11, 0.05
```

74. Display the current logged-in users.

```
(kali㉿kali)-[~]  
$ who  
kali    tty7      2024-09-08 15:15 (:0)
```

75. Check the identity of the current user.

```
(kali㉿kali)-[~]  
$ whoami  
kali
```

76. View the `/var/log/auth.log` file.

```
(kali㉿kali)-[~]  
$ sudo cat /var/log/auth.log  
cat: /var/log/auth.log: No such file or directory
```

77. Shred the `auth.log` file securely.

```
(kali㉿kali)-[~]  
$ sudo shred -u /var/log/auth.log  
shred: /var/log/auth.log: failed to open for writing: No such file or directory
```


78. How do you lock a user account to prevent them from logging in.

```
(kali㉿kali)-[~]
$ sudo usermod -l cyber
Usage: usermod [options] LOGIN

Options:
  -a, --append                append the user to the supplemental GROUPS
                              mentioned by the -G option without removing
                              the user from other groups
  -b, --badname               allow bad names
  -c, --comment COMMENT       new value of the GECOS field
  -d, --home HOME_DIR         new home directory for the user account
  -e, --expiredate EXPIRE_DATE set account expiration date to EXPIRE_DATE
  -f, --inactive INACTIVE     set password inactive after expiration
                              to INACTIVE
  -g, --gid GROUP             force use GROUP as new primary group
  -G, --groups GROUPS         new list of supplementary GROUPS
  -h, --help                  display this help message and exit
  -l, --login NEW_LOGIN       new value of the login name
  -L, --lock                  lock the user account
  -m, --move-home             move contents of the home directory to the
                              new location (use only with -d)
  -o, --non-unique            allow using duplicate (non-unique) UID
  -p, --password PASSWORD     use encrypted password for the new password
  -P, --prefix PREFIX_DIR     prefix directory where are located the /etc/* files
  -r, --remove                remove the user from only the supplemental GROUPS
                              mentioned by the -G option without removing
                              the user from other groups
  -R, --root CHROOT_DIR       directory to chroot into
  -s, --shell SHELL           new login shell for the user account
  -u, --uid UID               new UID for the user account
  -U, --unlock                unlock the user account
  -v, --add-subuids FIRST-LAST add range of subordinate uids
  -V, --del-subuids FIRST-LAST remove range of subordinate uids
  -w, --add-subgids FIRST-LAST add range of subordinate gids
  -W, --del-subgids FIRST-LAST remove range of subordinate gids
  -Z, --selinux-user SEUSER   new SELinux user mapping for the user account
```

79. What command would you use to change a user's default shell.

```
(kali㉿kali)-[~]
$ sudo chsh -s /bin/bash cyber
```

80. Display the system's boot messages.

```
(kali㉿kali)-[~]
$ dmesg
[ 0.000000] Linux version 6.3.0-kali1-amd64 (devel@kali.org) (gcc-12 (Debian 12.3.0-4) 12.3.0, GNU ld (
7-1kali1 (2023-06-29)
[ 0.000000] Command line: BOOT_IMAGE=/boot/vmlinuz-6.3.0-kali1-amd64 root=UUID=0d9f25ad-336a-4e48-bf93-
[ 0.000000] Disabled fast string operations
[ 0.000000] x86/fpu: Supporting XSAVE feature 0x001: 'x87 floating point registers'
[ 0.000000] x86/fpu: Supporting XSAVE feature 0x002: 'SSE registers'
[ 0.000000] x86/fpu: Supporting XSAVE feature 0x004: 'AVX registers'
[ 0.000000] x86/fpu: xstate_offset[2]: 576, xstate_sizes[2]: 256
[ 0.000000] x86/fpu: Enabled xstate features 0x7, context size is 832 bytes, using 'standard' format.
[ 0.000000] signal: max sigframe size: 1776
[ 0.000000] BIOS-provided physical RAM map:
[ 0.000000] BIOS-e820: [mem 0x0000000000000000-0x0000000000009f3ff] usable
[ 0.000000] BIOS-e820: [mem 0x0000000000009f400-0x0000000000009ffff] reserved
[ 0.000000] BIOS-e820: [mem 0x000000000000dc000-0x000000000000ffffff] reserved
[ 0.000000] BIOS-e820: [mem 0x00000000000100000-0x000000000007fedffff] usable
[ 0.000000] BIOS-e820: [mem 0x000000000007fee0000-0x000000000007fefefff] ACPI data
```



تم بحمد الله وفضلة ومعونته

اعداد وتنفيذ: م. محمد عبد الجليل الذبحاني