PROJECT PORTFOLIO DASHBOARD

FolioBoard setup guide

Next.js 15 + TypeScript + Supabase (Postgres, Auth, Storage) + Google login. Follow the steps in order. About 25 minutes.

What you get

- **Dashboards**: unlimited, each fully separate (own fields, projects, share links). A Home page combines all of them.
- **Field system**: 15 field types, 5 templates, drag/arrow reorder, required / sensitive flags, calculated profit. Removing a field archives its data.
- **Add Project** form generated from your fields, with URL preview, live money formatting, draft autosave and Ctrl+Enter.
- **Projects**: Pro Table (not a normal table), Gallery, Board, Timeline; search, sort, resize, reorder, inline edit, CSV import/export, PDF export, detail drawer.
- **Analytics**: weekly / monthly / quarterly / yearly, deltas, heatmap, streaks, best month, top client, goals.
- **Share links**: hide fields per link, password, expiry, revoke, QR, view counter, live preview. Hidden data is removed on the server.
- **Public profile** (/u/username), embeddable SVG badge, Cmd/Ctrl+K palette, dark / light / system theme, mobile bottom navigation.

STEP 1

Create the Supabase project

Go to **supabase.com** → New project. Pick a region near your users and save the database password.

When it is ready open **Project Settings** → **API** and copy: **Project URL**, **anon public** key, and **service_role** key (secret).

STEP 2

Run the four SQL files

Open **SQL Editor** → **New query**. Paste and run each file completely, in this order:

```
supabase/migrations/0001_schema.sql    -> tables, triggers, indexes
supabase/migrations/0002_security.sql  -> Row Level Security + storage bucket
supabase/migrations/0003_rpc.sql       -> share-link and public-profile functions
supabase/migrations/0004_grants.sql    -> table access for signed-in users (needed on new Supabase proj
```

Click **Run** and wait for each to end with *Success. No rows returned* before pasting the next. 0002, 0003 and 0004 are safe to run again; do not re-run 0001. The second file also creates the public **project-thumbnails** storage bucket (2 MB limit, images only); check it under Storage.

Optional: **supabase/tests/share_leak_test.sql** proves hidden fields cannot leak (it needs a plain Postgres with *tests/local_stub.sql*; do not run the stub on Supabase). **supabase/seed.sql** adds demo data after you sign up once.

STEP 3

Turn OFF email confirmation

Authentication → **Sign In / Providers** → **Email**. Make sure **Email** is enabled and switch **Confirm email** OFF, then Save. New users now land in the app instantly. If this stays on, sign-up shows a message reminding you.

STEP 4

Google login

a) Google Cloud Console → create a project → **APIs & Services** → **OAuth consent screen** (External, add your email). **b) Credentials** → **Create credentials** → **OAuth client ID** → **Web application**.

c) Under **Authorized redirect URIs** add exactly this (copy it from Supabase → Authentication → Providers → Google):

```
https://YOUR_PROJECT_REF.supabase.co/auth/v1/callback
```

d) Copy the Client ID and Client secret into **Supabase** → **Authentication** → **Providers** → **Google**, enable it, Save.

e) Authentication → **URL Configuration**: set **Site URL** to your site and add Redirect URLs:

```
http://localhost:3000/**
https://YOUR-DOMAIN.vercel.app/**
```

The Google redirect URI never changes between local and production; only the Supabase Site URL / Redirect URLs list does.

STEP 5

Configure and run locally

```
cd folioboard
cp .env.example .env.local
npm install
npm run dev
```

Fill **.env.local**:

```
NEXT_PUBLIC_SUPABASE_URL=https://YOUR_PROJECT_REF.supabase.co
NEXT_PUBLIC_SUPABASE_ANON_KEY=your anon key
SUPABASE_SERVICE_ROLE_KEY=your service role key   # server only
NEXT_PUBLIC_SITE_URL=http://localhost:3000
```

Open **http://localhost:3000** → Get started. The service-role key is used only to delete an account; it is never sent to the browser. Do not prefix it with NEXT_PUBLIC_.

STEP 6

Deploy to Vercel

Push the folder to GitHub → Vercel → Add New Project → import it. Add the same four environment variables (set **NEXT_PUBLIC_SITE_URL** to your Vercel domain, no trailing slash) and deploy.

Then go back to Supabase → Authentication → URL Configuration and set Site URL to the Vercel domain (add it to Redirect URLs as in Step 4e). A custom domain works the same way.

STEP 7

Prove the privacy feature yourself (2 minutes)

- Create a dashboard with the Freelancing template and add a project with an amount.
- Share → New share link. Project Amount, Money Spent, Profit and Client are pre-hidden because they are marked sensitive.
- Open the link in an incognito window. Press Ctrl+U (page source) and search for the amount: it is not there. Check the Network tab: no response contains it. Charts show counts, not revenue.
- Un-hide a field in the link editor and watch the live preview change before you save.

STEP 8

Tests and quality checks

```
npm test             # unit tests: analytics, money, CSV, validation
npm run typecheck
npm run lint
npm run build
npm run test:e2e      # browser test of the privacy flow (needs live Supabase, Confirm email OFF)
```

Already run for this delivery: type-check, lint, production build, 9 unit tests, and the SQL privacy / RLS test against a real Postgres 16.

Where things are

Path	What it holds
src/app	Routes: landing, auth, /app/*, /s/[token], /u/[username], /badge, SEO files
src/features	dashboards, fields, projects, analytics, share, profile (UI + server actions)
src/lib	Supabase clients, data layer, validators, currency, CSV, format
supabase/migrations	0001 schema, 0002 security, 0003 RPCs, 0004 grants (run in this order)
supabase/tests	share_leak_test.sql and local_stub.sql
e2e, tests	Playwright flow, Vitest unit tests
docs	ARCHITECTURE.md and this guide

Troubleshooting

- **Redirected back to /login after Google**: the Site URL or Redirect URLs in Supabase do not include the address you are using.
- **“Could not load your profile” / “permission denied”**: run 0004_grants.sql (then 0002 if it never completed) and refresh.
- **“Missing/invalid env”**: .env.local not filled or the dev server was not restarted.
- **Sign-up says confirmation is required**: Step 3 is not saved.

- **Image upload fails**: re-run 0002_security.sql (bucket and policies) and check Storage → project-thumbnails exists.
- **Share link shows 404**: it was revoked, expired, or its dashboard was deleted.
- **Combined totals on Home look off**: they use approximate static exchange rates in src/lib/currency.ts; edit the table if you want exact values.