

dohtyx4dn

February 10, 2023

```
[1]: import numpy as np
import matplotlib.pyplot as plt
from typing import NamedTuple
from google.colab import output
```

```
[2]: SEED = 0

BOARD_COL = 3
BOARD_ROW = 3
BOARD_SIZE = BOARD_COL * BOARD_ROW

"""
Game board and actions are: {q, w, e, a, s, d, z, x, c}

q | w | e
--/---/--
a | s | d
--/---/--
z | x | c
"""

ACTIONS_KEY_MAP = {'q': 0, 'w': 1, 'e': 2,
                    'a': 3, 's': 4, 'd': 5,
                    'z': 6, 'x': 7, 'c': 8}
```

```
[3]: np.random.seed(SEED)
```

State Defination

```
[4]: def print_state(board, clear_output=False):
    if clear_output:
        output.clear()
    for i in range(BOARD_ROW):
        print('-----')
        out = '| '
        for j in range(BOARD_COL):
            if board[i, j] == 1:
                token = 'x'
            elif board[i, j] == -1:
```

```

        token = 'o'
    else:
        token = ' ' # empty position
    out += token + ' | '
    print(out)
    print('-----')

```

```
class State:
```

```

    def __init__(self, symbol):
        # the board is represented by an n * n array,
        # 1 represents the player who moves first,
        # -1 represents another player
        # 0 represents an empty position
        self.board = np.zeros((BOARD_ROW, BOARD_COL))
        self.symbol = symbol
        self.winner = 0
        self.end = None

```

```
@property
```

```

    def hash_value(self):
        hash = 0
        for x in np.nditer(self.board):
            hash = 3*hash + x + 1 # unique hash

        return hash

```

```

    def next(self, action: str):
        id = ACTIONS_KEY_MAP[action]
        i, j = id // BOARD_COL, id % BOARD_COL
        return self.next_by_pos(i, j)

```

```

    def next_by_pos(self, i: int, j: int):
        assert self.board[i, j] == 0
        new_state = State(-self.symbol) # another player turn
        new_state.board = np.copy(self.board)
        new_state.board[i, j] = self.symbol # current player choose to play at (i,
↪ j) pos
        return new_state

```

```
@property
```

```

    def possible_actions(self):
        rev_action_map = {id: key for key, id in ACTIONS_KEY_MAP.items()}
        actions = []
        for i in range(BOARD_ROW):
            for j in range(BOARD_COL):
                if self.board[i, j] == 0:

```

```

        actions.append(rev_action_map[BOARD_COL*i+j])
    return actions

def is_end(self):
    if self.end is not None:
        return self.end

    check = []
    # check row
    for i in range(BOARD_ROW):
        check.append(sum(self.board[i, :]))

    # check col
    for i in range(BOARD_COL):
        check.append(sum(self.board[:, i]))

    # check diagonal
    diagonal = 0; reverse_diagonal = 0
    for i in range(BOARD_ROW):
        diagonal += self.board[i, i]
        reverse_diagonal += self.board[BOARD_ROW-i-1, i]
    check.append(diagonal)
    check.append(reverse_diagonal)

    for x in check:
        if x == 3:
            self.end = True
            self.winner = 1    # player 1 wins
            return self.end
        elif x == -3:
            self.end = True
            self.winner = 2    # player 2 wins
            return self.end

    for x in np.nditer(self.board):
        if x == 0:            # play available
            self.end = False
            return self.end

    self.winner = 0          # draw
    self.end = True
    return self.end

```

Environment

```

[5]: class Env:
    def __init__(self):

```

```

self.all_states = self.get_all_states()
self.curr_state = State(symbol=1)

def get_all_states(self):
    all_states = {} # is a dict with key as state_hash_value and value as
    ↪State object.
    def explore_all_substates(state):
        for i in range(BOARD_ROW):
            for j in range(BOARD_COL):
                if state.board[i, j] == 0:
                    next_state = state.next_by_pos(i, j)
                    if next_state.hash_value not in all_states:
                        all_states[next_state.hash_value] = next_state
                    if not next_state.is_end():
                        explore_all_substates(next_state)
    curr_state = State(symbol=1)
    all_states[curr_state.hash_value] = curr_state
    explore_all_substates(curr_state)
    return all_states

def reset(self):
    self.curr_state = State(symbol=1)
    return self.curr_state

def step(self, action):
    assert action in self.curr_state.possible_actions, f"Invalid {action} for
    ↪the current state \n{print_state(self.curr_state.board)}"
    next_state_hash = self.curr_state.next(action).hash_value
    next_state = self.all_states[next_state_hash]
    self.curr_state = next_state
    reward = 0
    return self.curr_state, reward

def is_end(self):
    return self.curr_state.is_end()

@property
def winner(self):
    result_id = self.curr_state.winner
    result = 'draw'
    if result_id == 1:
        result = 'player1'
    elif result_id == 2:
        result = 'player2'
    return result

```

Policy

```
[6]: class BasePolicy:
    def reset(self):
        pass

    def update_values(self, *args):
        pass

    def select_action(self, state):
        raise Exception('Not Implemented Error')
```

```
[7]: class HumanPolicy(BasePolicy):
    def __init__(self, symbol):
        self.symbol = symbol

    def select_action(self, state):
        assert state.symbol == self.symbol, f"Its not {self.symbol} symbol's turn"
        print_state(state.board, clear_output=True)
        key = input("Input your position: ")
        return key
```

```
[8]: class RandomPolicy(BasePolicy):
    def __init__(self, symbol):
        self.symbol = symbol

    def select_action(self, state):
        assert state.symbol == self.symbol, f"Its not {self.symbol} symbol's turn"
        return np.random.choice(state.possible_actions)
```

```
[9]: class ActionPlayed(NamedTuple):
    hash_value: str
    action: str

class MenacePolicy(BasePolicy):
    def __init__(self, all_states, symbol, tau=5.0):
        self.all_states = all_states
        self.symbol = symbol
        self.tau = tau

        # It store the number of stones for each action for each state
        self.state_action_value = self.initialize()
        # variable to store the history for updating the number of stones
        self.history = []

    def initialize(self):
        state_action_value = {}
        for hash_value, state in self.all_states.items():
```

```

        # initially all actions have 0 stones
        state_action_value[hash_value] = {action: 0 for action in state.
↪possible_actions}
        return state_action_value

def reset(self):
    for action_value in self.state_action_value.values():
        for action in action_value.keys():
            action_value[action] = 0

def print_updates(self, reward):
    print(f'Player with symbol {self.symbol} updates the following history with_
↪{reward} stone')
    for item in self.history:
        board = np.copy(self.all_states[item.hash_value].board)
        id = ACTIONS_KEY_MAP[item.action]
        i, j = id//BOARD_COL, id%BOARD_COL
        board[i, j] = self.symbol
        print_state(board)

def update_values(self, reward, show_update=False):
    # reward: if wins receive reward of 1 stone for the chosen action
    #         else -1 stone.
    # reward is either 1 or -1 depending upon if the player has won or lost the_
↪game.

    if show_update:
        self.print_updates(reward)
    for item in self.history:

        # your code here

        self.state_action_value[item.hash_value][item.action] += reward # update_
↪state_action with appropriate term.

    self.history = []

def select_action(self, state): # Softmax action probability
    assert state.symbol == self.symbol, f"Its not {self.symbol} symbol's turn"
    action_value = self.state_action_value[state.hash_value]
    max_value = action_value[max(action_value, key=action_value.get)]
    exp_values = {action: np.exp((v-max_value) / self.tau) for action, v in_
↪action_value.items()}
    normalizer = np.sum([v for v in exp_values.values()])
    prob = {action: v/normalizer for action, v in exp_values.items()}
    action = np.random.choice(list(prob.keys()), p=list(prob.values()))

```

```
self.history.append(ActionPlayed(state.hash_value, action))
return action
```

Game Board

```
[10]: class Game:
    def __init__(self, env, player1, player2):
        self.env = env
        self.player1 = player1
        self.player2 = player2
        self.show_updates = False

    def alternate(self):
        while True:
            yield self.player1
            yield self.player2

    def train(self, epochs=1_00_000):
        game_results = []
        player1_reward_map = {'player1': 1, 'player2': -1, 'draw': 0}
        for _ in range(epochs):
            result = self.play()

            # if player1 wins add 1 stone for the action chosen
            player1_reward = player1_reward_map[result]
            player2_reward = -player1_reward # if player2 wins add 1 stone

            self.player1.update_values(player1_reward)
            self.player2.update_values(player2_reward)

    def play(self):
        alternate = self.alternate()
        state = self.env.reset()
        while not self.env.is_end():
            player = next(alternate)
            action = player.select_action(state)
            state, _ = self.env.step(action)
        result = self.env.winner
        return result
```

Experiment

```
[11]: env = Env()

player1 = MenacePolicy(env.all_states, symbol=1)
player2 = MenacePolicy(env.all_states, symbol=-1)
# player2 = RandomPolicy(symbol=-1)
```

```
[12]: game = Game(env, player1, player2)
game.train(epochs=1_00_000)
```

```
[13]: game_with_human_player = Game(env, player1, HumanPolicy(symbol=-1))

game_with_human_player.play()

result = env.winner
print(f"winner: {result}")

player1_reward_map = {'player1': 1, 'player2': -1, 'draw': 0}
player1.update_values(player1_reward_map[result], show_update=True)
```

```
-----
| x | o | x |
-----
|   | o |   |
-----
| o | x | x |
-----
```

Input your position: d

winner: draw

Player with symbol 1 updates the following history with 0 stone

```
-----
|   |   | x |
-----
|   |   |   |
-----
|   |   |   |
-----
-----
| x |   | x |
-----
|   | o |   |
-----
|   |   |   |
-----
-----
| x | o | x |
-----
|   | o |   |
-----
|   | x |   |
-----
-----
| x | o | x |
-----
```


			o			

	o		x		x	

	x		o		x	

	x		o		o	

	o		x		x	

[13]: