

Experiment 6 – Qualys Virtual Scanner Appliance

Aim

To deploy and configure a Qualys Virtual Scanner Appliance in VirtualBox and verify connectivity with the Qualys Cloud Platform and Kali Linux.

Tools required:

- 1.Qualys
- 2.Ova file

VirtualBox Configuration

- CPU: 4 cores
- RAM: 8 GB
- Adapter 1: NAT
- Adapter 2: Host-Only

Procedure

- 1. Log in to Qualys with Manager/Unit Manager credentials.
- 2. Go to VM/VMDR → Scans → Appliances → New → Virtual Scanner Appliance.
- 3. Start the wizard, provide a scanner name, download the .ova and note the 14-digit Personalization Code.
- 4. In VirtualBox select File then Import Appliance and select the .ova.
- 5. Configure approximately 4 CPU cores and 8 GB RAM.
- 6. Set Adapter 1 to NAT and Adapter 2 to Host-Only.
- 7. Start the scanner VM and select Personalize this scanner.
- 8. Enter the 14-digit Personalization Code and wait for personalization/updates.
- 9. In Qualys → Scans → Appliances, refresh and verify scanner activation, name and IP.
- 10. Connect Kali to the same Host-Only network and verify its IP/connectivity.
- 11. In Qualys create a new scan, select the Kali IP/asset and the activated Virtual Scanner Appliance.
- 12. Launch the scan and review vulnerability results.

Kali Verification Commands

ip addr

ip route

Result:

Thus deploying and configuring a Qualys Virtual Scanner Appliance in VirtualBox and verifying connectivity with the Qualys Cloud Platform and Kali Linux was done successfully