

CS23333-Object Oriented Programming Using Java-2023

Dashboard / My courses / CS23333-OOPUJ-2023 / Lab-11-Set, Map / Lab-11-Logic Building

Quiz navigation

- 1
- 2
- 3

Show one page at a time

Finish review

| | |
|-----------|------------------------------------|
| Status | Finished |
| Started | Saturday, 9 November 2024, 6:38 PM |
| Completed | Saturday, 9 November 2024, 6:51 PM |
| Duration | 13 mins 41 secs |

Question 1

Correct

Marked out of 1.00

Flag question

Java HashSet class implements the Set interface, backed by a hash table which is actually a [HashMap](#) instance.

No guarantee is made as to the iteration order of the hash sets which means that the class does not guarantee the constant order of elements over time.

This class permits the null element.

The class also offers constant time performance for the basic operations like add, remove, contains, and size assuming the hash function disperses the elements properly among the buckets.

Java HashSet Features

A few important features of HashSet are mentioned below:

- Implements [Set Interface](#).
- The underlying data structure for HashSet is [Hashtable](#).
- As it implements the Set Interface, duplicate values are not allowed.
- Objects that you insert in HashSet are not guaranteed to be inserted in the same order. Objects are inserted based on their hash code.
- NULL elements are allowed in HashSet.
- HashSet also implements **Serializable** and **Cloneable** interfaces.

```
public class HashSet<E> extends AbstractSet<E> implements Set<E>, Cloneable, Serializable
Sample Input and Output:
5
90
56
45
78
25
78
Sample Output:
78 was found in the set.
Sample Input and output:
3
2
7
9
5
Sample Input and output:
5 was not found in the set.
```

Answer: (penalty regime: 0 %)

Reset answer

```
1 import java.util.HashSet;
2 import java.util.Scanner;
3 public class HashSetExample {
4     public static void main(String[] args) {
5         Scanner sc = new Scanner(System.in);
6         HashSet<Integer> set = new HashSet<>();
7         int n = sc.nextInt();
8         for (int i = 0; i < n; i++) {
9             set.add(sc.nextInt());
10        }
11        int num = sc.nextInt();
12        if (set.contains(num)) {
13            System.out.println(num + " was found in the set.");
14        } else {
15            System.out.println(num + " was not found in the set.");
16        }
17        sc.close();
18    }
19 }
```

| Test | Input | Expected | Got |
|------|---------------------------------------|-----------------------------|-----------------------------|
| 1 | 5 90 56 45 78 25 78 | 78 was found in the set. | 78 was found in the set. |
| 2 | 3 -1 2 4 5 | 5 was not found in the set. | 5 was not found in the set. |

Passed all tests!

Question 2

Correct

Marked out of 1.00

Flag question

Write a Java program to compare two sets and retain elements that are the same.

Sample Input and Output:

```
5
Football
Hockey
Cricket
Volleyball
Basketball
7 // HashSet 2:
Golf
Cricket
Badminton
Football
Hockey
Volleyball
Handball
```

SAMPLE OUTPUT:

```
Football
Hockey
Cricket
Volleyball
Basketball
```

Answer: (penalty regime: 0 %)

```
1 import java.util.HashSet;
```

```

2 import java.util.Scanner;
3 import java.util.Set;
4 public class SetIntersection {
5     public static void main(String[] args) {
6         Scanner sc = new Scanner(System.in);
7         Set<String> set1 = new HashSet<>();
8         Set<String> set2 = new HashSet<>();
9         int n1 = sc.nextInt();
10        sc.nextLine();
11        for (int i = 0; i < n1; i++) {
12            set1.add(sc.nextLine());
13        }
14        int n2 = sc.nextInt();
15        sc.nextLine();
16        for (int i = 0; i < n2; i++) {
17            set2.add(sc.nextLine());
18        }
19        set1.retainAll(set2);
20        for (String sport : set1) {
21            System.out.println(sport);
22        }
23        sc.close();
24    }
25 }

```

| Test | Input | Expected | Got |
|------|--|---|---|
| 1 | 5 Football Hockey Cricket Volleyball Basketball 7 Golf Cricket Badminton Football Hockey Volleyball Throwball | Cricket Hockey Volleyball Football Football | Cricket Hockey Volleyball Football |
| 2 | 4 Toy Bus Car Auto 3 Car Bus Lorry | Bus Car Car | Bus Car |

Passed all tests!

Question 3

Correct

Marked out of 1.00

Flag question

Java HashMap Methods

containsKey() Indicate if an entry with the specified key exists in the map

containsValue() Indicate if an entry with the specified value exists in the map

putIfAbsent() Write an entry into the map but only if an entry with the same key does not already exist

remove() Remove an entry from the map

replace() Write to an entry in the map only if it exists

size() Return the number of entries in the map

Your task is to fill the incomplete code to get desired output

Answer: (penalty regime: 0 %)

Reset answer

```

1 import java.util.HashMap;
2 import java.util.Map.Entry;
3 import java.util.Set;
4 import java.util.Scanner;
5 class prog {
6     public static void main(String[] args) {
7         HashMap<String, Integer> map = new HashMap<String, Integer>();
8         String name;
9         int num;
10        Scanner sc = new Scanner(System.in);
11        int n = sc.nextInt();
12        for (int i = 0; i < n; i++) {
13            name = sc.next();
14            num = sc.nextInt();
15            map.put(name, num);
16        }
17        Set<Entry<String, Integer>> entrySet = map.entrySet();
18        for (Entry<String, Integer> entry : entrySet) {
19            System.out.println(entry.getKey() + " : " + entry.getValue());
20        }
21        System.out.println("-----");
22        HashMap<String, Integer> anotherMap = new HashMap<String, Integer>();
23        anotherMap.put("SIX", 6);
24        anotherMap.put("SEVEN", 7);
25        anotherMap.putAll(map);
26        entrySet = anotherMap.entrySet();
27        for (Entry<String, Integer> entry : entrySet) {
28            System.out.println(entry.getKey() + " : " + entry.getValue());
29        }
30        map.putIfAbsent("FIVE", 5);
31        Integer value = map.get("TWO");
32        if (value != null) {
33            System.out.println(value);
34        } else {
35            System.out.println("Key 'TWO' not found in map.");
36        }
37        System.out.println(map.containsKey("ONE"));
38        System.out.println(map.containsValue(3));
39        System.out.println(map.size());
40    }
41 }

```

| Test | Input | Expected | Got |
|------|---|--|--|
| 1 | 3 ONE TWO : 2 THREE : 3 TWO ----- 2 THREE 3 SEVEN : 7 THREE : 3 2 true true 4 | ONE : 1 TWO : 2 THREE : 3 ----- SIX : 6 ONE : 1 TWO : 2 SEVEN : 7 THREE : 3 THREE : 3 2 true true 4 | ONE : 1 TWO : 2 THREE : 3 ----- SIX : 6 ONE : 1 TWO : 2 SEVEN : 7 THREE : 3 THREE : 3 2 true true 4 |

Passed all tests!

