SALES

PIZZA HUT SALES

SALES ANALYSIS USING SQL



PIZZA HUT

Contact

SALES ANALYSIS USING SQL

TURNING SALES DATA INTO BUSINESSINSIGHTS

THIS PROJECT FOCUSES ON ANALYZING PIZZA HUT SALES DATA USING MYSQL TO UNDERSTAND SALES PERFORMANCE,CUSTOMER ORDERING PATTERNS AND PRODUCT PREFERENCES

USING SQL QUERIES, THE DATASET IS EXPLORED TO IDENTIFY MEANINGFUL BUSINESS INSIGHTS AND SUPPORTS DATA-DRIVEN DECISION-MAKING



Presented by: MOHAN

PIZZA HUT
analysis

RETRIEVE THE TOTAL NUMBER OF ORDERS PLACED.


```
SELECT
    COUNT(order_id) as total_orders
FROM
    orders;
```

Result Grid

	total_orders
▶	21350

PIZZA HUT
analysis

CALCULATE THE TOTAL REVENUE GENERATED FROM PIZZA SALES.


```sql
SELECT
    ROUND(SUM(p.price * od.quantity), 2) AS Total_Revenue
FROM
    pizzas AS p
        JOIN
    order_details AS od ON p.pizza_id = od.pizza_id;
```

Result Grid

Total_Revenue
817860.05

PIZZA HUT
analysis

IDENTIFY THE HIGHEST-PRICED PIZZA


```sql
SELECT
    pt.name, p.price
FROM
    pizza_types as pt
    join pizzas as p
    on pt.pizza_type_id = p.pizza_type_id
ORDER BY price DESC
LIMIT 1;
```

Result Grid | Filter Rows

	name	price
▶	The Greek Pizza	35.95

PIZZA HUT
analysis

IDENTIFY THE MOST COMMON PIZZA SIZE ORDERED


```sql
SELECT p.size ,count(od.order_details_id) as comon_pizza_ordered
from pizzas as p
join order_details as od
on p.pizza_id = od.pizza_id
group by p.size order by comon_pizza_ordered desc;
```

Result Grid | Filter Rows:

size	comon_pizza_ordered
L	18526
M	15385
S	14137
XL	544
XXL	28

PIZZA HUT
analysis

LIST THE TOP 5 MOST ORDERED PIZZA TYPES ALONG WITH THEIR QUANTITIES.


```sql
select p.pizza_type_id, sum(od.quantity) as most_ordered
from pizzas as p
join order_details as od
on p.pizza_id = od.pizza_id
group by p.pizza_type_id
order by most_ordered desc
limit 5;
```

Result Grid | Filter Rows:

pizza_type_id	most_ordered
classic_dlx	2453
bbq_ckn	2432
hawaiian	2422
pepperoni	2418
thai_ckn	2371

PIZZA HUT
analysis

FIND THE TOTAL QUANTITY OF EACH PIZZA CATEGORY ORDERED.


```sql
SELECT pt.category , sum(od.quantity) total_quantity
from pizza_types as pt
join pizzas as p
on p.pizza_type_id = pt.pizza_type_id
join order_details as od
on p.pizza_id = od.pizza_id
group by pt.category
order by total_quantity desc;
```

Result Grid | Filter Rows:

category	total_quantity
Classic	14888
Supreme	11987
Veggie	11649
Chicken	11050

PIZZA HUT
analysis

DETERMINE THE DISTRIBUTION OF ORDERS BY HOUR OF THE DAY.


```
SELECT
    HOUR(order_time), COUNT(order_id) AS orders
FROM
    orders
GROUP BY HOUR(order_time)
ORDER BY orders DESC;
```

Result Grid | Filter Rows:

HOUR(order_time)	orders
19	2009
16	1920
20	1642
14	1472
15	1468
11	1231
21	1198

FIND THE CATEGORY-WISE DISTRIBUTION OF PIZZAS.


```sql
SELECT category, COUNT(pizza_type_id)
FROM  pizza_types
GROUP BY category;
```

Result Grid | Filter Rows:

category	COUNT(pizza_type_id)
Chicken	6
Classic	8
Supreme	9
Veggie	9

PIZZA HUT
analysis

CALCULATE THE AVERAGE NUMBER OF PIZZAS ORDERED PER DAY.


```
select round(avg(quantity),2)  as avg_pizzas_sales from
( select o.order_date , sum(od.quantity) as quantity from orders as o
 join order_details as od
 on o.order_id = od.order_id
 group by o.order_date
 ) as order_qty;
```

Result Grid

	avg_pizzas_sales
▶	138.47

PIZZA HUT
analysis

DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE.


```sql
select  p.pizza_type_id , sum(p.price* od.quantity) as revenue
from pizzas as p
join order_details as od
on p.pizza_id = od.pizza_id
group by p.pizza_type_id
order by revenue desc
limit 3;
```

Result Grid | Filter Rows:

pizza_type_id	revenue
thai_ckn	43434.25
bbq_ckn	42768
cali_ckn	41409.5

PIZZA HUT
analysis

CALCULATE THE PERCENTAGE CONTRIBUTION OF EACH PIZZA TYPE TO TOTAL REVENUE.


```sql
SELECT
    pt.category,
    ROUND (SUM(od.quantity * p.price) /
        (SELECT SUM(od.quantity * p.price)
         FROM order_details od
         JOIN pizzas p
         ON p.pizza_id = od.pizza_id) * 100,
        2
    ) AS revenue
FROM pizza_types pt
JOIN pizzas p
    ON pt.pizza_type_id = p.pizza_type_id
JOIN order_details od
    ON od.pizza_id = p.pizza_id
GROUP BY pt.category
ORDER BY revenue ;
```

Result Grid | Filter Rows:

category	revenue
Veggie	23.68
Chicken	23.96
Supreme	25.46
Classic	26.91

PIZZA HUT
analysis

ANALYZE THE CUMULATIVE REVENUE GENERATED OVER TIME.


```sql
select order_date,
sum(revenue) over(order by order_date) as cum_revenue
from
(select o.order_date,
sum(od.quantity * p.price) as revenue
from order_details
od
join pizzas as p
on od.pizza_id = p.pizza_id
join orders as o
on o.order_id = od.order_id
group by o.order_date) as sales;
```

Result Grid | Filter Rows:

order_date	cum_revenue
2015-01-01	2713.8500000000004
2015-01-02	5445.75
2015-01-03	8108.15
2015-01-04	9863.6
2015-01-05	11929.55
2015-01-06	14358.5
2015-01-07	16560.7
2015-01-08	19399.05
2015-01-09	21526.4
2015-01-10	23990.350000000002

PIZZA HUT
analysis

DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE FOR EACH PIZZA CATEGORY.


```sql
select name,revenue from
(select category,name, revenue,
rank() over( partition by category order by revenue desc) as rn
from
(select pt.category, pt.name,
sum((od.quantity)* p.price) as revenue
from pizza_types as pt
join pizzas as p
on pt.pizza_type_id = p.pizza_type_id
join order_details as od
on od.pizza_id = p.pizza_id
group by pt.category, pt.name) as a) as b
where rn <=3;
```

Result Grid | Filter Rows:

name	revenue
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5
The Classic Deluxe Pizza	38180.5
The Hawaiian Pizza	32273.25
The Pepperoni Pizza	30161.75

SUCCESSFULLY ANALYZED PIZZA HUT SALES DATA USING MYSQL TO IDENTIFY SAKES TRENDS AND PERFORMANCE PATTERNS

TECHNICAL SKILLS

MYSQL
SQL JOINS
AGGREGATIONS
SUBQUERIES
CTES
WINDOW FUNCTIONS

THANK YOU

PRESENTED BY: MOHAN