C1 BTS
C1 Chicago
C1 Online
C2 BTS
C2 Chicago
C2 Online
C3 BTS
C3 Chicago
C3 Online
C4 BTS
C4 Chicago
C4 Online
C5 BTS
C5 Chicago
C5 Online
default
defect_rate: 10%
defect_rate: 20%
defect_rate: 3%
defect_rate: 5%
history_window: window 10
history_window: window 3
history_window: window 8
outlier_sigma: 3-5 sd (mild)
outlier_sigma: 5-8 sd
outlier_sigma: 8-12 sd (severe)
range_k: k = 2.5
range_k: k = 3.5
range_k: k = 4
calibration_z: z = 2
calibration_z: z = 2.5
calibration_z: z = 3.5
calibration_z: z = 4
drift_alpha: alpha = 0.01
drift_alpha: alpha = 0.025
drift_alpha: alpha = 0.1
drift_alpha: alpha = 0.2
risk_thresholds: high = 0.4
risk_thresholds: high = 0.6
risk_thresholds: moderate = 0.1
risk_thresholds: moderate = 0.3
risk_thresholds: very_high = 0.6
risk_thresholds: very_high = 0.9
risk_weights: D removed
risk_weights: D x0.5
risk_weights: D x2
risk_weights: F removed
risk_weights: F x0.5
risk_weights: F x2
risk_weights: H removed
risk_weights: H x0.5
risk_weights: H x2
risk_weights: I removed
risk_weights: I x0.5
risk_weights: I x2
risk_weights: S removed
risk_weights: S x0.5
risk_weights: S x2
risk_weights: equal (0.2 each)
C1: H1a: adaptive FPR < fixed_pooled under drift
C2: H1a: recall non-inferior to fixed_pooled under drift
C3: adaptive FPR <= best calibrated rolling baseline under drift
C4: H1b: proposed macro-F1 >= gated_fixed_pooled
C5: H3: risk selection useful in sustained degradation (C, D)