Name: Moheet Dialani
Roll No. 2301028
Class: T13

EXPERIMENT NO.: 05

AIM:

To set up a Continuous Integration (CI) Pipeline using Jenkins and GitHub Actions for automatically building and testing an application.

THEORY:

Continuous Integration (CI) is a software development practice in which developers frequently integrate their code changes into a shared repository. Whenever new code is pushed to the repository, an automated CI pipeline can perform tasks such as building the application, running tests, and checking whether the code works correctly.

· Continuous Integration helps developers detect errors early.

· Developers push their source code to a version control system such as GitHub.

· A CI tool automatically detects changes made to the source code repository.

· The application is automatically built and tested.

· If all tests are successful, the pipeline is marked as successful.

· If a build or test fails, the pipeline reports a failure.

· Jenkins and GitHub Actions are commonly used tools for implementing Continuous Integration.

Jenkins is an automation server that allows developers to create pipelines for building, testing, and deploying applications.

GitHub Actions is a CI/CD automation platform integrated directly with GitHub repositories. Workflows can automatically run when events such as a code push or pull request occur.

A typical Continuous Integration process is represented as:

Developer
↓
Push Code to GitHub

Name: Moheet Dialani
Roll No. 2301028
Class: T13

↓
CI Pipeline Triggered
↓
Install Dependencies
↓
Build Application
↓
Run Tests
↓
Success / Failure Report

Network / Software Setup

Components Required

· Computer/Laptop

· Jenkins

· Git

· GitHub Account

· Node.js Application (Test Application)

· Internet Connection

· GitHub Repository

Sample Application Structure

test-application/
│
├── package.json
├── index.js
├── test/

Name: Moheet Dialani
Roll No. 2301028
Class: T13

```
│   └── app.test.js
│
├── Jenkinsfile
│
└── .github/
    └── workflows/
        └── ci.yml
```

Sample Application index.js

```
function add(a, b) {
return a + b;
}

module.exports = { add };
```

package.json

```
{
  "name": "jenkins-ci-demo",
  "version": "1.0.0",
  "scripts": {
    "test": "node test/app.test.js"
  }
}
```

test/app.test.js

```
const { add } = require("../index");
```

Name: Moheet Dialani
Roll No. 2301028
Class: T13

```
if (add(2, 3) !== 5) {
console.error("Test Failed!");
process.exit(1);
}

console.log("Test Passed Successfully!");
```

Jenkins Pipeline Setup

Jenkinsfile

Create a file named Jenkinsfile in the root directory of the project.

```
pipeline {
agent any

   stages {

      stage('Checkout') {
steps {
checkout scm
         }
      }

      stage('Install Dependencies') {
steps {            sh 'npm install'
         }
      }

      stage('Run Tests') {
steps {            sh
'npm test'
         }
      }
```

Name: Moheet Dialani
Roll No. 2301028
Class: T13

```
        stage('Build Status') {            steps {                echo 'Continuous
Integration Pipeline Completed Successfully!'
            }
        }
    }
}
```

The Jenkins pipeline performs the following operations:

Checkout Source Code
↓
Install Dependencies
↓
Run Tests
↓
Generate Build Status

GitHub Actions Setup

Create the following directory structure:

.github/workflows/

Inside the workflows folder, create a file named:

ci.yml

GitHub Actions Workflow

```
name: Continuous Integration

on:  push:
branches:
- main
```

Name: Moheet Dialani
Roll No. 2301028
Class: T13

```
  pull_request:
branches:
- main

jobs:  build-and-
test:

    runs-on: ubuntu-latest

    steps:

- name: Checkout Repository
  uses: actions/checkout@v4

- name: Setup Node.js          uses:
  actions/setup-node@v4

- name: Install Dependencies
  run: npm install

- name: Run Tests          run: npm test
```

The GitHub Actions workflow is automatically triggered when:

· Code is pushed to the main branch.

· A pull request is created for the main branch.

Procedure

1. Open the computer and ensure that Git, Jenkins, and Node.js are installed.
2. Create a simple test application.
3. Create the required project files such as index.js, package.json, and the test file.
4. Test the application locally using:

```
npm test
```

Name: Moheet Dialani
Roll No. 2301028
Class: T13

5. Create a GitHub repository for the application.

6. Initialize the local project as a Git repository.

git init

7. Add the project files to Git.

git add .

8. Commit the source code.

git commit -m "Initial CI application"

9. Connect the local repository to GitHub.

10. Push the project to the GitHub repository.

Jenkins Configuration Procedure

11. Start the Jenkins server.

12. Open Jenkins in a web browser.

http://localhost:8080

13. Click on **New Item**.

14. Enter a name for the project.

Example:

CI-Pipeline-Demo

Name: Moheet Dialani
Roll No. 2301028
Class: T13

15. Select **Pipeline** as the project type.

16. Click **OK**.

17. In the Pipeline configuration, select:

Pipeline script from SCM

18. Select:

Git

as the Source Code Management system.

19. Enter the GitHub repository URL.

20. Select the required branch, such as:

*/main

21. Enter the script path:

Jenkinsfile

22. Save the pipeline configuration.

23. Click **Build Now** to execute the Jenkins pipeline.

24. Observe the different stages of the Jenkins pipeline.

GitHub Actions Procedure

25. Create a .github/workflows directory in the project repository.

26. Create the GitHub Actions workflow file named:

ci.yml

Name: Moheet Dialani
Roll No. 2301028
Class: T13

27. Add the Continuous Integration workflow configuration.

28. Commit and push the workflow file to GitHub.

git add .
git commit -m "Add CI workflow" git
push origin main

29. Open the GitHub repository.

30. Navigate to the **Actions** tab.

31. Observe the automatically triggered workflow.

32. Verify the following CI stages:

Checkout Repository
↓
Setup Node.js
↓
Install Dependencies
↓
Run Tests


CI Pipeline Observation

Step	CI Stage	Operation	Observation
1	Source Code	Code pushed to GitHub	Repository receives updated source code
2	Pipeline Trigger	Jenkins/GitHub Actions starts	CI process begins automatically or manually
3	Checkout	Source code is downloaded	Latest version of application is obtained
4	Dependencies	Required packages are installed	Application environment is prepared
5	Testing	Automated tests are executed	Application functionality is verified

Name: Moheet Dialani
Roll No. 2301028
Class: T13

6	Result	Pipeline status generated	Build is marked as Success or Failure

Continuous Integration Workflow



Expected Result

· The application source code is successfully stored in the GitHub repository.

· Jenkins successfully checks out the source code.

Name: Moheet Dialani
Roll No. 2301028
Class: T13

· The CI pipeline installs the required dependencies.

· Automated tests are executed successfully.

· Jenkins displays the status of the pipeline.


· GitHub Actions automatically runs the CI workflow after a push or pull request.

· The workflow status is displayed as either successful or failed.


Screenshot:



Name: Moheet Dialani
Roll No. 2301028
Class: T13




Name: Moheet Dialani
Roll No. 2301028
Class: T13




Name: Moheet Dialani
Roll No. 2301028
Class: T13





Name: Moheet Dialani
Roll No. 2301028
Class: T13



Result:

The Continuous Integration Pipeline was successfully set up using Jenkins and GitHub Actions. The application source code was automatically checked out, dependencies were installed, and automated tests were executed. The pipeline successfully reported the build status.

CONCLUSION:

Thus, a Continuous Integration Pipeline was successfully implemented using Jenkins and GitHub Actions. The experiment demonstrated how source code changes can be automatically integrated, built, and tested using a CI pipeline. This process helps identify errors early and improves the reliability and quality of software development.