MindVault Operations Runbook: Incident Management and Disaster Recovery
Document Identifier: MV-DOC-03 | Version: 4.0 | Classification: Operational Runbook
==========

Section 1: Incident Severity Definitions
Incidents are classified into four tiers: Sev-1 (Complete cluster degradation or data unavailability), Sev-2 (Major performance degradation exceeding SLA), Sev-3 (Non-blocking component failure), and Sev-4 (Inquiry Tier-1 on-call manages Sev-1 triage and coordinates emergency operational response.

Section 2: Disaster Recovery Objectives and Failover Triggers
Disaster Recovery Target: Recovery Point Objective (RPO) < 1 minute; Recovery Time Objective (RTO) < 15 minut Automatic primary failover engages when replica lag exceeds 5000ms. If primary database becomes unresponsive, health probes initiate automatic promotion of the hot standby replica.

Section 3: Service Level Agreements (SLAs)
SLA mandates p99 retrieval latency < 150ms and initial token dispatched < 2000ms. If retrieval exceeds the 150ms boundary, alerts trigger priority auto-scaling.

Section 4: Ingestion Pipeline Queues and Dead-Letter Policies
Queue timeout triggers 3 retries then DLQ. Status COMPLETED triggers NotificationService WebSocket and schedu GraphExtractionTask for background entity resolution.