

# Session - Agent Development Kit

Source URL: <https://google.github.io/adk-docs/sessions/session/>

---

## Session: Tracking Individual Conversations

Following our Introduction, let's dive into the `Session`. Think back to the idea of a "conversation thread." Just like you wouldn't start every text message from scratch, agents need context regarding the ongoing interaction. `Session` is the ADK object designed specifically to track and manage these individual conversation threads.

### The `Session` Object

When a user starts interacting with your agent, the `SessionService` creates a `Session` object (`google.adk.sessions.Session`). This object acts as the container holding everything related to that *one specific chat thread*. Here are its key properties:

- **Identification ( `id` , `appName` , `userId` )**: Unique labels for the conversation.
- `id`: A unique identifier for *this specific* conversation thread, essential for retrieving it later. A `SessionService` object can handle multiple `Session` (s). This field identifies which particular session object are we referring to. For example, "test\_id\_modification".
- `app_name`: Identifies which agent application this conversation belongs to. For example, "id\_modifier\_workflow".
- `userId`: Links the conversation to a particular user.
- **History ( `events` )**: A chronological sequence of all interactions ( `Event` objects – user messages, agent responses, tool actions) that have occurred within this specific thread.
- **Session State ( `state` )**: A place to store temporary data relevant *only* to this specific, ongoing conversation. This acts as a scratchpad for the agent during the interaction. We will cover how to use and manage `state` in detail in the next section.

- **Activity Tracking ( `lastUpdateTime` )**: A timestamp indicating the last time an event occurred in this conversation thread.

## Example: Examining Session Properties

PythonJava

```
from google.adk.sessions import InMemorySessionService, Session

# Create a simple session to examine its properties
temp_service = InMemorySessionService()
example_session = await temp_service.create_session(
    app_name="my_app",
    user_id="example_user",
    state={"initial_key": "initial_value"} # State can be initialized
)

print(f"--- Examining Session Properties ---")
print(f"ID (`id`): {example_session.id}")
print(f"Application Name (`app_name`): {example_session.app_name}")
print(f"User ID (`user_id`): {example_session.user_id}")
print(f"State (`state`): {example_session.state}") # Note:
print(f"Events (`events`): {example_session.events}") # Initial
print(f>Last Update (`last_update_time`): {example_session.last_update_time}")
print(f"-----")

# Clean up (optional for this example)
temp_service = await temp_service.delete_session(app_name=example_session.app_name,
                                                  user_id=example_session.user_id, session_id=example_session.id)
print("The final status of temp_service - ", temp_service)
```

```
import com.google.adk.sessions.InMemorySessionService;
import com.google.adk.sessions.Session;
import java.util.concurrent.ConcurrentMap;
import java.util.concurrent.ConcurrentHashMap;
```

```

String sessionId = "123";
String appName = "example-app"; // Example app name
String userId = "example-user"; // Example user id
ConcurrentMap<String, Object> initialState = new ConcurrentHashMap<>()
InMemorySessionService exampleSessionService = new InMemorySessionSer

// Create Session
Session exampleSession = exampleSessionService.createSession(
    appName, userId, initialState, Optional.of(sessionId)).blockingGet()
System.out.println("Session created successfully.");

System.out.println("--- Examining Session Properties ---");
System.out.printf("ID (`id`): %s\n", exampleSession.id());
System.out.printf("Application Name (`appName`): %s\n", exampleSession.appName());
System.out.printf("User ID (`userId`): %s\n", exampleSession.userId());
System.out.printf("State (`state`): %s\n", exampleSession.state());
System.out.println("-----");

// Clean up (optional for this example)
var unused = exampleSessionService.deleteSession(appName, userId, sessionId);

```

*(Note: The state shown above is only the initial state. State updates happen via events, as discussed in the State section.)*

## Managing Sessions with a `SessionService` ¶

As seen above, you don't typically create or manage `Session` objects directly. Instead, you use a `SessionService`. This service acts as the central manager responsible for the entire lifecycle of your conversation sessions.

Its core responsibilities include:

- **Starting New Conversations:** Creating fresh `Session` objects when a user begins an interaction.

- **Resuming Existing Conversations:** Retrieving a specific `Session` (using its ID) so the agent can continue where it left off.
- **Saving Progress:** Appending new interactions ( `Event` objects) to a session's history. This is also the mechanism through which session `state` gets updated (more in the `State` section).
- **Listing Conversations:** Finding the active session threads for a particular user and application.
- **Cleaning Up:** Deleting `Session` objects and their associated data when conversations are finished or no longer needed.

## SessionService Implementations

ADK provides different `SessionService` implementations, allowing you to choose the storage backend that best suits your needs:

1. **InMemorySessionService**
2. **How it works:** Stores all session data directly in the application's memory.
3. **Persistence:** None. **All conversation data is lost if the application restarts.**
4. **Requires:** Nothing extra.
5. **Best for:** Quick development, local testing, examples, and scenarios where long-term persistence isn't required.

PythonJava

```
''' from google.adk.sessions import InMemorySessionService session_service
= InMemorySessionService()
```

```
'''
```

```
''' import com.google.adk.sessions.InMemorySessionService;
InMemorySessionService exampleSessionService = new
InMemorySessionService();
```

```
`` 2. ** VertexAiSessionService`**
```

- **How it works:** Uses Google Cloud's Vertex AI infrastructure via API calls for session management.

- **Persistence:** Yes. Data is managed reliably and scalably via [Vertex AI Agent Engine](#).
- **Requires:**
  - A Google Cloud project ( `pip install vertexai` )
  - A Google Cloud storage bucket that can be configured by this [step](#).
  - A Reasoning Engine resource name/ID that can setup following this [tutorial](#).
- **Best for:** Scalable production applications deployed on Google Cloud, especially when integrating with other Vertex AI features.

PythonJava

```

`` # Requires: pip install google-adk[vertexai] # Plus GCP setup and
authentication from google.adk.sessions import VertexAiSessionService

PROJECT_ID = "your-gcp-project-id" LOCATION = "us-central1" # The
app_name used with this service should be the Reasoning Engine ID or name
REASONING_ENGINE_APP_NAME = "projects/your-gcp-project-id/locations/
us-central1/reasoningEngines/your-engine-id"

session_service = VertexAiSessionService(project=PROJECT_ID,
location=LOCATION) # Use REASONING_ENGINE_APP_NAME when calling
service methods, e.g.: # session_service = await
session_service.create_session(app_name=REASONING_ENGINE_APP_NAME, ...)

...

`` // Please look at the set of requirements above, consequently export the
following in your bashrc file: // export
GOOGLE_CLOUD_PROJECT=my_gcp_project // export
GOOGLE_CLOUD_LOCATION=us-central1 // export
GOOGLE_API_KEY=my_api_key

import com.google.adk.sessions.VertexAiSessionService; import java.util.UUID;

String sessionId = UUID.randomUUID().toString(); String
reasoningEngineAppName = "123456789"; String userId = "u_123"; // Example
user id ConcurrentHashMap initialState = new ConcurrentHashMap<>(); // No initial
state needed for this example

```

```
VertexAiSessionService sessionService = new VertexAiSessionService();
Session mySession =
sessionService .createSession(reasoningEngineAppName, userId, initialState,
Optional.of(sessionId)) .blockingGet();
```

```
` ` 3.  ** DatabaseSessionService` **
```

Currently supported in [Python](#)

- **How it works:** Connects to a relational database (e.g., PostgreSQL, MySQL, SQLite) to store session data persistently in tables.
- **Persistence:** Yes. Data survives application restarts.
- **Requires:** A configured database.
- **Best for:** Applications needing reliable, persistent storage that you manage yourself.

```
''' from google.adk.sessions import DatabaseSessionService # Example using
a local SQLite file: db_url = "sqlite:///./my_agent_data.db" session_service =
DatabaseSessionService(db_url=db_url)
```

```
'''
```

Choosing the right `SessionService` is key to defining how your agent's conversation history and temporary data are stored and persist.

## The Session Lifecycle

Session lifecycle

Here's a simplified flow of how `Session` and `SessionService` work together during a conversation turn:

1. **Start or Resume:** Your application's `Runner` uses the `SessionService` to either `create_session` (for a new chat) or `get_session` (to retrieve an existing one).
2. **Context Provided:** The `Runner` gets the appropriate `Session` object from the appropriate service method, providing the agent with access to the corresponding Session's `state` and `events`.

3. **Agent Processing:** The user prompts the agent with a query. The agent analyzes the query and potentially the session `state` and `events` history to determine the response.
4. **Response & State Update:** The agent generates a response (and potentially flags data to be updated in the `state`). The `Runner` packages this as an `Event`.
5. **Save Interaction:** The `Runner` calls `sessionService.append_event(session, event)` with the `session` and the new `event` as the arguments. The service adds the `Event` to the history and updates the session's `state` in storage based on information within the event. The session's `last_update_time` also get updated.
6. **Ready for Next:** The agent's response goes to the user. The updated `Session` is now stored by the `SessionService`, ready for the next turn (which restarts the cycle at step 1, usually with the continuation of the conversation in the current session).
7. **End Conversation:** When the conversation is over, your application calls `sessionService.delete_session(...)` to clean up the stored session data if it is no longer required.

This cycle highlights how the `SessionService` ensures conversational continuity by managing the history and state associated with each `Session` object.