



KEY PARTNERS

8

Government & PSUs:
ALIMCO (Manufacturing & Quality), Ministry of Social Justice & Empowerment (ADIP Tender).

Disability NGOs:
National Association for the Blind (NAB), Blind People's Association (Field Trial Partners).

Production & Hardware:
Tier-1 PCB & SMT Assembly (JLCPCB / Local EMS), Carbon Fiber composite molders.

Clinical Validation:
National Institute for the Visually Handicapped (NIVH) Dehradun.

Strategic MoUs pre-aligned for mass deployment.

KEY ACTIVITIES

7

RTOS Firmware: 50ms deterministic safety loop arbitration & watchdog maintenance.

Edge AI Optimization: Int8 MobileNet & YOLO- Fastest training on Indian street datasets.

Statutory Certifications: ISO 11334-1 walking aids & IEC 62366 usability testing.

KEY RESOURCES

6

IP & CAD Assets: 52-component custom modular chassis & injection mold tooling designs.

Testing Infrastructure: RVCE Assistive Lab & multi-sensor testing benches.

Interdisciplinary Team: Embedded firmware, mechanical CAD, Edge ML & MedTech experts.

VALUE PROPOSITIONS

2

100% Fail-Safe Independence:
No smartphone app required. Reflex loop prevents high-hanging branch hits & EV collisions within 50ms.

Ears-Free Bone Conduction:
Sub-15ms directional palm haptics + bone conduction audio keep ear canals completely open for traffic.

Autonomous Direct-AT 112 SOS:
Cellular LTE voice call + live GPS SMS without needing an unlocked phone.

75% Cost Disruption (ADIP Ready):
Scales to ₹8,500 (vs ₹50,000 WeWALK), enabling 100% free distribution under Government ADIP scheme.

"True Dignity, Safety & Independence for 1.2 Crore PwDs"

CUSTOMER RELATIONSHIPS

4

NGO Trust & Training: Free user orientation camps with NAB certified mobility trainers.

Modular Snap-Repair: District-level replaceable tip/battery parts via DDRC centers.

Over-The-Air Upgrades: LTE automated firmware updates with zero user intervention.

CHANNELS

3

ADIP Govt. Camps: 70% bulk channel via Ministry & ALIMCO distribution drives.

Corporate CSR Grants: 20% funded distribution via Tata, Infosys & Reliance CSR.

Direct-to-Consumer Portal: Subsidized web store with assistive screen-reader UI.

CUSTOMER SEGMENTS

1

Primary Users (1.2 Crore):
Visually impaired & low-vision individuals in India needing independent outdoor navigation.

Geriatric Population:
Elderly citizens with combined visual deterioration & balance instability (helped by motorized tip).

Institutional Buyers:
Special schools, vocational blind rehabilitation centers, state welfare departments.

Caregivers & Families:
Seek peace of mind with real-time GPS tracking & automated fall detection alerts.

Total Addressable Market: ₹9,600 Cr in India alone.

COST STRUCTURE

9

BOM (Scale):
₹8,500 per cane (Electronic ICs: 60%, Mechanics & Carbon: 25%, Assembly: 15%).

Tooling & Molds:
₹12 Lakhs fixed one-time expenditure for polycarbonate injection molds.

Cloud & SIM Data:
₹15/month per device for emergency SMS & telemetry via BSNL/Airtel M2M SIMs.

Certification & QA:
₹3 Lakhs for NABL testing, EMI/EMC compliance & drop-shock durability testing.

REVENUE STREAMS

5

70% ADIP Bulk Tenders:
Government procurement at ₹9,990/unit (within ADIP aid limit).

20% CSR Sponsorships:
Corporates adopt blind schools & rural districts for free distribution.

7% Direct Retail Sales:
Subsidized direct sales to middle/higher income PwDs at ₹11,999.

3% Modular Accessories:
Replaceable rubber treads, bone-conduction bands, extra battery modules.



MARKET SIZING (TAM/SAM/SOM)

INDIA DATA

TAM (Total Addressable Market)

₹9,600 Cr

1.2 Crore visually impaired individuals in India × ₹8,000 average device lifecycle value.
Home to 20% of world's blind population.

SAM (Serviceable Addressable)

₹2,400 Cr

30 Lakh active commuters (students, working professionals & urban PwDs) navigating complex roads daily.

SOM (Obtainable 3-Yr Horizon)

₹480 Cr

6 Lakh units captured across 3 consecutive annual Government ADIP tenders & Tier-1 CSR distribution campaigns.

IN KEY DEMOGRAPHIC STATISTICS (WHO & NPCB):

- **<2% Access Rate:** Only 1.8% of blind individuals in India currently possess any assistive electronic aid.
- **High Economic Loss:** Estimated ₹1.1 Lakh Crore annual GDP loss due to reduced workforce participation of visually impaired.
- **Urban Hazard Index:** 78% of visually impaired individuals report head-level injuries at least once every month.



Aligned with National Education Policy (NEP) & Sugamya Bharat Abhiyan goals.



PRIMARY USER SURVEY INSIGHTS

N = 72 PwDs

Conducted in partnership with Bangalore blind schools & National Association for the Blind (NAB).

1. Head-Level Hanging Obstacles

92% Suffer Injuries

Low tree branches, shop awnings & open truck beds completely missed by traditional cane.

2. Silent Electric Vehicles & Scooters

86% Report Fear

EVs lack engine acoustic rumble; users unable to detect approaching vehicles in quiet streets.

3. Earphones Blocking Traffic Sounds

89% Reject Earbuds

Existing smart canes require phone earphones that plug the ear canal—considered a death trap.

4. Sudden Puddles & Muddy Slipping

79% Experience Slips

Monsoon potholes & standing dirty water cannot be sensed before shoes step in.

5. Phone App Crashes & Bluetooth Lag

74% Discard Apps

Smartphones overheat, disconnect BLE, or drain battery within 4 hours outdoors.

Direct Validation: Our 6 innovations solve the top 5 survey complaints directly.



PRIMARY USER PERSONA

REAL PROFILE



Ramesh Kumar (Age: 27)

Bank PO Candidate & Daily Commuter
Bangalore, Karnataka • 100% Blindness



Daily Routine & Goals:

Navigates 3.5 km daily via metro feeder buses, crowded footpaths, and overhead flyover construction zones to reach training center.



Daily Fears & Pain Points:

"I hit low hanging construction scaffolding at forehead level twice last month. Electric scooters zoom past from behind with zero sound. If my phone battery dies, I feel completely helpless."



How Our Cane Empowers Ramesh:

Dual Camera AI detects hanging beams 3 meters ahead; bone conduction headphone warns him without blocking traffic; direct I12 SOS allows emergency calling with one recessed button press.

Impact: Empowers Ramesh to secure employment with 100% outdoor travel independence.



🏆 COMPREHENSIVE 10-POINT TECHNICAL & COMMERCIAL BENCHMARK

CORE PARAMETER / FEATURE	STANDARD WHITE CANE	ULTRACANE (UK IMPORT)	WEWALK (TURKEY / US)	SMART CANE (TEAM VISIONAI)
Retail & Deployment Cost	₹300	₹65,000 (\$780)	₹50,000 (\$600)	₹8,500 (Scale) / FREE via ADIP
Smartphone Independence	N/A (Passive)	✅ Independent	❌ 100% Phone Dependent	✅ 100% Autonomous Dual-Core
Reflex Loop Safety Latency	N/A	150ms (Ultrasound only)	400–800ms (Phone BLE Lag)	⚡ 50ms Deterministic FreeRTOS
Ground & Pothole Sensing	Manual Tap Only	❌ No ground drop sensing	❌ No pothole/water sensor	✅ ST Laser ToF (50Hz) + Puddle Pins
Head-Level Obstacle AI	❌ Complete Blindspot	⚠️ Ultrasound narrow beam	⚠️ Single ultrasonic sensor	✅ Dual Camera AI + Ultrasonic
Audio HMI & Ear Safety	None	Tactile buzz only	❌ Earbuds plug ear canals	✅ Bone Conduction (Ears 100% Free)
Autonomous Emergency SOS	❌ None	❌ None	⚠️ Needs phone data app	📶 SIM7600G Direct-AT II2 + GPS
Rough Incline Terrain Tip	Rigid plastic tip	Rolling ball only	Rigid standard tip	🌀 Motorized Quad-Pod Auto-Deploy
Continuous Battery Life	Infinite (Mechanical)	8–10 Hours	12–15 Hours	🔋 36+ Hours (6800mAh 1S2P Pack)
Govt ADIP Scheme Eligibility	✅ Eligible	❌ Cost exceeds ceiling	❌ Ineligible import	✅ 100% Eligible (<₹10,000 ceiling)

🏠 ADIP SCHEME ECONOMIC FIT

Zero Out-Of-Pocket User Cost

Under DEPwD’s ADIP Scheme, assistive equipment up to ₹10,000 is 100% subsidized for BPL PwDs. Our ₹8,500 production price fits squarely under this ceiling, enabling ALIMCO to disburse thousands of units with zero financial burden on beneficiaries.

100% Direct Government Funding Path

🏥 HEALTHCARE ACCIDENT SAVINGS

₹42,000 Saved Per Fall Averted

Average cost of hospitalization, orthopedic plaster, and head-trauma scans in India is ₹42,000 per serious fall. By reducing falls by 85% through active ground laser ToF & haptic alerts, one device pays for itself in avoided healthcare expenses within 3 months.

ROI: 494% First-Year Healthcare Savings

🏠 NATIONAL PRODUCTIVITY GAIN

₹1.8 Lakh Annual Income Potential

Enabling an unemployed visually impaired individual to travel independently to bank PO jobs, call centers, or higher education institutions unlocks an average starting annual salary of ₹1.8–2.4 Lakhs—transforming dependent citizens into productive contributors.

21x Annual Economic Multiplier



52-PART CAD EXPLODED ENGINEERING VALIDATION

BLENDER 5.2 & SOLIDWORKS

HANDLE (23 PARTS)

HMI CORE

- OV5647 5MP Camera (1080p)
- SPH0645LM4H 3-Mic Array
- DRV2605L LRA Palm Haptic
- MAX30102 PPG Biosensor
- MAX98357A Bone-Conduction
- 4-Key Braille + Guarded SOS

Joint J1: 12-Pin Pogo Twist-Lock

SHAFT (13 PARTS)

COMPUTE CORE

- ESP32-S3 (50ms Safety Core)
- RPi Zero 2 W (YOLO AI)
- SIM7600G LTE & Multi-GNSS
- IS2P 6800mAh Panasonic Pack
- TI BQ25895 Fast PMIC
- 3K Aviation Carbon Fiber

Joint J2: Quick Snap Connector

TIP (16 PARTS)

TERRAIN CORE

- ST VL53LIX Laser ToF (50Hz)
- JSN-SR04T Waterproof Sonar
- Bosch BMI270 6-Axis IMU
- Galvanic Gold Puddle Pins
- N20 Metal Gear Lead-Screw
- Articulated 4-Leg Quad-Pod

High-Wear Vulcanized Rubber Foot

HANDLE SUBSYSTEM

₹4,150

23 Custom Parts • HMI & Audio

SHAFT SUBSYSTEM

₹9,105

13 Custom Parts • Dual AI & LTE

TIP SUBSYSTEM

₹3,075

16 Custom Parts • ToF & Quad-Pod

Total Prototype BOM: ₹16,330

Volume Scale BOM (10k units): ₹8,500

Total Weight: 420g Carbon Fiber

LIVE VERIFICATION LINKS

ONLINE



Interactive 3D Web CAD Explorer

LIVE

Explore assembled model, 52-part exploded animations & technical BOM specs in interactive WebGL.

<https://smartcane-3d-viewer.vercel.app/>



Firmware & Circuit Schematics

GITHUB

ESP32-S3 FreeRTOS code, Raspberry Pi Zero YOLO inference scripts & KiCAD differential PC schematics.

github.com/MohithGowda2807/SmartCane

All code & 3D models open for evaluator peer review.



HARDWARE BENCH TESTING RESULTS

LAB DATA

Reflex Loop Latency: FreeRTOS deterministic cycle48.2 ms (<50ms Target)

Haptic Actuation: DRV2605L linear resonant motor13.8 ms (<15ms Target)

Battery Endurance: Continuous active sensor loop37.4 Hours (6800mAh)

Direct-AT SOS Dispatch: SIM7600G 112 dial latency4.2 Seconds to Ring

Quad-Pod Deploy Time: N20 gear lead-screw stroke1.18 Seconds to Base

Empirical lab tests verify 100% adherence to technical specs.



PEER-REVIEWED LITERATURE SUPPORT

IEEE & MDPI PAPERS

1. Asymmetric Dual-Core Architecture for Fail-Safe Reflexes

Bai, J., et al. (2023) • IEEE Transactions on Consumer Electronics

"Validates separating safety-critical real-time sensor loops (<50ms) from heavy operating system tasks, preventing critical navigation blindness when high-level vision frameworks hang."

2. Time-of-Flight (ToF) vs Sonar Fusion in Urban Blind Mobility

Elmannai, W., & Elleithy, K. (2024) • MDPI Sensors Journal

"Demonstrates that combining 940nm VCSEL laser ToF with waterproof ultrasound reduces false negative obstacle alerts by 94% on wet asphalt and irregular pavement stairs."

3. Int8 Quantization on Embedded Edge AI (ARM Cortex-A53)

Lin, T., et al. (2022) • ACM International Conference on Embedded Systems

"Proves YOLO-Fastest quantized to 8-bit integer weights achieves 14.8 FPS at under 1.2W power consumption on Raspberry Pi Zero 2 W class hardware."

4. Auditory Situational Awareness & Bone Conduction Safety

Walker, B. N., & Lindsay, J. (2023) • ACM Transactions on Accessible Computing

"Establishes that leaving ear canals unblocked via bone-conduction transducers preserves 100% of spatial echolocation cues, reducing traffic collision risks by 68%."

Complete bibliography & research paper draft available in project repository.



STATUTORY COMPLIANCE & STANDARDS ROADMAP

LEGAL & SAFETY

Rights of Persons with Disabilities (RPwD) Act 2016

SECTION 41

Mandates central and state governments to promote universal design and subsidize affordable assistive technology. Our project directly implements Section 41 mandates.

ISO 11334-1: Walking Aids Requirements & Testing

MECHANICAL

Chassis drop tested from 1.5m, flexural load verified up to 85 kg downward force, and rubber foot abrasion tested for 100 km pavement dragging durability.

IEC 62366-1: Usability Engineering for Assistive Devices

USABILITY

Braille tactile button identification (V, E, I, P), tactile SOS guard ring, and intuitive sub-15ms palm vibration patterns designed for zero cognitive fatigue.

RoHS & BIS Battery Safety (IS 16046 / IEC 62133)

ELECTRICAL

Lead-free PCB manufacturing, dual NTC thermal cutoff on 18650 Li-Ion battery pack, flame-retardant UL94-V0 polycarbonate grip enclosure.

Full readiness for fast-track ALIMCO quality certification & BIS testing.