```sql
--Category, Yday Orders,  Yday GMV, Yday Revenue, Yday Customers, Yday Live Products,
Yday Live Stores, Yday New Customers--
SELECT
p.category,
COUNT(DISTINCT(o.order_id)) AS Yday_orders,
SUM(o.selling_price) AS Yday_GMV,
SUM(o.selling_price)/1.18 AS Yday_revenue,
COUNT(DISTINCT(o.customer_id)) AS Yday_customers,
COUNT(DISTINCT(o.product_id)) AS Yday_live_products,
COUNT(DISTINCT(o.store_id)) AS Yday_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
WHERE DATE(o.order_date) = DATE_SUB(current_date() ,INTERVAL 1 DAY)
GROUP BY 1;
```

```sql
--Sub Category, Category, Yday Orders,  Yday GMV, Yday Customers, Yday Revenue, Yday Live Products, Yday Live Stores, Yday New Customers
--
SELECT
p.sub_category,
p.category,
COUNT(DISTINCT(o.order_id)) AS Yday_orders,
SUM(o.selling_price) AS Yday_GMV,
SUM(o.selling_price)/1.18 AS Yday_revenue,
COUNT(DISTINCT(o.customer_id)) AS Yday_customers,
COUNT(DISTINCT(o.product_id)) AS Yday_live_products,
COUNT(DISTINCT(o.store_id)) AS Yday_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
AND DATE(o.order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1,2;
```

```sql
--Brand, Category, Yday Orders,  Yday GMV, Yday Customers  Yday Revenue, Yday Live
Products, Yday Live Stores, Yday New Customers--


SELECT
p.Brand,
p.category,
COUNT(DISTINCT(o.order_id)) AS Yday_orders,
SUM(o.selling_price) AS Yday_GMV,
SUM(o.selling_price)/1.18 AS Yday_revenue,
COUNT(DISTINCT(o.customer_id)) AS Yday_customers,
COUNT(DISTINCT(o.product_id)) AS Yday_live_products,
COUNT(DISTINCT(o.store_id)) AS Yday_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
AND DATE(o.order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1,2;


--Product Id, Brand,  Yday Orders,  Yday GMV, Yday Customers, Yday Revenue, Yday Live
Products, Yday Live Stores, Yday New Customers--
```

```sql
SELECT
p.product_id,
p.Brand,
COUNT(DISTINCT(o.order_id)) AS Yday_orders,
SUM(o.selling_price) AS Yday_GMV,
SUM(o.selling_price)/1.18 AS Yday_revenue,
COUNT(DISTINCT(o.customer_id)) AS Yday_customers,
COUNT(DISTINCT(o.product_id)) AS Yday_live_products,
COUNT(DISTINCT(o.store_id)) AS Yday_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
AND DATE(o.order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1,2;


--StoreType, Yday Orders,  Yday GMV, Yday Revenue, Yday Customers, Yday Live Products,
Yday Live Stores, Yday New Customers--

SELECT
o.store_id,
COUNT(DISTINCT(o.order_id)) AS Yday_orders,
SUM(o.selling_price) AS Yday_GMV,
SUM(o.selling_price)/1.18 AS Yday_revenue,
```

```sql
COUNT(DISTINCT(o.customer_id)) AS Yday_customers,
COUNT(DISTINCT(o.product_id)) AS Yday_live_products,
COUNT(DISTINCT(o.store_id)) AS Yday_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
AND DATE(o.order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1;


--Store Id,  StoreType,  Yday Orders,  Yday GMV, Yday Customers, Yday Revenue, Yday
Live Products, Yday Live Stores, Yday New Customers--
SELECT
o.store_id,
s.storetype_id,
COUNT(DISTINCT(o.order_id)) AS Yday_orders,
SUM(o.selling_price) AS Yday_GMV,
SUM(o.selling_price)/1.18 AS Yday_revenue,
COUNT(DISTINCT(o.customer_id)) AS Yday_customers,
COUNT(DISTINCT(o.product_id)) AS Yday_live_products,
COUNT(DISTINCT(o.store_id)) AS Yday_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
```

```
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.store_id = s.store_id
AND DATE(o.order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1,2;


--State, Yday Orders,  Yday GMV, Yday Revenue, Yday Customers, Yday Live Products,
Yday Live Stores, Yday New Customers--


SELECT
s.state,
COUNT(DISTINCT(o.order_id)) AS Yday_orders,
SUM(o.selling_price) AS Yday_GMV,
SUM(o.selling_price)/1.18 AS Yday_revenue,
COUNT(DISTINCT(o.customer_id)) AS Yday_customers,
COUNT(DISTINCT(o.product_id)) AS Yday_live_products,
COUNT(DISTINCT(o.store_id)) AS Yday_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
```

```sql
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.store_id = s.store_id
AND DATE(o.order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1;


--City, State,  Yday Orders,  Yday GMV, Yday Customers, Yday Revenue, Yday Live
Products, Yday Live Stores, Yday New Customers--
SELECT
s.city,
s.state,
COUNT(DISTINCT(o.order_id)) AS Yday_orders,
SUM(o.selling_price) AS Yday_GMV,
SUM(o.selling_price)/1.18 AS Yday_revenue,
COUNT(DISTINCT(o.customer_id)) AS Yday_customers,
COUNT(DISTINCT(o.product_id)) AS Yday_live_products,
COUNT(DISTINCT(o.store_id)) AS Yday_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
```

```sql
ON o.store_id = s.store_id
AND DATE(o.order_date) = DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1,2;


-------------------
--Category, MTD Orders, MTD GMV,  MTD Revenue,  MTD Live Products,  MTD Live Stores,
MTD New Customers--


SELECT
p.category,
COUNT(DISTINCT(o.order_id)) AS MTD_orders,
SUM(o.selling_price) AS MTD_GMV,
SUM(o.selling_price)/1.18 AS MTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS MTD_customers,
COUNT(DISTINCT(o.product_id)) AS MTD_live_products,
COUNT(DISTINCT(o.store_id)) AS MTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS MTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders ) AS o
WHERE rn=1
AND date((order_date)) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
```

```
WHERE date(o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1;


--Sub Category, Category, MTD Orders, MTD GMV,  MTD Revenue,  MTD Live Products,  MTD
Live Stores,  MTD New Customers--


SELECT
p.sub_category,
p.category,
COUNT(DISTINCT(o.order_id)) AS MTD_orders,
SUM(o.selling_price) AS MTD_GMV,
SUM(o.selling_price)/1.18 AS MTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS MTD_customers,
COUNT(DISTINCT(o.product_id)) AS MTD_live_products,
COUNT(DISTINCT(o.store_id)) AS MTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS MTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND date((order_date)) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
```

```sql
WHERE date(o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1,2;

--Brand,  Category, MTD Orders, MTD GMV,  MTD Revenue,  MTD Live Products,  MTD Live
Stores,  MTD New Customers--


SELECT
p.brand,
p.category,
COUNT(DISTINCT(o.order_id)) AS MTD_orders,
SUM(o.selling_price) AS MTD_GMV,
SUM(o.selling_price)/1.18 AS MTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS MTD_customers,
COUNT(DISTINCT(o.product_id)) AS MTD_live_products,
COUNT(DISTINCT(o.store_id)) AS MTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS MTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND date((order_date)) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
```

```sql
WHERE date(o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1,2;

--Product Id, Brand,  MTD Orders, MTD GMV,  MTD Revenue,  MTD Live Products,  MTD Live
Stores,  MTD New Customers--


SELECT
p.product_id,
p.brand,
COUNT(DISTINCT(o.order_id)) AS MTD_orders,
SUM(o.selling_price) AS MTD_GMV,
SUM(o.selling_price)/1.18 AS MTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS MTD_customers,
COUNT(DISTINCT(o.product_id)) AS MTD_live_products,
COUNT(DISTINCT(o.store_id)) AS MTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS MTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND date((order_date)) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
```

```sql
WHERE date(o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1,2;

--StoreType,  MTD Orders, MTD GMV,  MTD Revenue,  MTD Live Products,  MTD Live Stores,
MTD New Customers--


SELECT
o.store_id,
COUNT(DISTINCT(o.order_id)) AS MTD_orders,
SUM(o.selling_price) AS MTD_GMV,
SUM(o.selling_price)/1.18 AS MTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS MTD_customers,
COUNT(DISTINCT(o.product_id)) AS MTD_live_products,
COUNT(DISTINCT(o.store_id)) AS MTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS MTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND date((order_date)) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
WHERE date(o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
```

```sql
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY 1;


--Store Id, StoreType,  MTD Orders, MTD GMV,  MTD Revenue,  MTD Live Products,  MTD
Live Stores,  MTD New Customers--


SELECT
o.store_id,
s.storetype_id,
COUNT(DISTINCT(o.order_id)) AS MTD_orders,
SUM(o.selling_price) AS MTD_GMV,
SUM(o.selling_price)/1.18 AS MTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS MTD_customers,
COUNT(DISTINCT(o.product_id)) AS MTD_live_products,
COUNT(DISTINCT(o.store_id)) AS MTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS MTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND date((order_date)) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
WHERE date(o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
```

```sql
            AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
GROUP BY  1, 2;


--State,  MTD Orders, MTD GMV,  MTD Revenue,  MTD Live Products,  MTD Live Stores,
MTD New Customers--


SELECT
s.state,
COUNT(DISTINCT(o.order_id)) AS MTD_orders,
SUM(o.selling_price) AS MTD_GMV,
SUM(o.selling_price)/1.18 AS MTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS MTD_customers,
COUNT(DISTINCT(o.product_id)) AS MTD_live_products,
COUNT(DISTINCT(o.store_id)) AS MTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS MTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND date((order_date)) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
            AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
WHERE date(o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
            AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
```

```sql
GROUP BY 1;


--City, State,  MTD Orders, MTD GMV,  MTD Revenue,  MTD Live Products,  MTD Live
Stores,  MTD New Customers--


SELECT
s.city,
s.state,
COUNT(DISTINCT(o.order_id)) AS MTD_orders,
SUM(o.selling_price) AS MTD_GMV,
SUM(o.selling_price)/1.18 AS MTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS MTD_customers,
COUNT(DISTINCT(o.product_id)) AS MTD_live_products,
COUNT(DISTINCT(o.store_id)) AS MTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS MTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND date((order_date)) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
)AS nc
ON o.order_id = nc.order_id
WHERE date(o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY),
MONTH)
             AND DATE_SUB(CURRENT_DATE(), INTERVAL 1 DAY)
```

```sql
GROUP BY 1,2;



------------------------
--Category, LMTD Orders,  LMTD GMV, LMTD Revenue, LMTD Live Products, LMTD Live
Stores, LMTD New Customers--


SELECT
p.category,
COUNT(DISTINCT(o.order_id)) AS LMTD_orders,
SUM(o.selling_price) AS LMTD_GMV,
SUM(o.selling_price)/1.18 AS LMTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS LMTD_customers,
COUNT(DISTINCT(o.product_id)) AS LMTD_live_products,
COUNT(DISTINCT(o.store_id)) AS LMTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LMTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
```

```sql
)AS nc
ON o.order_id = nc.order_id

WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
GROUP BY 1;


--Sub Category, Category, LMTD Orders,  LMTD GMV, LMTD Revenue, LMTD Live Products,
LMTD Live Stores, LMTD New Customers--


SELECT
p.sub_category,
p.category,
COUNT(DISTINCT(o.order_id)) AS LMTD_orders,
SUM(o.selling_price) AS LMTD_GMV,
SUM(o.selling_price)/1.18 AS LMTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS LMTD_customers,
COUNT(DISTINCT(o.product_id)) AS LMTD_live_products,
COUNT(DISTINCT(o.store_id)) AS LMTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LMTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
```

```
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
)AS nc
ON o.order_id = nc.order_id

WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
GROUP BY 1,2;


--Brand,  Category, LMTD Orders,  LMTD GMV, LMTD Revenue, LMTD Live Products, LMTD
Live Stores, LMTD New Customers--


SELECT
p.brand,
p.category,
COUNT(DISTINCT(o.order_id)) AS LMTD_orders,
SUM(o.selling_price) AS LMTD_GMV,
SUM(o.selling_price)/1.18 AS LMTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS LMTD_customers,
COUNT(DISTINCT(o.product_id)) AS LMTD_live_products,
COUNT(DISTINCT(o.store_id)) AS LMTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LMTD_New_Customer
```

```
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
)AS nc
ON o.order_id = nc.order_id

WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
GROUP BY 1,2;


--Product Id, Brand,  LMTD Orders,  LMTD GMV, LMTD Revenue, LMTD Live Products, LMTD
Live Stores, LMTD New Customers--


SELECT
```

```sql
p.product_id,
p.brand,
COUNT(DISTINCT(o.order_id)) AS LMTD_orders,
SUM(o.selling_price) AS LMTD_GMV,
SUM(o.selling_price)/1.18 AS LMTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS LMTD_customers,
COUNT(DISTINCT(o.product_id)) AS LMTD_live_products,
COUNT(DISTINCT(o.store_id)) AS LMTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LMTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
)AS nc
ON o.order_id = nc.order_id

WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
```

```
 )
GROUP BY 1,2;


--StoreType,  LMTD Orders,  LMTD GMV, LMTD Revenue, LMTD Live Products, LMTD Live
Stores, LMTD New Customers--


SELECT
o.store_id,
COUNT(DISTINCT(o.order_id)) AS LMTD_orders,
SUM(o.selling_price) AS LMTD_GMV,
SUM(o.selling_price)/1.18 AS LMTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS LMTD_customers,
COUNT(DISTINCT(o.product_id)) AS LMTD_live_products,
COUNT(DISTINCT(o.store_id)) AS LMTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LMTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = o.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
)AS nc
```

```
ON o.order_id = nc.order_id

WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
GROUP BY 1;


--Store Id, StoreType,  LMTD Orders,  LMTD GMV, LMTD Revenue, LMTD Live Products, LMTD
Live Stores, LMTD New Customers--


SELECT
o.store_id,
s.storetype_id,
COUNT(DISTINCT(o.order_id)) AS LMTD_orders,
SUM(o.selling_price) AS LMTD_GMV,
SUM(o.selling_price)/1.18 AS LMTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS LMTD_customers,
COUNT(DISTINCT(o.product_id)) AS LMTD_live_products,
COUNT(DISTINCT(o.store_id)) AS LMTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LMTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
```

```sql
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
)AS nc
ON o.order_id = nc.order_id

WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
GROUP BY 1,2;


--State,  LMTD Orders,  LMTD GMV, LMTD Revenue, LMTD Live Products, LMTD Live Stores,
LMTD New Customers--


SELECT
s.state,
COUNT(DISTINCT(o.order_id)) AS LMTD_orders,
SUM(o.selling_price) AS LMTD_GMV,
SUM(o.selling_price)/1.18 AS LMTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS LMTD_customers,
COUNT(DISTINCT(o.product_id)) AS LMTD_live_products,
COUNT(DISTINCT(o.store_id)) AS LMTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LMTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
```

```sql
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
)AS nc
ON o.order_id = nc.order_id

WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
GROUP BY 1;


--City, State,  LMTD Orders,  LMTD GMV, LMTD Revenue, LMTD Live Products, LMTD Live
Stores, LMTD New Customers--


SELECT
s.city,
s.state,
```

```sql
COUNT(DISTINCT(o.order_id)) AS LMTD_orders,
SUM(o.selling_price) AS LMTD_GMV,
SUM(o.selling_price)/1.18 AS LMTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS LMTD_customers,
COUNT(DISTINCT(o.product_id)) AS LMTD_live_products,
COUNT(DISTINCT(o.store_id)) AS LMTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LMTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
)AS nc
ON o.order_id = nc.order_id

WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND
 DATE_ADD(
   DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH), MONTH),
   INTERVAL (EXTRACT(DAY FROM CURRENT_DATE()) - 2) DAY
 )
GROUP BY 1,2;
```

```
-----------------------------
--Category, LM Orders,  LM GMV, LM Revenue, LM Live Products, LM Live Stores, LM New
Customers--


SELECT
p.category,
COUNT(DISTINCT(o.order_id)) AS LM_orders,
SUM(o.selling_price) AS LM_GMV,
SUM(o.selling_price)/1.18 AS LM_revenue,
COUNT(DISTINCT(o.customer_id)) AS LM_customers,
COUNT(DISTINCT(o.product_id)) AS LM_live_products,
COUNT(DISTINCT(o.store_id)) AS LM_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LM_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date)BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
GROUP BY 1;
```

```sql
--Sub Category, Category, LM Orders,  LM GMV, LM Revenue, LM Live Products, LM Live
Stores, LM New Customers--


SELECT
p.sub_category,
p.category,
COUNT(DISTINCT(o.order_id)) AS LM_orders,
SUM(o.selling_price) AS LM_GMV,
SUM(o.selling_price)/1.18 AS LM_revenue,
COUNT(DISTINCT(o.customer_id)) AS LM_customers,
COUNT(DISTINCT(o.product_id)) AS LM_live_products,
COUNT(DISTINCT(o.store_id)) AS LM_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LM_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date)BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
GROUP BY 1,2;
```

```sql
--Brand,  Category, LM Orders,  LM GMV, LM Revenue, LM Live Products, LM Live Stores,
LM New Customers--


SELECT
p.Brand,
p.category,
COUNT(DISTINCT(o.order_id)) AS LM_orders,
SUM(o.selling_price) AS LM_GMV,
SUM(o.selling_price)/1.18 AS LM_revenue,
COUNT(DISTINCT(o.customer_id)) AS LM_customers,
COUNT(DISTINCT(o.product_id)) AS LM_live_products,
COUNT(DISTINCT(o.store_id)) AS LM_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LM_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date)BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
GROUP BY 1,2;
```

```sql
--Product Id, Brand,  LM Orders,  LM GMV, LM Revenue, LM Live Products, LM Live
Stores, LM New Customers--


SELECT
p.product_id,
p.Brand,
COUNT(DISTINCT(o.order_id)) AS LM_orders,
SUM(o.selling_price) AS LM_GMV,
SUM(o.selling_price)/1.18 AS LM_revenue,
COUNT(DISTINCT(o.customer_id)) AS LM_customers,
COUNT(DISTINCT(o.product_id)) AS LM_live_products,
COUNT(DISTINCT(o.store_id)) AS LM_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LM_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date)BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
GROUP BY 1,2;
--StoreType,  LM Orders,  LM GMV, LM Revenue, LM Live Products, LM Live Stores, LM New
Customers
```

```
SELECT
s.storetype_id,
COUNT(DISTINCT(o.order_id)) AS LM_orders,
SUM(o.selling_price) AS LM_GMV,
SUM(o.selling_price)/1.18 AS LM_revenue,
COUNT(DISTINCT(o.customer_id)) AS LM_customers,
COUNT(DISTINCT(o.product_id)) AS LM_live_products,
COUNT(DISTINCT(o.store_id)) AS LM_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LM_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date)BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
GROUP BY 1;


--Store Id, StoreType,  LM Orders,  LM GMV, LM Revenue, LM Live Products, LM Live
Stores, LM New Customers--
```

```sql
SELECT
s.store_id,
s.storetype_id,
COUNT(DISTINCT(o.order_id)) AS LM_orders,
SUM(o.selling_price) AS LM_GMV,
SUM(o.selling_price)/1.18 AS LM_revenue,
COUNT(DISTINCT(o.customer_id)) AS LM_customers,
COUNT(DISTINCT(o.product_id)) AS LM_live_products,
COUNT(DISTINCT(o.store_id)) AS LM_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LM_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date)BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
GROUP BY 1,2;


--State,  LM Orders,  LM GMV, LM Revenue, LM Live Products, LM Live Stores, LM New
Customers--
```

```
SELECT
s.state,
COUNT(DISTINCT(o.order_id)) AS LM_orders,
SUM(o.selling_price) AS LM_GMV,
SUM(o.selling_price)/1.18 AS LM_revenue,
COUNT(DISTINCT(o.customer_id)) AS LM_customers,
COUNT(DISTINCT(o.product_id)) AS LM_live_products,
COUNT(DISTINCT(o.store_id)) AS LM_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LM_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date)BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
GROUP BY 1;


--City, State,  LM Orders,  LM GMV, LM Revenue, LM Live Products, LM Live Stores, LM
New Customers--
```

```sql
SELECT
s.city,
s.state,
COUNT(DISTINCT(o.order_id)) AS LM_orders,
SUM(o.selling_price) AS LM_GMV,
SUM(o.selling_price)/1.18 AS LM_revenue,
COUNT(DISTINCT(o.customer_id)) AS LM_customers,
COUNT(DISTINCT(o.product_id)) AS LM_live_products,
COUNT(DISTINCT(o.store_id)) AS LM_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS LM_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Storecity AS s
ON o.store_id = s.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE (order_date) BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH),
MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date)BETWEEN DATE_TRUNC(DATE_SUB(CURRENT_DATE(), INTERVAL 1
MONTH), MONTH)
 AND LAST_DAY(DATE_SUB(CURRENT_DATE(), INTERVAL 1 MONTH))
GROUP BY 1,2;


--------Category, QTD Orders, QTD GMV,  QTD Revenue,  QTD Live Products,  QTD Live
Stores, QTD New customers----------

Select
```

```sql
p.category ,
COUNT(o.order_id) AS QTD_orders ,
SUM(o.selling_price) AS QTD_GMV ,
SUM(o.selling_price)/1.18 AS QTD_REVENUE ,
COUNT(DISTINCT(o.product_id)) AS QTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS QTD_live_store ,
COUNT(DISTINCT(nc.customer_id)) AS QTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS P
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1;

----------Sub Category, Category, QTD Orders, QTD GMV,  QTD Revenue,  QTD Live
Products,  QTD Live Stores, QTD New customers----------

Select
p.sub_category,
p.category ,
COUNT(o.order_id) AS QTD_orders ,
SUM(o.selling_price) AS QTD_GMV ,
SUM(o.selling_price)/1.18 AS QTD_REVENUE ,
COUNT(DISTINCT(o.product_id)) AS QTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS QTD_live_store ,
```

```sql
COUNT(DISTINCT(nc.customer_id)) AS QTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS P
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1,2;

-----------Brand, Category, QTD Orders, QTD GMV,  QTD Revenue,  QTD Live Products,
QTD Live Stores,QTD New customers-------

Select
p.brand,
p.category ,
COUNT(o.order_id) AS QTD_orders ,
SUM(o.selling_price) AS QTD_GMV ,
SUM(o.selling_price)/1.18 AS QTD_REVENUE ,
COUNT(DISTINCT(o.product_id)) AS QTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS QTD_live_store ,
COUNT(DISTINCT(nc.customer_id)) AS QTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS P
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
```

```sql
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1,2;

------Product Id, Brand,  QTD Orders, QTD GMV,  QTD Revenue,  QTD Live Products, QTD
Live Stores,QTD New customers----

Select
p.product_id,
p.brand,
COUNT(o.order_id) AS QTD_orders ,
SUM(o.selling_price) AS QTD_GMV ,
SUM(o.selling_price)/1.18 AS QTD_REVENUE ,
COUNT(DISTINCT(o.product_id)) AS QTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS QTD_live_store ,
COUNT(DISTINCT(nc.customer_id)) AS QTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS P
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
```

```sql
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON o.order_id = nc.order_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1,2;

-----StoreType, QTD Orders, QTD GMV,  QTD Revenue,  QTD Live Products, QTD Live
Stores,QTD New customers -----

Select
s.storetype_id,
COUNT(o.order_id) AS QTD_orders ,
SUM(o.selling_price) AS QTD_GMV ,
SUM(o.selling_price)/1.18 AS QTD_REVENUE ,
COUNT(DISTINCT(o.product_id)) AS QTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS QTD_live_store ,
COUNT(DISTINCT(nc.customer_id)) AS QTD_New_Customer
FROM  supermartproject-476809.supermartsell.Storecity AS s
JOIN supermartproject-476809.supermartsell.Orders AS o
ON s.store_id = o.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON s.store_id = nc.store_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1;
```

```sql
-------Store Id,  StoreType,  QTD Orders, QTD GMV,  QTD Revenue,  QTD Live Products,
QTD Live Stores, QTD New customers-----

Select
s.store_id,
s.storetype_id,
COUNT(o.order_id) AS QTD_orders ,
SUM(o.selling_price) AS QTD_GMV ,
SUM(o.selling_price)/1.18 AS QTD_REVENUE ,
COUNT(DISTINCT(o.product_id)) AS QTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS QTD_live_store ,
COUNT(DISTINCT(nc.customer_id)) AS QTD_New_Customer
FROM  supermartproject-476809.supermartsell.Storecity AS s
JOIN supermartproject-476809.supermartsell.Orders AS o
ON s.store_id = o.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON s.store_id = nc.store_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1,2;

-----State, QTD Orders, QTD GMV,  QTD Revenue,  QTD Live Products,  QTD Live Stores
,QTD New customers ------

Select
s.state,
COUNT(o.order_id) AS QTD_orders ,
```

```sql
SUM(o.selling_price) AS QTD_GMV ,
SUM(o.selling_price)/1.18 AS QTD_REVENUE ,
COUNT(DISTINCT(o.product_id)) AS QTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS QTD_live_store ,
COUNT(DISTINCT(nc.customer_id)) AS QTD_New_Customer
FROM  supermartproject-476809.supermartsell.Storecity AS s
JOIN supermartproject-476809.supermartsell.Orders AS o
ON s.store_id = o.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON s.store_id = nc.store_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1;

-----City,  State,  QTD Orders, QTD GMV,  QTD Revenue,  QTD Live Products,  QTD Live
Stores ,QTD New customers-----

Select
s.city,
s.state,
COUNT(o.order_id) AS QTD_orders ,
SUM(o.selling_price) AS QTD_GMV ,
SUM(o.selling_price)/1.18 AS QTD_REVENUE ,
COUNT(DISTINCT(o.product_id)) AS QTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS QTD_live_store ,
COUNT(DISTINCT(nc.customer_id)) AS QTD_New_Customer
FROM  supermartproject-476809.supermartsell.Storecity AS s
```

```sql
JOIN supermartproject-476809.supermartsell.Orders AS o
ON s.store_id = o.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON s.store_id = nc.store_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1,2;

-----Category,  YTD Orders, YTD GMV,  YTD Revenue,  YTD Live Products,  YTD Live
Stores, YTD New customers-------

SELECT
p.category,
COUNT(DISTINCT(o.order_id)) AS YTD_orders,
SUM(o.selling_price) AS YTD_GMV,
SUM(o.selling_price)/1.18 AS YTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS YTD_customers,
COUNT(DISTINCT(o.product_id)) AS YTD_live_products,
COUNT(DISTINCT(o.store_id)) AS YTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS YTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
```

```sql
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), YEAR) AND CURRENT_DATE()
)AS nc
ON o.order_id = nc.order_id
WHERE DATE(o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), YEAR) AND CURRENT_DATE()
GROUP BY 1;

-----Sub Category,  Category, YTD Orders, YTD GMV,  YTD Revenue,  YTD Live Products,
YTD Live Stores, YTD New customers-----

SELECT
p.sub_category,
p.category,
COUNT(DISTINCT(o.order_id)) AS YTD_orders,
SUM(o.selling_price) AS YTD_GMV,
SUM(o.selling_price)/1.18 AS YTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS YTD_customers,
COUNT(DISTINCT(o.product_id)) AS YTD_live_products,
COUNT(DISTINCT(o.store_id)) AS YTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS YTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), YEAR) AND CURRENT_DATE()
)AS nc
```

```
ON o.order_id = nc.order_id
WHERE DATE(o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), YEAR) AND CURRENT_DATE()
GROUP BY 1,2;

-----Brand, Category, YTD Orders, YTD GMV,  YTD Revenue,  YTD Live Products,YTD Live
Stores, YTD New customers-------

SELECT
p.brand,
p.category,
COUNT(DISTINCT(o.order_id)) AS YTD_orders,
SUM(o.selling_price) AS YTD_GMV,
SUM(o.selling_price)/1.18 AS YTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS YTD_customers,
COUNT(DISTINCT(o.product_id)) AS YTD_live_products,
COUNT(DISTINCT(o.store_id)) AS YTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS YTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), YEAR) AND CURRENT_DATE()
)AS nc
ON o.order_id = nc.order_id
WHERE DATE(o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), YEAR) AND CURRENT_DATE()
GROUP BY 1,2;

-------Product Id,  Brand ,YTD Orders,  YTD GMV,  YTD Revenue,  YTD Live Products,
YTD Live Stores , YTD New customers-------
```

```sql
SELECT
p.product_id,
p.brand,
COUNT(DISTINCT(o.order_id)) AS YTD_orders,
SUM(o.selling_price) AS YTD_GMV,
SUM(o.selling_price)/1.18 AS YTD_revenue,
COUNT(DISTINCT(o.customer_id)) AS YTD_customers,
COUNT(DISTINCT(o.product_id)) AS YTD_live_products,
COUNT(DISTINCT(o.store_id)) AS YTD_live_stores,
COUNT(DISTINCT(nc.customer_id)) AS YTD_New_Customer
FROM supermartproject-476809.supermartsell.Orders AS o
JOIN supermartproject-476809.supermartsell.Product AS p
ON o.product_id = p.product_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), YEAR) AND CURRENT_DATE()
)AS nc
ON o.order_id = nc.order_id
WHERE DATE(o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), YEAR) AND CURRENT_DATE()
GROUP BY 1,2;

-------StoreType, YTD Orders, YTD GMV,  YTD Revenue,  YTD Live Products,  YTD Live
Stores,YTD New customers-----

Select
s.storetype_id,
COUNT(o.order_id) AS YTD_orders ,
SUM(o.selling_price) AS YTD_GMV ,
SUM(o.selling_price)/1.18 AS YTD_REVENUE ,
```

```sql
COUNT(DISTINCT(o.product_id)) AS YTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS YTD_live_store ,
COUNT(DISTINCT(nc.customer_id)) AS YTD_New_Customer
FROM  supermartproject-476809.supermartsell.Storecity AS s
JOIN supermartproject-476809.supermartsell.Orders AS o
ON s.store_id = o.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON s.store_id = nc.store_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1;

-----Store Id,  StoreType,  YTD Orders, YTD GMV,  YTD Revenue,  YTD Live Products,
YTD Live Stores, YTD New customers----

Select
s.store_id,
s.storetype_id,
COUNT(o.order_id) AS YTD_orders ,
SUM(o.selling_price) AS YTD_GMV ,
SUM(o.selling_price)/1.18 AS YTD_REVENUE ,
COUNT(DISTINCT(o.product_id)) AS YTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS YTD_live_store ,
COUNT(DISTINCT(nc.customer_id)) AS YTD_New_Customer
FROM  supermartproject-476809.supermartsell.Storecity AS s
JOIN supermartproject-476809.supermartsell.Orders AS o
ON s.store_id = o.store_id
```

```
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON s.store_id = nc.store_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1,2;

-----State, YTD Orders, YTD GMV,  YTD Revenue,  YTD Live Products,  YTD Live Stores,
YTD New customers-----
Select
s.state,
COUNT(o.order_id) AS YTD_orders ,
SUM(o.selling_price) AS YTD_GMV ,
SUM(o.selling_price)/1.18 AS YTD_REVENUE ,
COUNT(DISTINCT(o.product_id)) AS YTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS YTD_live_store ,
COUNT(DISTINCT(nc.customer_id)) AS YTD_New_Customer
FROM  supermartproject-476809.supermartsell.Storecity AS s
JOIN supermartproject-476809.supermartsell.Orders AS o
ON s.store_id = o.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
```

```sql
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON s.store_id = nc.store_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1;

------City, State,  YTD Orders, YTD GMV,  YTD Revenue,  YTD Live Products,  YTD Live
Stores , YTD New customers----

Select
s.city,
s.state,
COUNT(o.order_id) AS YTD_orders ,
SUM(o.selling_price) AS YTD_GMV ,
SUM(o.selling_price)/1.18 AS YTD_REVENUE ,
COUNT(DISTINCT(o.product_id)) AS YTD_live_product ,
COUNT(DISTINCT(o.store_id)) AS YTD_live_store ,
COUNT(DISTINCT(nc.customer_id)) AS YTD_New_Customer
FROM  supermartproject-476809.supermartsell.Storecity AS s
JOIN supermartproject-476809.supermartsell.Orders AS o
ON s.store_id = o.store_id
LEFT JOIN
(SELECT *
FROM
(SELECT
*,
RANK() OVER (PARTITION BY customer_id ORDER BY order_date ASC )AS rn
FROM supermartproject-476809.supermartsell.Orders )
WHERE rn=1
AND DATE(order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND CURRENT_DATE()
)AS nc
ON s.store_id = nc.store_id
WHERE DATE (o.order_date) BETWEEN DATE_TRUNC(CURRENT_DATE(), QUARTER) AND
CURRENT_DATE()
GROUP BY 1,2;
```