Mohit patil D15A 37

Advance DevOps Practical Exam

Case study no 17:

1.Introduction:

Case Study Overview

This case study examines the deployment of an AWS Lambda function using Node.js 20.x, detailing the process of creating a zip file for the function code and integrating it with an S3 bucket and DynamoDB for data processing.

Key Feature and Application

The unique feature of this case study is the use of AWS Lambda, a serverless compute service that allows users to run code without provisioning or managing servers. This enables quick scaling and cost efficiency. The practical application involves setting up a Lambda function that processes JSON files uploaded to an S3 bucket and stores the processed data in a DynamoDB table.

2. Step-by-Step Explanation

Serverless Data Processing with DynamoDB

- **Concepts Used: AWS Lambda, DynamoDB, S3.**
- **Problem Statement: "Develop a Lambda function that processes a JSON file uploaded to an S3 bucket and writes specific fields from the JSON to a DynamoDB table."**
- **Tasks:**
  - **Create a DynamoDB table with relevant attributes.**
  - **Write a Lambda function in Node.js that triggers when a JSON file is uploaded to an S3 bucket.**
  - **Parse the JSON and write specific fields (e.g., userID and timestamp) to the DynamoDB table.**
  - **Upload a sample JSON file to S3 and verify that the data is correctly written to DynamoDB.**

Solution:

Step 1 : Open the AWS Management Console and navigate to DynamoDB.


Share your feedback on Amazon DynamoDB
Your feedback is an important part of helping us provide a better customer experience. Take this short survey to let us know how we're doing.

Database

Amazon DynamoDB
A fast and flexible NoSQL database service for any scale

DynamoDB is a fully managed, key-value, and document database that delivers single-digit-millisecond performance at any scale.

Get started
Create a new table to start exploring DynamoDB.

Pricing
DynamoDB charges for reading, writing, and storing data in your DynamoDB tables, along with any optional features you choose to turn on. DynamoDB has on-demand capacity mode and provisioned capacity mode, and these modes have pricing for processing reads and writes on your tables.

How it works

Step 2: Create table in Dynamo DB

- **Define the primary key (e.g., user ID as the partition key and timestamp as the sort key).**


Share your feedback on Amazon DynamoDB
Your feedback is an important part of helping us provide a better customer experience. Take this short survey to let us know how we're doing.

DynamoDB > Tables > Create table

Create table

Table details Info
DynamoDB is a schemaless database that requires only a table name and a primary key when you create the table.

Table name
This will be used to identify your table.
UserData
Between 3 and 255 characters, containing only letters, numbers, underscores (_), hyphens (-), and periods (.).

Partition key
The partition key is part of the table's primary key. It is a hash value that is used to retrieve items from your table and allocate data across hosts for scalability and availability.
userID — String
1 to 255 characters and case sensitive.

Sort key - *optional*
You can use a sort key as the second part of a table's primary key. The sort key allows you to sort or search among all items sharing the same partition key.
Enter the sort key name — String
1 to 255 characters and case sensitive.

Table settings

[✓ Default settings] The fastest way to create your table. You can modify these settings now or after your table has been created.
Customize settings — Use these advanced features to make DynamoDB work better for your needs.

Step 3: DynamoDB Table is created successfully


The UserData table was created successfully.

DynamoDB > Tables

Tables (1) Info

	Name ▲	Status	Partition key	Sort key	Indexes	Deletion protection	Read capacity mode	Write capacity mode	Tot
☐	UserData	✓ Active	userID (S)	-	0	Off	Provisioned (5)	Provisioned (5)	0 by

Step 4: Create a S3 Bucket


Amazon S3
Buckets
Access Grants
Access Points
Object Lambda Access Points
Multi-Region Access Points
Batch Operations
IAM Access Analyzer for S3
Block Public Access settings for this account
Storage Lens
Dashboards
Storage Lens groups
AWS Organizations settings
Feature spotlight 7
Introduction to Amazon S3
Copy link

Storage

Amazon S3

Store and retrieve any amount of data from anywhere

Amazon S3 is an object storage service that offers industry-leading scalability, data availability, security, and performance.

Create a bucket

Every object in S3 is stored in a bucket. To upload files and folders to S3, you'll need to create a bucket where the objects will be stored.

Create bucket

How it works

Pricing

With S3, there are no minimum fees. You only pay for what you use. Prices are based on the location of your S3 bucket.

Estimate your monthly bill using the AWS Simple Monthly Calculator

View pricing details

Step 5: Give naming to bucket



Amazon S3 > Buckets > Create bucket

Create bucket Info

Buckets are containers for data stored in S3.

General configuration

AWS Region

US East (N. Virginia) us-east-1

Bucket type Info

[✓ General purpose] Recommended for most use cases and access patterns. General purpose buckets are the original S3 bucket type. They allow a mix of storage classes that redundantly store objects across multiple Availability Zones.

Directory Recommended for low-latency use cases. These buckets use only the S3 Express One Zone storage class, which provides faster processing of data within a single Availability Zone.

Bucket name Info

my-json-upload-bucket

Bucket name must be unique within the global namespace and follow the bucket naming rules. See rules for bucket naming

Copy settings from existing bucket - *optional*

Only the bucket settings in the following configuration are copied.

Choose bucket

Format: s3://bucket/prefix

Object Ownership Info

Control ownership of objects written to this bucket from other AWS accounts and the use of access control lists (ACLs). Object ownership determines who can specify access to objects.

[✓ ACLs disabled (recommended)] ACLs enabled

Step 6: Bucket was created successfully



Successfully created bucket "my-json-upload-bucket"
To upload files and folders, or to configure additional bucket settings, choose **View details**.

Amazon S3 > Buckets

Account snapshot - *updated every 24 hours* All AWS Regions

Storage lens provides visibility into storage usage and activity trends. Learn more

General purpose buckets (2) Info All AWS Regions

Buckets are containers for data stored in S3.

Name	AWS Region	IAM Access Analyzer	Creation date
elasticbeanstalk-us-east-1-108955875398	US East (N. Virginia) us-east-1	View analyzer for us-east-1	August 8, 2024, 14:34:41 (UTC+05:30)
my-json-upload-bucket	US East (N. Virginia) us-east-1	View analyzer for us-east-1	October 15, 2024, 23:36:17 (UTC+05:30)

Step 7: Redirect to IAM console

- **Redirect to create policies**



Policies (1242) Info

A policy is an object in AWS that defines permissions.

Policy name	Type	Used as	Description
AccessAnalyzerService...	AWS managed	None	Allow Access Analyzer to analyze resource metadata
AdministratorAccess	AWS managed - job function	Permissions policy (1)	Provides full access to AWS services and resources.
AdministratorAccess-...	AWS managed	None	Grants account administrative permissions while explicitly allowi...
AdministratorAccess-...	AWS managed	None	Grants account administrative permissions. Explicitly allows devel...
AlexaForBusinessDevi...	AWS managed	None	Provide device setup access to AlexaForBusiness services
AlexaForBusinessFullA...	AWS managed	None	Grants full access to AlexaForBusiness resources and access to rel...
AlexaForBusinessGate...	AWS managed	None	Provide gateway execution access to AlexaForBusiness services
AlexaForBusinessLifes...	AWS managed	None	Provide access to Lifesize AVS devices
AlexaForBusinessNet...	AWS managed	None	This policy enables Alexa for Business to perform automated task...

- **Specify the permissions**



Specify permissions Info

Add permissions by selecting services, actions, resources, and conditions. Build permission statements using the JSON editor.

Policy editor

S3 — Allow All actions

Lambda — Allow All actions

DynamoDB — Allow All actions

- **Policy was created successfully**



Policy S3_json_lambda created.

Policies (1/1243) Info

A policy is an object in AWS that defines permissions.

Search: s3

Policy name	Type	Used as	Description
AmazonS3OutpostsFullAccess	AWS managed	None	Provides full access to Amazon S3 on ...
AmazonS3OutpostsReadOnlyA...	AWS managed	None	Provides read only access to Amazon S...
AmazonS3ReadOnlyAccess	AWS managed	None	Provides read only access to all bucket...
AWSBackupServiceRolePolicyF...	AWS managed	None	Policy containing permissions necessar...
AWSBackupServiceRolePolicyF...	AWS managed	None	Policy containing permissions necessar...
AWSS3OnOutpostsServiceRole...	AWS managed	None	Allow Amazon S3 on Outposts service ...
IVSRecordToS3	AWS managed	None	Service Linked Role to perform S3 Put...
QuickSightAccessForS3Storage...	AWS managed	None	Policy used by QuickSight team to acc...
S3_json__dynamodb	Customer managed	None	-
S3_json_lambda	Customer managed	None	-
S3StorageLensServiceRolePolicy	AWS managed	None	Enables access to AWS Services and Re...

Step 8: Create new Role


Identity and Access Management (IAM)

IAM > Roles

Roles (6) Info

An IAM role is an identity you can create that has specific permissions with credentials that are valid for short durations. Roles can be assumed by entities that you trust.

Role name	Trusted entities	Last activity
aws-elasticbeanstalk-service-role	AWS Service: elasticbeanstalk	60 days ago
AWSCodePipelineServiceRole-ap-south-1-mohit	AWS Service: codepipeline	60 days ago
AWSServiceRoleForApplicationAutoScaling_DynamoDBTable	AWS Service: dynamodb.application	31 minutes ago
AWSServiceRoleForAutoScaling	AWS Service: autoscaling (Service-Li	60 days ago
AWSServiceRoleForSupport	AWS Service: support (Service-Linke	-
AWSServiceRoleForTrustedAdvisor	AWS Service: trustedadvisor (Service	-

Roles Anywhere Info

Authenticate your non AWS workloads and securely provide access to AWS services.

Access AWS from your non AWS workloads

X.509 Standard

Temporary credentials

- **Provide naming to role**


Name, review, and create

Role details

Role name
Enter a meaningful name to identify this role.
s3_json_dynamodb
Maximum 64 characters. Use alphanumeric and '+=,.@-_' characters.

Description
Add a short explanation for this role.
Allows Lambda functions to call AWS services on your behalf.
Maximum 1000 characters. Use letters (A-Z and a-z), numbers (0-9), tabs, new lines, or any of the following characters: _+=,. @-/\[{}]!#$%^*();"' `

Step 1: Select trusted entities

Trust policy

```
{
    "Version": "2012-10-17",
```

- **Our new role was created**


Role s3_json_dynamodb created.

Roles (7) Info

An IAM role is an identity you can create that has specific permissions with credentials that are valid for short durations. Roles can be assumed by entities that you trust.

Role name	Trusted entities	Last activity
s3_json_dynamodb	AWS Service: lambda	-

Roles Anywhere Info

Authenticate your non AWS workloads and securely provide access to AWS services.

Access AWS from your non AWS workloads
Operate your non AWS workloads using the same authentication and authorization strategy that you use within AWS.

X.509 Standard
Use your own existing PKI infrastructure or use AWS Certificate Manager Private Certificate Authority to authenticate identities.

Temporary credentials
Use temporary credentials with ease and benefit from the enhanced security they provide.

Step 9: Create Lambda function



AWS Lambda
lets you run code without thinking about servers.

You pay only for the compute time that you consume — there is no charge when your code is not running. With Lambda, you can run code for virtually any type of application or backend service, all with zero administration.

Get started

Author a Lambda function from scratch, or choose from one of many preconfigured examples.

```
exports.handler = async (event) => {
  console.log(event);
  return 'Hello from Lambda!';
};
```

- **Create a function and name it**


Services
Search [Alt+S]
N. Virginia
voclabs/user3402853=PATIL_MOHIT_SANDIP @ 1089-5587-5398
Lambda > Functions > Create function

Create function Info

Choose one of the following options to create your function.

- [✓ Author from scratch] Start with a simple Hello World example.
- Use a blueprint: Build a Lambda application from sample code and configuration presets for common use cases.
- Container image: Select a container image to deploy for your function.

Basic information

Function name
Enter a name that describes the purpose of your function.
ProcessJSON
Function name must be 1 to 64 characters, must be unique to the Region, and can't include spaces. Valid characters are a-z, A-Z, 0-9, hyphens (-), and underscores (_).

Runtime Info
Choose the language to use to write your function. Note that the console code editor supports only Node.js, Python, and Ruby.
Node.js 20.x

Architecture Info
Choose the instruction set architecture you want for your function code.
[✓ x86_64] arm64

Permissions Info
By default, Lambda will create an execution role with permissions to upload logs to Amazon CloudWatch Logs. You can customize this default role later when adding triggers.

- **Lambda function was created**



Successfully created the function **ProcessJSON**. You can now change its code and configuration. To invoke your function with a test event, choose "Test".

ProcessJSON

Function overview Info

ProcessJSON
Layers (0)

Description
-
Last modified
33 seconds ago
Function ARN
arn:aws:lambda:us-east-1:108955875398:function:ProcessJSON
Function URL Info
-

Code source Info

Function configuration

Use the function overview to see your function's configuration. You can choose to view this as a diagram or as an AWS Serverless Application Model (AWS SAM) template. AWS SAM is is an open source framework for building serverless applications using infrastructure as code (IaC). You can see the following types of resources in the diagram or template:

Triggers are AWS services or resources that invoke the function.

Destinations are AWS resources that receive a record of an invocation after success or failure. You can configure Lambda to send invocation records when your function is invoked asynchronously, or if your function processes records from a stream. The contents of

Step 10 : Add trigger to the Lambda function

- **Add a S3 tigger**



Add trigger

Trigger configuration Info

S3
aws asynchronous storage

Bucket
Choose or enter the ARN of an S3 bucket that serves as the event source. The bucket must be in the same region as the function.
s3/my-json-upload-bucket
Bucket region: us-east-1

Event types
Select the events that you want to have trigger the Lambda function. You can optionally set up a prefix or suffix for an event. However, for each bucket, individual events cannot have multiple configurations with overlapping prefixes or suffixes that could match the same object key.
All object create events

Prefix - *optional*
Enter a single optional prefix to limit the notifications to objects with keys that start with matching characters. Any special characters must be URL encoded.
e.g. images/

Suffix - *optional*
Enter a single optional suffix to limit the notifications to objects with keys that end with matching characters. Any special characters must be URL encoded.
e.g. .jpg

Recursive invocation

- **S3 trigger was created and displayed on the dashboard console**



ProcessJSON

The trigger my-json-upload-bucket was successfully added to function ProcessJSON. The function is now receiving events from the trigger.

Function overview Info

ProcessJSON

S3

Description
-

Last modified
5 minutes ago

Function ARN
arn:aws:lambda:us-east-1:108955875398:function:ProcessJSON

Function URL Info
-

Step 11: Add the node js script in the code console of the Lambda function



```
const AWS = require('aws-sdk');
const S3 = new AWS.S3();
const DynamoDB = new AWS.DynamoDB.DocumentClient();

exports.handler = async (event) => {
    for (const record of event.Records) {
        const bucket = record.s3.bucket.name;
        const key = decodeURIComponent(record.s3.object.key.replace(/\+/g, ' '));

        try {
            // Get the JSON file from S3
            const data = await S3.getObject({ Bucket: bucket, Key: key }).promise();
            const jsonContent = JSON.parse(data.Body.toString('utf-8'));

            // Extract specific fields
            const userID = jsonContent.userID;
            const timestamp = jsonContent.timestamp;

            // Prepare the data to be inserted into DynamoDB
            const params = {
                TableName: 'UserData',
                Item: {
                    userID: userID,
                    timestamp: timestamp,
                },
            };

            // Insert data into DynamoDB
            await DynamoDB.put(params).promise();
            console.log(`Data inserted into DynamoDB for userID: ${userID}`);
        } catch (error) {
            console.error(`Error processing file: ${error}`);
        }
    }
};
```

Step 12: Test the code and deploy it



The test event **test1** was successfully saved.

```
const AWS = require('aws-sdk');
const S3 = new AWS.S3();
const DynamoDB = new AWS.DynamoDB.DocumentClient();

exports.handler = async (event) => {
    for (const record of event.Records) {
        const bucket = record.s3.bucket.name;
        const key = decodeURIComponent(record.s3.object.key.replace(/\+/g, ' '));

        try {
            // Get the JSON file from S3
            const data = await S3.getObject({ Bucket: bucket, Key: key }).promise();
            const jsonContent = JSON.parse(data.Body.toString('utf-8'));

            // Extract specific fields
            const userID = jsonContent.userID;
            const timestamp = jsonContent.timestamp;

            // Prepare the data to be inserted into DynamoDB
            const params = {
                TableName: 'UserData',
                Item: {
                    userID: userID,
                    timestamp: timestamp,
                },
            };

            // Insert data into DynamoDB
            await DynamoDB.put(params).promise();
            console.log(`Data inserted into DynamoDB for userID: ${userID}`);
        } catch (error) {
            console.error(`Error processing file: ${error}`);
        }
    }
};
```

- **Status 200 OK got displayed after testing of code**



Successfully updated the function **ProcessJSON**.

Execution results

Status: Succeeded | Max memory used: 62 MB | Time: 1.51 ms

Test Event Name

```
test1
```

Response

```
{
  "statusCode": 200,
  "body": "\"Hello from Lambda!\""
}
```

Function Logs

```
START RequestId: 543da5b8-5993-4114-bebf-c1cee3edbcba Version: $LATEST
END RequestId: 543da5b8-5993-4114-bebf-c1cee3edbcba
REPORT RequestId: 543da5b8-5993-4114-bebf-c1cee3edbcba  Duration: 1.51 ms   Billed Duration: 2 ms   Memory Size: 128 MB Max Memory Used: 62 MB
```

Request ID

```
543da5b8-5993-4114-bebf-c1cee3edbcba
```

Step 13: Upload the Json file in the S3 bucket



Amazon S3 > Buckets > my-json-upload-bucket > Upload

Upload Info

Add the files and folders you want to upload to S3. To upload a file larger than 160GB, use the AWS CLI, AWS SDK or Amazon S3 REST API. Learn more

Drag and drop files and folders you want to upload here, or choose **Add files** or **Add folder**.

Files and folders (1 Total, 67.0 B)

All files and folders in this table will be uploaded.

Name	Folder
sample.json	-

Destination Info

Destination
s3://my-json-upload-bucket

▶ **Destination details**
Bucket settings that impact new objects stored in the specified destination.

▶ **Permissions**
Grant public access and access to other AWS accounts.

- **Content in the JSON file**



C: > Users > mrmoh > OneDrive > Desktop > web Dev > {} sample2.json > ...

```json
{
  "userID": "12345",
  "timestamp": "2024-10-15T12:00:00Z"
}

```

- **File Successfully uploaded**



Upload succeeded
View details below.

Upload: status

The information below will no longer be available after you navigate away from this page.

Summary

Destination	Succeeded	Failed
s3://my-json-upload-bucket	1 file, 67.0 B (100.00%)	0 files, 0 B (0%)

Files and folders (1 Total, 67.0 B)

Name	Folder	Type	Size	Status	Error
sample.json	-	application/js...	67.0 B	Succeeded	-

- **Uploaded file**



Amazon S3 > Buckets > my-json-upload-bucket

my-json-upload-bucket Info

Objects | Properties | Permissions | Metrics | Management | Access Points

Objects (1) Info

Objects are the fundamental entities stored in Amazon S3. You can use Amazon S3 inventory to get a list of all objects in your bucket. For others to access your objects, you'll need to explicitly grant them permissions. Learn more

Name	Type	Last modified	Size	Storage class
sample.json	json	October 16, 2024, 00:17:22 (UTC+05:30)	67.0 B	Standard

Step 14: Now, redirect to DynamoDB and go to Tables section

- **Table named "UserDate" is seen**



DynamoDB > Tables

Tables (1) Info

Name	Status	Partition key	Sort key	Indexes	Deletion protection	Read capacity mode	Write capacity mode	Total size	Table class
UserData	Active	userID (S)	-	0	Off	Provisioned (1)	Provisioned (1)	0 bytes	Standard

- **Redirected to the table created**



DynamoDB > Tables > UserData

Tables (1)

UserData

UserData

Protect your DynamoDB table from accidental writes and deletes
When you turn on point-in-time recovery (PITR), DynamoDB backs up your table data automatically so that you can restore to any given second in the preceding 35 days. Additional charges apply. Learn more

General information Info

Partition key: userID (String)
Sort key: -
Capacity mode: Provisioned
Table status: Active
Alarms: No active alarms
Point-in-time recovery (PITR) Info: Off
Resource-based policy Info: Not active

Additional info

Items summary

DynamoDB updates the following information approximately every six hours.

Item count: 0
Table size: 0 bytes
Average item size: 0 bytes



[✓ Scan] Query

Select a table or index: Table - UserActivity

Select attribute projection: All attributes

Completed. Read capacity units consumed: 0.5

Items returned (1)

Step 15: Redirect to PartiQL editor

- Enter the query → SELECT * FROM "UserActivity" in the Query console
- Click on Run option
- Required data from the JSON file gets displayed in the JSON View part



```
SELECT * FROM "UserActivity"
```

```
[
  {
    "userID": {
      "S": "12345"
    },
    "timestamp": {
      "S": "024-10-15T12:00:00Z"
    }
  }
]
```

➢ **Required Output is displayed in the DynamoDB when uploaded in the JSON format**



```
[
  {
    "userID": {
      "S": "12345"
    },
    "timestamp": {
      "S": "2024-10-15T12:00:00Z"
    }
  }
]
```

Guidelines and Best Practices :

Keep Your Code Clean: Regularly refactor your code to maintain clarity and efficiency. Test Locally: Before zipping and uploading, test your Lambda function code locally to catch any issues early.

Version Control: Use version control systems like Git to track changes to your codebase, making it easier to manage updates. Dependency Management: Only include necessary libraries in your zip file to reduce size and improve performance.

4. Demonstration Preparation

Key Points

1. Overview of the Project:

- Briefly introduce the purpose of the project and the AWS services used (S3, Lambda, DynamoDB).
- Explain the significance of automating data processing and the benefits of a serverless architecture.

2. Architecture Explanation:

- Present a simple diagram illustrating the workflow: S3 bucket → Lambda function → DynamoDB.
- Highlight how data flows through these services upon file upload.

3. Step-by-Step Process:

- Demonstrate how to upload a JSON file to the S3 bucket.
- Show how the Lambda function is triggered by the S3 event notification.
- Verify that the data is successfully inserted into the DynamoDB table.

4. Error Handling and Logging:

- Discuss how CloudWatch logs can be used to monitor function execution and troubleshoot issues.
- Provide examples of common errors and how they were resolved during development.

5. Security and Permissions:

- Explain the IAM roles and policies associated with the Lambda function.
- Discuss the importance of granting the minimum necessary permissions for security

Potential Questions:

1. **What challenges did you face during implementation?**
    - Initially, the main challenge I faced was creating the necessary policies to obtain permissions for Lambda, DynamoDB, and S3 Bucket, as these permissions had not been granted earlier.

- Another issue arose when the data meant to be displayed in DynamoDB was not visible in the table, due to the S3 trigger not being properly set up.
- Additionally, the data passed was not visible in CloudWatch logs due to permission issues with the policies.

2. How does this solution scale with increasing data volume?

- **AWS Lambda Scalability:**
  - AWS Lambda automatically scales based on the number of incoming requests. When multiple JSON files are uploaded to the S3 bucket simultaneously, Lambda can run multiple instances of the function concurrently, allowing it to process each file in parallel without manual intervention.
- **DynamoDB Scalability:**
  - DynamoDB is designed to scale horizontally. It can handle large amounts of data and high request rates by automatically distributing data across multiple partitions. With features like on-demand capacity mode, DynamoDB can adjust its throughput automatically based on the incoming traffic, ensuring consistent performance regardless of data volume.

3. What additional features could be added in the future?

- **AWS Step Functions:**
  - I could integrate AWS Step Functions to manage complex workflows, allowing for orchestrating multiple Lambda functions and handling tasks like retries and error handling seamlessly.
- **API Gateway:**
  - Adding an API Gateway would allow external applications to interact with the Lambda function via RESTful APIs, making it easier to upload files and retrieve data programmatically.
- **Amazon SNS for Notifications:**
  - Implementing Amazon SNS (Simple Notification Service) could enhance monitoring by sending notifications upon successful data insertion into DynamoDB or alerting for any errors during processing, thus improving the observability of the system.

4. How did you ensure data integrity and security?

- **Data Validation:**
  - I implemented validation logic within the Lambda function to ensure that the incoming JSON data met the expected format and contained all required fields (like user ID). If the validation fails, the function logs the error and skips processing that file.
- **IAM Policies:**
  - The execution role for the Lambda function is configured with the principle of least privilege, ensuring that it only has access to the S3 bucket and DynamoDB table it needs. Regular audits of IAM policies are conducted to ensure that no excessive permissions are granted.

5. Can you explain the cost implications of using these AWS services?

- **Amazon S3 Costs:**
  - S3 charges are based on the amount of data stored, the number of requests made, and the data transfer out of the S3 bucket. It's cost-effective for storing large amounts of data since pricing decreases with increased storage volume.
- **AWS Lambda Costs:**
  - Lambda pricing is based on the number of requests and the duration of the execution. There is a free tier that allows for a generous number of requests and compute time each month, which is beneficial for low-traffic applications.
- **DynamoDB Costs:**
  - DynamoDB has a pricing model based on data storage, read and write requests, and optional features like backups and data transfer. The on-demand capacity mode is flexible for varying workloads, ensuring I only pay for what I use.

Conclusion :

In this case study, we explored the integration of AWS services to create an automated data processing pipeline using Amazon S3, AWS Lambda, and DynamoDB. By setting up an S3 bucket to store JSON files, we configured a Lambda function that triggers upon file uploads. This function processes the incoming data and stores it in a DynamoDB table, enabling seamless data management and retrieval.

Key takeaways from this project include:

1. **Automation:** The use of S3 event notifications to trigger the Lambda function allows for real-time data processing without manual intervention, showcasing the power of serverless architectures.
2. **Scalability:** AWS services like Lambda and DynamoDB offer scalable solutions that can handle varying amounts of data, making it suitable for projects of any size.
3. **Error Handling and Debugging:** By monitoring CloudWatch logs, we identified potential issues and improved the function's reliability. This highlights the importance of logging and error handling in serverless applications.
4. **Hands-on Experience:** This project provided valuable experience in configuring AWS services, understanding IAM roles and permissions, and developing serverless applications, which are critical skills in today’s cloud-centric development environment.

Overall, this case study demonstrates the effectiveness of leveraging AWS services to create efficient, automated workflows that enhance data management capabilities. Future enhancements could include adding more robust error handling, optimizing data processing, or integrating additional AWS services for advanced analytics.