

Q1
#include <stdio.h>

int main() {

int n;

scanf ("%d", &n);

printf ("Enter Sorted Array : ");

int a[n];

for (int i = 0; i < n; i++) {

scanf ("%d", &a[i]);

}

printf ("Enter Target Sum : ");

int target;

scanf ("%d", &target);

int l = 0, r = n - 1;

while (l < r) {

int sum = a[l] + a[r];

if (sum == target) {

printf ("%d, %d", a[l], a[r]);

return 0;

}

else if (sum < target) {

l++;

}

else {

r--;

}

}

```
printf("-1");
```

```
return 0;
```

```
}
```

Q2

```
#include <stdio.h>
```

```
int main() {
```

```
    int a[] = {1, 3, 8, 12, 4, 2};
```

```
    int n = 6;
```

```
    int i = 0, j = n - 1;
```

```
    while (i < j) {
```

```
        int mid = i + (j - i) / 2;
```

```
        if (a[mid] < a[mid + 1]) {
```

```
            i = mid + 1;
```

```
        }
```

```
        else {
```

```
            j = mid;
```

```
        }
```

```
    }
```

```
    printf("Peak element: %d", a[i]);
```

```
    return 0;
```

```
}
```

Q3

```
#include <stdio.h>
```

```
int ternarysearch ( int arr[], int left, int right, int key) {
```

```
    if ( left > right)
```

```
        return -1;
```

```
    int mid1 = left + (right - left) / 3
```

```
    int mid2 = right - (right - left) / 3
```

```
    if ( arr[mid1] == key)
```

```
        return mid1;
```

```
    if ( arr[mid2] == key)
```

```
        return mid2;
```

```
    if ( key < arr[mid1]) {
```

```
        return ternarysearch(arr, left, mid1-1, key);
```

```
    } else if ( key > arr[mid2]) {
```

```
        return ternarysearch(arr, mid1+1, mid2-1right, key);
```

```
    } else {
```

```
        return ternarysearch(arr, mid1+1, mid2-1, key);
```

```
    }
```

```

int main() {
    int n, k;
    scanf("%d", &n);
    printf("Enter Sorted array: ");
    int a[n];
    for(int i=0; i<n; i++) {
        scanf("%d", &a[i]);
    }
    printf("Enter key: ");
    scanf("%d", &k);

    printf("Index: %d", ternarySearch(a, 0, n-1, k));

    return 0;
}

```

Q4

```
#include <stdio.h>
```

```

int binarySearch(int arr[], int left, int right, int key) {
    while (left <= right) {
        int mid = left + (right - left) / 2;

        if (arr[mid] == key)
            return mid;
        else if (arr[mid] < key)
            left = mid + 1;
        else
            right = mid - 1;
    }
    return -1;
}

```

```
int exponentialSearch(int arr[], int n, int key) {
```

```
    if (arr[0] == key)
        return 0;
```

```
    int i = 1;
    while (i < n && arr[i] <= key)
        i = i * 2;
    int left = i / 2;
    int right = (i < n) ? i : n - 1;
```

```
    return binarySearch(arr, left, right, key);
```

```
}
```

```
int main() {
```

```
    int n;
```

```
    scanf("%d", &n);
```

```
    printf("Enter Sorted Array: ");
```

```
    int a[n];
```

```
    for (int i = 0; i < n; i++)
```

```
        scanf("%d", &a[i]);
```

```
}
```

```
    printf("Enter key: ");
```

```
    int k;
```

```
    scanf("%d", &k);
```

```
    printf("Position using Binary search: %d\n", binarySearch(a, 0, n-1, k));
```

```
    printf("Position using Exponential Search: %d\n", exponentialSearch(a, 0, n-1,
```

```
    return 0;
```

```
}
```