

Enterprise Payment Gateway & Authentication API Specification

1. Overview & Authentication

The Enterprise Payment Gateway API allows developers to process credit card payments, initiate refunds, and query transaction statuses securely over HTTPS.

All requests to the API must include a Bearer Token in the HTTP Authorization header. API keys can be generated from the Developer Dashboard.

Authentication Header Format:

Authorization: Bearer sec_live_994a2b89c7d1e0f34a5b
Content-Type: application/json

2. Payment Intent Endpoint (/v2/payments/charge)

HTTP Method: POST Endpoint: <https://api.enterprise-pay.com/v2/payments/charge>

Request Payload Schema:

```
{
  "amount": 1500,
  "currency": "USD",
  "customer_id": "cust_88392",
  "payment_method": {
    "type": "card",
    "card_token": "tok_visa_4242"
  }
}
```

3. Response & Error Handling

The API returns standard HTTP status codes to indicate success or failure.

HTTP 200 OK: Request succeeded. Response body contains transaction object.

HTTP 401 Unauthorized: Invalid or missing API key in the Authorization header.

HTTP 422 Unprocessable Entity: Validation error in request body or invalid currency code.

HTTP 429 Too Many Requests: Rate limit exceeded. Maximum 100 requests per minute allowed.

Sample Error Response (HTTP 401):

```
{
  "error": {
    "code": "INVALID_API_KEY",
    "message": "The provided API key is expired or invalid.",
    "request_id": "req_77a91b2c"
  }
}
```

4. Webhook Configuration

Webhooks allow your application to receive real-time HTTP POST notifications when payment events occur (e.g., payment.succeeded, payment.failed).

Webhook signatures are generated using HMAC-SHA256. Verify signatures using your Webhook Secret Key passed in the 'X-Signature-SHA256' header.