



Jenkins

/ Manage Jenkins



/ Nodes



/ New node

New node

Node name

compile-node

Type



Permanent Agent

Adds a plain, permanent agent to Jenkins. This is called "permanent" because Jenkins doesn't provide higher level of integration with these agents, such as dynamic provisioning. Select this type if no other agent types apply — for example such as when you are adding a physical computer, virtual machines managed outside Jenkins, etc.

Create



Jenkins

/ Manage Jenkins



/ Nodes



compile-node

Description ?

Jenkins agent for Maven compilation

Plain text [Preview](#)

Number of executors ?

1

Remote root directory ?

/home/jenkins/agent

Labels ?

compile

```
PS C:\Users\aaroh> mkdir C:\Users\aaroh\jenkins-agent
```

Directory: C:\Users\aaroh

Mode	LastWriteTime	Length	Name
d-----	13-08-2026 19:05		jenkins-agent

```
PS C:\Users\aaroh> cd C:\Users\aaroh\jenkins-agent
PS C:\Users\aaroh\jenkins-agent> notepad Dockerfile
PS C:\Users\aaroh\jenkins-agent>
```

```
Dockerfile.txt
File Edit View

FROM jenkins/inbound-agent:jdk17

USER root
|
RUN apt-get update && \
    apt-get install -y maven && \
    rm -rf /var/lib/apt/lists/*

USER jenkins
```

 **Jenkins** / Nodes / test-node

Status

Delete Agent

Configure

Build History

Load Statistics

Script Console

Log

System Information

Disconnect

Build Executor Status

0/1

Agent test-node

Jenkins agent for Maven testing

Agent is connected.

Monitoring Data

Labels

test

Projects tied to test-node

None

Edit description

Mark this node temporary

```
PS C:\Users\aaroh\jenkins-agent> docker ps
CONTAINER ID   IMAGE             COMMAND                  CREATED        STATUS        PORTS
e39450fa8c78   jenkins-maven-agent  "/usr/local/bin/jenk..."  52 seconds ago  Up 51 seconds
1729a0011fdf   jenkins-maven-agent  "/usr/local/bin/jenk..."  4 minutes ago  Up 4 minutes
03bd56810cd3   myjenkins-docker    "/usr/bin/tini -- /u..."  4 days ago    Up 19 minutes  0.0.0.0:8080->8080/tcp, [
::]:8080->8080/tcp, 0.0.0.0:50000->50000/tcp, [::]:50000->50000/tcp
PS C:\Users\aaroh\jenkins-agent>
```

```
pom.xml
File Edit View

<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
    http://maven.apache.org/xsd/maven-4.0.0.xsd">

  <modelVersion>4.0.0</modelVersion>

  <groupId>com.example</groupId>
  <artifactId>jenkins-maven-project</artifactId>
  <version>1.0</version>

  <properties>
    <maven.compiler.source>17</maven.compiler.source>
    <maven.compiler.target>17</maven.compiler.target>
  </properties>

  <dependencies>
    <dependency>
      <groupId>org.junit.jupiter</groupId>
      <artifactId>junit-jupiter</artifactId>
      <version>5.10.2</version>
      <scope>test</scope>
    </dependency>
  </dependencies>

  <build>
    <plugins>
      <plugin>
        <groupId>org.apache.maven.plugins</groupId>
        <artifactId>maven-surefire-plugin</artifactId>
        <version>3.2.5</version>
      </plugin>
    </plugins>
  </build>

</project>
```

```
Calculator.java CalculatorTest.java
File Edit View

public class Calculator {

    public int add(int a, int b) {
        return a + b;
    }

    public int multiply(int a, int b) {
        return a * b;
    }
}
```

```
Calculator.java  CalculatorTest.java  +
File Edit View

import org.junit.jupiter.api.Test;
import static org.junit.jupiter.api.Assertions.*;

public class CalculatorTest {

    @Test
    void testAddition() {
        Calculator c = new Calculator();
        assertEquals(5, c.add(2, 3));
    }

    @Test
    void testMultiplication() {
        Calculator c = new Calculator();
        assertEquals(6, c.multiply(2, 3));
    }
}
```

mllemmmm / jenkins-maven-project

<> Code Issues Pull requests Agents Actions Projects Wiki Security and quality Insights Settings

Files

main

Go to file

src

main/java

Calculator.java

test/java

CalculatorTest.java

pom.xml

jenkins-maven-project / src

mllemmmm Add Maven project

Name	Last commit message
..	
main/java	Add Maven project
test/java	Add Maven project

```
PS C:\Users\aaoroh\jenkins-maven-project> notepad src\test\java\CalculatorTest.java
PS C:\Users\aaoroh\jenkins-maven-project> cd C:\Users\aaoroh\jenkins-maven-project
PS C:\Users\aaoroh\jenkins-maven-project> git init
Initialized empty Git repository in C:/Users/aaoroh/jenkins-maven-project/.git/
PS C:\Users\aaoroh\jenkins-maven-project> git add .
PS C:\Users\aaoroh\jenkins-maven-project> git commit -m "Add Maven project"
[master (root-commit) 094ed41] Add Maven project
 3 files changed, 63 insertions(+)
 create mode 100644 pom.xml
 create mode 100644 src/main/java/Calculator.java
 create mode 100644 src/test/java/CalculatorTest.java
PS C:\Users\aaoroh\jenkins-maven-project> git remote add origin https://github.com/mllemmmm/jenkins-maven-project
PS C:\Users\aaoroh\jenkins-maven-project> git branch -M main
PS C:\Users\aaoroh\jenkins-maven-project> git push -u origin main
Enumerating objects: 10, done.
Counting objects: 100% (10/10), done.
Delta compression using up to 12 threads
Compressing objects: 100% (6/6), done.
Writing objects: 100% (10/10), 1.14 KiB | 291.00 KiB/s, done.
Total 10 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/mllemmmm/jenkins-maven-project
 * [new branch]    main -> main
branch 'main' set up to track 'origin/main'.
PS C:\Users\aaoroh\jenkins-maven-project>
```



New Item

Enter an item name

Distributed-Maven-Pipeline

Select an item type



Pipeline

Build, test, and deploy using pipelines. Supports stages, parallel work, and running on multiple agents.



Freestyle project

Classic, general-purpose job type that checks out from up to one SCM, executes build steps serially, followed by post-build steps like archiving artifacts and sending email notifications.



Multi-configuration project

Suitable for projects that need a large number of different configurations, such as testing on multiple environments, platform-specific builds, etc.



Folder

Creates a container that stores nested items in it. Useful for grouping things together. Unlike view, which is just a filter, a folder creates a separate namespace, so you can have multiple things of the same name as long as they are in different folders.

```
[1;34mINFO[m]
[1;34mINFO[m] -----
[1;34mINFO[m]  T E S T S
[1;34mINFO[m] -----
[1;34mINFO[m] Running [1mCalculatorTest[m
[1;34mINFO[m] [1;32mTests run: [0;1;32m2[m, Failures: 0, Errors: 0, Skipped: 0, Time elapsed: 0.059 s -- in [1mCalculatorTest[m
[1;34mINFO[m]
[1;34mINFO[m] Results:
[1;34mINFO[m]
[1;34mINFO[m] [1;32mTests run: 2, Failures: 0, Errors: 0, Skipped: 0[m
[1;34mINFO[m]
[1;34mINFO[m] [1m-----[m
[1;34mINFO[m] [1;32mBUILD SUCCESS[m
[1;34mINFO[m] [1m-----[m
[1;34mINFO[m] Total time: 13.474 s
[1;34mINFO[m] Finished at: 2026-08-13T13:56:39Z
[1;34mINFO[m] [1m-----[m
[Pipeline] }
[Pipeline] // node
[Pipeline] }
[Pipeline] // stage
[Pipeline] End of Pipeline
Finished: SUCCESS
```