

BIOMAX

Metal Bracket Conventional System

Prescriptions

- ROTH
- MBT



PRESCRIPTION/PRESCRIPCIÓN ROTH

SLOT	REFERENCIA/REFERENCE	KIT WITH HOOKS/KIT C. GANCHO 3, 4, 5
.022" x .028"	05.04.0390	5x5

METALLIC
METÁLICO

KITS VARIATION / VARIACIONES DE KITS 5X5			
SLOT .022	05.04.0300 Kit 10 casos c/g 3,4,5	05.04.0309 Kit 50 casos c/g 3,4,5	05.04.0302 Kit 100 casos c/g 3,4,5

Width	2,8 mm	2,8 mm	2,8 mm	2,6 mm	3,2 mm	3,2 mm	2,6 mm	2,8 mm	2,8 mm	2,8 mm
Torque	-7°	-7°	0°	8°	12°	12°	8°	0°	-7°	-7°
Ang	0°	0°	9°	9°	5°	5°	9°	9°	0°	0°
Offset	2°	2°	4°	0°	0°	0°	0°	4°	2°	2°
In-out	0,45 mm	0,45 mm	0,45 mm	0,65 mm	0,60 mm	0,60 mm	0,65 mm	0,45 mm	0,45 mm	0,45 mm

SLOT	REPLACEMENT/REPOSICIÓN - PK W/10									
.022" x .028"	05.04.3814	05.04.3814	05.04.0313	05.04.0312	05.04.0311	05.04.0321	05.04.0322	05.04.0323	05.04.3824	05.04.3824

	15	14	13	12	11	21	22	23	24	25
UPPER SUPERIOR										
LOWER INFERIOR										
	45	44	43	42	41	31	32	33	34	35

Width	2,8 mm	2,8 mm	2,8 mm	2,3 mm	2,3 mm	2,3 mm	2,3 mm	2,8 mm	2,8 mm	2,8 mm
Torque	-22°	-17°	-11°	0°	0°	0°	0°	-11°	-17°	-22°
Ang	0°	0°	5°	0°	0°	0°	0°	5°	0°	0°
Offset	4°	4°	2°	0°	0°	0°	0°	2°	4°	4°
In-out	0,45 mm	0,45 mm	0,48 mm	0,75 mm	0,75 mm	0,75 mm	0,75 mm	0,48 mm	0,45 mm	0,45 mm

SLOT	REPLACEMENT/REPOSICIÓN - PK W/10									
.022" x .028"	05.04.0345	05.04.0344	05.04.0343	05.04.0350	05.04.0350	05.04.0350	05.04.0350	05.04.0333	05.04.0334	05.04.0335



BIOMAX

Metal Bracket Conventional System

PRESCRIPTION/PRESCRIPCIÓN MBT

SLOT	REFERENCIA/REFERENCE	KIT WITH HOOKS/KIT C. GANCHO 3, 4, 5
.022" x .028"	05.04.0890	5x5

METALLIC
METÁLICO

KIT VARIATIONS/ VARIACIONES DE KITS 5X5			
SLOT .022	05.04.0800 Kit 10 cases w/g 3,4,5	05.04.0809 Kit 50 cases w/g 3,4,5	05.04.0802 Kit 100 cases w/g 3,4,5

Width	2,8 mm	2,8 mm	2,8 mm	2,6 mm	3,2mm	3,2mm	2,6 mm	2,8 mm	2,8 mm	2,8 mm
Torque	-7°	-7°	-7°	10°	17°	17°	10°	-7°	-7°	-7°
Ang	0°	0°	8°	8°	4°	4°	8°	8°	0°	0°
Offset	2°	2°	4°	0°	0°	0°	0°	4°	2°	2°
In-out	0,45 mm	0,45 mm	0,45 mm	0,65 mm	0,60 mm	0,60 mm	0,65 mm	0,45 mm	0,45 mm	0,45 mm

SLOT	REPLACEMENT/REPOSICIÓN - PK W/10									
.022" x .028"	05.04.3814	05.04.3814	05.04.0813	05.04.0812	05.04.0811	05.04.0821	05.04.0822	05.04.0823	05.04.3824	05.04.3824

	15	14	13	12	11	21	22	23	24	25
UPPER SUPERIOR										
LOWER INFERIOR										
	45	44	43	42	41	31	32	33	34	35

Width	2,8 mm	2,8 mm	2,8 mm	2,3 mm	2,3 mm	2,3 mm	2,3 mm	2,8 mm	2,8 mm	2,8 mm
Torque	-17°	-12°	-6°	-6°	-6°	-6°	-6°	-6°	-12°	-17°
Ang	0°	0°	3°	0°	0°	0°	0°	3°	0°	0°
Offset	4°	4°	2°	0°	0°	0°	0°	2°	4°	4°
In-out	0,48 mm	0,48 mm	0,50 mm	0,75 mm	0,75 mm	0,75 mm	0,75 mm	0,50 mm	0,48 mm	0,48 mm

SLOT	REPLACEMENT/REPOSICIÓN - PK W/10									
.022" x .028"	05.04.0845	05.04.0844	05.04.0843	05.04.0850	05.04.0850	05.04.0850	05.04.0850	05.04.0833	05.04.0834	05.04.0835



BIOMAX

Metal Bracket Conventional System



 Specifications

MIM (Metal Injection Molding)	• Bracket as a one unit • No separation between the base and body • High corrosion resistance and durability
Rounded corner & Low Profile	• Increase patient comfort • Reduced Soft Tissue Trauma • Improved Oral Hygiene
Integrated hook	• Reduced Risk of Breakage • Increased Patient Comfort
80 GAUGE	• Improved Bonding • Better Adaptation to Tooth Surface • Reduced Bulk
Midline permanent mark	• Facilitate positioning • Accuracy in bracket placement
Selective laser sintering	• Increased Mechanical Retention • More Consistent Bonding • Reduced Risk of Bracket Debonding • Compatible with Light Forces
Small (Mesio-distal) width	• Can be applied on small crowns OR sever crowding case
V Channel & Chamfered Slot & Expanded area under the wing	• Low Friction & higher precision in torque control due to chamfered slot