
CSE113: Parallel Programming

- **Topics**:
  - Linearizability
  - Input/output queues
  - Producer/consumer queues



Announcements

- HW 2 deadline stays Oct 22.

- Midterm on Tuesday.

Announcements

- HW 3 released.

- You will have what you need for Part 1 by the end of today's lecture

Demo

Plain CAS vs. relaxed peeking

- Folder: RMW_mutexes

Build with -O2

- At -O0 the plain CAS loop is slow, so its waiters barely disturb the holder.
- Peeking still pays its extra trip per handoff: see the flag free, then CAS.
- At -O2 the plain CAS storm is real and peeking's trip is cheap.

Watch the cache line

- The lock flag sat on the same line as the counter it protects.
- Every increment in the critical section knocked the flag out of every spinner's cache.
- Peeking is only local if nobody writes the line. Pad the lock: alignas(128).

Previous quiz + Review

Quiz 9.

Lock-free data structures are technically undefined because they contain data conflicts

Select one

A. True

B. False

Scan to answer

forms.gle/YtF1gSqYHRqyMh1X9

Previous quiz + Review

It is impossible to use objects that are not thread-safe in a concurrent program.

- ◯ True
- ◯ False

global variables:

```
bank_account tylers_account;
mutex m;
```

Tyler's coffee addiction:

```
for (int i = 0; i < HOURS; i++) {
   m.lock();
   tylers_account.buy_coffee();
   m.unlock();
}
```

Tyler's employer

```
for (int j = 0; j < HOURS; j++) {
   m.lock();
   tylers_account.get_paid();
   m.unlock();
}
```

what if you have multiple objects?

First solution: The client (user of the object) can use locks.

We might decide to wrap my bank account in an object

```
class bank_account {
  public:
    bank_account() {
      balance = 0;
    }

    void buy_coffee() {
      balance -= 1;
    }

    void get_paid() {
      balance += 1;
    }

  private:
    int balance;
};
```

The object is not "thread safe"

Previous quiz + Review

Non-locking objects do not use mutexes in their implementation. This is beneficial because:

- ◯ it is potentially faster
- ◯ it is easier to reason about
- ◯ it is easier to extend

Bank account example

global variables:

```
bank_account tylers_account;
```

Tyler's coffee addiction:

```
for (int i = 0; i < HOURS; i++) {
   tylers_account.buy_coffee();
}
```

Tyler's employer

```
for (int j = 0; j < HOURS; j++) {
   tylers_account.get_paid();
}
```

```
class bank_account {
  public:
    bank_account() {
      balance = 0;
    }

    void buy_coffee() {
      atomic_fetch_add(&balance, -1);
    }

    void get_paid() {
      atomic_fetch_add(&balance, 1);
    }

  private:
    atomic_int balance;
};
```

Demo

- Folder: concurrent_data_structures

Observation

- Mutex beats lock-free beats spinlock

Why

- One shared word: the cost is the cache line bouncing between cores.
- Lock-free: both threads run, the line bounces every update.
- Mutex: the waiter blocking waits, the holder keeps the line. Not runnable until the unlocker explicitly wakes it.
- Spinlock: both threads run, two atomics per update.

Conclusion

- Lock-free guarantees progress, not speed.
- Fair comparison, spinlock vs. lock-free: lock-free wins with one atomic instead of two.”
- Shared counters do not scale. Reduce sharing.

Previous quiz + Review

Write a few sentences about the pros and cons of using a concurrent data structure vs. using mutexes to protect data structures that are not thread-safe.

Previous quiz + Review

Write a few sentences about the pros and cons of using a concurrent data structure vs. using mutexes to protect data structures that are not thread-safe.

Pros: Easier to use
Cons: Composability

Previous quiz + Review

When multiple threads access a concurrent object, only 1 possible execution is allowed. We reason about that execution by sequentializing object method calls and it is called sequential consistency

- ◯ True
- ◯ False

Global variable:

```
CQueue<int> q;
```


Thread 0:

```
q.enq(6);
q.enq(7);
```


Thread 1:

```
int t = q.deq();
```


Construct a sequential timeline of API calls
Any sequence is valid:



t is 6



t is 6



t is None

Can t ever be 7?

Previous quiz + Review

What is the relationship between linearizable (L) and sequentially consistent (SC)?

- ◯ Objects can be one or the other, but not both
- ◯ Objects that are L are also SC, but not the other way around
- ◯ Objects that are SC are also L, but not the other way around
- ◯ SC and L are the different definitions for the same concept

Review


Sequential consistency and real time

- Add in real time:


This execution is allowed in sequential consistency!

SC doesn't care about real time, only if it can construct its virtual sequential timeline

Thread 0




Thread 1



Sequential consistency and real time

- Add in real time:


2 objects now: p and q



Sequential consistency and real time

- Add in real time:


2 objects now: p and q
Consider each object in isolation



Sequential consistency and real time

- Add in real time:


2 objects now: p and q
Consider each object in isolation



Sequential consistency and real time

- Add in real time:


2 objects now: p and q
Consider each object in isolation



Sequential consistency and real time

- Add in real time:


2 objects now: p and q
Consider each object in isolation




Sequential consistency and real time

- Add in real time:

2 objects now: p and q
Consider each object in isolation






Sequential consistency and real time

- Add in real time:

Now consider them all together



Global variable:

```
CQueue<int> p,q;
```

Thread 0:

```
p.enq(11)
q.enq(2)
p.deq()==12
```

Order 1

```
p.enq(12)
p.enq(11)
p.deq() == 12
```


Order 2

```
q.enq(2)
q.enq(1)
q.deq() == 2
```

Thread 1:

```
q.enq(1)
p.enq(12)
q.deq()==2
```


Combine



Linearizability

- Linearizability
  - Defined in term of real-time histories
  - SC + real-time preservation

- Slightly different game:
  - Sequential consistency is a game about stacking lego bricks
  - Linearizability is about sliders



Linearization point

Each operation has a linearization point (similar to the location of a call in sequential consistency)


- does not overlap with other with other linearizability points
- indivisible computation (critical section, atomic RMW, atomic load, atomic store)
- object update (or read) occurs exactly at this point



Linearizability

each operation has a linearizability point

- does not overlap with other with other linearizability points
- indivisible computation (critical section, atomic RMW, atomic load, atomic store)
- object update (or read) occurs exactly at this point




object state: M

object state: M’

Linearizability

each operation has a linearizability point


- does not overlap with other with other linearizability points
- indivisible computation (critical section, atomic RMW, atomic load, atomic store)
- object update (or read) occurs exactly at this point



Linearizability

each operation has a linearizability point


- does not overlap with other with other linearizability points
- indivisible computation (critical section, atomic RMW, atomic load, atomic store)
- object update (or read) occurs exactly at this point



Linearizability

each operation has a linearizability point


- does not overlap with other with other linearizability points
- indivisible computation (critical section, atomic RMW, atomic load, atomic store)
- object update (or read) occurs exactly at this point



Linearizability

each command gets a linearization point.


You can place the point anywhere **between its innovation and response! (respecting the real-time order)**



Linearizability

each command gets a linearization point.

You can place the point anywhere between its innovation and response!




Linearizability


each command gets a linearization point.

You can place the point anywhere between its innovation and response (so long as they don't overlap)!

Project the linearization points to a global timeline



Linearizability




each command gets a linearization point.


You can place the point anywhere between its innovation and response!

Project the linearization points to a global timeline


slider game!




Linearizability




Linearizability




Linearizability







Linearizability




Linearizability



Linearizability






guaranteed? No

Linearizability

- We spent a bunch of time on SC... did we waste our time?
  - No!
  - Linearizability is strictly stronger than SC. Every linearizable execution is SC, but not the other way around.
  - If a behavior is disallowed under SC, it is also disallowed under linearizability.


Providing Linearizability

- How do we write our programs to be linearizable?
  - Identify the linearizability point
  - One indivisible region (e.g. an atomic store, atomic load, atomic RMW, or critical section) where the method call takes effect. Modeled as a point.



Providing Linearizability

- Locked data structures are linearizable.




```
class bank_account {
  public:
    bank_account() {
      balance = 0;
    }

    void buy_coffee() {
      m.lock();
      balance -= 1;
      m.unlock();
    }


    void get_paid() {
      m.lock();
      balance += 1;
      m.unlock();
    }

  private:
    int balance;
    mutex m;
};
```

Linearizability

- Locked data structures are linearizable.

typically modeled as the point the lock is acquired or released




```
class bank_account {
  public:
    bank_account() {
      balance = 0;
    }

    void buy_coffee() {
      m.lock();
      balance -= 1;
      m.unlock();
    }


    void get_paid() {
      m.lock();
      balance += 1;
      m.unlock();
    }

  private:
    int balance;
    mutex m;
};
```

Linearizability

- Locked data structures are linearizable.

typically modeled as the point the lock is acquired or released
let's say released.




```
class bank_account {
  public:
    bank_account() {
      balance = 0;
    }

    void buy_coffee() {
      m.lock();
      balance -= 1;
      m.unlock();
    }

    void get_paid() {
      m.lock();
      balance += 1;
      m.unlock();
    }

  private:
    int balance;
    mutex m;
};
```

Linearizability


- Our lock-free bank account is linearizable:
  - The atomic operation is the linearizable point

```
class bank_account {
  public:
    bank_account() {
      balance = 0;
    }

    void buy_coffee() {
      atomic_fetch_add(&balance, -1);
    }

    void get_paid() {
      atomic_fetch_add(&balance, 1);
    }


  private:
    atomic_int balance;
};
```



Progress properties

- Going back to specifications:

Recall the mutex




Progress properties

- Going back to specifications:

Recall the mutex

Thread 0 is stopping Thread 1 from making progress.
If delays in one thread can cause delays in other threads, we say that it is blocking




Progress properties

- Going back to specifications:

Thread 0 is stopping Thread 1 from making progress.
If delays in one thread can cause delays in other threads, we say that it is blocking

Recall the mutex




Progress properties

- Going back to specifications:

Thread 0 is stopping Thread 1 from making progress.
If delays in one thread can cause delays in other threads, we say that it is blocking


Recall the mutex



What now?!

Linearizability


Two unfinished commands.



Linearizability

Two unfinished commands.


Linearizability does not dictate that one needs to wait for another



Linearizability

Two unfinished commands.


Linearizability does not dictate that one needs to wait for another



for mutexes, the specification required that the system hang.
no such specification here.


Linearizability

Non-blocking specification:
Every thread is allowed to continue executing
REGARDLESS of the behavior of other threads



Linearizability

Non-blocking specification:
Every thread is allowed to continue executing
REGARDLESS of the behavior of other threads



This is a specification property, not an implementation property! You can implement your concurrent objects with locks and have a “blocking implementation”.

But that is because of implementation choice, not because of specification requirements.

Terminology overview

- Thread-safe implementation:
- Sequential consistency:
- Linearizability:
- Linearizability point:

Terminology overview

- Lock-free implementation:
- (Non-)blocking specification:
- (non-)blocking implementation:

Concurrent Queues

- List of items, accessed in a first-in first-out (FIFO) way
- *duplicates allowed*
- Methods
  - **`enq(x)`** put **`x`** in the list at the end
  - **`deq()`** remove the item at the front of the queue and return it.
  - **`size()`** returns how many items are in the queue

Concurrent Queues

- General implementation given in Chapter 10 of the book.
- Similar types of reasoning as the linked list
  - Lots of reasoning about node insertion, node deletion
  - Using atomic RMWs (CAS) in clever ways

- We will think about specialized queues
  - Implementations can be simplified!

Quiz 9.

Write a few sentences about the pros and cons of using a specialized concurrent queue (e.g. an IO queue) and a fully general concurrent queue.

Free response: a few sentences on the form

Scan to answer

forms.gle/fBRaHAzLLFsHZqJq8

Three Variants of Concurrent Queues

- Input/Output Queues
  - Multiple threads enqueue, and multiple threads dequeue but not both
- Producer/Consumer Queues
  - 1 thread enqueues, 1 thread dequeues
  - Two variants:
    - Synchronous
    - Asynchronous

Input/Output Queues


- Queue in which multiple threads read (deq), or write (enq), but not both.
- Why would we want a thing?
- Computation done in phases:
  - First phase prepares the queue (by writing into it)
  - All threads join
  - Second phase reads values from the queue.


Input/Output Queues


- Example: Information flow in graph applications:

Input/Output Queues

- Example: Information flow in graph applications:










Input/Output Queues

- Example: Information flow in graph applications:










Input/Output Queues

- Example: Information flow in graph applications:










Input/Output Queues

- Example: Information flow in graph applications:









Input/Output Queues

- Example: Information flow in graph applications:




Input/Output Queues

- Example: Information flow in graph applications:




Input/Output Queues

- Example: Information flow in graph applications:




Input/Output Queues


- Example: Information flow in graph applications:




Input/Output Queues

- Example: Information flow in graph applications:









Input/Output Queues


- Example: Information flow in graph applications:



source 0




source 1





join all threads and clear input

Input/Output Queues

- Example: Information flow in graph applications:









Input/Output Queues


- Example: Information flow in graph applications:




Input/Output Queues

- Example: Information flow in graph applications:









Input/Output Queues

- Example: Information flow in graph applications:




Input/Output Queues


- Example: Information flow in graph applications:



source 0





source 1




Input/Output Queues

- Example: Information flow in graph applications:









Input/Output Queues


- Example: Information flow in graph applications:



source 0




source 1




Input/Output Queues

- Example: Information flow in graph applications:



source 0



source 1

and so on...

output

queue 1

input

7	9	8		

queue 0

Implementation

Implementation

Allocate a contiguous array



Pros:
?

Cons:
?

Implementation

Allocate a contiguous array



Pros:
+ fast!
+ we can use indexes instead of addresses


Cons:
- need to reason about overflow!

Note on terminology


- Head/tail - often used in queue implementations, but switches when we start doing circular buffers.

- Front/end - To avoid confusion, we will use front/end for input/output queues.


Implementation



Implementation




Implementation



What happens if a thread wants to add an element?

Think sequentially:


Implementation



What happens if a thread wants to add an element?

Think sequentially:
*reserve a space - increment end


Implementation



What happens if a thread wants to add an element?

Think sequentially:
*reserve a space - increment end


Implementation



What happens if a thread wants to add an element?

Think sequentially:
* reserve a space - increment end
* add the element


Implementation



What happens if a thread wants to add an element?

Think sequentially:
* reserve a space - increment end
* add the element

Implementation




What happens if a thread wants to add an element?

Think sequentially:
* reserve a space - increment end
* add the element

done!

Implementation




What happens if a thread wants
to add an element?

Think concurrently:

Two threads cannot reserve the same space!
We've seen this before

Implementation




What happens if a thread wants to add an element?

Think concurrently:

```
reserved_index = atomic_fetch_add(&end, 1);
```

Implementation



Thread 0:
enq(6);


Thread 1:
enq(7);

What happens if a thread wants to add an element?

Think concurrently:

```
reserved_index = atomic_fetch_add(&end, 1);
```

Implementation



Thread 0:
enq(6);

Thread 1:
enq(7);


What happens if a thread wants to add an element?

Think concurrently:

```
reserved_index = atomic_fetch_add(&end, 1);
```

Implementation

does it matter which order threads add their data?



Thread 0:
enq(6);

Thread 1:
enq(7);


What happens if a thread wants to add an element?

Think concurrently:

```
reserved_index = atomic_fetch_add(&end, 1);
```

Implementation

does it matter which order threads add their data?



Thread 0:
enq(6);

Thread 1:
enq(7);


What happens if a thread wants to add an element?

Think concurrently:

```
reserved_index = atomic_fetch_add(&end, 1);
```

Implementation

does it matter which order threads add their data? No! Because there are no deqs!



Thread 0:
enq(6);

Thread 1:
enq(7);

What happens if a thread wants to add an element?

Think concurrently:

```
reserved_index = atomic_fetch_add(&end, 1);
```

```
class InputOutputQueue {
  private:
    atomic_int end;
    int list[SIZE];

  public:
     InputOutputQueue() {
        end = 0;
     }

     void enq(int x) {
        int reserved_index = atomic_fetch_add(&end, 1);
        list[reserved_index] = x;
     }

     int size() {
        return end.load();
     }
 }
```

```
class InputOutputQueue {
  private:
    atomic_int end;
    int list[SIZE];

  public:
     InputOutputQueue() {
        end = 0;
     }

     void enq(int x) {
        int reserved_index = atomic_fetch_add(&end, 1);
        list[reserved_index] = x;
     }

     int size() {
        return end.load();
     }
 }
```

How to protect against overflows?

```
class InputOutputQueue {
  private:
    atomic_int end;
    int list[SIZE];


  public:
    InputOutputQueue() {
       end = 0;
    }

     boolean enq(int x) {
        int reserved_index = atomic_fetch_add(&end, 1);
        if (reserved_index >= SIZE) {
           atomic_fetch_sub(&end, 1); // give the reservation back
           return false;
        }
        list[reserved_index] = x;
        return true;
     }

     int size() { return min(end.load(), SIZE); }
 }
```


What about Input?

- Now we only do deqs




What about Input?

- Now we only do deqs



What about Input?

- Now we only do deqs




What happens if a thread wants to dequeue an element?

Think concurrently:

```
data_index = atomic_fetch_add(&front, 1);
```

What about Input?

- Now we only do deqs



Thread 0:
deq();

Thread 1:
deq();


What happens if a thread wants to dequeue an element?

Think concurrently:

```
data_index = atomic_fetch_add(&front, 1);
```

What about Input?

- Now we only do deqs



Thread 0:
deq();

Thread 1:
deq();


What happens if a thread wants to dequeue an element?

Think concurrently:

```
data_index = atomic_fetch_add(&front, 1);
```

What about Input?

- Now we only do deqs



Thread 0:
deq(); // reads 6

Thread 1:
deq(); // reads 7

What happens if a thread wants to dequeue an element?

Think concurrently:

```
data_index = atomic_fetch_add(&front, 1);
```

```
class InputOutputQueue {
  private:
    atomic_int front;
    atomic_int end;
    int list[SIZE];

  public:
    InputOutputQueue() {
        front = end = 0;
     }

     void enq(int x) {
        int reserved_index = atomic_fetch_add(&end, 1);
        list[reserved_index] = x;
     }

     void deq() {
       int reserved_index = atomic_fetch_add(&front, 1);
       return list[reserved_index];
     }

     int size() {
        return ??;
     }
 }
```

```
class InputOutputQueue {
  private:
    atomic_int front;
    atomic_int end;
    int list[SIZE];

  public:
    InputOutputQueue() {
        front = end = 0;
     }

     void enq(int x) {
        int reserved_index = atomic_fetch_add(&end, 1);
        list[reserved_index] = x;
     }

     void deq() {
       int reserved_index = atomic_fetch_add(&front, 1);
       return list[reserved_index];
     }

     int size() {
        return ??;
     }
 }
```

How about size?

```
class InputOutputQueue {
  private:
    atomic_int front;
    atomic_int end;
    int list[SIZE];

  public:
    InputOutputQueue() {
        front = end = 0;
     }

     void enq(int x) {
        int reserved_index = atomic_fetch_add(&end, 1);
        list[reserved_index] = x;
     }

     void deq() {
       int reserved_index = atomic_fetch_add(&front, 1);
       return list[reserved_index];
     }

     int size() {
        return end.load() - front.load();
     }
 }
```

how about size?

how do we reset?

```
class InputOutputQueue {
  private:
    atomic_int front;
    atomic_int end;
    int list[SIZE];

  public:
    InputOutputQueue() {
        front = end = 0;
     }

     void enq(int x) {
        int reserved_index = atomic_fetch_add(&end, 1);
        list[reserved_index] = x;
     }

     void deq() {
       int reserved_index = atomic_fetch_add(&front, 1);
       return list[reserved_index];
     }

     int size() {
        return end.load() - front.load();
     }
 }
```

how about size?

how do we reset?
Reset front and end

```
class InputOutputQueue {
  private:
    atomic_int front;
    atomic_int end;
    int list[SIZE];

  public:
    InputOutputQueue() {
        front = end = 0;
     }

     void enq(int x) {
        int reserved_index = atomic_fetch_add(&end, 1);
        list[reserved_index] = x;
     }

     void deq() {
       int reserved_index = atomic_fetch_add(&front, 1);
       return list[reserved_index];
     }

     int size() {
        return end.load() - front.load();
     }
 }
```

how about size?

how do we reset?
Reset front and end

does the list need
to be atomic?

```
class InputOutputQueue {
  private:
    atomic_int front;
    atomic_int end;
    int list[SIZE];

  public:
    InputOutputQueue() {
        front = end = 0;
     }

     void enq(int x) {
        int reserved_index = atomic_fetch_add(&end, 1);
        list[reserved_index] = x;
     }

     void deq() {
       int reserved_index = atomic_fetch_add(&front, 1);
       return list[reserved_index];
     }

     int size() {
        return end.load() - front.load();
     }
 }
```

how about size?

how do we reset?
Reset front and end

does the list need
to be atomic?
No, its elements are
not concurrently accessed

Quiz 9.

Input/output queues use atomic increments and decrements to protect against threads that are trying to concurrently enqueue and dequeue

Select one

A. True

B. False

Scan to answer

forms.gle/B93D4MK5Vdf3z4426

Producer Consumer Queues

- 1 thread enqueues, 1 thread dequeues
  - enq’er cannot deq
  - deq’er cannot enq

- Example: printf:
  - your program enqueues values to print
  - the terminal process dequeues values and prints them

Quiz 9.

The performance of an application using a producer-consumer queue depends most on:

Select one

A. If the queue is implemented using mutex or not

B. The rate at which the consumer enqueues elements

C. The rate at which the producer enqueues elements

Scan to answer

forms.gle/5wAVCbhdhbkkpdpd6

Synchronous Producer Consumer Queues

- First implementation:
  - Synchronous
  - Slow
  - Good for debugging

Synchronous Producer Consumer Queues


- First implementation:
  - Synchronous
  - Slow
  - Good for debugging

- enq does not return until value is deq’ed

Synchronous Producer Consumer Queues

Producer Thread


```
enq(7);
```




Consumer Thread

```
deq();
```


Synchronous Producer Consumer Queues



Synchronous Producer Consumer Queues



Synchronous Producer Consumer Queues



Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
```



Consumer Thread

```
deq();
```

both can continue

Synchronous Producer Consumer Queues

Producer Thread

```
sleep();
enq(7);
```




Consumer Thread

```
deq();
```

Synchronous Producer Consumer Queues

Producer Thread

```
sleep();
enq(7);
```




wait


Consumer Thread

```
deq();
```

Synchronous Producer Consumer Queues



Synchronous Producer Consumer Queues




They both can continue

Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
```




Consumer Thread

```
deq();
```

Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
```



Consumer Thread


```
deq();
```

Can the consumer just read?

Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
```



Consumer Thread


```
deq();
```

Can the consumer just read?
Needs to wait for a value to appear

Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
```



Consumer Thread


```
deq();
```

flag


Can the consumer just read?
Needs to wait for a value to appear

Spin waiting for the flag to turn green


Synchronous Producer Consumer Queues




Synchronous Producer Consumer Queues



Synchronous Producer Consumer Queues




Synchronous Producer Consumer Queues



Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
```



flag

Consumer Thread

```
deq();
```


```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
    }
  }
```

Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
```



flag

Consumer Thread


```
deq();
deq();
```

what happens when there are two deqs?

```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
    }
  }
```


Synchronous Producer Consumer Queues




```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
    }
  }
```

Synchronous Producer Consumer Queues





```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
    }
  }
```

what happens in the next deq?

How to fix?


Synchronous Producer Consumer Queues




```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```


Synchronous Producer Consumer Queues




```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```


Synchronous Producer Consumer Queues




```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```

Synchronous Producer Consumer Queues




```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```


waiting like we are supposed to

Synchronous Producer Consumer Queues

reset (now with extra enq)

Producer Thread

```
enq(7);
enq(8);
```



Consumer Thread

```
deq();
deq();
```

extra enq


```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```

Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
enq(8);
```



Consumer Thread

```
deq();
deq();
```


```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```

Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
enq(8);
```



Consumer Thread

```
deq();
deq();
```

```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```

Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
enq(8);
```



Consumer Thread

```
deq();
deq();
```

7 was dropped!


how to fix?

```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```

Synchronous Producer Consumer Queues

reset



Producer Thread

```
enq(7);
enq(8);
```

Consumer Thread

```
deq();
deq();
```


```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
      // wait for flag to be reset
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```

Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
enq(8);
```



Consumer Thread

```
deq();
deq();
```


```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
      // wait for flag to be reset
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```

Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
enq(8);
```



Consumer Thread

```
deq();
deq();
```


```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
      // wait for flag to be reset
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```

Synchronous Producer Consumer Queues

Producer Thread

```
enq(7);
enq(8);
```



Consumer Thread


```
deq();
deq();
```

```
class SyncQueue {
  private:
    atomic_int box;
    atomic_bool flag;

  public:
    void enq(int x) {
      // put value in box
      // set flag
      // wait for flag to be reset
    }
    void deq() {
      // wait for flag to be set
      // read from the box
      // reset flag
    }
  }
```


Producer Consumer Queues

- Asynchronous:



Producer Consumer Queues


- Asynchronous:



no waiting for producer (while there is room)

Producer Consumer Queues


- Asynchronous:



no waiting for producer (while there is room)

Producer Consumer Queues


- Asynchronous:



no waiting for producer (while there is room)

Producer Consumer Queues


- Asynchronous:



no waiting for producer (while there is room)

Producer Consumer Queues

- Asynchronous:




no waiting for producer (while there is room)

when there is no room, the queue will wait

Producer Consumer Queues

- Asynchronous:




no waiting for producer (while there is room)

returns 7

when there is no room, the queue will wait

Producer Consumer Queues

- Asynchronous:




no waiting for producer (while there is room)

returns 7

when there is no room, the queue will wait

Producer Consumer Queues

- Asynchronous:




no waiting for producer (while there is room)

returns 7

when there is no room, the queue will wait

Producer Consumer Queues

- Asynchronous:




no waiting for producer (while there is room)

returns 7

when there is no room, the queue will wait

Producer Consumer Queues

- Asynchronous:




no waiting for producer (while there is room)

returns 7

when there is no room, the queue will wait

Producer Consumer Queues

- Asynchronous:




no waiting for producer (while there is room)

returns 8

when there is no room, the queue will wait

Producer Consumer Queues

- Asynchronous:




no waiting for producer (while there is room)

returns 8

when there is no room, the queue will wait

Producer Consumer Queues

- Asynchronous:




no waiting for producer (while there is room)

returns 8

when there is no room, the queue will wait

Producer Consumer Queues


- Asynchronous:



returns 9


Producer Consumer Queues

- Asynchronous:




Producer Consumer Queues

- Asynchronous:




Producer Consumer Queues

- Asynchronous:



Producer Consumer Queues

- Asynchronous:



blocks when there is nothing in the queue

Producer Consumer Queues

- How do we implement it?

Producer Consumer Queues

- Start with a fixed size array



Producer Consumer Queues


- Start with a fixed size array



We will use what is called a *circular buffer method*

Producer Consumer Queues


- Start with a fixed size array



conceptually it is a circle

Producer Consumer Queues


- Start with a fixed size array



conceptually it is a circle

Producer Consumer Queues

- Start with a fixed size array




indexes will circulate in order and wrap around

conceptually it is a circle

Producer Consumer Queues

- Start with a fixed size array



indexes will circulate in order and wrap around


we will assume modular arithmetic:

if x = (SIZE - 1) then
x + 1 == 0;

conceptually it is a circle

Producer Consumer Queues

- Start with a fixed size array



indexes will circulate in order and wrap around


Two variables to keep track of where to deq and enq:

head and tail

conceptually it is a circle

Producer Consumer Queues

- Start with a fixed size array



indexes will circulate in order and wrap around

Two variables to keep track of where to deq and enq:

head and tail:


enq to the head, deq from the tail

valid items in the queue

conceptually it is a circle

Producer Consumer Queues

- Start with a fixed size array



indexes will circulate in order and wrap around

Two variables to keep track of where to deq and enq:


head and tail

Empty queue is when head == tail

conceptually it is a circle

Producer Consumer Queues

- Start with a fixed size array



indexes will circulate in order and wrap around

Two variables to keep track of where to deq and enq:

head and tail


Empty queue is when
head == tail

Full queue is when
head == tail?

conceptually it is a circle

Producer Consumer Queues

- Start with a fixed size array



indexes will circulate in order and wrap around

Two variables to keep track of where to deq and enq:

head and tail

Empty queue is when head == tail


Full queue is when head == tail?

but then how to tell full queue from empty?

conceptually it is a circle

Producer Consumer Queues

- Start with a fixed size array



indexes will circulate in order and wrap around

Two variables to keep track of where to deq and enq:

head and tail

Empty queue is when
head == tail

Full queue is when
head + 1 == tail

wasting one location, but its okay...

conceptually it is a circle

Quiz 9.

A circular buffer is:

Select one


A. A useful data representation for fixed-length queues

B. Part of the C++ standard library

C. A special type of memory that is organized in circular patters


Scan to answer

forms.gle/ZdqkrLPvwJfus3o3A





```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
}
```





```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
}
```





```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
}
```




```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];


  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
    int deq() {
      // get value at tail
      // increment tail
    }
}
```




```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
    int deq() {
      // get value at tail
      // increment tail
    }
}
```


This looks like the two threads don't even share head and tail! What is missing?




```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];


  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
    int deq() {
      // get value at tail
      // increment tail
    }
}
```

what happens if we try to dequeue here?





```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
    int deq() {
      // wait while queue is empty
      // get value at tail
      // increment tail
    }
}
```





```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
    int deq() {
      // wait while queue is empty
      // get value at tail
      // increment tail
    }
}
```





```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
    int deq() {
      // wait while queue is empty
      // get value at tail
      // increment tail
    }
}
```





```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
    int deq() {
      // wait while queue is empty
      // get value at tail
      // increment tail
    }
}
```




```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
    int deq() {
      // wait while queue is empty
      // get value at tail
      // increment tail
    }
}
```





```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
    int deq() {
      // wait while queue is empty
      // get value at tail
      // increment tail
    }
}
```

similarly for enqueue


but why can't we enqueue?




```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // store value at head
      // increment head
    }
    int deq() {
      // wait while queue is empty
      // get value at tail
      // increment tail
    }
}
```

incrementing the head would make it empty!





```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // wait for there to be room
      // store value at head
      // increment head
    }
    int deq() {
      // wait while queue is empty
      // get value at tail
      // increment tail
    }
}
```

we need to wait for there to be room


Other questions:



valid items in the queue

```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // wait for there to be room
      // store value at head
      // increment head
    }
    int deq() {
      // wait while queue is empty
      // get value at tail
      // increment tail
    }
}
```



valid items in the queue

Other questions:

Do these need to be atomic RMWs?

Remember 1 thread enqueues and 1 thread dequeues

```
class ProdConsQueue {
  private:
    atomic_int head;
    atomic_int tail;
    int buffer[SIZE];

  public:
    void enq(int x) {
      // wait for there to be room
      // store value at head
      // increment head
    }
    int deq() {
      // wait while queue is empty
      // get value at tail
      // increment tail
    }
}
```