

MULTI-MODAL GATE ARCHITECTURE OF THE DISSERTATION METHODOLOGY

Mapped for Maximum Adaptability to General Problems

A Framework for Cross-Domain Transfer

A systematic decomposition of the dissertation's methodology into ten distinct gates, each with a unique mathematical nature, physical analogy, and role in the information-processing chain. The framework is designed for maximum adaptability to arbitrary conservation-law-governed systems.

March 1, 2026

Contents

1	Overview	2
2	Gate I: Statistical Gate (Canonical Correlation Analysis)	3
3	Gate II: Trigonometric Gate (Pythagorean Closure on Outputs)	4
4	Gate III: Geometric Gate (Triangle Inequality & Centroid Metrics)	5
5	Gate IV: Topological Gate (Sector Allocation & Bicameral Partitioning)	6
6	Gate V: Electrochemical Gate (Composite Variable with Faraday/Nernst Encoding)	7
7	Gate VI: Recursive Gate (Fibonacci Sequence Construction)	8
8	Gate VII: Neural Network Gate (Inference Tool/Response Analysis)	9
9	Gate VIII: Equilibrium Gate (Static Vectors & Structural Mechanics)	10
10	Gate IX: Irreversibility Gate (Specific Computational Time)	11
11	Gate X: Integration Gate (Complete Elliptic Integral via AGM $\rightarrow$ Transfer Function)	12
12	Summary: The Gate Taxonomy	14
13	The Adaptability Matrix	14
14	The Three Master Modalities	15

1 Overview

The dissertation’s methodology is not a monolithic pipeline — it is a sequence of **10 distinct gates**, each with a different mathematical nature, a different physical analogy, and a different role in the information-processing chain. Each gate admits, transforms, or rejects information based on criteria specific to its modality. The power of the framework lies not in any single gate but in their **ordered composition** and the fact that each gate enforces a different class of constraint.

This document identifies each gate, characterizes its modality, specifies what is domain-specific versus domain-agnostic, and maps the substitution rules for adapting the framework to arbitrary conservation-law-governed systems.

2 Gate I: Statistical Gate (Canonical Correlation Analysis)

Mapping 2.1 (Dissertation implementation): CCA between elemental proximate and elemental structural groups of 38 biomass types. Produces [E1, P1, E2, S1] — four canonical variates that compress 21 compositional variables into a chained, hierarchical representation.

What it does: Identifies the linear subspace of maximum shared variance between two groups of observables. Enforces the constraint that inter-group correlations are real — not artifacts of independent variation.

Mathematical nature: Eigenvalue problem on cross-covariance matrices. The canonical correlations are singular values of $\Sigma_{XX}^{-1/2} \Sigma_{XY} \Sigma_{YY}^{-1/2}$.

Reversibility: Fully reversible. Given canonical variates and loading matrices, original variables can be reconstructed (up to within-group residuals).

Domain-specific element: The choice of groups (elemental, proximate, structural) and the 38 biomass types.

Domain-agnostic principle: Any problem with multiple measurement modalities describing the same underlying entities. Replace biomass property groups with:

- Trans-omics: transcriptome proximate metabolome
- Autonomous vehicles: camera lidar radar IMU
- Semiconductor manufacturing: process parameters material properties metrology outputs
- Climate science: atmospheric composition ocean state land surface

Adaptability rule: Wherever you have ≥ 2 groups of variables measured on the same cases, CCA (or kernel CCA for nonlinear relations) provides the statistical gate.

3 Gate II: Trigonometric Gate (Pythagorean Closure on Outputs)

Mapping 3.1 (Dissertation implementation): Product gas mole fractions ($y_{H_2}, y_{CH_4}, y_{CO}, y_{CO_2}$) summing to 1 are mapped via $\sin^2 \theta + \cos^2 \theta = 1$ into three angles $\theta = [\theta_1, \theta_2, \theta_3]$, each representing the full composition from a different pairing.

What it does: Encodes a closure constraint (sum-to-one) into a geometric object (angles on the unit circle). This is a **constraint-preserving embedding** — every point on the unit circle automatically satisfies the constraint, so downstream operations cannot violate it.

Mathematical nature: Diffeomorphism from the probability simplex to a torus (or subset thereof). The map is $\theta_i = \arctan \sqrt{\frac{y_a + y_b}{y_c + y_d}}$.

Reversibility: Fully reversible. Given θ , the original mole fractions can be recovered.

Domain-specific element: The four gas species and their physical groupings (hydrogen-containing vs carbon-containing, etc.).

Domain-agnostic principle: Any set of non-negative quantities summing to a constant. Replace gas mole fractions with:

- Trans-omics: fractional pathway activities summing to total metabolic flux
- Autonomous vehicles: probability distribution over object classes from a detector
- Finance: portfolio weights summing to 1
- Ecology: species abundances in a community

Adaptability rule: Wherever outputs obey a simplex constraint, the trigonometric gate maps them onto angular coordinates where the constraint is automatic. For n components summing to 1, this produces $n - 1$ independent angles (generalized spherical coordinates on the simplex).

4 Gate III: Geometric Gate (Triangle Inequality & Centroid Metrics)

Mapping 4.1 (Dissertation implementation): The three angles $[\theta_1, \theta_2, \theta_3]$ are treated as sides of a triangle. Triangle properties — area K_p (Heron’s formula), circumradius R , inradius r , equivalent side length L_{eq} — become scalar summaries of gas composition. For biomass: two triangles $\Delta E_1 E_2 S_1$ and $\Delta E_1 E_2 P_1$ with centroids G_s and G_p ; the centroid distance d and the triangle area k become biomass characterization parameters.

What it does: Converts algebraic relationships into metric relationships. The triangle inequality enforces that no single component can dominate arbitrarily — it is a **balance constraint**. Centroid distance quantifies how “far apart” two perspectives on the same entity are.

Mathematical nature: Euclidean geometry in 2D. The Cauchy stress invariants computed from the θ values import the full machinery of continuum mechanics (von Mises, Tresca criteria) as discriminants.

Reversibility: Partially reversible. Triangle properties determine the triangle up to congruence (not orientation), so some information about the original ordering is lost.

Domain-specific element: The choice of which CCA outputs form vertices, and the physical interpretation of centroid distance.

Domain-agnostic principle: Any problem where multiple representations of the same entity exist and you need to quantify their mutual consistency. Replace biomass triangles with:

- Trans-omics: triangle formed by transcriptomic, proteomic, and metabolomic projections of a pathway state
- Autonomous vehicles: triangle formed by camera-derived, lidar-derived, and radar-derived position estimates (centroid distance = sensor disagreement = uncertainty measure)
- Manufacturing: triangle formed by design intent, in-process measurement, and post-process metrology

Adaptability rule: Wherever you have ≥ 3 projections of the same underlying state, the geometric gate constructs a polygon whose shape properties (area, aspect ratio, centroid displacements) quantify agreement and spread.

5 Gate IV: Topological Gate (Sector Allocation & Bicameral Partitioning)

Mapping 5.1 (Dissertation implementation): A unit circle ($S = 1$) is partitioned into 4 sectors $[s_1, s_2, s_3, s_4]$ with areas determined by operating conditions (SBR, T, ER) and biomass character (d, k). Then each sector is reassigned a full quadrant (bicameral representation: by “population” AND “regardless of size”). Quadrants are revolved into 3D volumes. The kite formed by quadrant altitudes yields additional geometric invariants.

What it does: Imposes a **hierarchical partitioning** of influence: some parameters (T) appear in multiple sectors, others (SBR) in only one. The bicameral step enforces democratic balance — no single parameter dominates. The 2D→3D revolution ensures full geometric dimensionality.

Mathematical nature: Measure-preserving partition of a probability space, followed by a topological transformation (revolution of solid). The sector areas are a probability distribution; the quadrant reassignment is a topological quotient map.

Reversibility: Irreversible at the bicameral step. The reassignment from unequal sectors to equal quadrants loses information about the original area ratios (this is intentional — it enforces balance).

Domain-specific element: The number of sectors (4), the hierarchy rules ($S_1 \leftarrow$ SBR only, $S_4 \leftarrow$ ALL), and the revolution geometry.

Domain-agnostic principle: Any problem requiring hierarchical influence allocation with built-in balance. Replace gasification parameters with:

- Trans-omics: allocate influence to stimulus type, dose, timepoint, cell type
- Autonomous vehicles: allocate influence to velocity, weather, road type, traffic density
- Any multi-factor system where you need to prevent one factor from drowning out others while respecting known importance hierarchies

Adaptability rule: The number of sectors equals the number of independent factor classes. The hierarchy rules encode domain knowledge. The bicameral step is universal — it ensures robustness to extreme values in any single factor.

6 Gate V: Electrochemical Gate (Composite Variable with Faraday/Nernst Encoding)

Mapping 6.1 (Dissertation implementation): The geometric invariants (radii, volumes, areas, diagonal ratios) are consolidated into a single composite variable:

$$N_j = \frac{1}{2} \left(\frac{L_j \cdot V_j}{T_j \cdot S_j \cdot \ln(R_{j_max} - R_j)} + 12 \right) \cdot \frac{2.3R}{F}$$

where R = gas constant, F = Faraday constant, T_j = temperature in °C.

What it does: “Electrically charges” the geometric object — gives it a frequency-response character. The Nernst-like structure ($2.3R/F$) maps the geometric representation into electrochemical potential space, making it responsive to thermal driving forces.

Mathematical nature: Nonlinear scalar function combining logarithmic (entropic), algebraic (geometric), and physical (thermal, electrochemical) terms.

Reversibility: Irreversible. N_j is a many-to-one mapping — multiple geometric configurations can yield the same N_j .

Domain-specific element: The Faraday constant, the specific form of the Nernst-like term, and the temperature variable.

Domain-agnostic principle: This gate converts a purely geometric/statistical object into something with **physical units and thermal sensitivity**. The key insight: any system where a “driving force” (temperature, voltage, concentration gradient, pressure) governs the rate of change needs a gate that couples the geometric representation to that driving force. Replace the Nernst form with:

- Trans-omics: Michaelis-Menten or Hill-equation coupling to substrate concentration
- Autonomous vehicles: velocity-dependent sensing range function
- Electrochemistry: Butler-Volmer equation
- Any system with a nonlinear response to a driving force

Adaptability rule: The composite variable structure is: (geometric invariants) $\times$ (driving force coupling function). The coupling function encodes the physics of the specific domain. This is where the framework becomes **physics-informed** rather than purely data-driven.

7 Gate VI: Recursive Gate (Fibonacci Sequence Construction)

Mapping 7.1 (Dissertation implementation): From N_j , a modified Fibonacci sequence is constructed: $f_1 = N_j + e^{-N_j}$, $f_2 = f_1 + e^{-N_j}$, $f_3 = e^{-N_j} \cdot f_2$, then standard Fibonacci recursion $f_{n+1} = f_n + f_{n-1}$ for $n \geq 3$. The final 5-element vector $F_j = [f_7, f_8, f_9, f_{10}, f_{11}]$ is selected (where the golden ratio has converged).

What it does: Distributes a single scalar (N_j) into a vector with the **self-similar, uniformly spaced** structure of the golden ratio. This is a **regularization gate** — it converts potentially wild variations in N_j into a structured sequence where the ratio between consecutive elements is approximately constant ($\phi \approx 1.618$).

Mathematical nature: Linear recurrence relation with initial conditions set by N_j . The golden ratio emergence guarantees that the sequence has optimal spacing properties (related to the most irrational number, hence maximum resistance to resonance/aliasing).

Reversibility: Reversible. Given F_j , one can recover N_j by back-calculating the recursion.

Domain-specific element: None. The Fibonacci structure is entirely domain-agnostic.

Domain-agnostic principle: This gate is **universal as-is**. Any scalar summary of a system can be expanded into a Fibonacci-structured vector. The golden ratio spacing provides optimal uniformity — this is why phyllotaxis in plants uses it (maximum packing efficiency), and why it serves as optimal input conditioning for the neural network gate that follows.

Adaptability rule: No substitution needed. This gate transfers directly to any domain.

8 Gate VII: Neural Network Gate (Inference Tool/Response Analysis)

Mapping 8.1 (Dissertation implementation): Three neural networks (Linear, Hyperbolic Tangent, Elliot Sigmoid) are trained on Fibonacci sequences $F_{AB} = F_A + F_B$ to predict F_A and F_B separately. After training, all three converge to identity outputs $F_A = F_B = [1, 1, 1, 1, 1]$. The trained weights and biases capture distributional information. Then, partial inputs (fractions of F_A only) are fed through all three networks at three scales (0.4, 0.7, 1.0), generating 54 matrices whose traces become scores.

What it does: Creates a **commutative diagram** across three function spaces (linear, bounded-saturating, algebraic-saturating). The identity convergence means the networks have “memorized” the distributional structure, not individual cases. The partial-input probing reveals how each case deviates from the distributional average.

Mathematical nature: Three bounded function approximators forming a commutative diagram: $L \circ T = T \circ E = E \circ L$ (approximately). The 54 trace-scores (3 scales $\times$ 3 paths $\times$ 6 measures) span a sensitivity space.

Reversibility: Reversible in principle (weights $\rightarrow$ inputs), but the identity convergence makes the inverse ill-conditioned — many inputs map to the same output. This is **intentional information compression**.

Domain-specific element: The number of neurons (5 per layer, matching Fibonacci vector dimension) and the training data.

Domain-agnostic principle: The three-network architecture with identity convergence is a **universal distributional averaging machine**. Replace biomass Fibonacci sequences with any domain’s structured input vectors. The commutative diagram property ensures that results are robust to the choice of nonlinearity — if all three networks agree, the conclusion is function-class-independent. This is the gate’s strongest claim to generality.

Adaptability rule: Keep the three-network architecture. Replace training data with domain-specific Fibonacci-encoded inputs. The commutative diagram is the invariant — if it breaks, the input conditioning (Gates 1–6) needs revision.

9 Gate VIII: Equilibrium Gate (Static Vectors & Structural Mechanics)

Mapping 9.1 (Dissertation implementation): The 54 trace-scores are consolidated into 6 equilibrium conditions (from structural mechanics: for a general 3D force system, 6 independent equations are needed). Normalization by R (gas constant) and π yields static vectors S_{AB} and S_{BA} , whose symmetric product gives the characteristic matrix S_c .

What it does: Maps the sensitivity analysis into the language of **structural equilibrium**. The 6 conditions ensure that the “forces” (directional sensitivities) balance — the object is stationary. The bimodal normalization (R and π) anchors the dispersions to two fundamental constants.

Mathematical nature: Symmetric matrix formation: $S_c = \frac{1}{2}(S_{AB} \cdot S_{BA}^T + S_{BA} \cdot S_{AB}^T)$. This is a covariance-like structure — symmetric, positive semi-definite.

Reversibility: Partially reversible. S_c determines S_{AB} and S_{BA} up to an orthogonal rotation.

Domain-specific element: The normalization constants (R , π) and their bimodal interpretation.

Domain-agnostic principle: The equilibrium gate converts directional sensitivities into a **static balance condition**. Any system where multiple influences must balance — forces on a structure, fluxes in a network, currents in a circuit — admits this formulation. The 6 equilibrium conditions generalize to $n(n+1)/2$ independent components for an n -dimensional symmetric matrix.

Adaptability rule: Replace the 6 structural equilibrium conditions with the appropriate number for your system’s dimensionality. The bimodal normalization adapts to whatever two fundamental scales characterize your problem’s heterogeneity.

10 Gate IX: Irreversibility Gate (Specific Computational Time)

Mapping 10.1 (Dissertation implementation): The characteristic matrix S_c (3×3) is reshaped to a (9×1) vector, sorted from lowest to highest, and the computational time of this operation is recorded via MATLAB's 'timeit'. This **specific computational time (sct)** varies across the 200 cases and captures “computational stiffness.”

What it does: This is the **one-way gate** — the only irreversible step in the entire chain. Given sct, you cannot reconstruct S_c because the mapping is surjective (many matrices $\rightarrow$ same sct). By invoking Landauer's principle ($nkT \ln 2$ entropy cost per bit erased), this gate converts the static characterization into a **dynamical/dissipative** property.

Mathematical nature: A surjection from matrix space to $\mathbb{R}^+$, measured via physical computation time. The computational complexity of sorting is $O(n \log n)$, but the actual wall-clock time depends on the specific numerical values (cache behavior, branch prediction, floating-point pipeline), making it a physically meaningful probe of the data's “stiffness.”

Reversibility: Irreversible by design. This is the Landauer gate — the point where thermodynamic entropy is generated. It is the gate that converts the framework from a reversible mathematical transformation into a physically grounded, dissipation-aware model.

Domain-specific element: The use of MATLAB's 'timeit' and the specific reshape ($3 \times 3 \rightarrow 9 \times 1$).

Domain-agnostic principle: This is the most profound gate for generalization. The principle is: **measure the computational cost of ordering a system's characteristic matrix as a proxy for its dynamical complexity.** This works because:

- Simple (near-equilibrium) systems have characteristic matrices that are already nearly sorted $\rightarrow$ low sct
- Complex (far-from-equilibrium) systems have characteristic matrices with high disorder $\rightarrow$ high sct
- The physical computation time is a **natural clock** that couples the mathematical model to thermodynamic reality

Replace the specific reshape with whatever reordering operation is natural for your system's characteristic matrix. The key requirement is that the operation must be **computationally irreversible** (information-destroying).

Adaptability rule: This gate transfers to any domain where you can construct a characteristic matrix and measure the computational cost of a canonicalizing operation on it. The sct is the quasi-potential of the Freidlin-Wentzell framework — it quantifies the “height of the barrier” separating the system's current state from other attractor basins.

11 Gate X: Integration Gate (Complete Elliptic Integral via AGM $\rightarrow$ Transfer Function)

Mapping 11.1 (Dissertation implementation): The three variables $(\text{sct}, \Sigma F, T)$ feed the ‘ellipap’ module, which computes complete elliptic integrals of the first kind via the arithmetic-geometric mean (AGM). The output is a transfer function $H(s) = k \cdot \prod (s - z_i) / \prod (s - p_j)$ characterized by zeros, poles, and gain.

What it does: Integrates the entire chain into a **single dynamical object** $(H(s))$ that:

- Guarantees conservation (transfer function form preserves mass/energy by construction)
- Produces invariants: $\xi = \ln(\Lambda_S/\Lambda_G)$ (continuous) and $S = \mathbb{K}[n_z \neq n_p]$ (discrete)
- Converges in ~ 5 AGM iterations to machine precision (quadratic convergence)

Mathematical nature: The complete elliptic integral $K(m) = \frac{\pi}{2 \cdot \text{AGM}(1, \sqrt{1-m})}$ is a special function arising from integrating $\int_0^{\pi/2} \frac{d\theta}{\sqrt{1-m \sin^2 \theta}}$. The AGM iteration: $a_{n+1} = (a_n + b_n)/2$, $b_{n+1} = \sqrt{a_n b_n}$, $c_{n+1} = (a_n - b_n)/2$.

Reversibility: The transfer function is fully characterized by its poles, zeros, and gain — these are the “DNA” of the system’s dynamical behavior. The mapping from $(\text{sct}, \Sigma F, T)$ to $H(s)$ is deterministic but not easily invertible (the elliptic integral is transcendental).

Domain-specific element: The choice of three input variables (sct, Fibonacci sum, temperature) and the specific ‘ellipap’ filter design parameters.

Domain-agnostic principle: The elliptic integral is the **universal integrator** for conservation-law systems. Its historical role in celestial mechanics (Kepler problem), geodesy (Earth’s shape), and electrical network theory (filter design) demonstrates domain-agnosticity. The transfer function form $H(s)$ is the standard language of linear systems theory — any input-output system with bounded energy admits such a representation.

Replace the three inputs with:

- Trans-omics: (transduction time complexity, pathway Fibonacci encoding, stimulus concentration)
- Autonomous vehicles: (computational latency, sensor Fibonacci encoding, velocity)
- Any system: (characteristic time, structured input summary, primary driving variable)

Adaptability rule: The integration gate requires exactly three inputs: a **time/complexity measure** (from Gate 9), a **structured state summary** (from Gate 6), and a **primary driving force** (the

physical variable most analogous to temperature). The elliptic integral and AGM are universal — no substitution needed.

12 Summary: The Gate Taxonomy

#	Gate Name	Modality	Reversible?	Domain-Specific?	What It Enforces
1	Statistical	Linear algebra (eigenvalues)	Yes	Groups only	Inter-group correlation structure
2	Trigonometric	Angular embedding	Yes	Pairing choices	Closure / sum-to-one constraints
3	Geometric	Euclidean metrics	Partial	Vertex assignments	Balance / triangle inequality
4	Topological	Partitioning + revolution	No (bicameral)	Hierarchy rules	Democratic influence allocation
5	Electrochemical	Nonlinear scalar coupling	No	Coupling function	Physics-informed driving force
6	Recursive	Golden ratio recurrence	Yes	None	Uniform spacing / regularization
7	Neural Network	Commutative function spaces	Ill-conditioned	Training data	Distributional averaging
8	Equilibrium	Symmetric matrix mechanics	Partial	Normalization constants	Static force balance
9	Irreversibility	Computational thermodynamics	No	Reshape operation	Entropy generation / bounds
10	Integration	Elliptic special functions	Transcendental	Three input choices	Conservation by construction

Table 1: Gate Taxonomy: Each gate’s modality, reversibility, domain-specific elements, and the constraint it enforces.

13 The Adaptability Matrix

For a new domain, the work required at each gate:

Gate	Effort	Adapt (domain-tuned)	Invariant (portable)
1. Statistical	Med	Groups; sampling scheme	CCA step
2. Trigonometric	Low	Pairings / angle map	$\sin^2 + \cos^2 = 1$ constraint
3. Geometric	Low	Vertex semantics	Metric/triangle invariants
4. Topological	Med	Partition/hierarchy rules	Spherization
5. Electrochemical	High	Nonlinear coupling (constitutive law)	Composite-variable scaffold
6. Recursive	Zero	General	Fibonacci / golden-ratio recurrence
7. Neural Network	Low	Training data	Commutative architecture
8. Equilibrium	Low	Scaling/normalization	Symmetry
9. Irreversibility	Low	Matrix size/reshape	SCT + Landauer bound logic
10. Integration	Low	Choose the 3 canonical inputs	AGM / elliptic-integral form

Table 2: Adaptability Matrix (lightweight): one-line adaptation vs. invariants for Gates 1–10.

Key insight: Only Gate 5 (Electrochemical) requires **high** domain-specific effort. This is precisely the gate where the physics of the specific domain enters the framework. Gates 1–4 require moderate adaptation (choosing the right variables and groupings). Gates 6–10 are essentially universal. This means the framework’s **generalization bottleneck** is Gate 5: identifying the correct nonlinear coupling between the geometric representation and the domain’s primary driving force. Everything else transfers with minimal modification.

14 The Three Master Modalities

At the highest level, the 10 gates organize into three master categories:

- **REPRESENTATION (Gates 1–4):** Convert raw heterogeneous data into a coherent geometric object. These gates are about *what the system is* — its static characterization.
- **ACTIVATION (Gates 5–6):** Couple the geometric representation to a physical driving force and regularize it for downstream processing. These gates are about *what makes the system move* — the source of non-equilibrium.
- **INFERENCE (Gates 7–10):** Extract dynamical properties, enforce equilibrium, generate irreversibility, and integrate into a conservation-guaranteeing transfer function. These gates are about *what the system does* — its observable behavior.

The three-part structure (Representation → Activation → Inference) is itself the most general architectural pattern. It mirrors the structure of physical measurement: prepare the system, apply a stimulus, observe the response.

End of Gate Architecture Document