


THIS IS AI4001

GCR : t37g47w

Language Modeling

- **Language Modeling** is the task of predicting what word comes next



- More formally: given a sequence of words $\mathbf{x}^{(1)}, \mathbf{x}^{(2)}, \dots, \mathbf{x}^{(t)}$, compute the probability distribution of the next word $\mathbf{x}^{(t+1)}$

$$P(\mathbf{x}^{(t+1)} \mid \mathbf{x}^{(t)}, \dots, \mathbf{x}^{(1)})$$

where $\mathbf{x}^{(t+1)}$ can be any word in the vocabulary $V = \{\mathbf{w}_1, \dots, \mathbf{w}_{|V|}\}$

- A system that does this is called a **Language Model**


Language Modeling

- You can also think of a Language Model as a system that assigns probability to a piece of text
- For example, if we have some text $\mathbf{x}^{(1)}, \dots, \mathbf{x}^{(T)}$, then the probability of this text (according to the Language Model) is:

$$\begin{aligned} P(\mathbf{x}^{(1)}, \dots, \mathbf{x}^{(T)}) &= P(\mathbf{x}^{(1)}) \times P(\mathbf{x}^{(2)} | \mathbf{x}^{(1)}) \times \dots \times P(\mathbf{x}^{(T)} | \mathbf{x}^{(T-1)}, \dots, \mathbf{x}^{(1)}) \\ &= \prod_{t=1}^T P(\mathbf{x}^{(t)} | \mathbf{x}^{(t-1)}, \dots, \mathbf{x}^{(1)}) \end{aligned}$$



This is what our LM provides

You use Language Models every day!



You use Language Models every day!



what is the | 

what is the **weather**
what is the **meaning of life**
what is the **dark web**
what is the **xfl**
what is the **doomsday clock**
what is the **weather today**
what is the **keto diet**
what is the **american dream**
what is the **speed of light**
what is the **bill of rights**

Sparsity Problems with n-gram Language Models

Sparsity Problem 1

Problem: What if “students opened their w ” never occurred in data? Then w has probability 0!

(Partial) Solution: Add small δ to the count for every $w \in V$. This is called *smoothing*.

$$P(w|\text{students opened their}) = \frac{\text{count}(\text{students opened their } w)}{\text{count}(\text{students opened their})}$$

Sparsity Problem 2


Problem: What if “students opened their” never occurred in data? Then we can’t calculate probability for *any* w !

(Partial) Solution: Just condition on “opened their” instead. This is called *backoff*.

Note: Increasing n makes sparsity problems worse. Typically, we can’t have n bigger than 5.

Storage Problems with n -gram Language Models

Storage: Need to store count for all n -grams you saw in the corpus.


$$P(\boldsymbol{w} | \text{students opened their}) = \frac{\text{count}(\text{students opened their } \boldsymbol{w})}{\text{count}(\text{students opened their})}$$

Increasing n or increasing corpus increases model size!

Generating text with a n-gram Language Model

You can also use a Language Model to **generate text**

today the price of gold per ton , while production of shoe lasts and shoe industry , the bank intervened just after it considered and rejected an imf demand to rebuild depleted european stocks , sept 30 end primary 76 cts a share .

Surprisingly grammatical!

...but **incoherent**. We need to consider more than three words at a time if we want to model language well.

But increasing n worsens sparsity problem,
and increases model size...

A fixed-window neural Language Model

output distribution

$$\hat{y} = \text{softmax}(Uh + b_2) \in \mathbb{R}^{|V|}$$

hidden layer


$$h = f(We + b_1)$$

concatenated word embeddings

$$e = [e^{(1)}; e^{(2)}; e^{(3)}; e^{(4)}]$$

words / one-hot vectors

$$x^{(1)}, x^{(2)}, x^{(3)}, x^{(4)}$$



A fixed-window neural Language Model

Approximately: Y. Bengio, et al. (2000/2003): A Neural Probabilistic Language Model

Improvements over n -gram LM:

- No sparsity problem
- Don't need to store all observed n -grams


Remaining **problems**:

- Fixed window is **too small**
- Enlarging window enlarges W
- Window can never be large enough!
- $x^{(1)}$ and $x^{(i)}$ are multiplied by

completely different weights in W .

No symmetry in how the inputs are processed


we need a neural architecture
that can process *any length input*



Recurrent Neural Networks (RNN)

A family of neural architectures

Core idea: Apply
the same weights
 W repeatedly



A Simple RNN Language Model

output distribution

$$\hat{y}^{(t)} = \text{softmax}(U h^{(t)} + b_2) \in \mathbb{R}^{|V|}$$

hidden states

$$h^{(t)} = \sigma(W_h h^{(t-1)} + W_e e^{(t)} + b_1)$$


$h^{(0)}$ is the initial hidden state

word embeddings

$$e^{(t)} = E x^{(t)}$$

words / one-hot vectors

$$x^{(t)} \in \mathbb{R}^{|V|}$$



Note: this input sequence could be much longer now!


RNN Language Models


RNN Advantages:

- Can process **any length** input
- Computation for step t can (in theory) use information from **many steps back**
- **Model size doesn't increase** for longer input context
- Same weights applied on every timestep, so there is **symmetry** in how inputs are processed.


RNN Disadvantages:

- Recurrent computation is **slow**
 - In practice, difficult to access information from **many steps back**
- More on these later in the course





=



Training an RNN Language Model


- Get a **big corpus of text** which is a sequence of words $x^{(1)}, \dots, x^{(T)}$
- Feed into RNN-LM; compute output distribution $\hat{y}^{(t)}$ **for every step t** .
 - i.e. predict probability dist of *every word*, given words so far
- **Loss function** on step t is **cross-entropy** between predicted probability distribution $\hat{y}^{(t)}$, and the true next word $y^{(t)}$ (one-hot for $x^{(t+1)}$):

$$J^{(t)}(\theta) = CE(y^{(t)}, \hat{y}^{(t)}) = - \sum_{w \in V} y_w^{(t)} \log \hat{y}_w^{(t)} = - \log \hat{y}_{x_{t+1}}^{(t)}$$


- Average this to get **overall loss** for entire training set:

$$J(\theta) = \frac{1}{T} \sum_{t=1}^T J^{(t)}(\theta) = \frac{1}{T} \sum_{t=1}^T - \log \hat{y}_{x_{t+1}}^{(t)}$$


Training an RNN Language Model




Training an RNN Language Model



Training an RNN Language Model




Training an RNN Language Model



Training an RNN Language Model

“Teacher forcing”



Training a RNN Language Model


- However: Computing loss and gradients across **entire corpus** $x^{(1)}, \dots, x^{(T)}$ is **too expensive**!

$$J(\theta) = \frac{1}{T} \sum_{t=1}^T J^{(t)}(\theta)$$

- In practice, consider $x^{(1)}, \dots, x^{(T)}$ as a **sentence** (or a **document**)
- Recall: **Stochastic Gradient Descent** allows us to compute loss and gradients for small chunk of data, and update.
- Compute loss $J(\theta)$ for a sentence (actually, a batch of sentences), compute gradients and update weights. Repeat.

(Simple) Recurrent Neural Network

The state consists of a single “hidden” vector h :



$$h_t = f_W(h_{t-1}, x_t)$$



$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$


$$y_t = W_{hy}h_t$$

Sometimes called a “Vanilla RNN” or an “Elman RNN” after Prof. Jeffrey Elman

Example: Character-level Language Model

Vocabulary:
[h,e,l,o]

Example training
sequence:
“hello”




Example: Character-level Language Model

Vocabulary:
[h,e,l,o]

Example training
sequence:
“hello”


$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$



Example: Character-level Language Model

Vocabulary:
[h,e,l,o]


Example training
sequence:
“hello”



Example: Character-level Language Model Sampling

Vocabulary:
[h,e,l,o]


At test-time sample
characters one at a time,
feed back to model



Example: Character-level Language Model Sampling

Vocabulary:
[h,e,l,o]


At test-time sample
characters one at a time,
feed back to model



Example: Character-level Language Model Sampling

Vocabulary:
[h,e,l,o]


At test-time sample
characters one at a time,
feed back to model



Example: Character-level Language Model Sampling

Vocabulary:
[h,e,l,o]

At test-time sample
characters one at a time,
feed back to model



CODE

```
import numpy as np
import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Embedding, SimpleRNN, Dense
from tensorflow.keras.preprocessing.text import Tokenizer
from tensorflow.keras.preprocessing.sequence import pad_sequences
```

```
texts = ["I love this product", "This is terrible", "Awesome!", "Waste of money"]
labels = [1, 0, 1, 0] # 1 for positive, 0 for negative
# Tokenize the text data
tokenizer = Tokenizer()
tokenizer.fit_on_texts(texts)
sequences = tokenizer.texts_to_sequences(texts)
```

```
# Padding sequences to have the same length
max_sequence_length = max([len(seq) for seq in sequences])
sequences = pad_sequences(sequences, maxlen=max_sequence_length, padding='post')
```

CODE

```
model = Sequential()  
model.add(Embedding(input_dim=len(tokenizer.word_index) + 1, output_dim=16,  
input_length=max_sequence_length))  
model.add(SimpleRNN(8, activation='tanh'))  
model.add(Dense(1, activation='sigmoid'))
```

```
model.compile(optimizer='adam', loss='binary_crossentropy',  
metrics=['accuracy'])
```

```
labels = np.array(labels)  
model.fit(sequences, labels, epochs=10, batch_size=2)
```

```
test_text = ["I hate it", "Amazing product"]  
test_sequences = tokenizer.texts_to_sequences(test_text)  
test_sequences = pad_sequences(test_sequences, maxlen=max_sequence_length,  
padding='post')  
predictions = model.predict(test_sequences)  
print(predictions)
```

WORD2VEC VS RANDOM EMBEDDINGS

Word2Vec Embeddings


- Saves Time

Randomly Initialized Embeddings


- Low-Resource Languages
- Domain-Specific Tasks(e.g., medical or legal texts)
- Privacy and Data Security
- Customized Embeddings
- Data Augmentation

Backpropagation through time

Forward through entire sequence to compute loss, then backward through entire sequence to compute gradient




Truncated Backpropagation through time




Run forward and backward through chunks of the sequence instead of whole sequence

Truncated Backpropagation through time




Carry hidden states forward in time forever, but only backpropagate for some smaller number of steps

Truncated Backpropagation through time



Backpropagation for RNNs




Question: What's the derivative of $J^{(t)}(\theta)$ w.r.t. the **repeated** weight matrix W_h ?

Answer:
$$\frac{\partial J^{(t)}}{\partial W_h} = \sum_{i=1}^t \frac{\partial J^{(t)}}{\partial W_h} \Big|_{(i)}$$

"The gradient w.r.t. a repeated weight is the sum of the gradient w.r.t. each time it appears"

Why?

Training the parameters of RNNs: Backpropagation for RNNs



In practice, often "truncated" after ~ 20 timesteps for training efficiency reasons

Question: How do we calculate this?

Answer: Backpropagate over timesteps $i = t, \dots, 0$, summing gradients as you go. This algorithm is called "**backpropagation through time**" [Werbos, P.G., 1988, *Neural Networks 1*, and others]


Apply the multivariable chain rule:

$$\begin{aligned} \frac{\partial J^{(t)}}{\partial W_h} &= \sum_{i=1}^t \frac{\partial J^{(t)}}{\partial W_h} \Big|_{(i)} \frac{\partial W_h}{\partial W_h} \Big|_{(i)} \\ &= \sum_{i=1}^t \frac{\partial J^{(t)}}{\partial W_h} \Big|_{(i)} \end{aligned}$$

= 1

Generating text with a RNN Language Model

Just like a n-gram Language Model, you can use a RNN Language Model to **generate text** by **repeated sampling**. Sampled output becomes next step's input.



Generating text with an RNN Language Model

Let's have some fun!

- You can train an RNN-LM on any kind of text, then generate text in that style.
- RNN-LM trained on *Harry Potter*:



“Sorry,” Harry shouted, panicking—“I’ll leave those brooms in London, are they?”

“No idea,” said Nearly Headless Nick, casting low close by Cedric, carrying the last bit of treacle Charms, from Harry’s shoulder, and to answer him the common room perched upon it, four arms held a shining knob from when the spider hadn’t felt it seemed. He reached the teams too.

Source: <https://medium.com/deep-writing/harry-potter-written-by-artificial-intelligence-8a9431803da6>

Evaluating Language Models

- The standard **evaluation metric** for Language Models is **perplexity**.

$$\text{perplexity} = \prod_{t=1}^T \left(\underbrace{\frac{1}{P_{\text{LM}}(\mathbf{x}^{(t+1)} | \mathbf{x}^{(t)}, \dots, \mathbf{x}^{(1)})}}_{\text{Inverse probability of corpus, according to Language Model}} \right)^{1/T}$$

Normalized by number of words

- This is equal to the exponential of the cross-entropy loss $J(\theta)$:

$$= \prod_{t=1}^T \left(\frac{1}{\hat{\mathbf{y}}_{\mathbf{x}_{t+1}}^{(t)}} \right)^{1/T} = \exp \left(\frac{1}{T} \sum_{t=1}^T -\log \hat{\mathbf{y}}_{\mathbf{x}_{t+1}}^{(t)} \right) = \exp(J(\theta))$$

Lower perplexity is better!

RNNs have greatly improved perplexity

n -gram model →

Increasingly
complex RNNs
↓

Model	Perplexity
Interpolated Kneser-Ney 5-gram (Chelba et al., 2013)	67.6
RNN-1024 + MaxEnt 9-gram (Chelba et al., 2013)	51.3
RNN-2048 + BlackOut sampling (Ji et al., 2015)	68.3
Sparse Non-negative Matrix factorization (Shazeer et al., 2015)	52.9
LSTM-2048 (Jozefowicz et al., 2016)	43.7
2-layer LSTM-8192 (Jozefowicz et al., 2016)	30
Ours small (LSTM-2048)	43.9
Ours large (2-layer LSTM-2048)	39.8


Perplexity improves
(lower is better)
↓

Recap

- **Language Model**: A system that predicts the next word
- **Recurrent Neural Network**: A family of neural networks that:
 - Take sequential input of any length
 - Apply the same weights on each step
 - Can optionally produce output on each step
- Recurrent Neural Network \neq Language Model
- We've shown that RNNs are a great way to build a LM.
- But RNNs are useful for much more!


RNNs can be used for tagging

e.g., **part-of-speech tagging**, named entity recognition




RNNs can be used for sentence classification

e.g., sentiment classification




RNNs can be used for sentence classification

e.g., sentiment classification



RNNs can be used for sentence classification


e.g., sentiment classification



RNNs can be used as an encoder module


e.g., **question answering**, machine translation, *many other tasks!*

Here the RNN acts as an **encoder** for the Question (the hidden states represent the Question). The encoder is part of a larger neural system.



Bidirectional and Multi-layer RNNs: motivation

Task: Sentiment Classification




Bidirectional RNNs

This contextual representation of "terribly" has both left and right context!

Concatenated
hidden states

Backward RNN

Forward RNN



Bidirectional RNNs

On timestep t :

This is a general notation to mean “compute one forward step of the RNN” – it could be a simple RNN or LSTM computation.

Forward RNN $\vec{h}^{(t)} = \text{RNN}_{\text{FW}}(\vec{h}^{(t-1)}, \mathbf{x}^{(t)})$


Backward RNN $\overleftarrow{h}^{(t)} = \text{RNN}_{\text{BW}}(\overleftarrow{h}^{(t+1)}, \mathbf{x}^{(t)})$

} Generally, these two RNNs have separate weights

Concatenated hidden states $\mathbf{h}^{(t)} = [\vec{h}^{(t)}; \overleftarrow{h}^{(t)}]$

We regard this as “the hidden state” of a bidirectional RNN. This is what we pass on to the next parts of the network.

Bidirectional RNNs: simplified diagram



The two-way arrows indicate bidirectionality and the depicted hidden states are assumed to be the concatenated forwards+backwards states

Bidirectional RNNs

- Note: bidirectional RNNs are only applicable if you have access to the **entire input sequence**
 - They are **not** applicable to Language Modeling, because in LM you *only* have left context available.
- If you do have entire input sequence (e.g., any kind of encoding), **bidirectionality is powerful** (you should use it by default).
- For example, **BERT** (**Bidirectional** Encoder Representations from Transformers) is a powerful pretrained contextual representation system **built on bidirectionality**.
 - You will learn more about **transformers**, including BERT, in a couple of weeks!


Multi-layer RNNs

- RNNs are already “deep” on one dimension (they unroll over many timesteps)
- We can also make them “deep” in another dimension by **applying multiple RNNs** – this is a multi-layer RNN.
- This allows the network to compute **more complex representations**
 - The **lower RNNs** should **compute lower-level features** and the **higher RNNs** should compute **higher-level features**.
- Multi-layer RNNs are also called ***stacked RNNs***.



Multi-layer RNNs

The hidden states from RNN layer i are the inputs to RNN layer $i+1$



Multi-layer RNNs in practice

- Multi-layer or stacked RNNs allow a network to compute **more complex representations**
 - they work better than just have one layer of high-dimensional encodings!
 - The **lower RNNs** should **compute lower-level features** and the **higher RNNs** should compute **higher-level features**.
- **High-performing RNNs are usually multi-layer** (but aren't as deep as convolutional or feed-forward networks)
- For example: In a 2017 paper, Britz et al. find that for Neural Machine Translation, **2 to 4 layers** is best for the encoder RNN, and **4 layers** is best for the decoder RNN
 - Often 2 layers is a lot better than 1, and 3 might be a little better than 2
 - Usually, **skip-connections/dense-connections** are needed to train deeper RNNs (e.g., **8 layers**)
- **Transformer-based networks** (e.g., BERT) are usually deeper, like **12 or 24 layers**.
 - You will learn about Transformers later; they have a lot of skipping-like connections

REFERENCES

<https://web.stanford.edu/class/cs224n/slides/cs224n-2023-lecture05-rnnlm.pdf>

http://cs231n.stanford.edu/slides/2020/lecture_10.pdf

<https://web.stanford.edu/class/cs224n/slides/cs224n-2021-lecture06-fancy-rnn.pdf>