

Product Information



LUBREEZOL Hydraulic Oil

Lubreezol Hydraulic Fluid series are high-performance lubricants featuring excellent aging stability, wear protection, its careful blend of base fluids and selected additives chosen for their ability to meet all the typical requirement of Hydraulic Fluid

Applications

Ideal for construction, agriculture, and industrial hydraulic systems operating in moderate to high temperatures as it provides excellent oxidation resistance, anti-wear protection, and filterability.

Features and benefits

Compatible with usual seal materials

The base fluid has been selected for its ability to provide good lubrication under variety of applications

Excellent anti-wear and extreme pressure characteristics

Better air release and antifoam characteristics

Provides water separation characteristics

Lower possibility of contaminant ingress and oil leaks

Certifications and Specifications

- NSF ISO 21469
- DIN 51524 HLP
- ISO 6743-4 L-HM

Parameters / Properties

Parameters/Properties	Unit	ASTM Method	Test Values	
			46	68
Viscosity @ 40 °C, cSt	mm ² /s	D 445	42-48	64-72
Viscosity Index	mm ² /s	D 2270	120	120
Flash Point , °C	°C	D 92	235	235
Fire Point, , °C	°C	D 92	260	260
Pour Point , °C	°C	D 97	-15	-15
Copper Corrosion	Copper Test Strip	ASTM D-4048	1b	1b
Density @ 15°C, Kg/l	kg/m ³	D 1298	0.868	0.868