The design system for any URL.

An open-source agent that opens any public URL, screenshots it, extracts the real CSS tokens, and writes a structured design.md. Every swatch grounded. No hallucinated palettes.

02 · problem

Matching a brand is a manual, lossy ritual.

Three workflows, all of them wrong. Designers eyedrop. Developers screenshot LLMs and pray. Agents hallucinate hex codes that don't exist on the page they're cloning.

01 · MANUAL

Eyedrop, copy, guess weights.

DevTools open for 40 minutes. Half the swatches are wrong by a hue.

TODAY'S WORKFLOW

02 · LLM

Screenshot → LLM → hope.



Vision models invent palette values. Nothing is grounded in the actual stylesheet.

03 · BY HAND

Write the spec yourself.



Three drafts in. Inconsistent across teams. No one wants to maintain it.

SLOW · ERROR-PRONE · INCONSISTENT

03 · solution

Paste a URL. Get a design.md.

INPUT

https://linear.app

PUBLIC URL

READ-ONLY

~90S

design.md

9 SECTIONS

01 Visual theme & atmosphere

02 Color palette & roles

03 Typography rules

04 Component stylings

05 Layout principles

06 Depth & elevation

07 Interaction & motion

04 · output

Nine sections, in this order, every time.

Validated by a Zod schema on the LLM's structured output. The model can't skip a section, can't reorder, can't invent a tenth. The renderer is deterministic.

01
Visual Theme & Atmosphere
Mood, density, signature gestures.

02
Color Palette & Roles
Hex values + semantic roles.

03
Typography Rules
Stacks, scale, weights, leading.

04
Component Stylings
Buttons, inputs, cards, badges.

05
Layout Principles
Grids, rhythm, alignment.

06
Depth & Elevation
Shadows, surfaces, hierarchy.

07
Interaction & Motion
Easings, durations, gestures.

08
Responsive Behavior
Breakpoints, fluid scale.

09
Agent Prompt Guide
How to feed this into Cursor / Claude / v0.

05 · pipeline

Four phases. About ninety seconds.

A coordinator agent orchestrates four sub-agents inside a Daytona sandbox. Crawl is deterministic. Extraction is deterministic. Only synthesis touches the LLM, and only against grounded tokens.

PHASE 01

Crawl

Fetch HTML, all linked CSS, @import chains, font sources.

PHASE 02

Screenshot

Real Chromium in a Daytona sandbox. Hero + full-page stitch.

PHASE 03

Extract

Deterministic CSS parse into a DesignTokens Zod object.

PHASE 04

Synthesize

GPT-5.5 class via AI Gateway. Structured output, validated.

06 · grounding

Every color appears in the actual stylesheet.

Validation rule: 100% of palette values must trace back to the crawled CSS. Anything the model invents is rejected. This is the line between a spec and a hallucination.

Vision-only LLM

INVENTED FROM A SCREENSHOT

- #7C3AED — not in any stylesheet
- #06B6D4 — not in any stylesheet
- #F97316 — not in any stylesheet

100% PALETTE GROUNDING

getdesign · grounded

PARSED FROM REAL CSS VARIABLES

- #A3E635 — --accent · :root
- #0A0A0B — --background · :root
- #EDEDEE — --foreground · :root

DETERMINISM ≥ 95% ON REPEAT RUNS

07 · surfaces

Four surfaces. One agent core.

Same package, same schema, four ways in. Whatever your stack already is, getdesign meets it there. No per-surface drift.

01 · CHAT

getdesign.app

Live web UI

```
> paste a URL
> watch the agent run
> read the design.md
```

02 · API

api.getdesign.app

One-shot HTTP

```
curl api.getdesign.app/?url=
https://linear.app
⇒ text/markdown
```

03 · CLI

@getdesign/cli

Local one-shot or REPL

```
npx @getdesign/cli
https://stripe.com
⇒ design.md
```

04 · SDK

@getdesign/sdk

Typed TypeScript client

```
const { doc } =
await getDesign(url)
doc.palette.primary[0]
```

Open-source. Available today.

MIT-licensed agent core, hosted API, npm packages. Bring your own AI Gateway key or use the hosted run. Star it, fork it, build the surface that doesn't exist yet.

```
> npx @getdesign/cli https://linear.app
```

PASTE · GET · COMMIT

WEB	REPO	NPM	LICENSE
getdesign.app	github.com/mohtashammurshid/getdesign	@getdesign/sdk	MIT